

## NAG Library Function Document

### nag\_sum\_fft\_sine (c06rec)

## 1 Purpose

nag\_sum\_fft\_sine (c06rec) computes the discrete Fourier sine transforms of  $m$  sequences of real data values. The elements of each sequence and its transform are stored contiguously.

## 2 Specification

```
#include <nag.h>
#include <nagc06.h>
void nag_sum_fft_sine (Integer m, Integer n, double x[], NagError *fail)
```

## 3 Description

Given  $m$  sequences of  $n - 1$  real data values  $x_j^p$ , for  $j = 1, 2, \dots, n - 1$  and  $p = 1, 2, \dots, m$ , nag\_sum\_fft\_sine (c06rec) simultaneously calculates the Fourier sine transforms of all the sequences defined by

$$\hat{x}_k^p = \sqrt{\frac{2}{n}} \sum_{j=1}^{n-1} x_j^p \times \sin\left(jk\frac{\pi}{n}\right), \quad k = 1, 2, \dots, n - 1 \text{ and } p = 1, 2, \dots, m.$$

(Note the scale factor  $\sqrt{\frac{2}{n}}$  in this definition.)

This transform is also known as type-I DST.

Since the Fourier sine transform defined above is its own inverse, two consecutive calls of nag\_sum\_fft\_sine (c06rec) will restore the original data.

The transform calculated by this function can be used to solve Poisson's equation when the solution is specified at both left and right boundaries (see Swarztrauber (1977)).

The function uses a variant of the fast Fourier transform (FFT) algorithm (see Brigham (1974)) known as the Stockham self-sorting algorithm, described in Temperton (1983), together with pre- and post-processing stages described in Swarztrauber (1982). Special coding is provided for the factors 2, 3, 4 and 5.

## 4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice–Hall

Swarztrauber P N (1977) The methods of cyclic reduction, Fourier analysis and the FACR algorithm for the discrete solution of Poisson's equation on a rectangle *SIAM Rev.* **19(3)** 490–501

Swarztrauber P N (1982) Vectorizing the FFT's *Parallel Computation* (ed G Rodrique) 51–83 Academic Press

Temperton C (1983) Fast mixed-radix real Fourier transforms *J. Comput. Phys.* **52** 340–350

## 5 Arguments

1:	<b>m</b> – Integer	<i>Input</i>
----	--------------------	--------------

*On entry:*  $m$ , the number of sequences to be transformed.

*Constraint:*  $m \geq 1$ .

2: <b>n</b> – Integer	<i>Input</i>
<i>On entry:</i> one more than the number of real values in each sequence, i.e., the number of values in each sequence is $n - 1$ .	
<i>Constraint:</i> $\mathbf{n} \geq 1$ .	
3: <b>x</b> $[(\mathbf{n} - 1) \times \mathbf{m}] – double$	<i>Input/Output</i>
<i>On entry:</i> the $p$ th sequence to be transformed, denoted by $x_j^p$ , for $j = 1, 2, \dots, n - 1$ and $p = 1, 2, \dots, m$ , must be stored in $\mathbf{x}[(p - 1) \times (\mathbf{n} - 1) + j - 1]$ .	
<i>On exit:</i> the $m$ Fourier sine transforms, overwriting the corresponding original sequences. The $(n - 1)$ components of the $p$ th Fourier sine transform, denoted by $\hat{x}_k^p$ , for $k = 1, 2, \dots, n - 1$ and $p = 1, 2, \dots, m$ , are stored in $\mathbf{x}[(p - 1) \times (\mathbf{n} - 1) + k - 1]$ .	
4: <b>fail</b> – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 3.6 in the Essential Introduction).	

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_INT

On entry,  $\mathbf{m} = \langle value \rangle$ .

Constraint:  $\mathbf{m} \geq 1$ .

On entry,  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{n} \geq 1$ .

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

## 7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

## 8 Parallelism and Performance

`nag_sum_fft_sine` (`c06rec`) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

The time taken by `nag_sum_fft_sine` (`c06rec`) is approximately proportional to  $nm\log(n)$ , but also depends on the factors of  $n$ . `nag_sum_fft_sine` (`c06rec`) is fastest if the only prime factors of  $n$  are 2, 3 and 5, and is particularly slow if  $n$  is a large prime, or has large prime factors. Workspace is internally allocated by this function. The total amount of memory allocated is  $O(n)$  double values.

## 10 Example

This example reads in sequences of real data values and prints their Fourier sine transforms (as computed by nag\_sum\_fft\_sine (c06rec)). It then calls nag\_sum\_fft\_sine (c06rec) again and prints the results which may be compared with the original sequence.

### 10.1 Program Text

```
/* nag_sum_fft_sine (c06rec) Example Program.
*
* Copyright 2013 Numerical Algorithms Group.
*
* Mark 24, 2013.
*/
#include <nag.h>
#include <stdio.h>
#include <nag_stlib.h>
#include <nagc06.h>

int main(void)
{
    /* Scalars */
    Integer exit_status = 0, j, m, n, n1;
    /* Arrays */
    double *x = 0;
    char title[60];
    /* Nag Types */
    NagError fail;

    INIT_FAIL(fail);

    printf("nag_sum_fft_sine (c06rec) Example Program Results\n");

    /* Read dimensions of array from data file. */
    scanf("%*[^\n] %" NAG_IFMT "%*[^\\n]", &m, &n1);

    n = n1 + 1;

    if (!(x = NAG_ALLOC((m * n1), double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read array values from data file and print out. */
    for (j = 0; j < m*n1; j++)
        scanf("%lf", &x[j]);
    sprintf(title, "\n Original data values\n");
    nag_gen_real_mat_print_comp(Nag_RowMajor, Nag_GeneralMatrix,
                                Nag_NonUnitDiag, m, n1, x, n1, "%9.4f",
                                title, Nag_NoLabels, 0, Nag_NoLabels,
                                0, 80, 0, NULL, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_gen_real_mat_print_comp (x04cbc).\n%s\n",
               fail.message);
        exit_status = 1;
        goto END;
    }

    /* nag_sum_fft_sine (c06rec).
     * Discrete sine transforms
     */
    nag_sum_fft_sine(m, n, x, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_sum_fft_sine (c06rec).\n%s\n",
               fail.message);
    }
}
```

```

        fail.message);
    exit_status = 2;
    goto END;
}
sprintf(title, "\n Discrete Fourier sine transforms\n");
nag_gen_real_mat_print_comp(Nag_RowMajor, Nag_GeneralMatrix,
                             Nag_NonUnitDiag, m, n1, x, n1, "%9.4f",
                             title, Nag_NoLabels, 0, Nag_NoLabels,
                             0, 80, 0, NULL, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print_comp (x04cbc).\n%s\n",
           fail.message);
    exit_status = 3;
    goto END;
}

/* Two consecutive calls should restore the original data. */
nag_sum_fft_sine(m, n, x, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_sum_fft_sine (c06rec).\n%s\n",
           fail.message);
    exit_status = 4;
    goto END;
}
sprintf(title, "\n Original data as restored by inverse transform\n");
nag_gen_real_mat_print_comp(Nag_RowMajor, Nag_GeneralMatrix,
                             Nag_NonUnitDiag, m, n1, x, n1, "%9.4f",
                             title, Nag_NoLabels, 0, Nag_NoLabels,
                             0, 80, 0, NULL, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print_comp (x04cbc).\n%s\n",
           fail.message);
    exit_status = 5;
    goto END;
}

END:
NAG_FREE(x);
return exit_status;
}

```

## 10.2 Program Data

nag\_sum\_fft\_sine (c06rec) Example Program Data

```

3      5                               : m, n-1
0.6772  0.1138  0.6751  0.6362  0.1424
0.2983  0.1182  0.7255  0.8638  0.8723
0.0644  0.6037  0.6430  0.0428  0.4815  : x

```

## 10.3 Program Results

nag\_sum\_fft\_sine (c06rec) Example Program Results

Original data values

0.6772	0.1138	0.6751	0.6362	0.1424
0.2983	0.1182	0.7255	0.8638	0.8723
0.0644	0.6037	0.6430	0.0428	0.4815

Discrete Fourier sine transforms

1.0014	0.0062	0.0834	0.5286	0.2514
1.2478	-0.6598	0.2570	0.0858	0.2658
0.8521	0.0719	-0.0561	-0.4890	0.2056

Original data as restored by inverse transform

0.6772	0.1138	0.6751	0.6362	0.1424
0.2983	0.1182	0.7255	0.8638	0.8723
0.0644	0.6037	0.6430	0.0428	0.4815

---