

NAG Library Function Document

nag_1d_everett_interp (e01abc)

1 Purpose

nag_1d_everett_interp (e01abc) interpolates a function of one variable at a given point x from a table of function values evaluated at equidistant points, using Everett's formula.

2 Specification

```
#include <nag.h>
#include <nage01.h>
void nag_1d_everett_interp (Integer n, double p, double a[], double g[],
                           NagError *fail)
```

3 Description

nag_1d_everett_interp (e01abc) interpolates a function of one variable at a given point

$$x = x_0 + ph,$$

where $-1 < p < 1$ and h is the interval of differencing, from a table of values $x_m = x_0 + mh$ and y_m where $m = -(n-1), -(n-2), \dots, -1, 0, 1, \dots, n$. The formula used is that of Fröberg (1970), neglecting the remainder term:

$$y_p = \sum_{r=0}^{n-1} \left(\frac{1-p+r}{2r+1} \right) \delta^{2r} y_0 + \sum_{r=0}^{n-1} \left(\frac{p+r}{2r+1} \right) \delta^{2r} y_1.$$

The values of $\delta^{2r} y_0$ and $\delta^{2r} y_1$ are stored on exit from the function in addition to the interpolated function value y_p .

4 References

Fröberg C E (1970) *Introduction to Numerical Analysis* Addison–Wesley

5 Arguments

- | | |
|--|---------------------|
| 1: n – Integer | <i>Input</i> |
| <i>On entry:</i> n , half the number of points to be used in the interpolation. | |
| <i>Constraint:</i> $n > 0$. | |
| 2: p – double | <i>Input</i> |
| <i>On entry:</i> the point p at which the interpolated function value is required, i.e., $p = (x - x_0)/h$ with $-1.0 < p < 1.0$. | |
| <i>Constraint:</i> $-1.0 < p < 1.0$. | |
| 3: a [$2 \times n$] – double | <i>Input/Output</i> |
| <i>On entry:</i> $\mathbf{a}[i-1]$ must be set to the function value y_{i-n} , for $i = 1, 2, \dots, 2n$. | |
| <i>On exit:</i> the contents of a are unspecified. | |

4:	g [$2 \times n + 1$] – double	<i>Output</i>
<i>On exit:</i> the array contains		
	y_0 in g [0]	
	y_1 in g [1]	
	$\delta^{2r}y_0$ in g [$2r$]	
	$\delta^{2r}y_1$ in g [$2r + 1$], for $r = 1, 2, \dots, n - 1$.	
The interpolated function value y_p is stored in g [$2n$].		

5:	fail – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 3.6 in the Essential Introduction).		

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle value \rangle$.

Constraint: **n** > 0.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_REAL

On entry, **p** = $\langle value \rangle$.

Constraint: **p** < 1.0.

On entry, **p** = $\langle value \rangle$.

Constraint: **p** > -1.0.

7 Accuracy

In general, increasing n improves the accuracy of the result until full attainable accuracy is reached, after which it might deteriorate. If x lies in the central interval of the data (i.e., $0.0 \leq p < 1.0$), as is desirable, an upper bound on the contribution of the highest order differences (which is usually an upper bound on the error of the result) is given approximately in terms of the elements of the array **g** by $a \times (|g[2n - 2]| + |g[2n - 1]|)$, where $a = 0.1, 0.02, 0.005, 0.001, 0.0002$ for $n = 1, 2, 3, 4, 5$ respectively, thereafter decreasing roughly by a factor of 4 each time.

8 Parallelism and Performance

Not applicable.

9 Further Comments

The computation time increases as the order of n increases.

10 Example

This example interpolates at the point $x = 0.28$ from the function values

$$\begin{pmatrix} x_i & -1.00 & -0.50 & 0.00 & 0.50 & 1.00 & 1.50 \\ y_i & 0.00 & -0.53 & -1.00 & -0.46 & 2.00 & 11.09 \end{pmatrix}.$$

We take $n = 3$ and $p = 0.56$.

10.1 Program Text

```
/* nag_1d_everett_interp (e01abc) Example Program.
*
* Copyright 2011, Numerical Algorithms Group.
*
* Mark 23, 2011.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stlalloc.h>
#include <nage01.h>

int main(void)
{
    /* Scalars */
    Integer exit_status = 0;
    Integer i, n, r;
    double p;
    NagError fail;
    /* Local Arrays */
    double *a = 0, *g = 0;

    INIT_FAIL(fail);

    printf("nag_1d_everett_interp (e01abc) Example Program Results\n");

    /* Skip heading in data file*/
    scanf("%*[^\n] ");
    scanf("%"NAG_IFMT "", &n);
    scanf("%lf", &p);
    scanf("%*[^\n] ");

    /* Allocate memory */
    if (!(a = NAG_ALLOC((2*n), double)) ||
        !(g = NAG_ALLOC((2*n+1), double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    for (i = 0; i < 2*n; i++)
        scanf("%lf", &a[i]);
    scanf("%*[^\n] ");

    /* nag_1d_everett_interp (e01abc).
     * Interpolated values, Everett's formula, equally spaced data, one variable.
     */
    nag_1d_everett_interp(n, p, a, g, &fail);
    if (fail.code != NE_NOERROR){
        printf("Error from nag_1d_everett_interp (e01abc).\n%s\n",
               fail.message);
        exit_status = 1;
        goto END;
    }

    printf("\n");
    for (r = 0; r <= n - 1; r++) {
```

```

    printf("Central differences order %"NAG_IFMT "  of Y0 = %12.5f\n",
           r, g[2 * r]);
    printf("                                Y1 = %12.5f\n",
           g[2 * r + 1]);
}
printf("\n");
printf("Function value at interpolation point = %12.5f\n", g[2*n]);

END:
NAG_FREE(a);
NAG_FREE(g);

return exit_status;
}

```

10.2 Program Data

```
nag_1d_everett_interp (e01abc) Example Program Data
3          0.56
0.00     -0.53    -1.00    -0.46     2.00    11.09
```

10.3 Program Results

```
nag_1d_everett_interp (e01abc) Example Program Results

Central differences order 0  of Y0 =      -1.00000
                                Y1 =      -0.46000
Central differences order 1  of Y0 =      1.01000
                                Y1 =      1.92000
Central differences order 2  of Y0 =     -0.04000
                                Y1 =      3.80000

Function value at interpolation point =      -0.83591
```
