

NAG Library Function Document

nag_opt_sparse_nlp_jacobian (e04vjc)

1 Purpose

nag_opt_sparse_nlp_jacobian (e04vjc) may be used before nag_opt_sparse_nlp_solve (e04vhc) to determine the sparsity pattern for the Jacobian.

2 Specification

```
#include <nag.h>
#include <nage04.h>

void nag_opt_sparse_nlp_jacobian (Integer nf, Integer n,
    void (*usrfun)(Integer *status, Integer n, const double x[],
        Integer needf, Integer nf, double f[], Integer needg,
        Integer leng, double g[], Nag_Comm *comm),
    Integer iafun[], Integer javar[], double a[], Integer lena,
    Integer *nea, Integer igfun[], Integer jgvar[], Integer leng,
    Integer *neg, const double x[], const double xlow[],
    const double xupp[], Nag_E04State *state, Nag_Comm *comm,
    NagError *fail)
```

3 Description

When using nag_opt_sparse_nlp_solve (e04vhc), if you set the optional argument **Derivative Option** = 0 and **usrfun** provides none of the derivatives, you may need to call nag_opt_sparse_nlp_jacobian (e04vjc) to determine the input arrays **iafun**, **javar**, **a**, **igfun** and **jgvar**. These arrays define the pattern of nonzeros in the Jacobian matrix. A typical sequence of calls could be

```
e04vgc (&state, ... );
e04vjc (nf, n, ... );
e04v1c ("Derivative Option = 0", &state, ... );
e04vhc (start, nf, ... );
```

nag_opt_sparse_nlp_jacobian (e04vjc) determines the sparsity pattern for the Jacobian and identifies the constant elements automatically. To do so, nag_opt_sparse_nlp_jacobian (e04vjc) approximates the problem functions, $F(x)$, at three random perturbations of the given initial point x . If an element of the approximate Jacobian is the same at all three points, then it is taken to be constant. If it is zero, it is taken to be identically zero. Since the random points are not chosen close together, the heuristic will correctly classify the Jacobian elements in the vast majority of cases. In general, nag_opt_sparse_nlp_jacobian (e04vjc) finds that the Jacobian can be permuted to the form:

$$\begin{pmatrix} G(x) & A_3 \\ A_2 & A_4 \end{pmatrix},$$

where A_2 , A_3 and A_4 are constant. Note that $G(x)$ might contain elements that are also constant, but nag_opt_sparse_nlp_jacobian (e04vjc) must classify them as nonlinear. This is because nag_opt_sparse_nlp_solve (e04vhc) ‘removes’ linear variables from the calculation of F by setting them to zero before calling **usrfun**. A knowledgeable user would be able to move such elements from $F(x)$ in **usrfun** and enter them as part of **iafun**, **javar** and **a** for nag_opt_sparse_nlp_solve (e04vhc).

4 References

Hock W and Schittkowski K (1981) *Test Examples for Nonlinear Programming Codes. Lecture Notes in Economics and Mathematical Systems* **187** Springer-Verlag

5 Arguments

Note: all optional arguments are described in detail in Section 12.1 in nag_opt_sparse_nlp_solve (e04vhc).

- 1: **nf** – Integer *Input*
On entry: nf , the number of problem functions in $F(x)$, including the objective function (if any) and the linear and nonlinear constraints. Simple upper and lower bounds on x can be defined using the arguments **xlow** and **xupp** and should not be included in F .
Constraint: **nf** > 0.

- 2: **n** – Integer *Input*
On entry: n , the number of variables.
Constraint: **n** > 0.

- 3: **usrfun** – function, supplied by the user *External Function*
usrfun must define the problem functions $F(x)$. This function is passed to nag_opt_sparse_nlp_jacobian (e04vjc) as the external argument **usrfun**.

The specification of **usrfun** is:

```
void  usrfun (Integer *status, Integer n, const double x[],
             Integer needf, Integer nf, double f[], Integer needg,
             Integer leng, double g[], Nag_Comm *comm)
```

- 1: **status** – Integer * *Input/Output*
On entry: indicates the first call to **usrfun**.
status = 0
 There is nothing special about the current call to **usrfun**.
status = 1
 nag_opt_sparse_nlp_jacobian (e04vjc) is calling your function for the *first* time. Some data may need to be input or computed and saved.
On exit: may be used to indicate that you are unable to evaluate F at the current x . (For example, the problem functions may not be defined there).
 nag_opt_sparse_nlp_jacobian (e04vjc) evaluates $F(x)$ at random perturbation of the initial point x , say x_p . If the functions cannot be evaluated at x_p , you can set **status** = -1, nag_opt_sparse_nlp_jacobian (e04vjc) will use another random perturbation.
 If for some reason you wish to terminate the current problem, set **status** ≤ -2.

- 2: **n** – Integer *Input*
On entry: n , the number of variables, as defined in the call to nag_opt_sparse_nlp_jacobian (e04vjc).

- 3: **x[n]** – const double *Input*
On entry: the variables x at which the problem functions are to be calculated. The array x must not be altered.

- 4: **needf** – Integer *Input*
On entry: indicates if **f** must be assigned during the call to **usrfun** (see **f**).

| | | |
|-----|--|--------------------------------|
| 5: | nf – Integer | <i>Input</i> |
| | <i>On entry:</i> <i>nf</i> , the number of problem functions. | |
| 6: | f[nf] – double | <i>Input/Output</i> |
| | <i>On entry:</i> this will be set by <code>nag_opt_sparse_nlp_jacobian</code> (e04vjc). | |
| | <i>On exit:</i> the computed $F(x)$ according to the setting of needf . | |
| | If needf = 0, f is not required and is ignored. | |
| | If needf > 0, the components of $F(x)$ must be calculated and assigned to f . <code>nag_opt_sparse_nlp_jacobian</code> (e04vjc) will always call usrfun with needf > 0. | |
| | To simplify the code, you may ignore the value of needf and compute $F(x)$ on every entry to usrfun . | |
| 7: | needg – Integer | <i>Input</i> |
| | <i>On entry:</i> <code>nag_opt_sparse_nlp_jacobian</code> (e04vjc) will call usrfun with needg = 0 to indicate that g is not required. | |
| 8: | leng – Integer | <i>Input</i> |
| | <i>On entry:</i> the dimension of the array g . | |
| 9: | g[leng] – double | <i>Input/Output</i> |
| | <i>On entry:</i> concerns the calculations of the derivatives of the function $f(x)$. | |
| | <i>On exit:</i> <code>nag_opt_sparse_nlp_jacobian</code> (e04vjc) will always call usrfun with needg = 0: g is not required to be set on exit but must be declared correctly. | |
| 10: | comm – Nag_Comm * | <i>Communication Structure</i> |
| | Pointer to structure of type Nag_Comm; the following members are relevant to usrfun . | |
| | user – double * | |
| | iuser – Integer * | |
| | p – Pointer | |
| | The type Pointer will be <code>void *</code> . Before calling <code>nag_opt_sparse_nlp_jacobian</code> (e04vjc) you may allocate memory and initialize these pointers with various quantities for use by usrfun when called from <code>nag_opt_sparse_nlp_jacobian</code> (e04vjc) (see Section 3.2.1.1 in the Essential Introduction). | |

- 4: **iafun[lena]** – Integer *Output*
- 5: **javar[lena]** – Integer *Output*
- 6: **a[lena]** – double *Output*
- On exit:* define the coordinates (i, j) and values A_{ij} of the nonzero elements of the linear part A of the function $F(x) = f(x) + Ax$.
- In particular, **nea** triples $(\mathbf{iafun}[k-1], \mathbf{javar}[k-1], \mathbf{a}[k-1])$ define the row and column indices $i = \mathbf{iafun}[k-1]$ and $j = \mathbf{javar}[k-1]$ of the element $A_{ij} = \mathbf{a}[k-1]$.
- 7: **lena** – Integer *Input*
- On entry:* the dimension of the arrays **iafun**, **javar** and **a** that hold (i, j, A_{ij}) . **lena** should be an *overestimate* of the number of elements in the linear part of the Jacobian.
- Constraint:* **lena** ≥ 1 .

- 8: **nea** – Integer * *Output*
On exit: is the number of nonzero entries in A such that $F(x) = f(x) + Ax$.
- 9: **igfun**[**leng**] – Integer *Output*
10: **igvar**[**leng**] – Integer *Output*
On exit: define the coordinates (i, j) of the nonzero elements of G , the nonlinear part of the derivatives $J(x) = G(x) + A$ of the function $F(x) = f(x) + Ax$.
- 11: **leng** – Integer *Input*
On entry: the dimension of the arrays **igfun** and **igvar** that define the varying Jacobian elements (i, j, G_{ij}) . **leng** should be an *overestimate* of the number of elements in the nonlinear part of the Jacobian.
Constraint: **leng** ≥ 1 .
- 12: **neg** – Integer * *Output*
On exit: the number of nonzero entries in G .
- 13: **x**[**n**] – const double *Input*
On entry: an initial estimate of the variables x . The contents of x will be used by `nag_opt_sparse_nlp_jacobian (e04vjc)` in the call of **usrfun**, and so each element of **x** should be within the bounds given by **xlow** and **xupp**.
- 14: **xlow**[**n**] – const double *Input*
15: **xupp**[**n**] – const double *Input*
On entry: contain the lower and upper bounds l_x and u_x on the variables x .
To specify a nonexistent lower bound $[l_x]_j = -\infty$, set **xlow**[$j - 1$] $\leq -bigbnd$, where *bigbnd* is the optional argument **Infinite Bound Size**. To specify a nonexistent upper bound **xupp**[$j - 1$] $\geq bigbnd$.
To fix the j th variable (say, $x_j = \beta$, where $|\beta| < bigbnd$), set **xlow**[$j - 1$] = **xupp**[$j - 1$] = β .
- 16: **state** – Nag_E04State * *Communication Structure*
state contains internal information required for functions in this suite. It must not be modified in any way.
- 17: **comm** – Nag_Comm * *Communication Structure*
The NAG communication argument (see Section 3.2.1.1 in the Essential Introduction).
- 18: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Internal error: memory allocation failed when attempting to allocate workspace sizes $\langle value \rangle$, $\langle value \rangle$ and $\langle value \rangle$.

NE_ALLOC_INSUFFICIENT

Internal memory allocation was insufficient. Please contact NAG.

NE_ARRAY_TOO_SMALL

Either **lena** or **leng** is too small. Increase both of them and corresponding array sizes.
lena = $\langle value \rangle$ and **leng** = $\langle value \rangle$.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_E04VGC_NOT_INIT

Initialization function `nag_opt_sparse_nlp_init` (e04vgc) has not been called.

NE_INT

On entry, **lena** = $\langle value \rangle$.

Constraint: **lena** ≥ 1 .

On entry, **leng** = $\langle value \rangle$.

Constraint: **leng** ≥ 1 .

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_JACOBIAN_STRUCTURE_FAIL

Cannot estimate Jacobian structure at given point **x**.

NE_USER_STOP

User-supplied function **usrfun** requested termination.

NE_USRFUN_UNDEFINED

User-supplied function **usrfun** indicates that functions are undefined near given point **x**.

7 Accuracy

Not applicable.

8 Parallelism and Performance

`nag_opt_sparse_nlp_jacobian` (e04vjc) is not threaded by NAG in any implementation.

`nag_opt_sparse_nlp_jacobian` (e04vjc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

This example shows how to call `nag_opt_sparse_nlp_jacobian` (e04vjc) to determine the sparsity pattern of the Jacobian before calling `nag_opt_sparse_nlp_solve` (e04vhc) to solve a sparse nonlinear programming problem without providing the Jacobian information in **usrfun**.

It is a reformulation of Problem 74 from Hock and Schittkowski (1981) and involves the minimization of the nonlinear function

$$f(x) = 10^{-6}x_3^3 + \frac{2}{3} \times 10^{-6}x_4^3 + 3x_3 + 2x_4$$

subject to the bounds

$$\begin{aligned} -0.55 &\leq x_1 \leq 0.55, \\ -0.55 &\leq x_2 \leq 0.55, \\ 0 &\leq x_3 \leq 1200, \\ 0 &\leq x_4 \leq 1200, \end{aligned}$$

to the nonlinear constraints

$$\begin{aligned} 1000 \sin(-x_1 - 0.25) + 1000 \sin(-x_2 - 0.25) - x_3 &= -894.8, \\ 1000 \sin(x_1 - 0.25) + 1000 \sin(x_1 - x_2 - 0.25) - x_4 &= -894.8, \\ 1000 \sin(x_2 - 0.25) + 1000 \sin(x_2 - x_1 - 0.25) &= -1294.8, \end{aligned}$$

and to the linear constraints

$$\begin{aligned} -x_1 + x_2 &\geq -0.55, \\ x_1 - x_2 &\geq -0.55. \end{aligned}$$

The initial point, which is infeasible, is

$$x_0 = (0, 0, 0, 0)^T,$$

and $f(x_0) = 0$.

The optimal solution (to five figures) is

$$x^* = (0.11887, -0.39623, 679.94, 1026.0)^T,$$

and $f(x^*) = 5126.4$. All the nonlinear constraints are active at the solution.

The formulation of the problem combines the constraints and the objective into a single vector (F).

$$F = \begin{pmatrix} \left(\begin{array}{l} 1000 \sin(-x_1 - 0.25) + 1000 \sin(-x_2 - 0.25) - x_3 \\ 1000 \sin(x_1 - 0.25) + 1000 \sin(x_1 - x_2 - 0.25) - x_4 \\ 1000 \sin(x_2 - 0.25) + 1000 \sin(x_2 - x_1 - 0.25) \end{array} \right) \\ -x_1 + x_2 \\ x_1 - x_2 \\ 10^{-6}x_3^3 + \frac{2}{3} \times 10^{-6}x_4^3 + 3x_3 + 2x_4 \end{pmatrix}$$

10.1 Program Text

```

/* nag_opt_sparse_nlp_jacobian (e04vjc) Example Program.
 *
 * Copyright 2004 Numerical Algorithms Group.
 *
 * Mark 8, 2004.
 */
#include <stdio.h>
#include <math.h>
#include <string.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nage04.h>

#ifdef __cplusplus
extern "C" {
#endif
static void NAG_CALL usrfun(Integer *status, Integer n, const double x[],
                             Integer needf, Integer nf, double f[],
                             Integer needg, Integer leng, double g[],
                             Nag_Comm *comm);
#ifdef __cplusplus
}

```

```

#endif

int main(void)
{
    /* Scalars */
    double      objjadd, sinf;
    Integer     exit_status = 0;
    Integer     i, lena, leng, n, nea, neg, nf, nfname, ninf, ns, nxname,
                objrow;

    /* Arrays */
    char        **fnames = 0, prob[9], **xnames = 0;
    double      *a = 0, *f = 0, *flow = 0, *fmul = 0, *fupp = 0, *x = 0;
    double      *xlow = 0, *xmul = 0, *xupp = 0;
    Integer     *fstate = 0, *iafun = 0, *igfun = 0, *javar = 0, *jgvar = 0;
    Integer     *xstate = 0;

    /* Nag Types */
    Nag_E04State state;
    NagError     fail;
    Nag_Comm     comm;
    Nag_Start    start;
    Nag_FileID   fileid;

    exit_status = 0;
    INIT_FAIL(fail);

    printf(
        "nag_opt_sparse_nlp_jacobian (e04vjc) Example Program Results\n");

    /* Skip heading in data file */
    scanf("%*[\n] ");
    scanf("%ld%ld%*[\n] ", &n, &nf);
    if (n > 0 && nf > 0)
    {
        nfname = 1;
        nxname = 1;
        lena = 300;
        leng = 300;
        /* Allocate memory */
        if (!(fnames = NAG_ALLOC(nfname, char *)) ||
            !(xnames = NAG_ALLOC(nxname, char *)) ||
            !(a = NAG_ALLOC(lena, double)) ||
            !(f = NAG_ALLOC(nf, double)) ||
            !(flow = NAG_ALLOC(nf, double)) ||
            !(fmul = NAG_ALLOC(nf, double)) ||
            !(fupp = NAG_ALLOC(nf, double)) ||
            !(x = NAG_ALLOC(n, double)) ||
            !(xlow = NAG_ALLOC(n, double)) ||
            !(xmul = NAG_ALLOC(n, double)) ||
            !(xupp = NAG_ALLOC(n, double)) ||
            !(fstate = NAG_ALLOC(nf, Integer)) ||
            !(iafun = NAG_ALLOC(lena, Integer)) ||
            !(igfun = NAG_ALLOC(leng, Integer)) ||
            !(javar = NAG_ALLOC(lena, Integer)) ||
            !(jgvar = NAG_ALLOC(leng, Integer)) ||
            !(xstate = NAG_ALLOC(n, Integer)))
        {
            printf("Allocation failure\n");
            exit_status = -1;
            goto END;
        }
    }
    else
    {
        printf("Invalid n or nf\n");
        exit_status = 1;
        goto END;
    }

    /* nag_opt_sparse_nlp_init (e04vjc).

```

```

* Initialization function for nag_opt_sparse_nlp_solve
* (e04vhc)
*/
nag_opt_sparse_nlp_init(&state, &fail);
if (fail.code != NE_NOERROR)
{
    printf(
        "Initialisation of nag_opt_sparse_nlp_init (e04vjc) failed.\n%s\n",
        fail.message);
    exit_status = 1;
    goto END;
}

/* Read the bounds on the variables. */
for (i = 1; i <= n; ++i)
{
    scanf("%lf%lf%*[\n] ", &xlow[i - 1], &xupp[i - 1]);
}

for (i = 1; i <= n; ++i)
{
    x[i - 1] = 0.;
}

/* Illustrate how to pass information to the user-supplied
function usrfun via the comm structure */
comm.p = 0;

/* Determine the Jacobian structure. */
/* nag_opt_sparse_nlp_jacobian (e04vjc).
* Determine the pattern of nonzeros in the Jacobian matrix
* for nag_opt_sparse_nlp_solve (e04vhc)
*/
nag_opt_sparse_nlp_jacobian(nf, n, usrfun, iafun, javar, a, lena, &nea,
                            igfun, jgvar, leng, &neg, x, xlow, xupp,
                            &state, &comm, &fail);
if (fail.code != NE_NOERROR)
{
    printf("nag_opt_sparse_nlp_jacobian (e04vjc) failed to determine the"
        " Jacobian structure\n");
    exit_status = 1;
    goto END;
}

/* Print the Jacobian structure. */

printf("\n");
printf("NEA (the number of non-zero entries in A) = %3ld\n", nea);

printf(" I      IAFUN(I)   JAVAR(I)      A(I)\n");
printf("----      - - - - -      - - - - -      - - - - -\n");

for (i = 1; i <= nea; ++i)
{
    printf("%3ld%10ld%10ld%18.4e\n", i, iafun[i - 1],
        javar[i - 1], a[i - 1]);
}

printf("\n");
printf("NEG (the number of non-zero entries in G) = %3ld\n", neg);
printf(" I      IGFUN(I)   JGVAR(I)\n");
printf("----      - - - - -      - - - - -\n");

for (i = 1; i <= neg; ++i)
{
    printf("%3ld%10ld%10ld\n", i, igfun[i - 1],
        jgvar[i - 1]);
}

/* Now that we have the determined the structure of the
* Jacobian, set up the information necessary to solve

```

```

    * the optimization problem.
    */
start = Nag_Cold;
strcpy(prob, "          ");
objadd = 0.0;
for (i = 1; i <= n; ++i)
    {
        x[i - 1] = 0.;
        xstate[i - 1] = 0;
        xmul[i - 1] = 0.;
    }
for (i = 1; i <= nf; ++i)
    {
        f[i - 1] = 0.;
        fstate[i - 1] = 0;
        fmul[i - 1] = 0.;
    }

/* The row containing the objective function. */
scanf("%ld%*[\n] ", &objrow);

/* Read the bounds on the functions. */
for (i = 1; i <= nf; ++i)
    {
        scanf("%lf%lf%*[\n] ", &flow[i - 1], &fupp[i - 1]);
    }

/* By default nag_opt_sparse_nlp_solve (e04vhc) does not print monitoring
 * information. Call nag_open_file (x04acc) to set the print file fileid
 */
/* nag_open_file (x04acc).
 * Open unit number for reading, writing or appending, and
 * associate unit with named file
 */
nag_open_file("", 2, &fileid, &fail);
if (fail.code != NE_NOERROR)
    {
        exit_status = 2;
        goto END;
    }
/* nag_opt_sparse_nlp_option_set_integer (e04vmc).
 * Set a single option for nag_opt_sparse_nlp_solve (e04vhc)
 * from an integer argument
 */
nag_opt_sparse_nlp_option_set_integer("Print file", fileid, &state, &fail);
if (fail.code != NE_NOERROR)
    {
        exit_status = 1;
        goto END;
    }

/* Tell nag_opt_sparse_nlp_solve (e04vhc) that we supply no derivatives in
 * usrfun. */
/* nag_opt_sparse_nlp_option_set_string (e04vlc).
 * Set a single option for nag_opt_sparse_nlp_solve (e04vhc)
 * from a character string
 */
nag_opt_sparse_nlp_option_set_string("Derivative option 0", &state, &fail);
if (fail.code != NE_NOERROR)
    {
        exit_status = 1;
        goto END;
    }
}
for (i = 1; i <= nfname; ++i)
    {
        fnames[i - 1] = NAG_ALLOC(9, char);
        strcpy(fnames[i-1], "");
    }

for (i = 1; i <= nxname; ++i)
    {

```

```

        xnames[i-1] = NAG_ALLOC(9, char);
        strcpy(xnames[i-1], "");
    }

/* Solve the problem. */
/* nag_opt_sparse_nlp_solve (e04vhc).
 * General sparse nonlinear optimizer
 */
fflush(stdout);
nag_opt_sparse_nlp_solve(start, nf, n, nxname, nfname, objadd, objrow, prob,
                        usrfun, iafun, javar, a, lena, nea, igfun, jgvar,
                        leng, neg, xlow, xupp, (const char **) xnames, flow,
                        fupp, (const char **) fnames, x, xstate, xmul, f,
                        fstate, fmul, &ns, &ninf, &sinf, &state, &comm,
                        &fail);
if (fail.code == NE_NOERROR || fail.code == NW_NOT_FEASIBLE)
{
    printf("Final objective value = %11.1f\n", f[objrow - 1]);
    printf("Optimal X = ");

    for (i = 1; i <= n; ++i)
        printf("%9.2f%s", x[i - 1], i%7 == 0 || i == n ? "\n" : " ");
}
else
{
    printf("Error message from nag_opt_sparse_nlp_solve (e04vhc).\n%s\n",
          fail.message);
    exit_status = 1;
    goto END;
}
fflush(stdout);

if (fail.code != NE_NOERROR)
    exit_status = 2;

END:
for (i = 0; i < nxname; i++)
    NAG_FREE(xnames[i]);
for (i = 0; i < nfname; i++)
    NAG_FREE(fnames[i]);
NAG_FREE(fnames);
NAG_FREE(xnames);
NAG_FREE(a);
NAG_FREE(f);
NAG_FREE(flow);
NAG_FREE(fmul);
NAG_FREE(fupp);
NAG_FREE(x);
NAG_FREE(xlow);
NAG_FREE(xmul);
NAG_FREE(xupp);
NAG_FREE(fstate);
NAG_FREE(iafun);
NAG_FREE(igfun);
NAG_FREE(javar);
NAG_FREE(jgvar);
NAG_FREE(xstate);

return exit_status;
}

static void NAG_CALL usrfun(Integer *status, Integer n, const double x[],
                            Integer needf, Integer nf, double f[],
                            Integer needg, Integer leng, double g[],
                            Nag_Comm *comm)
{
    /* Parameter adjustments */
#define X(I) x[(I) - 1]
#define F(I) f[(I) - 1]
#define G(I) g[(I) - 1]

```

```

/* Check whether information came from the main program
   via the comm structure. Even if it was, we ignore it
   in this example. */
if (comm->p)
    printf("Pointer %p was passed to usrfun via the comm struct\n", comm->p);

/* Function Body */
if (needf > 0)
{
    F(1) = sin(-X(1) - .25) * 1e3 + sin(-X(2) - .25) * 1e3 - X(3);
    F(2) = sin(X(1) - .25) * 1e3 + sin(X(1) - X(2) - .25) * 1e3 - X(4);
    F(3) = sin(X(2) - X(1) - .25) * 1e3 + sin(X(2) - .25) * 1e3;
    F(4) = -X(1) + X(2);
    F(5) = X(1) - X(2);
    F(6) = X(3) * (X(3) * X(3)) * 1e-6 + X(4) * (X(4) * X(4)) * 2e-6 / 3.
    + X(3) * 3 + X(4) * 2;
}

return;
} /* usrfun */

```

10.2 Program Data

```

nag_opt_sparse_nlp_jacobian (e04vjc) Example Program Data
 4   6           : Values of n and nf
-0.55E0   0.55E0 : Bounds on the variables, XLOW(i), XUPP(i), for i = 1 to n
-0.55E0   0.55E0
 0.0E0  1200.0E0
 0.0E0  1200.0E0

 6           : Value of objrow
-894.8E0 -894.8E0 : Bounds on the functions, FLOW(i), FUPP(i), for i = 1 to nf
-894.8E0 -894.8E0
-1294.8E0 -1294.8E0
-0.55E0   1.0E25
-0.55E0   1.0E25
-1.0E25   1.0E25

```

10.3 Program Results

nag_opt_sparse_nlp_jacobian (e04vjc) Example Program Results

NEA (the number of non-zero entries in A) = 4

| I | IAFUN(I) | JAVAR(I) | A(I) |
|---|----------|----------|-------------|
| 1 | 4 | 1 | -1.0000e+00 |
| 2 | 5 | 1 | 1.0000e+00 |
| 3 | 4 | 2 | 1.0000e+00 |
| 4 | 5 | 2 | -1.0000e+00 |

NEG (the number of non-zero entries in G) = 10

| I | IGFUN(I) | JGVAR(I) |
|----|----------|----------|
| 1 | 1 | 1 |
| 2 | 2 | 1 |
| 3 | 3 | 1 |
| 4 | 1 | 2 |
| 5 | 2 | 2 |
| 6 | 3 | 2 |
| 7 | 6 | 3 |
| 8 | 6 | 4 |
| 9 | 1 | 3 |
| 10 | 2 | 4 |

Parameters
=====

Files

```

-----
Solution file..... 0      Old basis file ..... 0      (Print file)..... 6

```

```

Insert file..... 0      New basis file ..... 0      (Summary file)..... 0
Punch file..... 0      Backup basis file..... 0
Load file..... 0      Dump file..... 0

Frequencies
-----
Print frequency..... 100    Check frequency..... 60      Save new basis map..... 100
Summary frequency..... 100    Factorization frequency 50      Expand frequency..... 10000

QP subproblems
-----
QP solver Cholesky.....
Scale tolerance..... 0.900    Minor feasibility tol.. 1.00E-06    Iteration limit..... 10000
Scale option..... 0      Minor optimality tol.. 1.00E-06    Minor print level..... 1
Crash tolerance..... 0.100    Pivot tolerance..... 2.05E-11    Partial price..... 1
Crash option..... 3      Elastic weight..... 1.00E+04    Prtl price section ( A) 4
New superbasics..... 99      Prtl price section (-I) 5

The SQP Method
-----
Minimize.....
Nonlinear objectiv vars 2      Cold start.....
Unbounded step size... 1.00E+20    Objective Row..... 6      Proximal Point method.. 1
Unbounded objective... 1.00E+15    Superbasics limit..... 4      Function precision.... 1.72E-13
Major step limit..... 2.00E+00    Reduced Hessian dim... 4      Difference interval... 4.15E-07
Major iterations limit. 1000    Nonderiv. linesearch.. 0      Central difference int. 5.57E-05
Minor iterations limit. 500      Line search tolerance... 0.90000    Derivative option..... 0
Penalty parameter..... 0.00E+00    Verify level..... 0
Major optimality tol... 2.00E-06    Major Print Level..... 1

Hessian Approximation
-----
Full-Memory Hessian...      Hessian updates..... 99999999    Hessian frequency..... 99999999
Hessian flush..... 99999999

Nonlinear constraints
-----
Nonlinear constraints.. 3      Major feasibility tol.. 1.00E-06    Violation limit..... 1.00E+06
Nonlinear Jacobian vars 4

Miscellaneous
-----
LU factor tolerance... 3.99    LU singularity tol.... 2.05E-11    Timing level..... 0
LU update tolerance... 3.99    LU swap tolerance..... 1.03E-04    Debug level..... 0
LU partial pivoting...      eps (machine precision) 1.11E-16    System information..... No

Matrix statistics
-----
Total      Normal      Free      Fixed      Bounded
Rows       5          2          0          3          0
Columns   4          0          0          0          4

No. of matrix elements      12      Density      60.000
Biggest      1.0000E+00 (excluding fixed columns,
Smallest     0.0000E+00 free rows, and RHS)

No. of objective coefficients      0

Nonlinear constraints      3      Linear constraints      2
Nonlinear variables      4      Linear variables      0
Jacobian variables      4      Objective variables      2
Total constraints      5      Total variables      4

The user has defined      0 out of      10 first derivatives

```

| Itns | Major | Minors | Step | nCon | Feasible | Optimal | MeritFunction | L+U | BSwap | nS | condHz | Penalty |
|------|-------|--------|---------|------|----------------------|---------------|---------------|-----|-------|----|---------|---------------|
| 3 | 0 | 3 | | 1 | 8.0E+02 | 1.0E-00 | 0.0000000E+00 | 14 | | 1 | 3.0E+07 | _ r |
| 4 | 1 | 1 | 1.2E-03 | 2 | 4.0E+02 | 1.0E-00 | 1.7331708E+06 | 13 | | 1 | 1.3E+07 | 5.1E+00 _n r1 |
| 5 | 2 | 1 | 1.3E-03 | 3 | 2.7E+02 | 5.5E-01 | 1.7301151E+06 | 13 | | | | 5.1E+00 _s 1 |
| 5 | 3 | 0 | 7.5E-03 | 4 | 8.8E+01 | 5.4E-01 | 8.8193381E+05 | 13 | | | | 2.8E+00 _ 1 |
| 5 | 4 | 0 | 2.3E-02 | 5 | 2.9E+01 | 5.3E-01 | 8.4262004E+05 | 13 | | | | 2.8E+00 _ 1 |
| 5 | 5 | 0 | 6.9E-02 | 6 | 8.9E+00 | 5.2E-01 | 7.3075567E+05 | 13 | | | | 2.8E+00 _ 1 |
| 6 | 6 | 1 | 2.2E-01 | 7 | 2.3E+00 | 8.0E+01 | 4.4817382E+05 | 13 | | 1 | 1.2E+04 | 2.8E+00 _ 1 |
| 7 | 7 | 1 | 8.3E-01 | 8 | 1.7E-01 | 9.2E+00 | 2.4330986E+04 | 13 | | 1 | 9.5E+03 | 2.8E+00 _ 1 |
| 8 | 8 | 1 | 1.0E+00 | 9 | 6.5E-03 | 4.0E+01 | 5.3126065E+03 | 13 | 1 | 1 | 1.3E+02 | 2.8E+00 _ |
| 9 | 9 | 1 | 1.0E+00 | 10 | 4.6E-03 | 1.2E+01 | 5.1602362E+03 | 13 | | 1 | 9.4E+01 | 2.8E+00 _ |
| 10 | 10 | 1 | 1.0E+00 | 11 | 2.3E-04 | 6.1E-02 | 5.1265654E+03 | 13 | | 1 | 9.6E+01 | 2.8E+00 _ |
| 11 | 11 | 1 | 1.0E+00 | 12 | (1.3E-08) | 2.9E-04 | 5.1264981E+03 | 13 | | 1 | 1.2E+02 | 2.8E+00 _ c |
| 12 | 11 | 2 | 1.0E+00 | 12 | (1.3E-08) | 2.7E-04 | 5.1264981E+03 | 13 | | 1 | 1.2E+02 | 2.8E+00 _ c |
| 13 | 12 | 1 | 1.0E+00 | 13 | (5.6E-13) | 7.1E-05 | 5.1264981E+03 | 13 | | 1 | 9.5E+01 | 2.8E+00 _ c |
| 14 | 13 | 1 | 1.0E+00 | 14 | (1.8E-14)(5.8E-11) | 5.1264981E+03 | 5.1264981E+03 | 13 | | 1 | 9.5E+01 | 2.8E+00 _ c |

E04VHU EXIT 0 -- finished successfully
 E04VHU INFO 1 -- optimality conditions satisfied

Problem name
 No. of iterations 14 Objective value 5.1264981096E+03
 No. of major iterations 13 Linear objective 0.0000000000E+00
 Penalty parameter 2.780E+00 Nonlinear objective 5.1264981096E+03
 No. of calls to funobj 106 No. of calls to funcon 106
 Calls with modes 1,2 (known g) 14 Calls with modes 1,2 (known g) 14
 Calls for forward differencing 48 Calls for forward differencing 48
 Calls for central differencing 24 Calls for central differencing 24
 No. of superbasics 1 No. of basic nonlinears 3
 No. of degenerate steps 0 Percentage 0.00
 Max x 2 1.0E+03 Max pi 3 5.5E+00
 Max Primal infeas 0 0.0E+00 Max Dual infeas 1 5.6E-10
 Nonlinear constraint violn 1.5E-11

Name Objective Value 5.1264981096E+03
 Status Optimal Soln Iteration 14 Superbasics 1

Objective (Min)
 RHS
 Ranges
 Bounds

Section 1 - Rows

| Number | ..Row.. | State | ...Activity... | Slack | Activity | ..Lower Limit. | ..Upper Limit. | ..Dual Activity | ..i |
|--------|---------|-------|----------------|-------------|----------|----------------|----------------|-----------------|-----|
| 5 | r | 1 | EQ | -894.80000 | 0.00000 | -894.80000 | -894.80000 | -4.38698 | 1 |
| 6 | r | 2 | EQ | -894.80000 | 0.00000 | -894.80000 | -894.80000 | -4.10563 | 2 |
| 7 | r | 3 | EQ | -1294.80000 | 0.00000 | -1294.80000 | -1294.80000 | -5.46328 | 3 |
| 8 | r | 4 | BS | -0.51511 | 0.03489 | -0.55000 | None | . | 4 |
| 9 | r | 5 | BS | 0.51511 | 1.06511 | -0.55000 | None | . | 5 |

Section 2 - Columns

| Number | .Column. | State | ...Activity... | .Obj Gradient. | ..Lower Limit. | ..Upper Limit. | Reduced Gradnt | m+j | |
|--------|----------|-------|----------------|----------------|----------------|----------------|----------------|----------|---|
| 1 | x | 1 | BS | 0.11888 | . | -0.55000 | 0.55000 | 0.00000 | 6 |
| 2 | x | 2 | BS | -0.39623 | . | -0.55000 | 0.55000 | 0.00000 | 7 |
| 3 | x | 3 | SBS | 679.94532 | 4.38698 | . | 1200.00000 | -0.00000 | 8 |
| 4 | x | 4 | BS | 1026.06713 | 4.10563 | . | 1200.00000 | 0.00000 | 9 |

Final objective value = 5126.5
 Optimal X = 0.12 -0.40 679.95 1026.07