

NAG Library Function Document

nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc)

1 Purpose

nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) computes the action of the matrix exponential e^{tA} , on the matrix B , where A is a complex n by n matrix, B is a complex n by m matrix and t is a complex scalar. It uses reverse communication for evaluating matrix products, so that the matrix A is not accessed explicitly.

2 Specification

```
#include <nag.h>
#include <nagf01.h>

void nag_matop_complex_gen_matrix_actexp_rcomm (Integer *irevcm, Integer n,
Integer m, Complex b[], Integer pdb, Complex t, Complex tr,
Complex b2[], Integer pdb2, Complex x[], Integer pdx, Complex y[],
Integer pdy, Complex p[], Complex r[], Complex z[], Complex ccomm[],
double comm[], Integer icomm[], NagError *fail)
```

3 Description

$e^{tA}B$ is computed using the algorithm described in Al-Mohy and Higham (2011) which uses a truncated Taylor series to compute the $e^{tA}B$ without explicitly forming e^{tA} .

The algorithm does not explicitly need to access the elements of A ; it only requires the result of matrix multiplications of the form AX or A^HY . A reverse communication interface is used, in which control is returned to the calling program whenever a matrix product is required.

4 References

Al-Mohy A H and Higham N J (2011) Computing the action of the matrix exponential, with an application to exponential integrators *SIAM J. Sci. Statist. Comput.* **33(2)** 488-511

Higham N J (2008) *Functions of Matrices: Theory and Computation* SIAM, Philadelphia, PA, USA

5 Arguments

Note: this function uses **reverse communication**. Its use involves an initial entry, intermediate exits and re-entries, and a final exit, as indicated by the **argument irevcm**. Between intermediate exits and re-entries, **all arguments other than b2, x, y, p and r must remain unchanged**.

1: **irevcm** – Integer * *Input/Output*

On initial entry: must be set to 0.

On intermediate exit: **irevcm** = 1, 2, 3, 4 or 5. The calling program must:

- (a) if **irevcm** = 1: evaluate $B_2 = AB$, where B_2 is an n by m matrix, and store the result in **b2**;
if **irevcm** = 2: evaluate $Y = AX$, where X and Y are n by 2 matrices, and store the result in **y**;
if **irevcm** = 3: evaluate $X = A^HY$ and store the result in **x**;
if **irevcm** = 4: evaluate $p = Az$ and store the result in **p**;
if **irevcm** = 5: evaluate $r = A^Hz$ and store the result in **r**.
- (b) call nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) again with all other parameters unchanged.

- On final exit: **irevcn** = 0.
- 2: **n** – Integer Input
 On entry: n , the order of the matrix A .
 Constraint: $n \geq 0$.
- 3: **m** – Integer Input
 On entry: the number of columns of the matrix B .
 Constraint: $m \geq 0$.
- 4: **b**[dim] – Complex Input/Output
Note: the dimension, dim , of the array **b** must be at least $pdb \times m$.
 The (i, j) th element of the matrix B is stored in $b[(j - 1) \times pdb + i - 1]$.
 On initial entry: the n by m matrix B .
 On intermediate exit: if **irevcn** = 1, contains the n by m matrix B .
 On intermediate re-entry: must not be changed.
 On final exit: the n by m matrix $e^{tA}B$.
- 5: **pdb** – Integer Input
 On entry: the stride separating matrix row elements in the array **b**.
 Constraint: $pdb \geq n$.
- 6: **t** – Complex Input
 On entry: the scalar t .
- 7: **tr** – Complex Input
 On entry: the trace of A . If this is not available then any number can be supplied (0 is a reasonable default); however, in the trivial case, $n = 1$, the result $e^{trt}B$ is immediately returned in the first row of B . See Section 9.
- 8: **b2**[dim] – Complex Input/Output
Note: the dimension, dim , of the array **b2** must be at least $pdb2 \times m$.
 The (i, j) th element of the matrix is stored in $b2[(j - 1) \times pdb2 + i - 1]$.
 On initial entry: need not be set.
 On intermediate re-entry: if **irevcn** = 1, must contain AB .
 On final exit: the array is undefined.
- 9: **pdb2** – Integer Input
 On entry: the stride separating matrix row elements in the array **b2**.
 Constraint: $pdb2 \geq n$.
- 10: **x**[dim] – Complex Input/Output
Note: the dimension, dim , of the array **x** must be at least $pdx \times 2$.
 The (i, j) th element of the matrix X is stored in $x[(j - 1) \times pdx + i - 1]$.
 On initial entry: need not be set.

On intermediate exit: if **irevcn** = 2, contains the current n by 2 matrix X .

On intermediate re-entry: if **irevcn** = 3, must contain $A^H Y$.

On final exit: the array is undefined.

- 11: **pdx** – Integer *Input*
On entry: the stride separating matrix row elements in the array **x**.
Constraint: **pdx** \geq **n**.
- 12: **y[*dim*]** – Complex *Input/Output*
Note: the dimension, *dim*, of the array **y** must be at least **pdy** \times 2.
The (*i*, *j*)th element of the matrix Y is stored in **y**[(*j* – 1) \times **pdy** + *i* – 1].
On initial entry: need not be set.
On intermediate exit: if **irevcn** = 3, contains the current n by 2 matrix Y .
On intermediate re-entry: if **irevcn** = 2, must contain AX .
On final exit: the array is undefined.
- 13: **pdy** – Integer *Input*
On entry: the stride separating matrix row elements in the array **y**.
Constraint: **pdy** \geq **n**.
- 14: **p[n]** – Complex *Input/Output*
On initial entry: need not be set.
On intermediate re-entry: if **irevcn** = 4, must contain Az .
On final exit: the array is undefined.
- 15: **r[n]** – Complex *Input/Output*
On initial entry: need not be set.
On intermediate re-entry: if **irevcn** = 5, must contain $A^H z$.
On final exit: the array is undefined.
- 16: **z[n]** – Complex *Input/Output*
On initial entry: need not be set.
On intermediate exit: if **irevcn** = 4 or 5, contains the vector z .
On intermediate re-entry: must not be changed.
On final exit: the array is undefined.
- 17: **ccomm**[**n** \times (**m** + 2)] – Complex *Communication Array*
- 18: **comm**[3 \times **n** + 14] – double *Communication Array*
- 19: **icomm**[2 \times **n** + 40] – Integer *Communication Array*
- 20: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{m} = \langle value \rangle$.

Constraint: $\mathbf{m} \geq 0$.

On entry, $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{n} \geq 0$.

On initial entry, $\mathbf{irevcn} = \langle value \rangle$.

Constraint: $\mathbf{irevcn} = 0$.

On intermediate re-entry, $\mathbf{irevcn} = \langle value \rangle$.

Constraint: $\mathbf{irevcn} = 1, 2, 3, 4$ or 5 .

NE_INT_2

On entry, $\mathbf{pdb} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{pdb} \geq \mathbf{n}$.

On entry, $\mathbf{pdb2} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{pdb2} \geq \mathbf{n}$.

On entry, $\mathbf{pdx} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{pdx} \geq \mathbf{n}$.

On entry, $\mathbf{pdy} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{pdy} \geq \mathbf{n}$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NW_SOME_PRECISION_LOSS

$e^{tA}B$ has been computed using an IEEE double precision Taylor series, although the arithmetic precision is higher than IEEE double precision.

7 Accuracy

For an Hermitian matrix A (for which $A^H = A$) the computed matrix $e^{tA}B$ is guaranteed to be close to the exact matrix, that is, the method is forward stable. No such guarantee can be given for non-Hermitian matrices. See Section 4 of Al-Mohy and Higham (2011) for details and further discussion.

8 Parallelism and Performance

Not applicable.

9 Further Comments

9.1 Use of $Tr(A)$

The elements of A are not explicitly required by `nag_matop_complex_gen_matrix_actexp_rcomm` (f01hbc). However, the trace of A is used in the preprocessing phase of the algorithm. If $Tr(A)$ is not available to the calling function then any number can be supplied (0 is recommended). This will not affect the stability of the algorithm, but it may reduce its efficiency.

9.2 When to use nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc)

nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) is designed to be used when A is large and sparse. Whenever a matrix multiplication is required, the function will return control to the calling program so that the multiplication can be done in the most efficient way possible. Note that $e^{tA}B$ will not, in general, be sparse even if A is sparse.

If A is small and dense then nag_matop_complex_gen_matrix_actexp (f01hac) can be used to compute $e^{tA}B$ without the use of a reverse communication interface.

The real analog of nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) is nag_matop_real_gen_matrix_actexp_rcomm (f01gbc).

9.3 Use in Conjunction with NAG C Library Functions

To compute $e^{tA}B$, the following skeleton code can normally be used:

```
do {
  f01hbc(&irevcm,n,m,b,tdb,t,tr,b2,tdb2,x,tdx,y,tdy,p,r,z,ccomm,comm, &
        icomm,&fail);
  if (irevcm == 1) {
    .. Code to compute B2=AB ..
  }
  else if (irevcm == 2){
    .. Code to compute Y=AX ..
  }
  else if (irevcm == 3){
    .. Code to compute X=A^H Y ..
  }
  else if (irevcm == 4){
    .. Code to compute P=AZ ..
  }
  else if (irevcm == 5){
    .. Code to compute R=A^H Z ..
  }
} (while irevcm !=0)
```

The code used to compute the matrix products will vary depending on the way A is stored. If all the elements of A are stored explicitly, then nag_zgemm (f16zac) can be used. If A is triangular then nag_ztrmm (f16zfc) should be used. If A is Hermitian, then nag_zhemm (f16zcc) should be used. If A is symmetric, then nag_zsymm (f16ztc) should be used. For sparse A stored in coordinate storage format nag_sparse_nherm_matvec (f11xnc) and nag_sparse_herm_matvec (f11xsc) can be used. For sparse A stored in compressed column storage format (CCS) the program text of Section 10 contains the function matmul to perform matrix products.

10 Example

This example computes $e^{tA}B$ where

$$A = \begin{pmatrix} 0.7 + 0.8i & -0.2 + 0.0i & 1.0 + 0.0i & 0.6 + 0.5i \\ 0.3 + 0.7i & 0.7 + 0.0i & 0.9 + 3.0i & 1.0 + 0.8i \\ 0.3 + 3.0i & -0.7 + 0.0i & 0.2 + 0.6i & 0.7 + 0.5i \\ 0.0 + 0.9i & 4.0 + 0.0i & 0.0 + 0.0i & 0.2 + 0.0i \end{pmatrix},$$

$$B = \begin{pmatrix} 0.1 + 0.0i & 1.2 + 0.1i \\ 1.3 + 0.9i & -0.2 + 2.0i \\ 4.0 + 0.6i & -1.0 + 0.8i \\ 0.4 + 0.0i & -0.9 + 0.0i \end{pmatrix}$$

and

$$t = 1.1 + 0.0i.$$

A is stored in compressed column storage format (CCS) and matrix multiplications are performed using the function matmul.

10.1 Program Text

```

/* nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) Example Program.
 *
 * Copyright 2013 Numerical Algorithms Group.
 *
 * Mark 24, 2013.
 */

#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <naga02.h>
#include <nagf01.h>
#include <nagf11.h>
#include <nagf16.h>
#include <nagx02.h>
#include <nagx04.h>

static void matmul(Nag_TransType tran, Integer n, Integer m, Complex a[],
                  Integer icolzp[], Integer irowix[], Complex b[],
                  Complex c[]);

int main(void)
{
    /* Scalars */
    Integer      exit_status = 0, irevcm = 0;
    Integer      i, j, m, n, nnz, ldb, ldb2, ldx, ldy;
    Complex      t, tr;

    /* Arrays */
    Complex      *a = 0, *b = 0, *b2 = 0, *ccomm = 0;
    Complex      *p = 0, *r = 0, *x = 0, *y = 0, *z = 0;
    double       *comm = 0;
    Integer      *icolzp = 0, *irowix = 0, *icomm = 0;

    /* Nag Types */
    NagError      fail;
    Nag_OrderType order = Nag_ColMajor;
    Nag_TransType tran = Nag_ConjTrans, notran = Nag_NoTrans;

    INIT_FAIL(fail);

#define B(I, J) b[(J-1)*ldb + I-1]

    /* Output preamble */
    printf("nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) ");
    printf("Example Program Results\n\n");
    fflush(stdout);

    /* Skip heading in data file */
    scanf("%*[\n]");

    /* Read in the problem size and the value of the parameter t */
    scanf("%ld %ld (%lf , %lf ) %*[\n]", &n, &m, &t.re, &t.im);

    ldb = ldb2 = ldx = ldy = n;

    if (!(b = NAG_ALLOC(n*m, Complex)) ||
        !(b2 = NAG_ALLOC(n*m, Complex)) ||
        !(ccomm = NAG_ALLOC(n*(m+2), Complex)) ||
        !(p = NAG_ALLOC(n, Complex)) ||
        !(r = NAG_ALLOC(n, Complex)) ||
        !(x = NAG_ALLOC(n*2, Complex)) ||
        !(y = NAG_ALLOC(n*2, Complex)) ||
        !(z = NAG_ALLOC(n, Complex)) ||
        !(comm = NAG_ALLOC(3*n+14, double)) ||
        !(icolzp = NAG_ALLOC(n+1, Integer)) ||
        !(icomm = NAG_ALLOC(2*n+40, Integer))) {
        printf("Allocation failure\n");
    }

```

```

    exit_status = -1;
    goto END;
}

/* Read in the sparse matrix a in compressed column format */
for (i = 0; i < n + 1; ++i)
    scanf("%ld", &icolzp[i]);
scanf("%*[\n]");

nnz = icolzp[n] - 1;

if (!(a = NAG_ALLOC(nnz, Complex)) ||
    !(irowix = NAG_ALLOC(nnz, Integer))) {
    printf("Allocation failure\n");
    exit_status = -2;
    goto END;
}

for (i = 0; i < nnz; ++i)
    scanf(" ( %lf , %lf ) %ld%*[\n]", &a[i].re, &a[i].im, &irowix[i]);

/* Read in the matrix b from data file */
for (i = 1; i <= n; i++)
    for (j = 1; j <= m; j++)
        scanf(" ( %lf , %lf ) ", &B(i, j).re, &B(i, j).im);
scanf("%*[\n]");

/* Compute the trace of A */
tr.re = 0.0;
tr.im = 0.0;
j = 1;
for (i = 0; i < nnz; ++i) {
    /* new column? */
    if (icolzp[j] <= i+1)
        j++;
    /* diagonal element? */
    if (irowix[i] == j) {
        tr.re += a[i].re;
        tr.im += a[i].im;
    }
}

/* Find exp(tA) B using
 * nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc)
 * Action of the exponential of a complex matrix on a complex matrix
 */
while (1) {
    nag_matop_complex_gen_matrix_actexp_rcomm(&irevcm, n, m, b, ldb, t, tr, b2,
                                             ldb2, x, ldx, y, ldy, p, r, z,
                                             ccomm, comm, icomm, &fail);

    switch(irevcm) {
    case 0:
        /* Final exit.*/
        goto END_REVCM;
        break;
    case 1 :
        /* Compute AB and store in B2 */
        matmul(notran, n, m, a, icolzp, irowix, b, b2);
    case 2 :
        /* Compute AX and store in Y */
        matmul(notran, n, 2, a, icolzp, irowix, x, y);
    case 3 :
        /* Compute A^H Y and store in X */
        matmul(tran, n, 2, a, icolzp, irowix, y, x);
    case 4 :
        /* Compute AZ and store in P */
        matmul(notran, n, 1, a, icolzp, irowix, z, p);
    case 5 :
        /* Compute A^H Z and store in R */
        matmul(tran, n, 1, a, icolzp, irowix, z, r);
    }
}

```

```

    }
}

END_REVCM:
if (fail.code != NE_NOERROR) {
    printf("Error from nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc)\n"
           "%s\n", fail.message);
    exit_status = 2;
    goto END;
}

/* Print solution using
 * nag_gen_complex_mat_print (x04dac)
 * Print complex general matrix (easy-to-use)
 */
nag_gen_complex_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n, m,
                           b, ldb, "exp(tA) B", NULL, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_gen_complex_mat_print (x04dac)\n%s\n", fail.message);
    exit_status = 3;
    goto END;
}

END:
NAG_FREE(a);
NAG_FREE(b);
NAG_FREE(b2);
NAG_FREE(comm);
NAG_FREE(ccomm);
NAG_FREE(p);
NAG_FREE(r);
NAG_FREE(x);
NAG_FREE(y);
NAG_FREE(z);
NAG_FREE(icomm);
NAG_FREE(icolzp);
NAG_FREE(irowix);
return exit_status;
}

static void matmul(Nag_TransType tran, Integer n, Integer m, Complex a[],
                  Integer icolzp[], Integer irowix[], Complex b[],
                  Complex c[])
{
    Integer    i, ir, j, k, l;
    Complex    a1, a2, t1;

    for (j = 0; j < m*n; j++) {
        c[j].re = 0.0;
        c[j].im = 0.0;
    }
    if (tran==Nag_NoTrans) {
        l = -1;
        for(j = 0; j < m; j++) {
            for (i = 0; i < n; i++) {
                l++;
                t1.re = b[l].re;
                t1.im = b[l].im;
                for (k = icolzp[i]-1; k < icolzp[i+1] - 1; k++) {
                    ir = j*n + irowix[k] - 1;
                    /* Evaluate t1*a[k] using nag_complex_multiply (a02ccc). */
                    a1 = nag_complex_multiply(t1,a[k]);
                    c[ir].re += a1.re;
                    c[ir].im += a1.im;
                }
            }
        }
    } else {
        l = -1;
        for(j = 0; j < m; j++) {
            for (i = 0; i < n; i++) {

```



```

l++;
t1.re = 0.0;
t1.im = 0.0;
for (k = icolzp[i]-1; k < icolzp[i+1] - 1; k++) {
    ir = j*n + irowix[k] - 1;
    /* Evaluate conjg(a[k]) using nag_complex_conjg (a02cfc). */
    a2 = nag_complex_conjg(a[k]);
    /* Evaluate conjg(a[k])*b[ir] using nag_complex_multiply (a02ccc). */
    a1 = nag_complex_multiply(a2,b[ir]);
    t1.re += a1.re;
    t1.im += a1.im;
}
c[l].re += t1.re;
c[l].im += t1.im;
}
}
}
}
}
}
}
}

```

10.2 Program Data

nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) Example Program Data

```

4      2      (1.1,0.0)      : n, m and t

1      5      9      12      16 : icolzp

( 0.7,0.8)  1
( 0.3,0.7)  2
( 0.3,3.0)  3
( 0.0,0.9)  4
(-0.2,0.0)  1
( 0.7,0.0)  2
(-7.0,0.0)  3
( 4.0,0.0)  4
( 1.0,0.0)  1
( 0.9,3.0)  2
( 0.2,0.6)  3
( 0.6,0.5)  1
( 1.0,0.8)  2
( 0.7,0.5)  3
( 0.2,0.0)  4      : (a[i], irowix[i]) i = 0, nnz-1

( 0.1,0.0) ( 1.2,0.1)
( 1.3,0.9) (-0.2,2.0)
( 4.0,0.6) (-1.0,0.8)
( 0.4,0.0) (-0.9,0.0)      : matrix b

```

10.3 Program Results

nag_matop_complex_gen_matrix_actexp_rcomm (f01hbc) Example Program Results

```

exp(tA) B
      1      2
1  -15.3125  -4.5605
   5.9123   -2.4288

2   12.3396   9.2005
  -50.6993 -10.3632

3  -65.4353 -17.6075
   34.3271  -1.0019

4   45.6506  11.3339
  -28.3253   0.1127

```
