

NAG Library Function Document

nag_zpotri (f07fwc)

1 Purpose

nag_zpotri (f07fwc) computes the inverse of a complex Hermitian positive definite matrix A , where A has been factorized by nag_zpotrf (f07frc).

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_zpotri (Nag_OrderType order, Nag_UploType uplo, Integer n,
                Complex a[], Integer pda, NagError *fail)
```

3 Description

nag_zpotri (f07fwc) is used to compute the inverse of a complex Hermitian positive definite matrix A , the function must be preceded by a call to nag_zpotrf (f07frc), which computes the Cholesky factorization of A .

If **uplo** = Nag_Upper, $A = U^H U$ and A^{-1} is computed by first inverting U and then forming $(U^{-1})U^{-H}$.

If **uplo** = Nag_Lower, $A = L L^H$ and A^{-1} is computed by first inverting L and then forming $L^{-H}(L^{-1})$.

4 References

Du Croz J J and Higham N J (1992) Stability of methods for matrix inversion *IMA J. Numer. Anal.* **12** 1–19

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UploType *Input*

On entry: specifies how A has been factorized.

uplo = Nag_Upper
 $A = U^H U$, where U is upper triangular.

uplo = Nag_Lower
 $A = L L^H$, where L is lower triangular.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

3: **n** – Integer *Input*

On entry: n , the order of the matrix A .

Constraint: $n \geq 0$.

- 4: **a**[*dim*] – Complex *Input/Output*
Note: the dimension, *dim*, of the array **a** must be at least $\max(1, \mathbf{pda} \times \mathbf{n})$.
On entry: the upper triangular matrix *U* if **uplo** = Nag_Upper or the lower triangular matrix *L* if **uplo** = Nag_Lower, as returned by nag_zpotrf (f07frc).
On exit: *U* is overwritten by the upper triangle of A^{-1} if **uplo** = Nag_Upper; *L* is overwritten by the lower triangle of A^{-1} if **uplo** = Nag_Lower.
- 5: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix in the array **a**.
Constraint: **pda** $\geq \max(1, \mathbf{n})$.
- 6: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 0 .

On entry, **pda** = $\langle value \rangle$.

Constraint: **pda** > 0 .

NE_INT_2

On entry, **pda** = $\langle value \rangle$ and **n** = $\langle value \rangle$.

Constraint: **pda** $\geq \max(1, \mathbf{n})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_SINGULAR

Diagonal element $\langle value \rangle$ of the Cholesky factor is zero; the Cholesky factor is singular and the inverse of *A* cannot be computed.

7 Accuracy

The computed inverse *X* satisfies

$$\|XA - I\|_2 \leq c(n)\epsilon\kappa_2(A) \quad \text{and} \quad \|AX - I\|_2 \leq c(n)\epsilon\kappa_2(A),$$

where $c(n)$ is a modest function of *n*, ϵ is the *machine precision* and $\kappa_2(A)$ is the condition number of *A* defined by

$$\kappa_2(A) = \|A\|_2 \|A^{-1}\|_2.$$

8 Parallelism and Performance

nag_zpotri (f07fwc) is not threaded by NAG in any implementation.

nag_zpotri (f07fwc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of real floating-point operations is approximately $\frac{8}{3}n^3$.

The real analogue of this function is nag_dpotri (f07fjc).

10 Example

This example computes the inverse of the matrix A , where

$$A = \begin{pmatrix} 3.23 + 0.00i & 1.51 - 1.92i & 1.90 + 0.84i & 0.42 + 2.50i \\ 1.51 + 1.92i & 3.58 + 0.00i & -0.23 + 1.11i & -1.18 + 1.37i \\ 1.90 - 0.84i & -0.23 - 1.11i & 4.09 + 0.00i & 2.33 - 0.14i \\ 0.42 - 2.50i & -1.18 - 1.37i & 2.33 + 0.14i & 4.29 + 0.00i \end{pmatrix}.$$

Here A is Hermitian positive definite and must first be factorized by nag_zpotrf (f07frc).

10.1 Program Text

```

/* nag_zpotri (f07fwc) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer      i, j, n, pda;
    Integer      exit_status = 0;
    NagError     fail;
    Nag_UploType uplo;
    Nag_MatrixType matrix;
    Nag_OrderType order;
    /* Arrays */
    char         nag_enum_arg[40];
    Complex      *a = 0;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

```

```

printf("nag_zpotri (f07fwc) Example Program Results\n\n");

/* Skip heading in data file */
scanf("%*[^\\n] ");
scanf("%ld%*[^\\n] ", &n);
#ifdef NAG_COLUMN_MAJOR
  pda = n;
#else
  pda = n;
#endif

/* Allocate memory */
if (!(a = NAG_ALLOC(n * n, Complex)))
{
  printf("Allocation failure\n");
  exit_status = -1;
  goto END;
}

/* Read A from data file */
scanf(" %39s%*[^\\n] ", nag_enum_arg);
/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);

if (uplo == Nag_Upper)
{
  matrix = Nag_UpperMatrix;
  for (i = 1; i <= n; ++i)
  {
    for (j = i; j <= n; ++j)
      scanf(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
  }
  scanf("%*[^\\n] ");
}
else
{
  matrix = Nag_LowerMatrix;
  for (i = 1; i <= n; ++i)
  {
    for (j = 1; j <= i; ++j)
      scanf(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
  }
  scanf("%*[^\\n] ");
}

/* Factorize A */
/* nag_zpotrf (f07frc).
 * Cholesky factorization of complex Hermitian
 * positive-definite matrix
 */
nag_zpotrf(order, uplo, n, a, pda, &fail);
if (fail.code != NE_NOERROR)
{
  printf("Error from nag_zpotrf (f07frc).\n%s\n", fail.message);
  exit_status = 1;
  goto END;
}

/* Compute inverse of A */
/* nag_zpotri (f07fwc).
 * Inverse of complex Hermitian positive-definite matrix,
 * matrix already factorized by nag_zpotrf (f07frc)
 */
nag_zpotri(order, uplo, n, a, pda, &fail);
if (fail.code != NE_NOERROR)
{
  printf("Error from nag_zpotri (f07fwc).\n%s\n", fail.message);
  exit_status = 1;
  goto END;
}

```

```

    }
    /* Print inverse */
    /* nag_gen_complx_mat_print_comp (x04dbc).
    * Print complex general matrix (comprehensive)
    */
    fflush(stdout);
    nag_gen_complx_mat_print_comp(order, matrix, Nag_NonUnitDiag, n, n, a, pda,
                                Nag_BracketForm, "%7.4f", "Inverse",
                                Nag_IntegerLabels, 0, Nag_IntegerLabels, 0, 80,
                                0, 0, &fail);

    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_gen_complx_mat_print_comp (x04dbc).\n%s\n",
              fail.message);
        exit_status = 1;
        goto END;
    }
END:
    NAG_FREE(a);
    return exit_status;
}

```

10.2 Program Data

```

nag_zpotri (f07fwc) Example Program Data
 4                                     :Value of n
  Nag_Lower                           :Value of uplo
(3.23, 0.00)
(1.51, 1.92) ( 3.58, 0.00)
(1.90,-0.84) (-0.23,-1.11) ( 4.09, 0.00)
(0.42,-2.50) (-1.18,-1.37) ( 2.33, 0.14) ( 4.29, 0.00) :End of matrix A

```

10.3 Program Results

```

nag_zpotri (f07fwc) Example Program Results

Inverse
      1          2          3          4
1 ( 5.4691, 0.0000)
2 (-1.2624,-1.5491) ( 1.1024, 0.0000)
3 (-2.9746,-0.9616) ( 0.8989,-0.5672) ( 2.1589, 0.0000)
4 ( 1.1962, 2.9772) (-0.9826,-0.2566) (-1.3756,-1.4550) ( 2.2934,-0.0000)

```
