

NAG Library Function Document

nag_dsytrf (f07mdc)

1 Purpose

nag_dsytrf (f07mdc) computes the Bunch–Kaufman factorization of a real symmetric indefinite matrix.

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_dsytrf (Nag_OrderType order, Nag_UploType uplo, Integer n,
                double a[], Integer pda, Integer ipiv[], NagError *fail)
```

3 Description

nag_dsytrf (f07mdc) factorizes a real symmetric matrix A , using the Bunch–Kaufman diagonal pivoting method. A is factorized as either $A = PUDU^T P^T$ if **uplo** = Nag_Upper or $A = PLDL^T P^T$ if **uplo** = Nag_Lower, where P is a permutation matrix, U (or L) is a unit upper (or lower) triangular matrix and D is a symmetric block diagonal matrix with 1 by 1 and 2 by 2 diagonal blocks; U (or L) has 2 by 2 unit diagonal blocks corresponding to the 2 by 2 blocks of D . Row and column interchanges are performed to ensure numerical stability while preserving symmetry.

This method is suitable for symmetric matrices which are not known to be positive definite. If A is in fact positive definite, no interchanges are performed and no 2 by 2 blocks occur in D .

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UploType *Input*

On entry: specifies whether the upper or lower triangular part of A is stored and how A is to be factorized.

uplo = Nag_Upper

The upper triangular part of A is stored and A is factorized as $PUDU^T P^T$, where U is upper triangular.

uplo = Nag_Lower

The lower triangular part of A is stored and A is factorized as $PLDL^T P^T$, where L is lower triangular.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.
- 4: **a**[*dim*] – double *Input/Output*
Note: the dimension, *dim*, of the array **a** must be at least $\max(1, \mathbf{pda} \times \mathbf{n})$.
On entry: the n by n symmetric indefinite matrix A .
If **order** = 'Nag_ColMajor', A_{ij} is stored in $\mathbf{a}[(j-1) \times \mathbf{pda} + i - 1]$.
If **order** = 'Nag_RowMajor', A_{ij} is stored in $\mathbf{a}[(i-1) \times \mathbf{pda} + j - 1]$.
If **uplo** = 'Nag_Upper', the upper triangular part of A must be stored and the elements of the array below the diagonal are not referenced.
If **uplo** = 'Nag_Lower', the lower triangular part of A must be stored and the elements of the array above the diagonal are not referenced.
On exit: the upper or lower triangle of A is overwritten by details of the block diagonal matrix D and the multipliers used to obtain the factor U or L as specified by **uplo**.
- 5: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix A in the array **a**.
Constraint: $\mathbf{pda} \geq \max(1, \mathbf{n})$.
- 6: **ipiv**[*dim*] – Integer *Output*
Note: the dimension, *dim*, of the array **ipiv** must be at least $\max(1, \mathbf{n})$.
On exit: details of the interchanges and the block structure of D . More precisely,
if **ipiv**[$i-1$] = $k > 0$, d_{ii} is a 1 by 1 pivot block and the i th row and column of A were interchanged with the k th row and column;
if **uplo** = Nag_Upper and **ipiv**[$i-2$] = **ipiv**[$i-1$] = $-l < 0$, $\begin{pmatrix} d_{i-1,i-1} & \bar{d}_{i,i-1} \\ \bar{d}_{i,i-1} & d_{ii} \end{pmatrix}$ is a 2 by 2 pivot block and the $(i-1)$ th row and column of A were interchanged with the l th row and column;
if **uplo** = Nag_Lower and **ipiv**[$i-1$] = **ipiv**[i] = $-m < 0$, $\begin{pmatrix} d_{ii} & d_{i+1,i} \\ d_{i+1,i} & d_{i+1,i+1} \end{pmatrix}$ is a 2 by 2 pivot block and the $(i+1)$ th row and column of A were interchanged with the m th row and column.
- 7: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 0 .

On entry, **pda** = $\langle value \rangle$.

Constraint: **pda** > 0 .

NE_INT_2

On entry, **pda** = $\langle value \rangle$ and **n** = $\langle value \rangle$.

Constraint: **pda** $\geq \max(1, \mathbf{n})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_SINGULAR

$D(\langle value \rangle, \langle value \rangle)$ is exactly zero. The factorization has been completed, but the block diagonal matrix D is exactly singular, and division by zero will occur if it is used to solve a system of equations.

7 Accuracy

If **uplo** = Nag_Upper, the computed factors U and D are the exact factors of a perturbed matrix $A + E$, where

$$|E| \leq c(n)\epsilon P|U||D||U^T|P^T,$$

$c(n)$ is a modest linear function of n , and ϵ is the *machine precision*.

If **uplo** = Nag_Lower, a similar statement holds for the computed factors L and D .

8 Parallelism and Performance

nag_dsytrf (f07mdc) is not threaded by NAG in any implementation.

nag_dsytrf (f07mdc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The elements of D overwrite the corresponding elements of A ; if D has 2 by 2 blocks, only the upper or lower triangle is stored, as specified by **uplo**.

The unit diagonal elements of U or L and the 2 by 2 unit diagonal blocks are not stored. The remaining elements of U or L are stored in the corresponding columns of the array **a**, but additional row interchanges must be applied to recover U or L explicitly (this is seldom necessary). If **ipiv** $[i - 1] = i$, for $i = 1, 2, \dots, n$ (as is the case when A is positive definite), then U or L is stored explicitly (except for its unit diagonal elements which are equal to 1).

The total number of floating-point operations is approximately $\frac{1}{3}n^3$.

A call to nag_dsytrf (f07mdc) may be followed by calls to the functions:

nag_dsytrs (f07mec) to solve $AX = B$;

nag_dsycon (f07mgc) to estimate the condition number of A ;

nag_dsytri (f07mjc) to compute the inverse of A .

The complex analogues of this function are nag_zhetrf (f07mrc) for Hermitian matrices and nag_zsytrf (f07nrc) for symmetric matrices.

10 Example

This example computes the Bunch–Kaufman factorization of the matrix A , where

$$A = \begin{pmatrix} 2.07 & 3.87 & 4.20 & -1.15 \\ 3.87 & -0.21 & 1.87 & 0.63 \\ 4.20 & 1.87 & 1.15 & 2.06 \\ -1.15 & 0.63 & 2.06 & -1.81 \end{pmatrix}.$$

10.1 Program Text

```

/* nag_dsytrf (f07mdc) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer      i, j, n, nrhs, pda, pdb;
    Integer      exit_status = 0;
    NagError     fail;
    Nag_UploType uplo;
    Nag_OrderType order;
    /* Arrays */
    char         nag_enum_arg[40];
    Integer      *ipiv = 0;
    double       *a = 0, *b = 0;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
#define B(I, J) b[(J-1)*pdb + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
#define B(I, J) b[(I-1)*pdb + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_dsytrf (f07mdc) Example Program Results\n\n");
    /* Skip heading in data file */
    scanf("%*[\n] ");
    scanf("%ld%ld%*[\n] ", &n, &nrhs);
#ifdef NAG_COLUMN_MAJOR
    pda = n;
    pdb = n;
#else
    pda = n;
    pdb = nrhs;
#endif
    /* Allocate memory */
    if (!(ipiv = NAG_ALLOC(n, Integer)) ||
        !(a = NAG_ALLOC(n * n, double)) ||

```

```

    !(b = NAG_ALLOC(n * nrhs, double)))
  {
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
  }

/* Read A and B from data file */
scanf(" %39s%*[\n] ", nag_enum_arg);
/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);

if (uplo == Nag_Upper)
  {
    for (i = 1; i <= n; ++i)
      {
        for (j = i; j <= n; ++j)
          scanf("%lf", &A(i, j));
      }
    scanf("%*[\n] ");
  }
else
  {
    for (i = 1; i <= n; ++i)
      {
        for (j = 1; j <= i; ++j)
          scanf("%lf", &A(i, j));
      }
    scanf("%*[\n] ");
  }

for (i = 1; i <= n; ++i)
  {
    for (j = 1; j <= nrhs; ++j)
      scanf("%lf", &B(i, j));
  }
scanf("%*[\n] ");

/* Factorize A */
/* nag_dsytrf (f07mdc).
 * Bunch-Kaufman factorization of real symmetric indefinite
 * matrix
 */
nag_dsytrf(order, uplo, n, a, pda, ipiv, &fail);
if (fail.code != NE_NOERROR)
  {
    printf("Error from nag_dsytrf (f07mdc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
  }
/* Compute solution */
/* nag_dsytrs (f07mec).
 * Solution of real symmetric indefinite system of linear
 * equations, multiple right-hand sides, matrix already
 * factorized by nag_dsytrf (f07mdc)
 */
nag_dsytrs(order, uplo, n, nrhs, a, pda, ipiv, b, pdb,
           &fail);
if (fail.code != NE_NOERROR)
  {
    printf("Error from nag_dsytrs (f07mec).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
  }
/* Print solution */
/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
fflush(stdout);

```

```

nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n, nrhs, b,
                        pdb, "Solution(s)", 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
          fail.message);
    exit_status = 1;
    goto END;
}
END:
NAG_FREE(ipiv);
NAG_FREE(a);
NAG_FREE(b);
return exit_status;
}

```

10.2 Program Data

```

nag_dsytrf (f07mdc) Example Program Data
  4  2          :Values of n and nrhs
  Nag_Lower          :Value of uplo
  2.07
  3.87  -0.21
  4.20  1.87  1.15
 -1.15  0.63  2.06  -1.81  :End of matrix A
 -9.50 27.85
 -8.38  9.90
 -6.07 19.25
 -0.96  3.93          :End of matrix B

```

10.3 Program Results

```

nag_dsytrf (f07mdc) Example Program Results

```

```

Solution(s)
           1           2
  1    -4.0000    1.0000
  2    -1.0000    4.0000
  3     2.0000    3.0000
  4     5.0000    2.0000

```
