

# NAG Library Function Document

## nag\_zgesdd (f08krc)

### 1 Purpose

nag\_zgesdd (f08krc) computes the singular value decomposition (SVD) of a complex  $m$  by  $n$  matrix  $A$ , optionally computing the left and/or right singular vectors, by using a divide-and-conquer method.

### 2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_zgesdd (Nag_OrderType order, Nag_JobType job, Integer m, Integer n,
                 Complex a[], Integer pda, double s[], Complex u[], Integer pdu,
                 Complex vt[], Integer pdvt, NagError *fail)
```

### 3 Description

The SVD is written as

$$A = U\Sigma V^H,$$

where  $\Sigma$  is an  $m$  by  $n$  matrix which is zero except for its  $\min(m, n)$  diagonal elements,  $U$  is an  $m$  by  $m$  unitary matrix, and  $V$  is an  $n$  by  $n$  unitary matrix. The diagonal elements of  $\Sigma$  are the singular values of  $A$ ; they are real and non-negative, and are returned in descending order. The first  $\min(m, n)$  columns of  $U$  and  $V$  are the left and right singular vectors of  $A$ .

Note that the function returns  $V^H$ , not  $V$ .

### 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

### 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **job** – Nag\_JobType *Input*

*On entry:* specifies options for computing all or part of the matrix  $U$ .

**job** = Nag\_DoAll

All  $m$  columns of  $U$  and all  $n$  rows of  $V^H$  are returned in the arrays **u** and **vt**.

**job** = Nag\_DoSquare

The first  $\min(m, n)$  columns of  $U$  and the first  $\min(m, n)$  rows of  $V^H$  are returned in the arrays **u** and **vt**.

**job** = Nag\_DoOverwrite

If  $m \geq n$ , the first  $n$  columns of  $U$  are overwritten on the array **a** and all rows of  $V^H$  are returned in the array **vt**. Otherwise, all columns of  $U$  are returned in the array **u** and the first  $m$  rows of  $V^H$  are overwritten in the array **vt**.

**job** = Nag\_DoNothing

No columns of  $U$  or rows of  $V^H$  are computed.

*Constraint:* **job** = Nag\_DoAll, Nag\_DoSquare, Nag\_DoOverwrite or Nag\_DoNothing.

3: **m** – Integer *Input*

*On entry:*  $m$ , the number of rows of the matrix  $A$ .

*Constraint:*  $m \geq 0$ .

4: **n** – Integer *Input*

*On entry:*  $n$ , the number of columns of the matrix  $A$ .

*Constraint:*  $n \geq 0$ .

5: **a**[*dim*] – Complex *Input/Output*

**Note:** the dimension, *dim*, of the array **a** must be at least

$\max(1, \mathbf{pda} \times \mathbf{n})$  when **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{m} \times \mathbf{pda})$  when **order** = Nag\_RowMajor.

The ( $i, j$ )th element of the matrix  $A$  is stored in

**a**[( $j - 1$ )  $\times$  **pda** +  $i - 1$ ] when **order** = Nag\_ColMajor;  
**a**[( $i - 1$ )  $\times$  **pda** +  $j - 1$ ] when **order** = Nag\_RowMajor.

*On entry:* the  $m$  by  $n$  matrix  $A$ .

*On exit:* if **job** = Nag\_DoOverwrite, **a** is overwritten with the first  $n$  columns of  $U$  (the left singular vectors, stored column-wise) if  $m \geq n$ ; **a** is overwritten with the first  $m$  rows of  $V^H$  (the right singular vectors, stored row-wise) otherwise.

If **job**  $\neq$  Nag\_DoOverwrite, the contents of **a** are destroyed.

6: **pda** – Integer *Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **a**.

*Constraints:*

if **order** = Nag\_ColMajor, **pda**  $\geq$   $\max(1, \mathbf{m})$ ;  
 if **order** = Nag\_RowMajor, **pda**  $\geq$   $\max(1, \mathbf{n})$ .

7: **s**[ $\min(\mathbf{m}, \mathbf{n})$ ] – double *Output*

*On exit:* the singular values of  $A$ , sorted so that  $\mathbf{s}[i - 1] \geq \mathbf{s}[i]$ .

8: **u**[*dim*] – Complex *Output*

**Note:** the dimension, *dim*, of the array **u** must be at least

$\max(1, \mathbf{pdu} \times \mathbf{m})$  when **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and  $\mathbf{m} < \mathbf{n}$ ;  
 $\max(1, \mathbf{pdu} \times \min(\mathbf{m}, \mathbf{n}))$  when **job** = Nag\_DoSquare and **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{m} \times \mathbf{pdu})$  when **job** = Nag\_DoSquare and **order** = Nag\_RowMajor;  
 1 otherwise.

The  $(i, j)$ th element of the matrix  $U$  is stored in

$$\begin{aligned} &\mathbf{u}[(j-1) \times \mathbf{pdu} + i - 1] \text{ when } \mathbf{order} = \text{Nag\_ColMajor}; \\ &\mathbf{u}[(i-1) \times \mathbf{pdu} + j - 1] \text{ when } \mathbf{order} = \text{Nag\_RowMajor}. \end{aligned}$$

*On exit:*

If  $\mathbf{job} = \text{Nag\_DoAll}$  or  $\mathbf{job} = \text{Nag\_DoOverwrite}$  and  $\mathbf{m} < \mathbf{n}$ ,  $\mathbf{u}$  contains the  $m$  by  $m$  unitary matrix  $U$ .

If  $\mathbf{job} = \text{Nag\_DoSquare}$ ,  $\mathbf{u}$  contains the first  $\min(m, n)$  columns of  $U$  (the left singular vectors, stored column-wise).

If  $\mathbf{job} = \text{Nag\_DoOverwrite}$  and  $\mathbf{m} \geq \mathbf{n}$ , or  $\mathbf{job} = \text{Nag\_DoNothing}$ ,  $\mathbf{u}$  is not referenced.

9: **pdu** – Integer

*Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array  $\mathbf{u}$ .

*Constraints:*

if **order** = Nag\_ColMajor,  
     if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and  $\mathbf{m} < \mathbf{n}$ ,  $\mathbf{pdu} \geq \max(1, \mathbf{m})$ ;  
     if **job** = Nag\_DoSquare,  $\mathbf{pdu} \geq \max(1, \mathbf{m})$ ;  
     otherwise  $\mathbf{pdu} \geq 1$ .;  
 if **order** = Nag\_RowMajor,  
     if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and  $\mathbf{m} < \mathbf{n}$ ,  $\mathbf{pdu} \geq \max(1, \mathbf{m})$ ;  
     if **job** = Nag\_DoSquare,  $\mathbf{pdu} \geq \max(1, \min(\mathbf{m}, \mathbf{n}))$ ;  
     otherwise  $\mathbf{pdu} \geq 1$ .

10: **vt**[*dim*] – Complex

*Output*

**Note:** the dimension, *dim*, of the array  $\mathbf{vt}$  must be at least

$\max(1, \mathbf{pdvt} \times \mathbf{n})$  when **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and  $\mathbf{m} \geq \mathbf{n}$ ;  
 $\max(1, \mathbf{pdvt} \times \mathbf{n})$  when **job** = Nag\_DoSquare and **order** = Nag\_ColMajor;  
 $\max(1, \min(\mathbf{m}, \mathbf{n}) \times \mathbf{pdvt})$  when **job** = Nag\_DoSquare and **order** = Nag\_RowMajor;  
 1 otherwise.

The  $(i, j)$ th element of the matrix is stored in

$$\begin{aligned} &\mathbf{vt}[(j-1) \times \mathbf{pdvt} + i - 1] \text{ when } \mathbf{order} = \text{Nag\_ColMajor}; \\ &\mathbf{vt}[(i-1) \times \mathbf{pdvt} + j - 1] \text{ when } \mathbf{order} = \text{Nag\_RowMajor}. \end{aligned}$$

*On exit:* if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and  $\mathbf{m} \geq \mathbf{n}$ ,  $\mathbf{vt}$  contains the  $n$  by  $n$  unitary matrix  $V^H$ .

If **job** = Nag\_DoSquare,  $\mathbf{vt}$  contains the first  $\min(m, n)$  rows of  $V^H$  (the right singular vectors, stored row-wise).

If **job** = Nag\_DoOverwrite and  $\mathbf{m} < \mathbf{n}$ , or **job** = Nag\_DoNothing,  $\mathbf{vt}$  is not referenced.

11: **pdvt** – Integer

*Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array  $\mathbf{vt}$ .

*Constraints:*

if **order** = Nag\_ColMajor,  
     if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and  $\mathbf{m} \geq \mathbf{n}$ ,  $\mathbf{pdvt} \geq \max(1, \mathbf{n})$ ;  
     if **job** = Nag\_DoSquare,  $\mathbf{pdvt} \geq \max(1, \min(\mathbf{m}, \mathbf{n}))$ ;  
     otherwise  $\mathbf{pdvt} \geq 1$ .;

if **order** = Nag\_RowMajor,  
 if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and **m**  $\geq$  **n**, **pdvt**  $\geq$  max(1, **n**);  
 if **job** = Nag\_DoSquare, **pdvt**  $\geq$  max(1, **n**);  
 otherwise **pdvt**  $\geq$  1..

12: **fail** – NagError \*

*Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_CONVERGENCE

nag\_zgesdd (f08krc) did not converge, the updating process failed.

### NE\_ENUM\_INT\_3

On entry, **job** =  $\langle value \rangle$ , **pdu** =  $\langle value \rangle$ , **m** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .  
 Constraint: if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and **m** < **n**, **pdu**  $\geq$  max(1, **m**);  
 if **job** = Nag\_DoSquare, **pdu**  $\geq$  max(1, **m**);  
 otherwise **pdu**  $\geq$  1.

On entry, **job** =  $\langle value \rangle$ , **pdu** =  $\langle value \rangle$ , **m** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .  
 Constraint: if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and **m** < **n**, **pdu**  $\geq$  max(1, **m**);  
 if **job** = Nag\_DoSquare, **pdu**  $\geq$  max(1, min(**m**, **n**));  
 otherwise **pdu**  $\geq$  1.

On entry, **job** =  $\langle value \rangle$ , **pdvt** =  $\langle value \rangle$ , **m** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .  
 Constraint: if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and **m**  $\geq$  **n**, **pdvt**  $\geq$  max(1, **n**);  
 if **job** = Nag\_DoSquare, **pdvt**  $\geq$  max(1, min(**m**, **n**));  
 otherwise **pdvt**  $\geq$  1.

On entry, **job** =  $\langle value \rangle$ , **pdvt** =  $\langle value \rangle$ , **m** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .  
 Constraint: if **job** = Nag\_DoAll or **job** = Nag\_DoOverwrite and **m**  $\geq$  **n**, **pdvt**  $\geq$  max(1, **n**);  
 if **job** = Nag\_DoSquare, **pdvt**  $\geq$  max(1, **n**);  
 otherwise **pdvt**  $\geq$  1.

### NE\_INT

On entry, **m** =  $\langle value \rangle$ .  
 Constraint: **m**  $\geq$  0.

On entry, **n** =  $\langle value \rangle$ .  
 Constraint: **n**  $\geq$  0.

On entry, **pda** =  $\langle value \rangle$ .  
 Constraint: **pda** > 0.

On entry, **pdu** =  $\langle value \rangle$ .  
 Constraint: **pdu** > 0.

On entry, **pdvt** =  $\langle value \rangle$ .  
 Constraint: **pdvt** > 0.

**NE\_INT\_2**

On entry, **pda** =  $\langle value \rangle$  and **m** =  $\langle value \rangle$ .  
 Constraint: **pda**  $\geq \max(1, \mathbf{m})$ .

On entry, **pda** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .  
 Constraint: **pda**  $\geq \max(1, \mathbf{n})$ .

**NE\_INTERNAL\_ERROR**

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

**7 Accuracy**

The computed singular value decomposition is nearly the exact singular value decomposition for a nearby matrix  $(A + E)$ , where

$$\|E\|_2 = O(\epsilon)\|A\|_2,$$

and  $\epsilon$  is the *machine precision*. In addition, the computed singular vectors are nearly orthogonal to working precision. See Section 4.9 of Anderson *et al.* (1999) for further details.

**8 Parallelism and Performance**

nag\_zgesdd (f08krc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag\_zgesdd (f08krc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

**9 Further Comments**

The total number of floating-point operations is approximately proportional to  $mn^2$  when  $m > n$  and  $m^2n$  otherwise.

The singular values are returned in descending order.

The real analogue of this function is nag\_dgesdd (f08kdc).

**10 Example**

This example finds the singular values and left and right singular vectors of the 4 by 6 matrix

$$A = \begin{pmatrix} 0.96 + 0.81i & -0.98 - 1.98i & 0.62 + 0.46i & -0.37 - 0.38i & 0.83 - 0.51i & 1.08 + 0.28i \\ -0.03 - 0.96i & -1.20 - 0.19i & 1.01 - 0.02i & 0.19 + 0.54i & 0.20 - 0.01i & 0.20 + 0.12i \\ -0.91 - 2.06i & -0.66 - 0.42i & 0.63 + 0.17i & -0.98 + 0.36i & -0.17 + 0.46i & -0.07 - 1.23i \\ -0.05 - 0.41i & -0.81 - 0.56i & -1.11 - 0.60i & 0.22 + 0.20i & 1.47 - 1.59i & 0.26 - 0.26i \end{pmatrix},$$

together with approximate error bounds for the computed singular values and vectors.

The example program for nag\_zgesvd (f08kpc) illustrates finding a singular value decomposition for the case  $m \geq n$ .

## 10.1 Program Text

```

/* nag_zgesdd (f08krc) Example Program.
 *
 * Copyright 2011 Numerical Algorithms Group.
 *
 * Mark 23, 2011.
 */

#include <stdio.h>
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>
#include <nagf16.h>
#include <nagx02.h>
#include <nagx04.h>
#include <naga02.h>

int main(void)
{
    /* Scalars */
    Complex      alpha, beta;
    double       eps, norm, serrbd;
    Integer      exit_status = 0, i, j, m, minmn, n, pda, pdd, pdu, pdvt;

    /* Arrays */
    Complex      *a = 0, *d = 0, *u = 0, *vt = 0;
    double       *rcondu = 0, *rcondv = 0, *s = 0, *uerrbd = 0, *verrbd = 0;

    /* Nag Types */
    NagError     fail;
    Nag_OrderType order;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J - 1) * pda + I - 1]
#define U(I, J) u[(J - 1) * pdu + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I - 1) * pda + J - 1]
#define U(I, J) u[(I - 1) * pdu + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_zgesdd (f08krc) Example Program Results\n\n");

    /* Skip heading in data file */
    scanf("%*[\n]");
    scanf("%ld%ld%*[\n]", &m, &n);
    if (m < 0 || n < 0)
    {
        printf("Invalid m or n\n");
        exit_status = 1;
        goto END;
    }

    minmn = MIN(m,n);
    /* Allocate memory */
    if (!(a      = NAG_ALLOC(m * n, Complex)) ||
        !(d      = NAG_ALLOC(m * n, Complex)) ||
        !(vt     = NAG_ALLOC(n * n, Complex)) ||
        !(u      = NAG_ALLOC(m * m, Complex)) ||
        !(rcondu = NAG_ALLOC(minmn, double)) ||
        !(rcondv = NAG_ALLOC(minmn, double)) ||
        !(s      = NAG_ALLOC(minmn, double)) ||
        !(uerrbd = NAG_ALLOC(minmn, double)) ||
        !(verrbd = NAG_ALLOC(minmn, double)))
    {

```

```

        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

#ifdef NAG_COLUMN_MAJOR
    pda = m;
#else
    pda = n;
#endif
    pdd = pda;
    pdu = m;
    pdvt = n;

    /* Read the m by n matrix A from data file. */
    for (i = 1; i <= m; ++i)
        for (j = 1; j <= n; ++j)
            scanf(" %lf %lf ", &A(i, j).re, &A(i, j).im);
    scanf("%*[\n]");

    /* Copy A to D: nag_zge_copy (f16tfc),
     * Complex valued general matrix copy.
     */
    nag_zge_copy(order, Nag_NoTrans, m, n, a, pda, d, pdd, &fail);

    /* nag_gen_complx_mat_print_comp (x04dbc): Print matrix A */
    fflush(stdout);
    nag_gen_complx_mat_print_comp(order, Nag_GeneralMatrix, Nag_NonUnitDiag, m,
                                   n, a, pda, Nag_BracketForm, "%5.2f",
                                   "Matrix A", Nag_IntegerLabels, 0,
                                   Nag_IntegerLabels, 0, 80, 0, 0, &fail);

    printf("\n");
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_gen_complx_mat_print_comp (x04dbc).\n%s\n",
               fail.message);
        exit_status = 1;
        goto END;
    }

    /* Compute the singular values and left and right singular vectors */
    /* of A (A = U*S*(V**H), m.le.n) */
    nag_zgesdd(order, Nag_DoAll, m, n, a, pda, s, u, pdu, vt, pdvt, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_zgesdd (f08krc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

    /* Reconstruct A from its decomposition and subtract from original A:
     * first, U <- U*S, then D <- D - U*S*V^H using
     * nag_zgemm (f16zac).
     */
    for(i = 1; i <= m; i++)
        for(j = 1; j <= minmn; j++)
            U(i, j).re *= s[j-1], U(i, j).im *= s[j-1];

    alpha = nag_complex(-1.0,0.0);
    beta = nag_complex(1.0,0.0);
    nag_zgemm(order, Nag_NoTrans, Nag_NoTrans, m, n, minmn, alpha, u, pdu,
              vt, pdvt, beta, d, pdd, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_zgemm (f16zac).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

    /* Find norm of difference matrix D and print warning if it is too large.
     * nag_zge_norm (f16uac) using one-norm.

```

```

*/
nag_zge_norm(order, Nag_OneNorm, m, n, d, pdd, &norm, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_zge_norm (f16uac).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
/* Get the machine precision, using nag_machine_precision (x02ajc) */
eps = nag_machine_precision;
if (norm > pow(eps, 0.8))
{
    printf("Norm of A-(U*S*V^H) is much greater than 0.\n"
           " Schur factorization has failed.\n");
    exit_status = 1;
    goto END;
}

/* Print singular values and error estimates on values and vectors. */
printf("\nSingular values\n");
for (i = 0; i < minmn; ++i) printf("%10.4f%s", s[i], i%8 == 7?"\n":" ");
printf("\n");

/* Approximate error bound for the computed singular values.
 * Note that for the 2-norm, s[0] = norm(A).
 */
serrbd = eps * s[0];

/* Call nag_ddisna (f08flc) to estimate reciprocal condition numbers for the
 * singular vectors.
 */
nag_ddisna(Nag_LeftSingVecs, m, n, s, rcondu, &fail);
nag_ddisna(Nag_RightSingVecs, m, n, s, rcondv, &fail);

/* Compute the error estimates for the singular vectors */
for (i = 0; i < m; ++i)
{
    uerrbd[i] = serrbd / rcondu[i];
    verrbd[i] = serrbd / rcondv[i];
}

printf("\nError estimate for the singular values\n%11.1e\n", serrbd);
printf("\nError estimates for the left singular vectors\n");
for (i = 0; i < m; ++i) printf(" %10.1e%s", uerrbd[i], i%6 == 5?"\n":""");

printf("\n\nError estimates for the right singular vectors\n");
for (i = 0; i < m; ++i) printf(" %10.1e%s", verrbd[i], i%6 == 5?"\n":""");
printf("\n");

END:
NAG_FREE(a);
NAG_FREE(d);
NAG_FREE(vt);
NAG_FREE(u);
NAG_FREE(rcondu);
NAG_FREE(rcondv);
NAG_FREE(s);
NAG_FREE(uerrbd);
NAG_FREE(verrbd);

return exit_status;
}
#undef A
#undef U

```



## 10.2 Program Data

nag\_zgesdd (f08krc) Example Program Data

```

      4              6              : m and n

( 0.96, 0.81) (-0.98,-1.98) ( 0.62, 0.46)
(-0.37,-0.38) ( 0.83,-0.51) ( 1.08, 0.28)

(-0.03,-0.96) (-1.20,-0.19) ( 1.01,-0.02)
( 0.19, 0.54) ( 0.20,-0.01) ( 0.20, 0.12)

(-0.91,-2.06) (-0.66,-0.42) ( 0.63, 0.17)
(-0.98, 0.36) (-0.17, 0.46) (-0.07,-1.23)

(-0.05,-0.41) (-0.81,-0.56) (-1.11,-0.60)
( 0.22, 0.20) ( 1.47,-1.59) ( 0.26,-0.26) : matrix A

```

## 10.3 Program Results

nag\_zgesdd (f08krc) Example Program Results

Matrix A

```

      1              2              3              4              5
1 ( 0.96, 0.81) (-0.98,-1.98) ( 0.62, 0.46) (-0.37,-0.38) ( 0.83,-0.51)
2 (-0.03,-0.96) (-1.20,-0.19) ( 1.01,-0.02) ( 0.19, 0.54) ( 0.20,-0.01)
3 (-0.91,-2.06) (-0.66,-0.42) ( 0.63, 0.17) (-0.98, 0.36) (-0.17, 0.46)
4 (-0.05,-0.41) (-0.81,-0.56) (-1.11,-0.60) ( 0.22, 0.20) ( 1.47,-1.59)

      6
1 ( 1.08, 0.28)
2 ( 0.20, 0.12)
3 (-0.07,-1.23)
4 ( 0.26,-0.26)

```

Singular values

```

3.9994      3.0003      1.9944      0.9995

```

Error estimate for the singular values

```

4.4e-16

```

Error estimates for the left singular vectors

```

4.4e-16      4.4e-16      4.5e-16      4.5e-16

```

Error estimates for the right singular vectors

```

4.4e-16      4.4e-16      4.5e-16      4.5e-16

```

---