

## NAG Library Function Document

### **nag\_sparse\_nsym\_sort (f11zac)**

## 1 Purpose

`nag_sparse_nsym_sort (f11zac)` sorts the nonzero elements of a real sparse nonsymmetric matrix, represented in coordinate storage format.

## 2 Specification

```
#include <nag.h>
#include <nagf11.h>
void nag_sparse_nsym_sort (Integer n, Integer *nnz, double a[],  

    Integer irow[], Integer icol[], Nag_SparseNsym_Dups dup,  

    Nag_SparseNsym_Zeros zero, Integer istr[], NagError *fail)
```

## 3 Description

`nag_sparse_nsym_sort (f11zac)` takes a coordinate storage (CS) representation (see the f11 Chapter Introduction) of a real  $n$  by  $n$  sparse nonsymmetric matrix  $A$ , and reorders the nonzero elements by increasing row index and increasing column index within each row. Entries with duplicate row and column indices may be removed, or the values may be summed. Any entries with zero values may optionally be removed.

`nag_sparse_nsym_sort (f11zac)` also returns `istr` which contains the starting indices of each row in  $A$ . This can be used to construct a compressed column storage (CCS) representation of the matrix (see Section 9).

## 4 References

None.

## 5 Arguments

1:	<b>n</b> – Integer	<i>Input</i>
<i>On entry:</i> the order of the matrix $A$ .		
<i>Constraint:</i> $\mathbf{n} \geq 1$ .		
2:	<b>nnz</b> – Integer *	<i>Input/Output</i>
<i>On entry:</i> the number of nonzero elements in the matrix $A$ .		
<i>Constraint:</i> $\mathbf{nnz} \geq 0$ .		
<i>On exit:</i> the number of nonzero elements with unique row and column indices.		
3:	<b>a</b> [ <b>max(1, nnz)</b> ] – double	<i>Input/Output</i>
<i>On entry:</i> the nonzero elements of the matrix $A$ . These may be in any order and there may be multiple nonzero elements with the same row and column indices.		
<i>On exit:</i> the nonzero elements ordered by increasing row index, and by increasing column index within each row. Each nonzero element has a unique row and column index.		

4:	<b>irow</b> [max(1, nnz)] – Integer	<i>Input/Output</i>
<i>On entry:</i> the row indices of the elements supplied in array <b>a</b> .		
<i>Constraint:</i> $1 \leq \text{irow}[i] \leq \mathbf{n}$ , for $i = 0, 1, \dots, \mathbf{nnz} - 1$ .		
<i>On exit:</i> the first <b>nnz</b> elements contain the row indices corresponding to the elements returned in array <b>a</b> .		
5:	<b>icol</b> [max(1, nnz)] – Integer	<i>Input/Output</i>
<i>On entry:</i> the column indices of the elements supplied in array <b>a</b> .		
<i>Constraint:</i> $1 \leq \text{icol}[i] \leq \mathbf{n}$ , for $i = 0, 1, \dots, \mathbf{nnz} - 1$ .		
<i>On exit:</i> the first <b>nnz</b> elements contain the column indices corresponding to the elements returned in array <b>a</b> .		
6:	<b>dup</b> – Nag_SparseNsym_Dups	<i>Input</i>
<i>On entry:</i> indicates how any nonzero elements with duplicate row and column indices are to be treated:		
if <b>dup</b> = Nag_SparseNsym_RemoveDups then duplicate elements are removed;		
if <b>dup</b> = Nag_SparseNsym_SumDups then the relevant values in array <b>a</b> are summed;		
if <b>dup</b> = Nag_SparseNsym_FailDups then the function fails on detecting a duplicate.		
<i>Constraint:</i> <b>dup</b> = Nag_SparseNsym_RemoveDups, Nag_SparseNsym_SumDups or Nag_SparseNsym_FailDups.		
7:	<b>zero</b> – Nag_SparseNsym_Zeros	<i>Input</i>
<i>On entry:</i> indicates how any elements with zero values in <b>a</b> are to be treated:		
if <b>zero</b> = Nag_SparseNsym_RemoveZeros then the entries are removed;		
if <b>zero</b> = Nag_SparseNsym_KeepZeros then the entries are kept;		
if <b>zero</b> = Nag_SparseNsym_FailZeros then the function fails on detecting a zero.		
<i>Constraint:</i> <b>zero</b> = Nag_SparseNsym_RemoveZeros, Nag_SparseNsym_KeepZeros or Nag_SparseNsym_FailZeros.		
8:	<b>istr</b> [n + 1] – Integer	<i>Output</i>
<i>On exit:</i> <b>istr</b> [i – 1] – 1, for $i = 1, 2, \dots, \mathbf{n}$ , is the starting index in the arrays <b>a</b> , <b>irow</b> and <b>icol</b> of each row $i$ of the matrix $A$ . <b>istr</b> [n] contains the number of nonzero elements in $A$ plus one.		
9:	<b>fail</b> – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 3.6 in the Essential Introduction).		

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

### NE\_BAD\_PARAM

On entry, argument **dup** had an illegal value.

On entry, argument **zero** had an illegal value.

**NE\_INT\_ARG\_LT**

On entry, **n** =  $\langle value \rangle$ .

Constraint: **n**  $\geq 1$ .

On entry, **nnz** =  $\langle value \rangle$ .

Constraint: **nnz**  $\geq 0$ .

**NE\_NON\_ZERO\_DUP**

Nonzero elements have been supplied which have duplicate row and column indices, when **dup** = Nag\_SparseNsym\_FailDups.

**NE\_NONSYMM\_MATRIX**

A nonzero element has been supplied which does not lie within the matrix  $A$ , i.e., one or more of the following constraints has been violated:

$1 \leq \mathbf{irow}[i] \leq \mathbf{n}$ ,  $1 \leq \mathbf{icol}[i] \leq \mathbf{n}$ , for  $i = 0, 1, \dots, \mathbf{nnz} - 1$ .

**NE\_ZERO\_COEFF**

At least one matrix element has been supplied with a zero coefficient value, when **zero** = Nag\_SparseNsym\_FailZeros.

**7 Accuracy**

Not applicable.

**8 Parallelism and Performance**

Not applicable.

**9 Further Comments**

The time taken for a call to nag\_sparse\_nsym\_sort (f11zac) is proportional to **nnz**.

Note that the resulting matrix may have either rows or columns with no entries. If row  $i$  has no entries then **istr**[ $i - 1$ ] = **istr**[ $i$ ].

It is also possible to use this function to convert between coordinate storage (CS) and compressed column storage (CCS) formats. To achieve this the CS storage format arrays **irow** and **icol** must be interchanged in the call to nag\_sparse\_nsym\_sort (f11zac). On exit from nag\_sparse\_nsym\_sort (f11zac), the CCS representation of the matrix is then defined by arrays **a**, **irow** and **istr**. This is illustrated in Section 10.

**10 Example**

This example program reads the CS representation of a real sparse matrix  $A$ , calls nag\_sparse\_nsym\_sort (f11zac) to reorder the nonzero elements, and outputs the original and the reordered representations. It then calls nag\_sparse\_nsym\_sort (f11zac) again with the alternative ordering, creating a CCS representation which is then passed to a function that computes a matrix norm for that representation.

$$A = \begin{pmatrix} 2.00 & 1.00 & 0 & 0 & 0 \\ 0 & 0 & 1.00 & -1.00 & 0 \\ 4.00 & 0 & 1.00 & 0 & 1.00 \\ 0 & 0 & 0 & 1.00 & 2.00 \\ 0 & -2.00 & 0 & 0 & 3.00 \end{pmatrix}.$$

## 10.1 Program Text

```

/* nag_sparse_nsym_sort (f11zac) Example Program.
*
* Copyright 1998 Numerical Algorithms Group.
*
* Mark 5, 1998.
*/
*/

#include <nag.h>
#include <nag_stdlib.h>
#include <stdio.h>
#include <nagf11.h>

int main(void)
{
    double             *a = 0, anorm = 0.0;
    Integer           *icol = 0;
    Integer           *irow = 0, *istr = 0;
    Integer           exit_status = 0, i, n, nnz;
    Nag_SparseNsym_Zeros zero;
    Nag_SparseNsym_Dups dup;
    Nag_NormType      norm;
    NagError          fail;

    INIT_FAIL(fail);

    printf("nag_sparse_nsym_sort (f11zac) Example Program Results\n\n");

    /* Skip heading in data file */
    scanf(" %*[^\n]");

    /* Read order of matrix and number of non-zero entries */
    scanf("%ld%*[^\n]", &n);
    scanf("%ld%*[^\n]", &nnz);

    /* Allocate memory */
    istr = NAG_ALLOC(n+1, Integer);
    a = NAG_ALLOC(nnz, double);
    irow = NAG_ALLOC(nnz, Integer);
    icol = NAG_ALLOC(nnz, Integer);

    if (!istr || !irow || !icol || !a)
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read and output the original non-zero elements */
    for (i = 0; i < nnz; ++i)
        scanf("%lf%ld%ld%*[^\n]", &a[i], &irow[i], &icol[i]);

    printf("Original elements \n");
    printf("nnz = %4ld\n", nnz);
    printf("%8s%16s%8s%8s\n", "", "a", "irow", "icol");
    for (i = 0; i < nnz; ++i)
        printf("%8ld%16.4e%8ld%8ld\n", i, a[i],
               irow[i], icol[i]);

    /* Reorder along rows, sum duplicates and remove zeros */

    dup = Nag_SparseNsym_SumDups;
    zero = Nag_SparseNsym_RemoveZeros;

    /* nag_sparse_nsym_sort (f11zac).
     * Sparse sort (nonsymmetric)
     */
    nag_sparse_nsym_sort(n, &nnz, a, irow, icol, dup, zero, istr, &fail);
    if (fail.code != NE_NOERROR)

```

```

{
    printf("Error from nag_sparse_nsym_sort (f11zac).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Output results */
printf("Reordered elements, along rows first\n");
printf("nnz = %4ld\n", nnz);

for (i = 0; i < nnz; ++i)
    printf("%8ld%16.4e%8ld%8ld\n", i, a[i],
           irow[i], icol[i]);

/* Reorder down columns, fail on duplicates or zeros.
 * Creates CCS storage format as side-effect
 */

dup = Nag_SparseNsym_FailDups;
zero = Nag_SparseNsym_FailZeros;
INIT_FAIL(fail);

/* nag_sparse_nsym_sort (f11zac).
 * Sparse sort (nonsymmetric)
 */
nag_sparse_nsym_sort(n, &nnz, a, icol, irow, dup, zero, istr, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_sparse_nsym_sort (f11zac).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Output results */
printf("Reordered elements, along columns first\n");
printf("nnz = %4ld\n", nnz);

for (i = 0; i < nnz; ++i)
    printf("%8ld%16.4e%8ld%8ld\n", i, a[i],
           irow[i], icol[i]);
printf("%8s%8s\n", "", "istr");
for (i = 0; i <= n; ++i)
    printf("%8ld%8ld\n", i, istr[i]);

/* Calculate 1-norm in Compressed Column Storage format */
norm = Nag_RealOneNorm;
INIT_FAIL(fail);

/* nag_superlu_matrix_norm (f11mlc).
 * 1-norm, infinity-norm, largest absolute element, real
 * general matrix
 */
nag_superlu_matrix_norm(norm, &anorm, n, istr, irow, a, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_superlu_matrix_norm (f11mlc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}
/* Output norm */
printf("%s %16.4e\n", "One-norm", anorm);

END:
NAG_FREE(istr);
NAG_FREE(irow);
NAG_FREE(icol);
NAG_FREE(a);

```

```
    return exit_status;
}
```

## 10.2 Program Data

```
nag_sparse_nsym_sort (fllzac) Example Program Data
      5          n
     15         nnz
 4.   3   1
 -2.   5   2
 1.   4   4
 -2   4   2
 -3   5   5
 1.   1   2
 0.   1   5
 1.   3   5
 -1.   2   4
 6.   5   5
 2.   1   1
 2.   4   2
 1.   2   3
 1.   3   3
 2.   4   5           a[i-1], irow[i-1], icol[i-1], i=1,...,nnz
```

## 10.3 Program Results

```
nag_sparse_nsym_sort (fllzac) Example Program Results
```

Original elements

nnz = 15

	a	irow	icol
0	4.0000e+00	3	1
1	-2.0000e+00	5	2
2	1.0000e+00	4	4
3	-2.0000e+00	4	2
4	-3.0000e+00	5	5
5	1.0000e+00	1	2
6	0.0000e+00	1	5
7	1.0000e+00	3	5
8	-1.0000e+00	2	4
9	6.0000e+00	5	5
10	2.0000e+00	1	1
11	2.0000e+00	4	2
12	1.0000e+00	2	3
13	1.0000e+00	3	3
14	2.0000e+00	4	5

Reordered elements, along rows first

nnz = 11

0	2.0000e+00	1	1
1	1.0000e+00	1	2
2	1.0000e+00	2	3
3	-1.0000e+00	2	4
4	4.0000e+00	3	1
5	1.0000e+00	3	3
6	1.0000e+00	3	5
7	1.0000e+00	4	4
8	2.0000e+00	4	5
9	-2.0000e+00	5	2
10	3.0000e+00	5	5

Reordered elements, along columns first

nnz = 11

0	2.0000e+00	1	1
1	4.0000e+00	3	1
2	1.0000e+00	1	2
3	-2.0000e+00	5	2
4	1.0000e+00	2	3
5	1.0000e+00	3	3
6	-1.0000e+00	2	4
7	1.0000e+00	4	4

8	1.0000e+00	3	5
9	2.0000e+00	4	5
10	3.0000e+00	5	5
	istr		
0	1		
1	3		
2	5		
3	7		
4	9		
5	12		
One-norm	6.0000e+00		

---