

## NAG Library Function Document

### nag\_real\_sparse\_eigensystem\_sol (f12acc)

#### 1 Purpose

nag\_real\_sparse\_eigensystem\_sol (f12acc) is a post-processing function that must be called following a final exit from nag\_real\_sparse\_eigensystem\_iter (f12abc). These are part of a suite of functions for the solution of real sparse eigensystems. The suite also includes nag\_real\_sparse\_eigensystem\_init (f12aac), nag\_real\_sparse\_eigensystem\_option (f12adc) and nag\_real\_sparse\_eigensystem\_monit (f12aec).

#### 2 Specification

```
#include <nag.h>
#include <nagf12.h>

void nag_real_sparse_eigensystem_sol (Integer *nconv, double dr[],
    double di[], double z[], double sigmar, double sigmai,
    const double resid[], double v[], double comm[], Integer icomm[],
    NagError *fail)
```

#### 3 Description

The suite of functions is designed to calculate some of the eigenvalues,  $\lambda$ , (and optionally the corresponding eigenvectors,  $x$ ) of a standard eigenvalue problem  $Ax = \lambda x$ , or of a generalized eigenvalue problem  $Ax = \lambda Bx$  of order  $n$ , where  $n$  is large and the coefficient matrices  $A$  and  $B$  are sparse, real and nonsymmetric. The suite can also be used to find selected eigenvalues/eigenvectors of smaller scale dense, real and nonsymmetric problems.

Following a call to nag\_real\_sparse\_eigensystem\_iter (f12abc), nag\_real\_sparse\_eigensystem\_sol (f12acc) returns the converged approximations to eigenvalues and (optionally) the corresponding approximate eigenvectors and/or an orthonormal basis for the associated approximate invariant subspace. The eigenvalues (and eigenvectors) are selected from those of a standard or generalized eigenvalue problem defined by real nonsymmetric matrices. There is negligible additional cost to obtain eigenvectors; an orthonormal basis is always computed, but there is an additional storage cost if both are requested.

nag\_real\_sparse\_eigensystem\_sol (f12acc) is based on the function **dneupd** from the ARPACK package, which uses the Implicitly Restarted Arnoldi iteration method. The method is described in Lehoucq and Sorensen (1996) and Lehoucq (2001) while its use within the ARPACK software is described in great detail in Lehoucq *et al.* (1998). An evaluation of software for computing eigenvalues of sparse nonsymmetric matrices is provided in Lehoucq and Scott (1996). This suite of functions offers the same functionality as the ARPACK software for real nonsymmetric problems, but the interface design is quite different in order to make the option setting clearer and to simplify some of the interfaces.

nag\_real\_sparse\_eigensystem\_sol (f12acc), is a post-processing function that must be called following a successful final exit from nag\_real\_sparse\_eigensystem\_iter (f12abc). nag\_real\_sparse\_eigensystem\_sol (f12acc) uses data returned from nag\_real\_sparse\_eigensystem\_iter (f12abc) and options, set either by default or explicitly by calling nag\_real\_sparse\_eigensystem\_option (f12adc), to return the converged approximations to selected eigenvalues and (optionally):

- the corresponding approximate eigenvectors;
- an orthonormal basis for the associated approximate invariant subspace;
- both.

## 4 References

Lehoucq R B (2001) Implicitly restarted Arnoldi methods and subspace iteration *SIAM Journal on Matrix Analysis and Applications* **23** 551–562

Lehoucq R B and Scott J A (1996) An evaluation of software for computing eigenvalues of sparse nonsymmetric matrices *Preprint MCS-P547-1195* Argonne National Laboratory

Lehoucq R B and Sorensen D C (1996) Deflation techniques for an implicitly restarted Arnoldi iteration *SIAM Journal on Matrix Analysis and Applications* **17** 789–821

Lehoucq R B, Sorensen D C and Yang C (1998) *ARPACK Users' Guide: Solution of Large-scale Eigenvalue Problems with Implicitly Restarted Arnoldi Methods* SIAM, Philadelphia

## 5 Arguments

- 1: **nconv** – Integer \* *Output*  
*On exit:* the number of converged eigenvalues as found by nag\_real\_sparse\_eigensystem\_iter (f12abc).
- 2: **dr**[*dim*] – double *Output*  
**Note:** the dimension, *dim*, of the array **dr** must be at least **nev** (see nag\_real\_sparse\_eigensystem\_init (f12aac)).  
*On exit:* the first **nconv** locations of the array **dr** contain the real parts of the converged approximate eigenvalues.
- 3: **di**[*dim*] – double *Output*  
**Note:** the dimension, *dim*, of the array **di** must be at least **nev** (see nag\_real\_sparse\_eigensystem\_init (f12aac)).  
*On exit:* the first **nconv** locations of the array **di** contain the imaginary parts of the converged approximate eigenvalues.
- 4: **z**[**n** × (**nev** + 1)] – double *Output*  
*On exit:* if the default option **Vectors** = 'RITZ' (see nag\_real\_sparse\_eigensystem\_option (f12adc)) has been selected then **z** contains the final set of eigenvectors corresponding to the eigenvalues held in **dr** and **di**. The complex eigenvector associated with the eigenvalue with positive imaginary part is stored in two consecutive array segments. The first segment holds the real part of the eigenvector and the second holds the imaginary part. The eigenvector associated with the eigenvalue with negative imaginary part is simply the complex conjugate of the eigenvector associated with the positive imaginary part.  
For example, the first eigenvector has real parts stored in locations **z**[*i* – 1], for *i* = 1, 2, ..., **n** and imaginary parts stored in **z**[*i* – 1], for *i* = **n** + 1, 2**n**.
- 5: **sigmar** – double *Input*  
*On entry:* if one of the **Shifted Inverse Real** modes have been selected then **sigmar** contains the real part of the shift used; otherwise **sigmar** is not referenced.
- 6: **sigmai** – double *Input*  
*On entry:* if one of the **Shifted Inverse Real** modes have been selected then **sigmai** contains the imaginary part of the shift used; otherwise **sigmai** is not referenced.
- 7: **resid**[*dim*] – const double *Input*  
**Note:** the dimension, *dim*, of the array **resid** must be at least **n** (see nag\_real\_sparse\_eigensystem\_init (f12aac)).

*On entry:* must not be modified following a call to `nag_real_sparse_eigensystem_iter` (f12abc) since it contains data required by `nag_real_sparse_eigensystem_sol` (f12acc).

8: **v**[**n** × **ncv**] – double *Input/Output*

The  $i$ th element of the  $j$ th basis vector is stored in location  $\mathbf{v}[\mathbf{n} \times (j - 1) + i - 1]$ , for  $i = 1, 2, \dots, \mathbf{n}$  and  $j = 1, 2, \dots, \mathbf{ncv}$ .

*On entry:* the **ncv** sections of **v**, of length  $n$ , contain the Arnoldi basis vectors for OP as constructed by `nag_real_sparse_eigensystem_iter` (f12abc).

*On exit:* if the option **Vectors** = 'SCHUR' has been set, or the option **Vectors** = 'RITZ' has been set and a separate array **z** has been passed (i.e., **z** does not equal **v**), then the first **nconv** sections of **v**, of length  $n$ , will contain approximate Schur vectors that span the desired invariant subspace.

9: **comm**[*dim*] – double *Communication Array*

**Note:** the dimension, *dim*, of the array **comm** must be at least  $\max(1, \mathbf{lcomm})$  (see `nag_real_sparse_eigensystem_init` (f12aac)).

*On initial entry:* must remain unchanged from the prior call to `nag_real_sparse_eigensystem_iter` (f12abc).

*On exit:* contains data on the current state of the solution.

10: **icomm**[*dim*] – Integer *Communication Array*

**Note:** the dimension, *dim*, of the array **icomm** must be at least  $\max(1, \mathbf{licomm})$  (see `nag_real_sparse_eigensystem_init` (f12aac)).

*On initial entry:* must remain unchanged from the prior call to `nag_real_sparse_eigensystem_iter` (f12abc).

*On exit:* contains data on the current state of the solution.

11: **fail** – NagError \* *Input/Output*

The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_INITIALIZATION

Either the solver function has not been called prior to the call of this function or a communication array has become corrupted.

### NE\_INTERNAL\_EIGVEC\_FAIL

In calculating eigenvectors, an internal call returned with an error. Please contact NAG.

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

### NE\_INVALID\_OPTION

On entry, **Vectors** = 'SELECT', but this is not yet implemented.

**NE\_RITZ\_COUNT**

Got a different count of the number of converged Ritz values than the value passed to it through the argument **icomm**: number counted =  $\langle value \rangle$ , number expected =  $\langle value \rangle$ . This usually indicates that a communication array has been altered or has become corrupted between calls to `nag_real_sparse_eigensystem_iter` (f12abc) and `nag_real_sparse_eigensystem_sol` (f12acc).

**NE\_SCHUR\_EIG\_FAIL**

During calculation of a real Schur form, there was a failure to compute  $\langle value \rangle$  eigenvalues in a total of  $\langle value \rangle$  iterations.

**NE\_SCHUR\_REORDER**

The computed Schur form could not be reordered by an internal call. This function returned with **fail.code** =  $\langle value \rangle$ . Please contact NAG.

**NE\_ZERO\_EIGS\_FOUND**

The number of eigenvalues found to sufficient accuracy, as communicated through the argument **icomm**, is zero. You should experiment with different values of **nev** and **ncv**, or select a different computational mode or increase the maximum number of iterations prior to calling `nag_real_sparse_eigensystem_iter` (f12abc).

**7 Accuracy**

The relative accuracy of a Ritz value,  $\lambda$ , is considered acceptable if its Ritz estimate  $\leq \mathbf{Tolerance} \times |\lambda|$ . The default **Tolerance** used is the *machine precision* given by `nag_machine_precision` (X02AJC).

**8 Parallelism and Performance**

`nag_real_sparse_eigensystem_sol` (f12acc) is not threaded by NAG in any implementation.

`nag_real_sparse_eigensystem_sol` (f12acc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

**9 Further Comments**

None.

**10 Example**

This example solves  $Ax = \lambda Bx$  in regular-invert mode, where  $A$  and  $B$  are obtained from the standard central difference discretization of the one-dimensional convection-diffusion operator  $\frac{d^2u}{dx^2} + \rho \frac{du}{dx}$  on  $[0, 1]$ , with zero Dirichlet boundary conditions.

**10.1 Program Text**

```
/* nag_real_sparse_eigensystem_sol (f12acc) Example Program.
 *
 * Copyright 2005 Numerical Algorithms Group.
 *
 * Mark 8, 2005.
 */

#include <nag.h>
#include <nag_stdlib.h>
#include <stdio.h>
```

```

#include <nagf12.h>
#include <nagf16.h>

static void av(Integer, double, double *, double *);
static void mv(Integer, double *, double *);
static void my_dpstrf(Integer, double *, double *, Integer *);
static void my_dpstrs(Integer, double *, double *, double *);

int main(void)
{
    /* Constants */
    Integer licomm = 140, imon = 0;
    /* Scalars */
    double estnrm, h, rho, sigmai = 0.0, sigmar = 0.0;
    Integer exit_status, info, irevcm, j, lcomm, n, nconv, ncv;
    Integer nev, niter, nshift, nx;
    /* Nag types */
    NagError fail;
    /* Arrays */
    double *comm = 0, *eigvr = 0, *eigvi = 0, *eigest = 0, *md = 0, *me = 0;
    double *resid = 0, *v = 0;
    Integer *icomm = 0;
    /* Pointers */
    double *mx = 0, *x = 0, *y = 0;

    exit_status = 0;
    INIT_FAIL(fail);

    printf(
        "nag_real_sparse_eigensystem_sol (f12acc) Example Program Results\n");
    /* Skip heading in data file */
    scanf("%*[\n] ");
    /* Read problem parameter values from data file. */
    scanf("%ld%ld%ld%lf%*[\n] ", &nx, &nev, &ncv, &rho);
    n = nx * nx;
    lcomm = 3*n + 3*ncv*ncv + 6*ncv + 60;
    /* Allocate memory */
    if (!(comm = NAG_ALLOC(lcomm, double)) ||
        !(eigvr = NAG_ALLOC(ncv, double)) ||
        !(eigvi = NAG_ALLOC(ncv, double)) ||
        !(eigest = NAG_ALLOC(ncv, double)) ||
        !(md = NAG_ALLOC(n, double)) ||
        !(me = NAG_ALLOC(n, double)) ||
        !(resid = NAG_ALLOC(n, double)) ||
        !(v = NAG_ALLOC(n * ncv, double)) ||
        !(icomm = NAG_ALLOC(licomm, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
    /* Initialise communication arrays for problem using
    nag_real_sparse_eigensystem_init (f12aac). */
    nag_real_sparse_eigensystem_init(n, nev, ncv, icomm, lcomm, comm,
        lcomm, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf(
            "Error from nag_real_sparse_eigensystem_init (f12aac).\n%s\n",
            fail.message);
        exit_status = 1;
        goto END;
    }
    /* Set the mode. */
    /* Select the mode using
    nag_real_sparse_eigensystem_option (f12adc). */
    nag_real_sparse_eigensystem_option("REGULAR INVERSE", icomm, comm,
        &fail);
    /* Select the problem type using
    nag_real_sparse_eigensystem_option (f12adc). */
    nag_real_sparse_eigensystem_option("GENERALIZED", icomm, comm, &fail);
}

```

```

/* Construct M, and factorize using my_dpttrf. */
h = 1.0 / (double)(n + 1);
for (j = 0; j <= n - 2; ++j)
{
    md[j] = h * 4.0;
    me[j] = h;
}
md[n - 1] = h * 4.0;

my_dpttrf(n, md, me, &info);

irevcm = 0;
REVCOMLOOP:
/* repeated calls to reverse communication routine
   nag_real_sparse_eigensystem_iter (f12abc). */
nag_real_sparse_eigensystem_iter(&irevcm, resid, v, &x, &y, &mx,
                                &nshift, comm, icomm, &fail);
if (irevcm != 5)
{
    if (irevcm == -1 || irevcm == 1)
    {
        /* Perform  $y \leftarrow OP*x = inv[M]*A*x$  using my_dpttrs. */
        av(nx, rho, x, y);
        my_dpttrs(n, md, me, y);
    }
    else if (irevcm == 2)
    {
        /* Perform  $y \leftarrow M*x$ . */
        mv(nx, x, y);
    }
    else if (irevcm == 4 && imon == 1)
    {
        /* If imon=1, get monitoring information using
           nag_real_sparse_eigensystem_monit (f12aec). */
        nag_real_sparse_eigensystem_monit(&niter, &nconv, eigvr,
                                          eigvi, eigest, icomm, comm);
        /* Compute 2-norm of Ritz estimates using
           nag_dge_norm (f16rac). */
        nag_dge_norm(Nag_ColMajor, Nag_FrobeniusNorm, nev, 1, eigest,
                    nev, &estnrm, &fail);
        printf("Iteration %3ld, ", niter);
        printf(" No. converged = %3ld,", nconv);
        printf(" norm of estimates = %17.8e\n", estnrm);
    }
    goto REVCOMLOOP;
}
if (fail.code == NE_NOERROR)
{
    /* Post-Process using nag_real_sparse_eigensystem_sol (f12acc)
       to compute eigenvalues/vectors. */
    nag_real_sparse_eigensystem_sol(&nconv, eigvr, eigvi, v, sigmar,
                                    sigmai, resid, v, comm, icomm,
                                    &fail);

    /* Print computed eigenvalues. */
    printf("\n The %4ld generalized", nconv);
    printf(" Ritz values of largest magnitude are:\n\n");
    for (j = 0; j <= nconv-1; ++j)
    {
        printf("%8ld%5s( %12.4f ,%12.4f )\n", j+1, "",
              eigvr[j], eigvi[j]);
    }
}
else
{
    printf(
        " Error from nag_real_sparse_eigensystem_iter (f12abc).\n%s\n",
        fail.message);
    exit_status = 1;
    goto END;
}
}

```

```

END:
  NAG_FREE(comm);
  NAG_FREE(eigvr);
  NAG_FREE(eigvi);
  NAG_FREE(eigest);
  NAG_FREE(md);
  NAG_FREE(me);
  NAG_FREE(resid);
  NAG_FREE(v);
  NAG_FREE(icom);
  return exit_status;
}

static void av(Integer nx, double rho, double *v, double *y)
{
  /* Scalars */
  double dd, dl, du, h, s;
  Integer j, n;
  /* Function Body */
  n = nx * nx;
  h = 1.0 / (double)(n + 1);
  s = rho / 2.0;
  dd = 2.0 / h;
  dl = -1.0 / h - s;
  du = -1.0 / h + s;
  y[0] = dd * v[0] + du * v[1];
  for (j = 1; j <= n - 2; ++j)
  {
    y[j] = dl * v[j-1] + dd * v[j] + du * v[j+1];
  }
  y[n-1] = dl * v[n-2] + dd * v[n-1];
  return;
} /* av */

static void mv(Integer nx, double *v, double *y)
{
  /* Scalars */
  double h;
  Integer j, n;
  /* Function Body */
  n = nx * nx;
  h = 1. / (double)(n + 1);
  y[0] = h*(v[0] * 4. + v[1]);
  for (j = 1; j <= n - 2; ++j)
  {
    y[j] = h*(v[j-1] + v[j] * 4. + v[j+1]);
  }
  y[n-1] = h*(v[n-2] + v[n-1] * 4.);
  return;
} /* mv */

static void my_dpstrf(Integer n, double d[], double e[], Integer *info)
{
  /* A simple C version of the Lapack routine dpstrf with argument
  checking removed */
  /* Scalars */
  double ei;
  Integer i;
  /* Function Body */
  *info = 0;
  for (i = 0; i < n-1; ++i)
  {
    if (d[i] <= 0.0)
    {
      *info = i+1;
      goto END_DPSTRF;
    }
    ei = e[i];
    e[i] = ei/d[i];
    d[i+1] = d[i+1] - e[i]*ei;
  }
}

```

```

    if (d[n-1] <= 0.0)
    {
        *info = n;
    }
END_DPTTRF:
    return;
}

static void my_dpttrs(Integer n, double d[], double e[], double b[])
{
    /* A simple C version of the Lapack routine dpttrs with argument
       checking removed and nrhs=1 */
    /* Scalars */
    Integer i;
    /* Function Body */
    for (i = 1; i < n; ++i)
    {
        b[i] = b[i] - b[i-1]*e[i-1];
    }
    b[n-1] = b[n-1]/d[n-1];
    for (i = n-2; i >= 0; --i)
    {
        b[i] = b[i]/d[i] - b[i+1]*e[i];
    }
    return;
}

```

## 10.2 Program Data

nag\_real\_sparse\_eigensystem\_sol (f12acc) Example Program Data  
 10 4 20 10.0 : Values for nx, nev, ncv, rho

## 10.3 Program Results

nag\_real\_sparse\_eigensystem\_sol (f12acc) Example Program Results

The 4 generalized Ritz values of largest magnitude are:

1	(	20383.0384	,	0.0000	)
2	(	20338.7563	,	0.0000	)
3	(	20265.2844	,	0.0000	)
4	(	20163.1142	,	0.0000	)

---