

NAG Library Function Document

nag_zamax_val (f16jsc)

1 Purpose

nag_zamax_val (f16jsc) computes, with respect to absolute value, the largest component of a complex vector, along with the index of that component.

2 Specification

```
#include <nag.h>
#include <nagf16.h>

void nag_zamax_val (Integer n, const Complex x[], Integer incx, Integer *k,
                   double *r, NagError *fail)
```

3 Description

nag_zamax_val (f16jsc) computes, with respect to absolute value, the largest component, r , of an n -element complex vector x , and determines the smallest index, k , such that

$$r = |\operatorname{Re} x_k| + |\operatorname{Im} x_k| = \max_j |\operatorname{Re} x_j| + |\operatorname{Im} x_j|.$$

4 References

Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001) *Basic Linear Algebra Subprograms Technical (BLAST) Forum Standard* University of Tennessee, Knoxville, Tennessee <http://www.netlib.org/blas/blast-forum/blas-report.pdf>

5 Arguments

- | | | |
|----|---|---------------|
| 1: | n – Integer | <i>Input</i> |
| | <i>On entry:</i> n , the number of elements in x . | |
| | <i>Constraint:</i> $n \geq 0$. | |
| 2: | x [<i>dim</i>] – const Complex | <i>Input</i> |
| | Note: the dimension, dim , of the array x must be at least $\max(1, 1 + (n - 1) \times \mathbf{incx})$. | |
| | <i>On entry:</i> the vector x . Element x_i is stored in x [($i - 1$) \times incx], for $i = 1, 2, \dots, n$. | |
| 3: | incx – Integer | <i>Input</i> |
| | <i>On entry:</i> the increment in the subscripts of x between successive elements of x . | |
| | <i>Constraint:</i> incx \neq 0. | |
| 4: | k – Integer * | <i>Output</i> |
| | <i>On exit:</i> k , the index, from the set $\{0, \mathbf{incx} , \dots, (n - 1) \times \mathbf{incx} \}$, of the largest component of x with respect to absolute value. If $n = 0$ on input then k is returned as -1 . | |
| 5: | r – double * | <i>Output</i> |
| | <i>On exit:</i> r , the largest component of x with respect to absolute value. If $n = 0$ on input then r is returned as 0.0. | |

6: **fail** – NagError *

Input/Output

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **incx** = $\langle value \rangle$.

Constraint: **incx** $\neq 0$.

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 0 .

7 Accuracy

The BLAS standard requires accurate implementations which avoid unnecessary over/underflow (see Section 2.7 of Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001)).

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

This example computes the largest component with respect to absolute value and index of that component for the vector

$$x = (-4 + 2.1i, 3.7 + 4.5i, -6 + 1.2i)^T.$$

10.1 Program Text

```

/* nag_zamax_val (f16jsc) Example Program.
 *
 * Copyright 2005 Numerical Algorithms Group.
 *
 * Mark 9, 2009.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf16.h>

int main(void)
{
    /* Scalars */
    Integer  exit_status, i, incx, k, n, xlen;
    double   r;
    /* Arrays */
    Complex  *x = 0;
    /* Nag Types */
    NagError fail;

    exit_status = 0;

```

```

INIT_FAIL(fail);

printf("nag_zamax_val (f16jsc) Example Program Results\n\n");

/* Skip heading in data file */
scanf("%*[\n] ");
/* Read the number of elements and the increment */
scanf("%ld%ld%*[\n] ", &n, &incx);

xlen = MAX(1, 1 + (n - 1)*ABS(incx));

if (n > 0)
{
    /* Allocate memory */
    if (!(x = NAG_ALLOC(xlen, Complex)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
}
else
{
    printf("Invalid n\n");
    exit_status = 1;
    goto END;
}
/* Input vector x */
for (i = 0; i < xlen; i = i + incx)
    scanf(" ( %lf , %lf ) ", &x[i].re, &x[i].im);
scanf("%*[\n] ");

/* nag_zamax_val (f16jsc).
 * Get absolutely maximum value (r) and location of that value (k)
 * of Complex array */
nag_zamax_val(n, x, incx, &k, &r, &fail);

if (fail.code != NE_NOERROR)
{
    printf("Error from nag_zamax_val (f16jsc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print the absolutely maximum value */
printf("Absolutely maximum element of x is %12.5f\n", r);
/* Print its location */
printf("Index of absolutely maximum element of x is %3ld\n", k);

END:
NAG_FREE(x);

return exit_status;
}

```

10.2 Program Data

```

nag_zamax_val (f16jsc) Example Program Data
  3  1                                     : n and incx
 (-4., 2.1) ( 3.7, 4.5) (-6., 1.2)       : Array x

```

10.3 Program Results

```

nag_zamax_val (f16jsc) Example Program Results

Absolutely maximum element of x is      8.20000
Index of absolutely maximum element of x is  1

```
