

NAG Library Function Document

nag_dtr_load (f16qgc)

1 Purpose

nag_dtr_load (f16qgc) initializes a real triangular matrix.

2 Specification

```
#include <nag.h>
#include <nagf16.h>
void nag_dtr_load (Nag_OrderType order, Nag_UptoType uplo, Integer n,
                   double alpha, double diag, double a[], Integer pda, NagError *fail)
```

3 Description

nag_dtr_load (f16qgc) forms the real n by n triangular matrix A given by

$$a_{ij} = \begin{cases} d & \text{if } i = j \\ \alpha & \text{if } i \neq j \end{cases}$$

4 References

Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001) *Basic Linear Algebra Subprograms Technical (BLAST) Forum Standard* University of Tennessee, Knoxville, Tennessee <http://www.netlib.org/blast-forum/blas-report.pdf>

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UptoType *Input*

On entry: specifies whether the upper or lower triangular part of A is stored.

uplo = Nag_Upper
The upper triangular part of A is stored.

uplo = Nag_Lower
The lower triangular part of A is stored.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

3: **n** – Integer *Input*

On entry: n , the order of the matrix A .

Constraint: **n** ≥ 0 .

4: **alpha** – double *Input*

On entry: the value, α , to be assigned to the off-diagonal elements of A .

5:	diag – double	<i>Input</i>
<i>On entry:</i> the value, d , to be assigned to the diagonal elements of A .		
6:	a [<i>dim</i>] – double	<i>Output</i>
Note: the dimension, dim , of the array a must be at least $\max(1, \mathbf{pda} \times \mathbf{n})$.		
<i>On exit:</i> the n by n triangular matrix A .		
If order = 'Nag_ColMajor', A_{ij} is stored in a [($j - 1$) \times pda + $i - 1$].		
If order = 'Nag_RowMajor', A_{ij} is stored in a [($i - 1$) \times pda + $j - 1$].		
If uplo = 'Nag_Upper', A is upper triangular and the elements of the array corresponding to the lower triangular part of A are not referenced.		
If uplo = 'Nag_Lower', A is lower triangular and the elements of the array corresponding to the upper triangular part of A are not referenced.		
7:	pda – Integer	<i>Input</i>
<i>On entry:</i> the stride separating row or column elements (depending on the value of order) of the matrix A in the array a .		
<i>Constraint:</i> pda $\geq \max(1, \mathbf{n})$.		
8:	fail – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 3.6 in the Essential Introduction).		

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle value \rangle$.
Constraint: **n** ≥ 0 .

NE_INT_2

On entry, **pda** = $\langle value \rangle$, **n** = $\langle value \rangle$.
Constraint: **pda** $\geq \max(1, \mathbf{n})$.

7 Accuracy

The BLAS standard requires accurate implementations which avoid unnecessary over/underflow (see Section 2.7 of Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001)).

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

This example initializes the lower triangular matrix A with diagonal elements given by $d = 3.45$ and off-diagonal elements given by $\alpha = 1.23$.

10.1 Program Text

```
/* nag_dtr_load (f16qgc) Example Program.
*
* Copyright 2005 Numerical Algorithms Group.
*
* Mark 8, 2005.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf16.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    double alpha, diag;
    Integer exit_status, n, pda;

    /* Arrays */
    double *a = 0;
    char nag_enum_arg[40];

    /* Nag Types */
    NagError fail;
    Nag_MatrixType matrix;
    Nag_OrderType order;
    Nag_UptoType uplo;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
    order = Nag_RowMajor;
#endif

    exit_status = 0;
    INIT_FAIL(fail);

    printf("nag_dtr_load (f16qgc) Example Program Results\n\n");

    /* Skip heading in data file */
    scanf("%*[^\n] ");
    /* Read the problem dimension */
    scanf("%ld%*[^\n] ", &n);
    /* Read uplo */
    scanf("%39s%*[^\n] ", nag_enum_arg);
    /* nag_enum_name_to_value (x04nac).
     * Converts NAG enum member name to value
     */
    uplo = (Nag_UptoType) nag_enum_name_to_value(nag_enum_arg);
    /* Read scalar parameters */
    scanf("%lf%lf%*[^\n] ", &alpha, &diag);

    pda = n;

    if (n > 0)
    {
        /* Allocate memory */
        if (!(a = NAG_ALLOC(n*pda, double)))

```

```

    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
}
else
{
    printf("Invalid n\n");
    exit_status = 1;
    return exit_status;
}

/* nag_dtr_load (f16qgc).
 * Triangular matrix initialise.
 */
nag_dtr_load(order, uplo, n, alpha, diag, a, pda, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dtr_load (f16qgc).\\n%s\\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print output */
/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
if (uplo == Nag_Upper)
    matrix = Nag_UpperMatrix;
else
    matrix = Nag_LowerMatrix;

fflush(stdout);
nag_gen_real_mat_print(order, matrix, Nag_NonUnitDiag,
                       n, n, a, pda, "Matrix A",
                       0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print (x04cac).\\n%s\\n",
           fail.message);
    exit_status = 1;
    goto END;
}

END:
NAG_FREE(a);

return exit_status;
}

```

10.2 Program Data

```
nag_dtr_load (f16qgc) Example Program Data
 4                               :Value of n
 Nag_Lower                         :Value of uplo
 1.23 3.45                          :Values of alpha, diag
```

10.3 Program Results

```
nag_dtr_load (f16qgc) Example Program Results
```

Matrix A

	1	2	3	4
1	3.4500			
2	1.2300	3.4500		
3	1.2300	1.2300	3.4500	
4	1.2300	1.2300	1.2300	3.4500
