

NAG Library Function Document

nag_multi_normal_pdf_vector (g01lbc)

1 Purpose

nag_multi_normal_pdf_vector (g01lbc) returns a number of values of the probability density function (PDF), or its logarithm, for the multivariate Normal (Gaussian) distribution.

2 Specification

```
#include <nag.h>
#include <nagg01.h>
void nag_multi_normal_pdf_vector (Nag_Boolean ilog, Integer k, Integer n,
const double x[], Integer pdx, const double xmu[], Nag_MatrixType iuld,
const double sig[], Integer pdsig, double pdf[], Integer *rank,
NagError *fail)
```

3 Description

The probability density function, $f(X : \mu, \Sigma)$ of an n -dimensional multivariate Normal distribution with mean vector μ and n by n variance-covariance matrix Σ , is given by

$$f(X : \mu, \Sigma) = ((2\pi)^n |\Sigma|)^{-1/2} \exp\left(-\frac{1}{2}(X - \mu)^T \Sigma^{-1} (X - \mu)\right).$$

If the variance-covariance matrix, Σ , is not of full rank then the probability density function, is calculated as

$$f(X : \mu, \Sigma) = ((2\pi)^r \text{pdet}(\Sigma))^{-1/2} \exp\left(-\frac{1}{2}(X - \mu)^T \Sigma^- (X - \mu)\right)$$

where $\text{pdet}(\Sigma)$ is the pseudo-determinant, Σ^- a generalized inverse of Σ and r its rank.

nag_multi_normal_pdf_vector (g01lbc) evaluates the PDF at k points with a single call.

4 References

None.

5 Arguments

1: **ilog** – Nag_Boolean *Input*

On entry: the value of **ilog** determines whether the logarithmic value is returned in PDF.

ilog = Nag_FALSE

$f(X : \mu, \Sigma)$, the probability density function is returned.

ilog = Nag_TRUE

$\log(f(X : \mu, \Sigma))$, the logarithm of the probability density function is returned.

2: **k** – Integer *Input*

On entry: k , the number of points the PDF is to be evaluated at.

Constraint: $k \geq 0$.

3: **n** – Integer *Input*

On entry: n , the number of dimensions.

Constraint: $\mathbf{n} \geq 2$.

4: **x**[*dim*] – const double *Input*

Note: the dimension, dim , of the array **x** must be at least **pdx** \times **k**.

Where $\mathbf{X}(i, j)$ appears in this document, it refers to the array element $\mathbf{x}[(j - 1) \times \mathbf{pdx} + i - 1]$.

On entry: X , the matrix of k points at which to evaluate the probability density function, with the i th dimension for the j th point held in $\mathbf{X}(i, j)$.

5: **pdx** – Integer *Input*

On entry: the stride separating matrix row elements in the array **x**.

Constraint: **pdx** $\geq n$.

6: **xmu[n]** – const double *Input*

On entry: μ , the mean vector of the multivariate Normal distribution.

7: **iuld** – Nag_MatrixType *Input*

On entry: indicates the form of Σ and how it is stored in **sig**.

iuld = Nag_LowerMatrix

sig holds the lower triangular portion of Σ .

iuld = Nag_UpperMatrix

sig holds the upper triangular portion of Σ .

iuld = Nag_DiagonalMatrix

Σ is a diagonal matrix and **sig** only holds the diagonal elements.

iuld = Nag_LowerFactored

sig holds the lower Cholesky decomposition, L such that $LL^T = \Sigma$.

iuld = Nag_UpperFactored

sig holds the upper Cholesky decomposition, U such that $U^TU = \Sigma$.

Constraint: **iuld** = Nag_LowerMatrix, Nag_UpperMatrix, Nag_DiagonalMatrix, Nag_LowerFactored or Nag_UpperFactored.

8: **sig**[*dim*] – const double *Input*

Note: the dimension, dim , of the array **sig** must be at least **pdsig** \times **n**.

Where $\mathbf{SIG}(i, j)$ appears in this document, it refers to the array element $\mathbf{sig}[(j - 1) \times \mathbf{pdsig} + i - 1]$.

On entry: information defining the variance-covariance matrix, Σ .

iuld = Nag_LowerMatrix or Nag_UpperMatrix

sig must hold the lower or upper portion of Σ , with Σ_{ij} held in $\mathbf{SIG}(i, j)$. The supplied variance-covariance matrix must be positive semidefinite.

iuld = Nag_DiagonalMatrix

Σ is a diagonal matrix and the i th diagonal element, Σ_{ii} , must be held in $\mathbf{SIG}(1, i)$

iuld = Nag_LowerFactored or Nag_UpperFactored

sig must hold L or U , the lower or upper Cholesky decomposition of Σ , with L_{ij} or U_{ij} held in $\mathbf{SIG}(i, j)$, depending on the value of **iuld**. No check is made that LL^T or U^TU is a valid variance-covariance matrix. The diagonal elements of the supplied L or U must be greater than zero

9:	pdsig – Integer	<i>Input</i>
<i>On entry:</i> the stride separating matrix row elements in the array sig .		
<i>Constraints:</i>		
	if iuld = Nag_DiagonalMatrix, pdsig ≥ 1 ; otherwise pdsig $\geq n$.	
10:	pdf[k] – double	<i>Output</i>
<i>On exit:</i> $f(X : \mu, \Sigma)$ or $\log(f(X : \mu, \Sigma))$ depending on the value of ilog .		
11:	rank – Integer *	<i>Output</i>
<i>On exit:</i> r , rank of Σ .		
12:	fail – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 3.6 in the Essential Introduction).		

6 Error Indicators and Warnings

NE_ARRAY_SIZE

On entry, **pdsig** = $\langle value \rangle$.

Constraint: if **iuld** = Nag_DiagonalMatrix, **pdsig** ≥ 1 .

On entry, **pdsig** = $\langle value \rangle$.

Constraint: if **iuld** \neq Nag_DiagonalMatrix, **pdsig** $\geq n$.

On entry, **pdx** = $\langle value \rangle$ and **n** = $\langle value \rangle$.

Constraint: **pdx** $\geq n$.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_DIAG_ELEMENTS

On entry, at least one diagonal element of Σ is less than or equal to 0.

NE_INT

On entry, **k** = $\langle value \rangle$.

Constraint: **k** ≥ 0 .

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 2 .

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_MAT_NOT_POS_DEF

On entry, Σ is not positive definite and eigenvalue decomposition failed.

NE_NOT_POS_SEM_DEF

On entry, Σ is not positive semidefinite.

7 Accuracy

Not applicable.

8 Parallelism and Performance

`nag_multi_normal_pdf_vector` (g01lbc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_multi_normal_pdf_vector` (g01lbc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

This example prints the value of the multivariate Normal PDF at a number of different points.

10.1 Program Text

```
/* nag_multi_normal_pdf_vector (g01lbc) Example Program.
*
* Copyright 2011, Numerical Algorithms Group.
*
* Mark 23, 2011.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlb.h>
#include <nagg01.h>
#include <nagx04.h>

#define X(I, J)    x[(J) *pdx + I]
#define SIG(I, J)  sig[(J) *pdsig + I]

int main(void)
{
    /* Integer scalar and array declarations */
    Integer i, j, k, n, pdx, pdsig, rank,
    Integer exit_status = 0;

    /* NAG structures and types */
    NagError fail;
    Nag_MatrixType iuld;
    Nag_Boolean ilog;

    /* Double scalar and array declarations */
    double *x = 0, *xmu = 0, *sig = 0, *pdf = 0;

    /* Character scalar and array declarations */
    char ciuld[40], cilog[40];

    /* Initialise the error structure */
    INIT_FAIL(fail);

    printf("nag_multi_normal_pdf_vector (g01lbc) Example Program Results\n\n");

    /* Skip heading in data file */
    scanf("%*[^\n] ");
}
```

```

/* Read in the problem size */
scanf("%ld%ld%39s%39s*[^\n] ", &k, &n, ciuld, cilog);
ilog = (Nag_Boolean) nag_enum_name_to_value(cilog);
iuld = (Nag_MatrixType) nag_enum_name_to_value(ciuld);

pdx = n;
pdsig = (iuld==Nag_DiagonalMatrix) ? 1 : n;
if (!(x = NAG_ALLOC(pdx*k, double)) ||
    !(xmu = NAG_ALLOC(n,double)) ||
    !(sig = NAG_ALLOC(pdsig*n, double)) ||
    !(pdf = NAG_ALLOC(k,double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read in and echo the vector of means */
for (i = 0; i < n; i++)
    scanf("%lf", &xmu[i]);
scanf("%*[^\n] ");

printf("Vector of Means:\n");
for (i = 0; i < n; i++)
    printf("%8.4f ", xmu[i]);
printf("\n\n");

/* Read in and echo the covariance matrix */

if (iuld == Nag_DiagonalMatrix) {

    for (i = 0; i < n; i++)
        scanf("%lf", &SIG(1,i));
    scanf("%*[^\n] ");

    printf("Diagonal Elements of Covariance Matrix:\n");
    for (i = 0; i < n; i++)
        printf("%8.4f ", SIG(1,i));
    printf("\n\n");

} else if (iuld == Nag_LowerMatrix || iuld == Nag_LowerFactored) {

    for (i = 0; i < n; i++) {
        for (j = 0; j <= i; j++)
            scanf("%lf", &SIG(i,j));
        scanf("%*[^\n] ");
    }
    /* Print details of Covariance matrix using
     * nag_gen_real_mat_print (x04cac)
     */
    if (iuld == Nag_LowerMatrix)
        nag_gen_real_mat_print(Nag_ColMajor, Nag_LowerMatrix, Nag_NonUnitDiag, n,
                               n, sig, pdsig, "Covariance Matrix:", NULL, &fail);
    else
        nag_gen_real_mat_print(Nag_ColMajor, Nag_LowerMatrix, Nag_NonUnitDiag, n,
                               n, sig, pdsig, "Lower Triangular Cholesky Factor "
                               "of Covariance Matrix:", NULL, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_gen_real_mat_print (x04cac).\\n%s\\n", fail.message);
        exit_status = 1;
        goto END;
    }

} else {
    /* Upper triangle of matrix or factor is stored */

    for (i = 0; i < n; i++) {
        for (j = i; j < n; j++)
            scanf("%lf", &SIG(i,j));
        scanf("%*[^\n] ");
    }
}

```

```

}
/* Print details of Covariance matrix using
 * nag_gen_real_mat_print (x04cac)
 */
if (iuld == Nag_UpperMatrix)
    nag_gen_real_mat_print(Nag_ColMajor, Nag_UpperMatrix, Nag_NonUnitDiag, n,
                           n, sig, pdsig, "Covariance Matrix:", NULL, &fail);
else
    nag_gen_real_mat_print(Nag_ColMajor, Nag_UpperMatrix, Nag_NonUnitDiag, n,
                           n, sig, pdsig, "Upper Triangular Cholesky Factor "
                           "of Covariance Matrix:", NULL, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_gen_real_mat_print (x04cac).\\n%s\\n", fail.message);
    exit_status = 1;
    goto END;
}
}

/* Read in the points at which to evaluate the PDF */
for (j = 0; j < k; j++)
    for (i = 0; i < n; i++)
        scanf("%lf", &X(i,j));

/* nag_multi_normal_pdf_vector (g01lbc): evaluate the PDF */
nag_multi_normal_pdf_vector(ilog, k, n, x, pdx, xmu, iuld, sig, pdsig,
                            pdf, &rank, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_multi_normal_pdf_vector (g01lbc).\\n%s\\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Display results */
printf("\nRank of the covariance matrix: %ld\\n\\n", rank);
if (ilog)
    printf("      log(PDF)          X\\n");
else
    printf("      PDF              X\\n");
printf("  -----\\n");
for (j = 0; j < k; j++) {
    printf(" %13.4e", pdf[j]);
    for (i = 0; i < n; i++)
        printf(" %8.4f", X(i,j));
    printf("\\n");
}
}

END:
NAG_FREE(x);
NAG_FREE(xmu);
NAG_FREE(sig);
NAG_FREE(pdf);

return exit_status;
}

```

10.2 Program Data

```

nag_multi_normal_pdf_vector (g01lbc) Example Program Data
2 4 Nag_LowerMatrix Nag_FALSE : k,n,iuld,ilog
0.10  0.20  0.30  0.40      : End xmu
4.16
-3.12  5.03
0.56 -0.83  0.76
-0.10  1.18  0.34  1.18      : End sig
1.00  1.00  1.00  1.00
1.00  2.00  3.00  4.00      : End of x

```

10.3 Program Results

nag_multi_normal_pdf_vector (g01lbc) Example Program Results

Vector of Means:

0.1000 0.2000 0.3000 0.4000

Covariance Matrix:

	1	2	3	4
1	4.1600			
2	-3.1200	5.0300		
3	0.5600	-0.8300	0.7600	
4	-0.1000	1.1800	0.3400	1.1800

Rank of the covariance matrix: 4

PDF	X
-----	---

3.0307e-03	1.0000	1.0000	1.0000	1.0000
4.5232e-06	1.0000	2.0000	3.0000	4.0000
