

NAG Library Function Document

nag_estimate_agarchII (g13fcc)

1 Purpose

nag_estimate_agarchII (g13fcc) estimates the arguments of a univariate regression-type II AGARCH(p, q) process.

2 Specification

```
#include <nag.h>
#include <nagg13.h>
void nag_estimate_agarchII (const double yt[], const double x[], Integer tdx,
                           Integer num, Integer p, Integer q, Integer nreg, Integer mn,
                           double theta[], double se[], double sc[], double covar[], Integer tdc,
                           double *hp, double et[], double ht[], double *lgf,
                           Nag_Garch_Stationary_Type stat_opt, Nag_Garch_Est_Initial_Type est_opt,
                           Integer max_iter, double tol, NagError *fail)
```

3 Description

A univariate regression-type II AGARCH(p, q) process, with p coefficients α_i , for $i = 1, 2, \dots, p$, q , coefficients, β_i , for $i = 1, 2, \dots, q$, mean b_o , and k linear regression coefficients b_i , for $i = 1, 2, \dots, k$, can be represented by:

$$y_t = b_o + x_t^T b + \epsilon_t \quad (1)$$

$$\epsilon_t | \psi_{t-1} \sim N(0, h_t)$$

$$h_t = \alpha_0 + \sum_{i=1}^q \alpha_i (|\epsilon_{t-i}| + \gamma \epsilon_{t-i})^2 + \sum_{i=1}^p \beta_i h_{t-i}, \quad t = 1, \dots, T.$$

Here T is the number of terms in the sequence, y_t denotes the endogenous variables, x_t the exogenous variables, b_o the mean, b the regression coefficients, ϵ_t the residuals, γ the asymmetry argument, h_t the conditional variance, and ψ_t the information set of all information up to time t .

nag_estimate_agarchII (g13fcc) provides an estimate for $\hat{\theta}$, the $(p+q+k+3) \times 1$ parameter vector $\theta = (b_o, b^T, \omega^T)$ where $\omega^T = (\alpha_0, \alpha_1, \dots, \alpha_q, \beta_1, \dots, \beta_p, \gamma)$ and $b^T = (b_1, \dots, b_k)$.

mn, **nreg** can be used to simplify the GARCH(p, q) expression in equation (1) as follows:

No Regression or Mean

$$y_t = \epsilon_t,$$

$$\mathbf{mn} = 0,$$

$$\mathbf{nreg} = 0, \text{ and}$$

$$\theta \text{ is a } (p+q+2) \times 1 \text{ vector.}$$

No Regression

$$y_t = b_o + \epsilon_t,$$

$$\mathbf{mn} = 1,$$

$$\mathbf{nreg} = 0, \text{ and}$$

$$\theta \text{ is a } (p+q+3) \times 1 \text{ vector.}$$

Note: if the $y_t = \mu + \epsilon_t$, where μ is known (not to be estimated by nag_estimate_agarchII (g13fcc)) then equation (1) can be written as $y_t^\mu = \epsilon_t$, where $y_t^\mu = y_t - \mu$. This corresponds to the case **No Regression or Mean**, with y_t replaced by $y_t - \mu$.

No Mean

$y_t = x_t^T b + \epsilon_t$,
mn = 0,
nreg = k and
 θ is a $(p + q + k + 2) \times 1$ vector.

4 References

- Bollerslev T (1986) Generalised autoregressive conditional heteroskedasticity *Journal of Econometrics* **31** 307–327
- Engle R (1982) Autoregressive conditional heteroskedasticity with estimates of the variance of United Kingdom inflation *Econometrica* **50** 987–1008
- Engle R and Ng V (1993) Measuring and testing the impact of news on volatility *Journal of Finance* **48** 1749–1777
- Hamilton J (1994) *Time Series Analysis* Princeton University Press

5 Arguments

Note: for convenience *npar* will be used here to denote the expression $2 + \mathbf{q} + \mathbf{p} + \mathbf{mn} + \mathbf{nreg}$ representing the number of model parameters.

- 1: **yt[num]** – const double *Input*
On entry: the sequence of observations, y_t , for $t = 1, 2, \dots, T$.
- 2: **x[num × tdx]** – const double *Input*
Note: the i th element of the j th vector X is stored in $\mathbf{x}[(i - 1) \times \mathbf{tdx} + j - 1]$.
On entry: row t of \mathbf{x} must contain the time dependent exogenous vector x_t , where $x_t^T = (x_t^1, \dots, x_t^k)$, for $t = 1, 2, \dots, T$.
- 3: **tdx** – Integer *Input*
On entry: the stride separating matrix column elements in the array \mathbf{x} .
Constraint: $\mathbf{tdx} \geq \mathbf{nreg}$.
- 4: **num** – Integer *Input*
On entry: the number of terms in the sequence, T .
Constraint: $\mathbf{num} \geq \mathbf{npar}$.
- 5: **p** – Integer *Input*
On entry: the GARCH(p, q) argument p .
Constraint: $\mathbf{p} \geq 0$.
- 6: **q** – Integer *Input*
On entry: the GARCH(p, q) argument q .
Constraint: $\mathbf{q} \geq 1$.

7:	nreg – Integer	<i>Input</i>
	<i>On entry:</i> k , the number of regression coefficients.	
	<i>Constraint:</i> $\mathbf{nreg} \geq 0$.	
8:	mn – Integer	<i>Input</i>
	<i>On entry:</i> if $\mathbf{mn} = 1$, the mean term b_0 will be included in the model.	
	<i>Constraint:</i> $\mathbf{mn} = 0$ or 1 .	
9:	theta [npar] – double	<i>Input/Output</i>
	<i>On entry:</i> the initial parameter estimates for the vector θ .	
	The first element contains the coefficient α_o , the next \mathbf{q} elements contain the autoregressive coefficients α_i , for $i = 1, 2, \dots, q$.	
	The next \mathbf{p} elements are the moving average coefficients β_j , for $j = 1, 2, \dots, p$.	
	The next element contains the asymmetry argument γ .	
	If est_opt = Nag_Garch_Est_Initial_False, (when $\mathbf{mn} = 1$) the next term contains an initial estimate of the mean term b_o and the remaining nreg elements are taken as initial estimates of the linear regression coefficients b_i , for $i = 1, 2, \dots, k$.	
	<i>On exit:</i> the estimated values $\hat{\theta}$ for the vector θ .	
	The first element contains the coefficient α_o , the next \mathbf{q} elements contain the coefficients α_i , for $i = 1, 2, \dots, q$.	
	The next \mathbf{p} elements are the coefficients β_j , for $j = 1, 2, \dots, p$.	
	The next element contains the estimate for the asymmetry parameter γ .	
	If $\mathbf{mn} = 1$, the next element contains an estimate for the mean term b_o .	
	The final nreg elements are the estimated linear regression coefficients b_i , for $i = 1, 2, \dots, k$.	
10:	se [npar] – double	<i>Output</i>
	<i>On exit:</i> the standard errors for $\hat{\theta}$.	
	The first element contains the standard error for α_o .	
	The next \mathbf{q} elements contain the standard errors for α_i , for $i = 1, 2, \dots, q$.	
	The next \mathbf{p} elements are the standard errors for β_j , for $j = 1, 2, \dots, p$.	
	The next element contains the standard error for γ .	
	If $\mathbf{mn} = 1$, the next element contains the standard error for b_o .	
	The final nreg elements are the standard errors for b_j , for $j = 1, 2, \dots, k$.	
11:	sc [npar] – double	<i>Output</i>
	<i>On exit:</i> the scores for $\hat{\theta}$.	
	The first element contains the score for α_o .	
	The next \mathbf{q} elements contain the score for α_i , for $i = 1, 2, \dots, q$.	
	The next \mathbf{p} elements are the scores for β_j , for $j = 1, 2, \dots, p$.	
	The next element contains the score for γ .	
	If $\mathbf{mn} = 1$, the next element contains the score for b_o .	
	The final nreg elements are the scores for b_j , for $j = 1, 2, \dots, k$.	

12: **covar**[*npar* × **tdc**] – double *Output*

Note: the (i, j) th element of the matrix is stored in **covar**[(*i* − 1) × **tdc** + *j* − 1].

On exit: the covariance matrix of the parameter estimates $\hat{\theta}$, that is the inverse of the Fisher Information Matrix.

13: **tdc** – Integer *Input*

On entry: the stride separating matrix column elements in the array **covar**.

Constraint: **tdc** $\geq npar$.

14: **hp** – double * *Input/Output*

On entry: if **est_opt** = Nag_Garch_Est_Initial_False, **hp** is the value to be used for the pre-observed conditional variance.

If **est_opt** = Nag_Garch_Est_Initial_True, **hp** is not referenced.

On exit: if **est_opt** = Nag_Garch_Est_Initial_True, **hp** is the estimated value of the pre-observed of the conditional variance.

15: **et[num]** – double *Output*

On exit: the estimated residuals, ϵ_t , for $t = 1, 2, \dots, T$.

16: **ht[num]** – double *Output*

On exit: the estimated conditional variances, h_t , for $t = 1, 2, \dots, T$.

17: **lgf** – double * *Output*

On exit: the value of the log likelihood function at $\hat{\theta}$.

18: **stat_opt** – Nag_Garch_Stationary_Type *Input*

On entry: if **stat_opt** = Nag_Garch_Stationary_True, Stationary conditions are enforced.

If **stat_opt** = Nag_Garch_Stationary_False, Stationary conditions are not enforced.

Constraint: **stat_opt** = Nag_Garch_Stationary_True or Nag_Garch_Stationary_False.

19: **est_opt** – Nag_Garch_Est_Initial_Type *Input*

On entry: if **est_opt** = Nag_Garch_Est_Initial_True, the function provides initial parameter estimates of the regression terms (b_0, b^T) .

If **est_opt** = Nag_Garch_Est_Initial_False, you must supply the initial estimations of the regression parameters (b_0, b^T) .

Constraint: **est_opt** = Nag_Garch_Est_Initial_True or Nag_Garch_Est_Initial_False.

20: **max_iter** – Integer *Input*

On entry: the maximum number of iterations to be used by the optimization function when estimating the GARCH(*p, q*) arguments. If **max_iter** is set to 0, the standard errors, score vector and variance-covariance are calculated for the input value of θ in **theta**; however the value of θ is not updated.

Constraint: **max_iter** ≥ 0 .

21: **tol** – double *Input*

On entry: the tolerance to be used by the optimization function when estimating the GARCH(*p, q*) parameters.

22: **fail** – NagError *

Input/Output

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_2_INT_ARG_LT

On entry, **num** = $\langle value \rangle$ while $2 + \mathbf{q} + \mathbf{p} + \mathbf{mn} + \mathbf{nreg} = \langle value \rangle$. These arguments must satisfy $\mathbf{num} \geq 2 + \mathbf{q} + \mathbf{p} + \mathbf{mn} + \mathbf{nreg}$.

On entry, **tdc** = $\langle value \rangle$ while $2 + \mathbf{q} + \mathbf{p} + \mathbf{mn} + \mathbf{nreg} = \langle value \rangle$. These arguments must satisfy $\mathbf{tdc} \geq 2 + \mathbf{q} + \mathbf{p} + \mathbf{mn} + \mathbf{nreg}$.

On entry, **tdx** = $\langle value \rangle$ while **nreg** = $\langle value \rangle$. These arguments must satisfy $\mathbf{tdx} \geq \mathbf{nreg}$.

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_BAD_PARAM

On entry, argument **est_opt** had an illegal value.

On entry, argument **stat_opt** had an illegal value.

NE_INT_ARG_LT

On entry, **max_iter** must not be less than 0: **max_iter** = $\langle value \rangle$.

On entry, **nreg** = $\langle value \rangle$.

Constraint: $\mathbf{nreg} \geq 0$.

On entry, **p** = $\langle value \rangle$.

Constraint: $\mathbf{p} \geq 0$.

On entry, **q** = $\langle value \rangle$.

Constraint: $\mathbf{q} \geq 1$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_INVALID_INT_RANGE_2

Value $\langle value \rangle$ given to **mn** is not valid. Correct range is 0 to 1.

NE_MAT_NOT_FULL_RANK

Matrix X does not give a model of full rank.

NE_MAT_NOT_POS_DEF

Attempt to invert the second derivative matrix needed in the calculation of the covariance matrix of the parameter estimates has failed. The matrix is not positive definite, possibly due to rounding errors.

7 Accuracy

Not applicable.

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

This example program illustrates the use of nag_estimate_agarchII (g13fcc) to model a GARCH(1,1) sequence generated by nag_rand_agarchII (g05pec), a three step forecast is then calculated using nag_forecast_agarchII (g13fdc).

10.1 Program Text

```
/* nag_estimate_agarchII (g13fcc) Example Program.
*
* Copyright 2000 Numerical Algorithms Group.
*
* NAG C Library
*
* Mark 6, 2000.
*
*/
#include <nag.h>
#include <nag_stdlib.h>
#include <stdio.h>
#include <ctype.h>
#include <math.h>
#include <nagg05.h>
#include <nagg13.h>

#define X(I, J) x[(I) *tdx + (J)]

int main(void)
{
    /* Integer scalar and array declarations */
    Integer          exit_status = 0;
    Integer          i, j, k, npar, tdc, tdx, lstate, lr;
    Integer          *state = 0;

    /* NAG structures and data types */
    NagError         fail;
    Nag_Boolean      fcall;

    /* Double scalar and array declarations */
    double           fac1, hp, lgf, xterm,
                    *covar = 0, *cvar = 0, *et = 0, *ht = 0, *sc = 0;
    double           *se = 0, *theta = 0, *x = 0, *yt = 0, *r = 0;

    /* Choose the base generator */
    Nag_BaseRNG      genid = Nag_Basic;
    Integer          subid = 0;

    /* Set the seed */
    Integer          seed[] = { 111 };
    Integer          lseed = 1;

    /* Set parameters for the (randomly generated) time series ... */
    /* Generate data assuming normally distributed errors */
    Nag_ErrorDistn  dist = Nag_NormalDistn;
    double           df = 0;

    /* Size of the time series */
    Integer          num = 1500;

    /* MA and AR parameters */
    Integer          ip = 1;
    Integer          iq = 1;
    double           param[] = { 0.08, 0.2, 0.7 };
}
```

```

/* Asymmetry parameter */
double gamma = -0.4;

/* Regression parameters */
Integer nreg = 2;
double mean = 3.0;
double bx[] = { 1.5, 2.5 };
/* ... end of parameters for (randomly generated) time series */

/* When fitting a model to the time series ... */
/* Include mean in the model */
Integer mn = 1;

/* Use the following maximum number of iterations and tolerance */
Integer maxit = 50;
double tol = 1e-12;

/* Enforce stationary conditions */
Nag_Garch_Stationary_Type stat_opt = Nag_Garch_Stationary_True;

/* Estimate initial values for regression parameters */
Nag_Garch_Est_Initial_Type est_opt = Nag_Garch_Est_Initial_True;

/* Set the number of values to forecast from the fitted model */
Integer nt = 3;
/* ... end of model fitting options */

/* Initialise the error structure */
INIT_FAIL(fail);

printf("nag_estimate_agarchII (g13fcc) Example Program Results\n\n");

/* Get the length of the state array */
lstate = -1;
nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Derive various amounts */
npar = iq + ip + 1;
tdc = npar + mn + nreg + 1;
tdx = nreg;

/* Calculate the size of the reference vector */
lr = 2 * (iq + ip + 2);

/* Allocate arrays */
if (!(covar = NAG_ALLOC((npar + mn + nreg + 1) * tdc, double)) ||
    !(et = NAG_ALLOC(num, double)) ||
    !(ht = NAG_ALLOC(num, double)) ||
    !(sc = NAG_ALLOC(npar + mn + nreg + 1, double)) ||
    !(se = NAG_ALLOC(npar + mn + nreg + 1, double)) ||
    !(state = NAG_ALLOC(lstate, Integer)) ||
    !(r = NAG_ALLOC(lr, double)) ||
    !(theta = NAG_ALLOC(npar + mn + nreg + 1, double)) ||
    !(x = NAG_ALLOC(num * tdx, double)) ||
    !(cvar = NAG_ALLOC(nt, double)) ||
    !(yt = NAG_ALLOC(num, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Initialise the generator to a repeatable sequence */
nag_rand_init_repeatable(genid, subid, seed, lseed, state, &fail);

```

```

if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Set up the time dependent exogenous matrix x */
for (i = 0; i < num; ++i)
{
    fac1 = (double)(i + 1) *.01;
    X(i, 0) = sin(fac1) * 0.7 + 0.01;
    X(i, 1) = fac1 * 0.1 + 0.5;
}

/* Generate a realization of a random AGARCH II time series to use */
fcall = Nag_TRUE;
nag_rand_agarchII(dist, num, ip, iq, param, gamma, df, ht, yt, fcall, r, lr,
                   state, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_agarchII (g05pec).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Adjust the randomly generated time series to take into account for the
   exogenous matrix x */
for (i = 0; i < num; ++i)
{
    xterm = 0.0;
    for (k = 0; k < nreg; ++k)
        xterm += X(i, k) * bx[k];

    if (mn == 1)
        yt[i] = mean + xterm + yt[i];
    else
        yt[i] = xterm + yt[i];
}

/* Set initial estimates for the parameters */
for (i = 0; i < npars; ++i)
{
    theta[i] = param[i] * 0.5;
}
theta[npars] = gamma * 0.5;
if (mn == 1)
{
    theta[npars + mn] = mean * 0.5;
}
if (est_opt != Nag_Garch_Est_Initial_True)
{
    for (i = 0; i < nreg; ++i)
        theta[npars + mn + 1 + i] = bx[i] * 0.5;
}

/* nag_estimate_agarchII (g13fcc).
 * Univariate time series, parameter estimation for a GARCH
 * process with asymmetry of the form
 * (|epsilon_(t-1)| + gamma epsilon_(t-1))^2
 */
nag_estimate_agarchII(yt, x, tdx, num, ip, iq, nreg, mn, theta, se, sc,
                      covar, tdc, &hp, et, ht, &lgf, stat_opt, est_opt,
                      maxit, tol, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_estimate_agarchII (g13fcc).\n%s\n",
           fail.message);
    exit_status = 1;
}

```

```

        goto END;
    }

/* Display the results */
printf("      Parameter estimates      Standard errors      "
      "Correct values\n");
for (j = 0; j < npar; ++j)
    printf("%20.4f          (%6.4f) %20.4f\n", theta[j], se[j],
           param[j]);
printf("%20.4f          (%6.4f) %20.4f\n", theta[npar], se[npar],
       gamma);
if (mn == 1)
    printf("%20.4f          (%6.4f) %20.4f\n", theta[npar + mn],
           se[npar + mn], mean);
for (j = 0; j < nreg; ++j)
    printf("%20.4f          (%6.4f) %20.4f\n",
           theta[mn + npar + 1 + j], se[mn + npar + 1 + j], bx[j]);

/* Now forecast nt steps ahead */
gamma = theta[npar];

/* nag_forecast_agarchII (g13fdc).
 * Univariate time series, forecast function for a GARCH
 * process with asymmetry of the form
 * (|epsilon_(t-1)| + gamma epsilon_(t-1))^2
 */
nag_forecast_agarchII(num, nt, ip, iq, theta, gamma, cvar, ht, et, &fail);
printf("\n%ld step forecast = %8.4f\n", nt, cvar[nt-1]);

END:
NAG_FREE(covar);
NAG_FREE(et);
NAG_FREE(ht);
NAG_FREE(state);
NAG_FREE(r);
NAG_FREE(sc);
NAG_FREE(se);
NAG_FREE(theta);
NAG_FREE(cvar);
NAG_FREE(x);
NAG_FREE(yt);

return exit_status;
}

```

10.2 Program Data

None.

10.3 Program Results

nag_estimate_agarchII (g13fcc) Example Program Results

Parameter estimates	Standard errors	Correct values
0.0916	(0.0147)	0.0800
0.2268	(0.0324)	0.2000
0.6596	(0.0326)	0.7000
-0.4188	(0.0686)	-0.4000
2.9804	(0.0565)	3.0000
1.5345	(0.0362)	1.5000
2.5314	(0.0424)	2.5000

3 step forecast = 0.4238
