

NAG Library Function Document

nag_bessel_i_nu_scaled (s18ecc)

1 Purpose

nag_bessel_i_nu_scaled (s18ecc) returns the value of the scaled modified Bessel function $e^{-x}I_{\nu/4}(x)$ for real $x > 0$.

2 Specification

```
#include <nag.h>
#include <nags.h>
double nag_bessel_i_nu_scaled (double x, Integer nu, NagError *fail)
```

3 Description

nag_bessel_i_nu_scaled (s18ecc) evaluates an approximation to the scaled modified Bessel function of the first kind $e^{-x}I_{\nu/4}(x)$, where the order $\nu = -3, -2, -1, 1, 2$ or 3 and x is real and positive. For positive orders it may also be called with $x = 0$, since $I_{\nu/4}(0) = 0$ when $\nu > 0$. For negative orders the formula

$$I_{-\nu/4}(x) = I_{\nu/4}(x) + \frac{2}{\pi} \sin\left(\frac{\pi\nu}{4}\right) K_{\nu/4}(x)$$

is used prior to multiplication by the scale factor e^{-x} .

4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

5 Arguments

- | | | |
|----|---|---------------------|
| 1: | x – double | <i>Input</i> |
| | <i>On entry</i> : the argument x of the function. | |
| | <i>Constraints</i> : | |
| | if nu < 0, x > 0.0;
if nu > 0, x ≥ 0.0. | |
| 2: | nu – Integer | <i>Input</i> |
| | <i>On entry</i> : the argument ν of the function. | |
| | <i>Constraint</i> : $1 \leq \text{abs}(\text{nu}) \leq 3$. | |
| 3: | fail – NagError * | <i>Input/Output</i> |
| | The NAG error argument (see Section 3.6 in the Essential Introduction). | |

6 Error Indicators and Warnings

NE_INT

On entry, **nu** = $\langle value \rangle$.
 Constraint: $1 \leq \text{abs}(\mathbf{nu}) \leq 3$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_OVERFLOW_LIKELY

The evaluation has been abandoned due to the likelihood of overflow. The result is returned as zero.

NE_REAL_INT

On entry, **x** = $\langle value \rangle$, **nu** = $\langle value \rangle$.

Constraint: **x** > 0.0 when **nu** < 0.

On entry, **x** = $\langle value \rangle$, **nu** = $\langle value \rangle$.

Constraint: **x** \geq 0.0 when **nu** > 0.

NE_TERMINATION_FAILURE

The evaluation has been abandoned due to failure to satisfy the termination condition. The result is returned as zero.

NE_TOTAL_PRECISION_LOSS

The evaluation has been abandoned due to total loss of precision. The result is returned as zero.

NW_SOME_PRECISION_LOSS

The evaluation has been completed but some precision has been lost.

7 Accuracy

All constants in the underlying functions are specified to approximately 18 digits of precision. If t denotes the number of digits of precision in the floating-point arithmetic being used, then clearly the maximum number of correct digits in the results obtained is limited by $p = \min(t, 18)$. Because of errors in argument reduction when computing elementary functions inside the underlying functions, the actual number of correct digits is limited, in general, by $p - s$, where $s \approx \max(1, |\log_{10} x|)$ represents the number of digits lost due to the argument reduction. Thus the larger the value of x , the less the precision in the result.

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

The example program reads values of the arguments x and ν from a file, evaluates the function and prints the results.

10.1 Program Text

```
/* nag_bessel_i_nu_scaled (s18ecc) Example Program.
*
* Copyright 2000 Numerical Algorithms Group.
*
* NAG C Library
*
* Mark 6, 2000.
* Mark 7, revised, 2001.
*/
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nags.h>

int main(void)
{
    Integer exit_status = 0, nu;
    NagError fail;
    double x, y;

    INIT_FAIL(fail);

    /* Skip heading in data file */
    scanf("%*[^\n]");
    printf("nag_bessel_i_nu_scaled (s18ecc) Example Program Results\n");
    printf(" x      nu      y\n");
    while (scanf("%lf %ld%*[^\n]", &x, &nu) != EOF)
    {
        /* nag_bessel_i_nu_scaled (s18ecc).
         * Scaled modified Bessel function exp(-x) I_(nu/4)(x)
         */
        y = nag_bessel_i_nu_scaled(x, nu, &fail);
        if (fail.code != NE_NOERROR)
        {
            printf("Error from nag_bessel_i_nu_scaled (s18ecc).\n%s\n",
                   fail.message);
            exit_status = 1;
            goto END;
        }
        printf("%4.1f %6ld %13.4e\n", x, nu, y);
    }
END:
    return exit_status;
}
```

10.2 Program Data

```
nag_bessel_i_nu_scaled (s18ecc) Example Program Data
3.9  -3
1.4  -2
8.2  -1
6.7   1
0.5   2
2.3   3  : Values of x and nu
```

10.3 Program Results

```
nag_bessel_i_nu_scaled (s18ecc) Example Program Results
      x        nu        Y
    3.9      -3    1.9272e-01
    1.4      -2    3.5767e-01
    8.2      -1    1.4103e-01
    6.7       1    1.5649e-01
    0.5       2    3.5664e-01
    2.3       3    2.3748e-01
```
