NAG Library Function Document

nag real sym posdef packed lin solve (f04bec)

1 Purpose

nag_real_sym_posdef_packed_lin_solve (f04bec) computes the solution to a real system of linear equations AX = B, where A is an n by n symmetric positive definite matrix, stored in packed format, and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

2 Specification

3 Description

The Cholesky factorization is used to factor A as $A = U^{T}U$, if **uplo** = Nag_Upper, or $A = LL^{T}$, if **uplo** = Nag_Lower, where U is an upper triangular matrix and L is a lower triangular matrix. The factored form of A is then used to solve the system of equations AX = B.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia http://www.netlib.org/lapack/lug

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

5 Arguments

1: **order** – Nag_OrderType

Input

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: order = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UploType

Input

On entry: if $uplo = Nag_Upper$, the upper triangle of the matrix A is stored.

If $uplo = Nag_Lower$, the lower triangle of the matrix A is stored.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

3: **n** – Integer

Input

On entry: the number of linear equations n, i.e., the order of the matrix A.

Constraint: $\mathbf{n} \geq 0$.

NAG Library Manual

4: **nrhs** – Integer Input

On entry: the number of right-hand sides r, i.e., the number of columns of the matrix B.

Constraint: $\mathbf{nrhs} \geq 0$.

5: ap[dim] - double

Input/Output

Note: the dimension, dim, of the array ap must be at least $\max(1, \mathbf{n} \times (\mathbf{n} + 1)/2)$.

On entry: the n by n symmetric matrix A. The upper or lower triangular part of the symmetric matrix is packed column-wise in a linear array. The jth column of A is stored in the array ap as follows:

The storage of elements A_{ij} depends on the **order** and **uplo** arguments as follows:

```
if \mathbf{order} = \mathrm{Nag\_ColMajor} and \mathbf{uplo} = \mathrm{Nag\_Upper}, A_{ij} is stored in \mathbf{ap}[(j-1) \times j/2 + i - 1], for i \leq j; if \mathbf{order} = \mathrm{Nag\_ColMajor} and \mathbf{uplo} = \mathrm{Nag\_Lower}, A_{ij} is stored in \mathbf{ap}[(2n-j) \times (j-1)/2 + i - 1], for i \geq j; if \mathbf{order} = \mathrm{Nag\_RowMajor} and \mathbf{uplo} = \mathrm{Nag\_Upper}, A_{ij} is stored in \mathbf{ap}[(2n-i) \times (i-1)/2 + j - 1], for i \leq j; if \mathbf{order} = \mathrm{Nag\_RowMajor} and \mathbf{uplo} = \mathrm{Nag\_Lower}, A_{ij} is stored in \mathbf{ap}[(i-1) \times i/2 + j - 1], for i \geq j.
```

On exit: if fail.code = NE_NOERROR or NE_RCOND, the factor U or L from the Cholesky factorization $A = U^TU$ or $A = LL^T$, in the same storage format as A.

6: $\mathbf{b}[dim]$ – double

Input/Output

Note: the dimension, dim, of the array b must be at least

```
\max(1, \mathbf{pdb} \times \mathbf{nrhs}) when \mathbf{order} = \text{Nag\_ColMajor}; \max(1, \mathbf{n} \times \mathbf{pdb}) when \mathbf{order} = \text{Nag\_RowMajor}.
```

The (i, j)th element of the matrix B is stored in

```
\mathbf{b}[(j-1) \times \mathbf{pdb} + i - 1] when \mathbf{order} = \text{Nag\_ColMajor}; \mathbf{b}[(i-1) \times \mathbf{pdb} + j - 1] when \mathbf{order} = \text{Nag\_RowMajor}.
```

On entry: the n by r matrix of right-hand sides B.

On exit: if fail.code = NE NOERROR or NE RCOND, the n by r solution matrix X.

7: **pdb** – Integer

Input

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **b**.

Constraints:

```
if order = Nag_ColMajor, pdb \ge max(1, n); if order = Nag_RowMajor, pdb \ge max(1, nrhs).
```

8: **rcond** – double *

Output

On exit: if fail.code = NE_NOERROR or NE_RCOND, an estimate of the reciprocal of the condition number of the matrix A, computed as $\mathbf{rcond} = 1/(\|A\|_1 \|A^{-1}\|_1)$.

9: **errbnd** – double *

Output

On exit: if **fail.code** = NE_NOERROR or NE_RCOND, an estimate of the forward error bound for a computed solution \hat{x} , such that $\|\hat{x} - x\|_1 / \|x\|_1 \le \text{errbnd}$, where \hat{x} is a column of the computed solution returned in the array **b** and x is the corresponding column of the exact solution X. If **rcond** is less than *machine precision*, then **errbnd** is returned as unity.

f04bec.2 Mark 25

10: **fail** – NagError *

Input/Output

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE ALLOC FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE INT

```
On entry, \mathbf{n} = \langle value \rangle.
Constraint: \mathbf{n} \geq 0.
On entry, \mathbf{nrhs} = \langle value \rangle.
Constraint: \mathbf{nrhs} \geq 0.
On entry, \mathbf{pdb} = \langle value \rangle.
Constraint: \mathbf{pdb} > 0.
```

NE INT 2

```
On entry, \mathbf{pdb} = \langle value \rangle and \mathbf{n} = \langle value \rangle.
Constraint: \mathbf{pdb} \geq \max(1, \mathbf{n}).
On entry, \mathbf{pdb} = \langle value \rangle and \mathbf{nrhs} = \langle value \rangle.
Constraint: \mathbf{pdb} \geq \max(1, \mathbf{nrhs}).
```

NE INTERNAL ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG. See Section 3.6.6 in the Essential Introduction for further information.

NE NO LICENCE

Your licence key may have expired or may not have been installed correctly. See Section 3.6.5 in the Essential Introduction for further information.

NE_POS_DEF

The principal minor of order $\langle value \rangle$ of the matrix A is not positive definite. The factorization has not been completed and the solution could not be computed.

NE RCOND

A solution has been computed, but **rcond** is less than **machine precision** so that the matrix A is numerically singular.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A+E)\hat{x} = b,$$

where

$$||E||_1 = O(\epsilon)||A||_1$$

and ϵ is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \le \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$, the condition number of A with respect to the solution of the linear equations. nag_real_sym_posdef_packed_lin_solve (f04bec) uses the approximation $\|E\|_1 = \epsilon \|A\|_1$ to estimate **errbnd**. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Parallelism and Performance

nag_real_sym_posdef_packed_lin_solve (f04bec) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag_real_sym_posdef_packed_lin_solve (f04bec) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The Integer allocatable memory required is \mathbf{n} , and the double allocatable memory required is $3 \times \mathbf{n}$. Allocation failed before the solution could be computed.

The packed storage scheme is illustrated by the following example when n=4 and **uplo** = Nag_Upper. Two-dimensional storage of the symmetric matrix A:

$$\begin{array}{ccccc} a_{11} & a_{12} & a_{13} & a_{14} \\ & a_{22} & a_{23} & a_{24} \\ & & a_{33} & a_{34} \\ & & & a_{44} \end{array} \quad \left(a_{ij} = a_{ji}\right)$$

Packed storage of the upper triangle of A:

$$\mathbf{ap} = \begin{bmatrix} a_{11}, & a_{12}, & a_{22}, & a_{13}, & a_{23}, & a_{33}, & a_{14}, & a_{24}, & a_{34}, & a_{44} \end{bmatrix}$$

The total number of floating-point operations required to solve the equations AX = B is proportional to $\left(\frac{1}{3}n^3 + n^2r\right)$. The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

The complex analogue of nag_real_sym_posdef_packed_lin_solve (f04bec) is nag herm posdef packed lin solve (f04cec).

10 Example

This example solves the equations

$$AX = B$$
.

where A is the symmetric positive definite matrix

f04bec.4 Mark 25

$$A = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.18 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.18 & 0.34 & 1.18 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 8.70 & 8.30 \\ -13.35 & 2.13 \\ 1.89 & 1.61 \\ -4.14 & 5.00 \end{pmatrix}.$$

An estimate of the condition number of A and an approximate error bound for the computed solutions are also printed.

10.1 Program Text

```
/* nag_real_sym_posdef_packed_lin_solve (f04bec) Example Program.
* Copyright 2014 Numerical Algorithms Group.
* Mark 8, 2004.
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf04.h>
#include <nagx04.h>
int main(void)
  /* Scalars */
 double
               errbnd, rcond;
               exit_status, i, j, n, nrhs, pdb;
 Integer
  /* Arrays */
 char
               nag_enum_arg[40];
               *ap = 0, *b = 0;
 double
  /* Nag Types */
 NagError
               fail;
 Nag_OrderType order;
 Nag_UploType uplo;
#ifdef NAG COLUMN MAJOR
#define A_UPPER(I, J) ap[J*(J-1)/2 + I - 1]
#define A_LOWER(I, J) ap[(2*n-J)*(J-1)/2 + I - 1]
#define B(I, J)
                  b[(J-1)*pdb + I - 1]
 order = Nag_ColMajor;
#else
#define A_LOWER(I, J) ap[I*(I-1)/2 + J - 1]
#define A_UPPER(I, J) ap[(2*n-I)*(I-1)/2 + J - 1]
                     b[(I-1)*pdb + J - 1]
#define B(I, J)
 order = Nag_RowMajor;
#endif
 exit_status = 0;
 INIT_FAIL(fail);
 printf("nag_real_sym_posdef_packed_lin_solve (f04bec) Example "
          "Program Results\n\n");
  /* Skip heading in data file */
#ifdef _WIN32
 scanf_s("%*[^\n] ");
#else
 scanf("%*[^\n] ");
#endif
#ifdef _WIN32
 scanf_s("%"NAG_IFMT"%"NAG_IFMT"%*[^\n] ", &n, &nrhs);
 scanf("%"NAG_IFMT"%"NAG_IFMT"%*[^\n] ", &n, &nrhs);
#endif
```

```
if (n > 0 \&\& nrhs > 0)
      /* Allocate memory */
      if (!(ap = NAG\_ALLOC(n*(n+1)/2, double)) | |
          !(b = NAG_ALLOC(n*nrhs, double)))
          printf("Allocation failure\n");
          exit_status = -1;
          goto END;
#ifdef NAG_COLUMN_MAJOR
     pdb = n;
#else
      pdb = nrhs;
#endif
    }
 else
    {
      printf("%s\n", "n and/or nrhs too small");
      exit_status = 1;
      return exit_status;
#ifdef _WIN32
 scanf_s("%39s%*[^\n] ", nag_enum_arg, _countof(nag_enum_arg));
 scanf("%39s%*[^\n] ", nag_enum_arg);
#endif
  /* nag_enum_name_to_value (x04nac).
  * Converts NAG enum member name to value
   * /
 uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);
 /* Read the upper or lower triangular part of the matrix A from */
 /* data file */
 if (uplo == Nag_Upper)
      for (i = 1; i \leq n; ++i)
          for (j = i; j \le n; ++j)
#ifdef _WIN32
              scanf_s("%lf", &A_UPPER(i, j));
#else
              scanf("%lf", &A_UPPER(i, j));
#endif
#ifdef _WIN32
      scanf_s("%*[^\n] ");
      scanf("%*[^\n] ");
#endif
    }
 else
      for (i = 1; i \le n; ++i)
          for (j = 1; j \le i; ++j)
#ifdef _WIN32
              scanf_s("%lf", &A_LOWER(i, j));
#else
              scanf("%lf", &A_LOWER(i, j));
#endif
#ifdef _WIN32
      _scanf_s("%*[^\n] ");
```

f04bec.6 Mark 25

```
#else
     scanf("%*[^\n] ");
#endif
   }
  /* Read B from data file */
 for (i = 1; i \le n; ++i)
      for (j = 1; j \le nrhs; ++j)
#ifdef _WIN32
         scanf_s("%lf", &B(i, j));
#else
          scanf("%lf", &B(i, j));
#endif
        }
#ifdef _WIN32
 scanf_s("%*[^\n] ");
#else
 scanf("%*[^\n] ");
#endif
  /* Solve the equations AX = B for X */
  /* nag_real_sym_posdef_packed_lin_solve (f04bec).
   * Computes the solution and error-bound to a real symmetric
   {}^{\star} positive-definite system of linear equations, packed
  * storage
  */
 nag_real_sym_posdef_packed_lin_solve(order, uplo, n, nrhs, ap, b, pdb,
                                        &rcond, &errbnd, &fail);
  if (fail.code == NE NOERROR)
    {
      /* Print solution, estimate of condition number and approximate */
      /* error bound */
      /* nag_gen_real_mat_print (x04cac).
       * Print real general matrix (easy-to-use)
      */
      fflush(stdout);
     nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n,
                             nrhs, b, pdb, "Solution", 0, &fail);
      if (fail.code != NE_NOERROR)
        {
          printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
                  fail.message);
          exit_status = 1;
          goto END;
     printf("\n");
     printf("%s\n%6s%10.1e\n\n", "Estimate of condition number", "",
              1.0/rcond);
      printf("%s\n\%6s\%10.1e\n\n",
              "Estimate of error bound for computed solutions", "", errbnd);
 else if (fail.code == NE_RCOND)
      ^{\prime \star} Matrix A is numerically singular. Print estimate of ^{\star \prime}
      /* reciprocal of condition number and solution */
     printf("\n%s\n%6s%10.1e\n\n",
              "Estimate of reciprocal of condition number", "", rcond);
      /* nag_gen_real_mat_print (x04cac), see above. */
      fflush(stdout);
      nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n,
                             nrhs, b, pdb, "Solution", 0, &fail);
      if (fail.code != NE_NOERROR)
          printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
                  fail.message);
          exit_status = 1;
```

f04bec NAG Library Manual

10.2 Program Data

nag_real_sym_posdef_packed_lin_solve (f04bec) Example Program Data

```
:Values of n and nrhs
 Nag_Upper
                           :Value of uplo
 4.16 -3.12
              0.56 -0.10
        5.03 -0.83 1.18
               0.76
                    0.34
                      1.18 :End of matrix A
 8.70
        8.30
-13.35
        2.13
 1.89
        1.61
-4.14
        5.00
                          :End of matrix B
```

10.3 Program Results

nag_real_sym_posdef_packed_lin_solve (f04bec) Example Program Results

```
Solution

1 2
1 1.0000 4.0000
2 -1.0000 3.0000
3 2.0000 2.0000
4 -3.0000 1.0000
```

Estimate of condition number 9.7e+01

Estimate of error bound for computed solutions 1.1e-14

f04bec.8 (last) Mark 25