

NAG Library Function Document

nag_dgetrs (f07aec)

1 Purpose

nag_dgetrs (f07aec) solves a real system of linear equations with multiple right-hand sides,

$$AX = B \quad \text{or} \quad A^T X = B,$$

where A has been factorized by nag_dgetrf (f07adc).

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_dgetrs (Nag_OrderType order, Nag_TransType trans, Integer n,
                Integer nrhs, const double a[], Integer pda, const Integer ipiv[],
                double b[], Integer pdb, NagError *fail)
```

3 Description

nag_dgetrs (f07aec) is used to solve a real system of linear equations $AX = B$ or $A^T X = B$, the function must be preceded by a call to nag_dgetrf (f07adc) which computes the LU factorization of A as $A = PLU$. The solution is computed by forward and backward substitution.

If **trans** = Nag_NoTrans, the solution is computed by solving $PLY = B$ and then $UX = Y$.

If **trans** = Nag_Trans or Nag_ConjTrans, the solution is computed by solving $U^T Y = B$ and then $L^T P^T X = Y$.

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **trans** – Nag_TransType *Input*

On entry: indicates the form of the equations.

trans = Nag_NoTrans
 $AX = B$ is solved for X .

trans = Nag_Trans or Nag_ConjTrans
 $A^T X = B$ is solved for X .

Constraint: **trans** = Nag_NoTrans, Nag_Trans or Nag_ConjTrans.

- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.
- 4: **nrhs** – Integer *Input*
On entry: r , the number of right-hand sides.
Constraint: $\text{nrhs} \geq 0$.
- 5: **a**[dim] – const double *Input*
Note: the dimension, dim , of the array **a** must be at least $\max(1, \text{pda} \times n)$.
The (i, j) th element of the matrix A is stored in
 $\mathbf{a}[(j-1) \times \text{pda} + i - 1]$ when **order** = Nag_ColMajor;
 $\mathbf{a}[(i-1) \times \text{pda} + j - 1]$ when **order** = Nag_RowMajor.
On entry: the LU factorization of A , as returned by nag_dgetrf (f07adc).
- 6: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) in the array **a**.
Constraint: $\text{pda} \geq \max(1, n)$.
- 7: **ipiv**[dim] – const Integer *Input*
Note: the dimension, dim , of the array **ipiv** must be at least $\max(1, n)$.
On entry: the pivot indices, as returned by nag_dgetrf (f07adc).
- 8: **b**[dim] – double *Input/Output*
Note: the dimension, dim , of the array **b** must be at least
 $\max(1, \text{pdb} \times \text{nrhs})$ when **order** = Nag_ColMajor;
 $\max(1, n \times \text{pdb})$ when **order** = Nag_RowMajor.
The (i, j) th element of the matrix B is stored in
 $\mathbf{b}[(j-1) \times \text{pdb} + i - 1]$ when **order** = Nag_ColMajor;
 $\mathbf{b}[(i-1) \times \text{pdb} + j - 1]$ when **order** = Nag_RowMajor.
On entry: the n by r right-hand side matrix B .
On exit: the n by r solution matrix X .
- 9: **pdb** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) in the array **b**.
Constraints:
if **order** = Nag_ColMajor, $\text{pdb} \geq \max(1, n)$;
if **order** = Nag_RowMajor, $\text{pdb} \geq \max(1, \text{nrhs})$.
- 10: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.
See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{n} = \langle value \rangle$.
Constraint: $\mathbf{n} \geq 0$.

On entry, $\mathbf{nrhs} = \langle value \rangle$.
Constraint: $\mathbf{nrhs} \geq 0$.

On entry, $\mathbf{pda} = \langle value \rangle$.
Constraint: $\mathbf{pda} > 0$.

On entry, $\mathbf{pdb} = \langle value \rangle$.
Constraint: $\mathbf{pdb} > 0$.

NE_INT_2

On entry, $\mathbf{pda} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.
Constraint: $\mathbf{pda} \geq \max(1, \mathbf{n})$.

On entry, $\mathbf{pdb} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.
Constraint: $\mathbf{pdb} \geq \max(1, \mathbf{n})$.

On entry, $\mathbf{pdb} = \langle value \rangle$ and $\mathbf{nrhs} = \langle value \rangle$.
Constraint: $\mathbf{pdb} \geq \max(1, \mathbf{nrhs})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.
See Section 3.6.6 in the Essential Introduction for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.
See Section 3.6.5 in the Essential Introduction for further information.

7 Accuracy

For each right-hand side vector b , the computed solution x is the exact solution of a perturbed system of equations $(A + E)x = b$, where

$$|E| \leq c(n)\epsilon P|L|U,$$

$c(n)$ is a modest linear function of n , and ϵ is the *machine precision*.

If \hat{x} is the true solution, then the computed solution x satisfies a forward error bound of the form

$$\frac{\|x - \hat{x}\|_{\infty}}{\|x\|_{\infty}} \leq c(n) \text{cond}(A, x)\epsilon$$

where $\text{cond}(A, x) = \| |A^{-1}| |A| |x| \|_{\infty} / \|x\|_{\infty} \leq \text{cond}(A) = \| |A^{-1}| |A| \|_{\infty} \leq \kappa_{\infty}(A)$.

Note that $\text{cond}(A, x)$ can be much smaller than $\text{cond}(A)$, and $\text{cond}(A^T)$ can be much larger (or smaller) than $\text{cond}(A)$.

Forward and backward error bounds can be computed by calling `nag_dgerfs` (f07ahc), and an estimate for $\kappa_\infty(A)$ can be obtained by calling `nag_dgecon` (f07agc) with `norm = Nag_InfNorm`.

8 Parallelism and Performance

`nag_dgetrs` (f07aec) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_dgetrs` (f07aec) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is approximately $2n^2r$.

This function may be followed by a call to `nag_dgerfs` (f07ahc) to refine the solution and return an error estimate.

The complex analogue of this function is `nag_zgetrs` (f07asc).

10 Example

This example solves the system of equations $AX = B$, where

$$A = \begin{pmatrix} 1.80 & 2.88 & 2.05 & -0.89 \\ 5.25 & -2.95 & -0.95 & -3.80 \\ 1.58 & -2.69 & -2.90 & -1.04 \\ -1.11 & -0.66 & -0.59 & 0.80 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 9.52 & 18.47 \\ 24.35 & 2.25 \\ 0.77 & -13.28 \\ -6.22 & -6.21 \end{pmatrix}.$$

Here A is nonsymmetric and must first be factorized by `nag_dgetrf` (f07adc).

10.1 Program Text

```
/* nag_dgetrs (f07aec) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer    i, j, n, nrhs, pda, pdb;
    Integer    exit_status = 0;
    NagError   fail;
    Nag_OrderType order;

    /* Arrays */
    double     *a = 0, *b = 0;
    Integer    *ipiv = 0;
```

```

#ifdef NAG_LOAD_FP
  /* The following line is needed to force the Microsoft linker
     to load floating point support */
  float      force_loading_of_ms_float_support = 0;
#endif /* NAG_LOAD_FP */

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
#define B(I, J) b[(J-1)*pdb + I - 1]
  order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
#define B(I, J) b[(I-1)*pdb + J - 1]
  order = Nag_RowMajor;
#endif

  INIT_FAIL(fail);

  printf("nag_dgetrs (f07aec) Example Program Results\n\n");

  /* Skip heading in data file */
#ifdef _WIN32
  scanf_s("%*[\n] ");
#else
  scanf("%*[\n] ");
#endif

#ifdef _WIN32
  scanf_s("%NAG_IFMT%"NAG_IFMT"%*[\n] ", &n, &nrhs);
#else
  scanf("%NAG_IFMT%"NAG_IFMT"%*[\n] ", &n, &nrhs);
#endif

  /* Allocate memory */
  if (!(a = NAG_ALLOC(n * n, double)) ||
      !(b = NAG_ALLOC(n * nrhs, double)) ||
      !(ipiv = NAG_ALLOC(n, Integer)))
  {
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
  }
#ifdef NAG_COLUMN_MAJOR
  pda = n;
  pdb = n;
#else
  pda = n;
  pdb = nrhs;
#endif

  /* Read A and B from data file */
  for (i = 1; i <= n; ++i)
  {
    for (j = 1; j <= n; ++j)
#ifdef _WIN32
      scanf_s("%lf", &A(i, j));
#else
      scanf("%lf", &A(i, j));
#endif
  }
#ifdef _WIN32
  scanf_s("%*[\n] ");
#else
  scanf("%*[\n] ");
#endif
  for (i = 1; i <= n; ++i)
  {
    for (j = 1; j <= nrhs; ++j)
#ifdef _WIN32
      scanf_s("%lf", &B(i, j));

```

```

#else
    scanf("%lf", &B(i, j));
#endif
}
#ifdef _WIN32
    scanf_s("%*[^\\n] ");
#else
    scanf("%*[^\\n] ");
#endif

/* Factorize A */
/* nag_dgetrf (f07adc).
 * LU factorization of real m by n matrix
 */
nag_dgetrf(order, n, n, a, pda, ipiv, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dgetrf (f07adc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Compute solution */
/* nag_dgetrs (f07aec).
 * Solution of real system of linear equations, multiple
 * right-hand sides, matrix already factorized by nag_dgetrf
 * (f07adc)
 */
nag_dgetrs(order, Nag_NoTrans, n, nrhs, a, pda, ipiv, b, pdb, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dgetrs (f07aec).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print solution */
/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
fflush(stdout);
nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n, nrhs,
    b, pdb, "Solution(s)", 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
        fail.message);
    exit_status = 1;
    goto END;
}
END:
    NAG_FREE(a);
    NAG_FREE(b);
    NAG_FREE(ipiv);
    return exit_status;
}

```

10.2 Program Data

```

nag_dgetrs (f07aec) Example Program Data
  4  2          :Values of N and NRHS
  1.80  2.88  2.05 -0.89
  5.25 -2.95 -0.95 -3.80
  1.58 -2.69 -2.90 -1.04
 -1.11 -0.66 -0.59  0.80  :End of matrix A
  9.52 18.47
 24.35  2.25
  0.77 -13.28
 -6.22 -6.21          :End of matrix B

```

10.3 Program Results

nag_dgetrs (f07aec) Example Program Results

Solution(s)

	1	2
1	1.0000	3.0000
2	-1.0000	2.0000
3	3.0000	4.0000
4	-5.0000	1.0000
