

# NAG Library Function Document

## nag\_zgerfs (f07avc)

### 1 Purpose

nag\_zgerfs (f07avc) returns error bounds for the solution of a complex system of linear equations with multiple right-hand sides,  $AX = B$ ,  $A^T X = B$  or  $A^H X = B$ . It improves the solution by iterative refinement, in order to reduce the backward error as much as possible.

### 2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_zgerfs (Nag_OrderType order, Nag_TransType trans, Integer n,
                Integer nrhs, const Complex a[], Integer pda, const Complex af[],
                Integer pdaf, const Integer ipiv[], const Complex b[], Integer pdb,
                Complex x[], Integer pdx, double ferr[], double berr[], NagError *fail)
```

### 3 Description

nag\_zgerfs (f07avc) returns the backward errors and estimated bounds on the forward errors for the solution of a complex system of linear equations with multiple right-hand sides  $AX = B$ ,  $A^T X = B$  or  $A^H X = B$ . The function handles each right-hand side vector (stored as a column of the matrix  $B$ ) independently, so we describe the function of nag\_zgerfs (f07avc) in terms of a single right-hand side  $b$  and solution  $x$ .

Given a computed solution  $x$ , the function computes the *component-wise backward error*  $\beta$ . This is the size of the smallest relative perturbation in each element of  $A$  and  $b$  such that  $x$  is the exact solution of a perturbed system

$$(A + \delta A)x = b + \delta b$$

$$|\delta a_{ij}| \leq \beta |a_{ij}| \quad \text{and} \quad |\delta b_i| \leq \beta |b_i|.$$

Then the function estimates a bound for the *component-wise forward error* in the computed solution, defined by:

$$\max_i |x_i - \hat{x}_i| / \max_i |x_i|$$

where  $\hat{x}$  is the true solution.

For details of the method, see the f07 Chapter Introduction.

### 4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

### 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

- 2: **trans** – Nag\_TransType *Input*  
*On entry:* indicates the form of the linear equations for which  $X$  is the computed solution as follows:  
**trans** = Nag\_NoTrans  
 The linear equations are of the form  $AX = B$ .  
**trans** = Nag\_Trans  
 The linear equations are of the form  $A^T X = B$ .  
**trans** = Nag\_ConjTrans  
 The linear equations are of the form  $A^H X = B$ .  
*Constraint:* **trans** = Nag\_NoTrans, Nag\_Trans or Nag\_ConjTrans.
- 3: **n** – Integer *Input*  
*On entry:*  $n$ , the order of the matrix  $A$ .  
*Constraint:*  $n \geq 0$ .
- 4: **nrhs** – Integer *Input*  
*On entry:*  $r$ , the number of right-hand sides.  
*Constraint:* **nrhs**  $\geq 0$ .
- 5: **a**[*dim*] – const Complex *Input*  
**Note:** the dimension, *dim*, of the array **a** must be at least  $\max(1, \mathbf{pda} \times \mathbf{n})$ .  
 The  $(i, j)$ th element of the matrix  $A$  is stored in  
 $\mathbf{a}[(j-1) \times \mathbf{pda} + i - 1]$  when **order** = Nag\_ColMajor;  
 $\mathbf{a}[(i-1) \times \mathbf{pda} + j - 1]$  when **order** = Nag\_RowMajor.  
*On entry:* the  $n$  by  $n$  original matrix  $A$  as supplied to nag\_zgetrf (f07arc).
- 6: **pda** – Integer *Input*  
*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **a**.  
*Constraint:* **pda**  $\geq \max(1, \mathbf{n})$ .
- 7: **af**[*dim*] – const Complex *Input*  
**Note:** the dimension, *dim*, of the array **af** must be at least  $\max(1, \mathbf{pdaf} \times \mathbf{n})$ .  
 The  $(i, j)$ th element of the matrix is stored in  
 $\mathbf{af}[(j-1) \times \mathbf{pdaf} + i - 1]$  when **order** = Nag\_ColMajor;  
 $\mathbf{af}[(i-1) \times \mathbf{pdaf} + j - 1]$  when **order** = Nag\_RowMajor.  
*On entry:* the  $LU$  factorization of  $A$ , as returned by nag\_zgetrf (f07arc).
- 8: **pdaf** – Integer *Input*  
*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **af**.  
*Constraint:* **pdaf**  $\geq \max(1, \mathbf{n})$ .
- 9: **ipiv**[*dim*] – const Integer *Input*  
**Note:** the dimension, *dim*, of the array **ipiv** must be at least  $\max(1, \mathbf{n})$ .  
*On entry:* the pivot indices, as returned by nag\_zgetrf (f07arc).

- 10: **b**[*dim*] – const Complex *Input*
- Note:** the dimension, *dim*, of the array **b** must be at least  
 $\max(1, \mathbf{pdb} \times \mathbf{nrhs})$  when **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{n} \times \mathbf{pdb})$  when **order** = Nag\_RowMajor.
- The (*i*, *j*)th element of the matrix *B* is stored in  
 $\mathbf{b}[(j-1) \times \mathbf{pdb} + i - 1]$  when **order** = Nag\_ColMajor;  
 $\mathbf{b}[(i-1) \times \mathbf{pdb} + j - 1]$  when **order** = Nag\_RowMajor.
- On entry:* the *n* by *r* right-hand side matrix *B*.
- 11: **pdb** – Integer *Input*
- On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **b**.
- Constraints:*  
 if **order** = Nag\_ColMajor, **pdb**  $\geq \max(1, \mathbf{n})$ ;  
 if **order** = Nag\_RowMajor, **pdb**  $\geq \max(1, \mathbf{nrhs})$ .
- 12: **x**[*dim*] – Complex *Input/Output*
- Note:** the dimension, *dim*, of the array **x** must be at least  
 $\max(1, \mathbf{pdx} \times \mathbf{nrhs})$  when **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{n} \times \mathbf{pdx})$  when **order** = Nag\_RowMajor.
- The (*i*, *j*)th element of the matrix *X* is stored in  
 $\mathbf{x}[(j-1) \times \mathbf{pdx} + i - 1]$  when **order** = Nag\_ColMajor;  
 $\mathbf{x}[(i-1) \times \mathbf{pdx} + j - 1]$  when **order** = Nag\_RowMajor.
- On entry:* the *n* by *r* solution matrix *X*, as returned by nag\_zgetrs (f07asc).  
*On exit:* the improved solution matrix *X*.
- 13: **pdx** – Integer *Input*
- On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **x**.
- Constraints:*  
 if **order** = Nag\_ColMajor, **pdx**  $\geq \max(1, \mathbf{n})$ ;  
 if **order** = Nag\_RowMajor, **pdx**  $\geq \max(1, \mathbf{nrhs})$ .
- 14: **ferr**[**nrhs**] – double *Output*
- On exit:* **ferr**[*j* - 1] contains an estimated error bound for the *j*th solution vector, that is, the *j*th column of *X*, for *j* = 1, 2, ..., *r*.
- 15: **berr**[**nrhs**] – double *Output*
- On exit:* **berr**[*j* - 1] contains the component-wise backward error bound  $\beta$  for the *j*th solution vector, that is, the *j*th column of *X*, for *j* = 1, 2, ..., *r*.
- 16: **fail** – NagError \* *Input/Output*
- The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in the Essential Introduction for further information.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_INT

On entry,  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{n} \geq 0$ .

On entry,  $\mathbf{nrhs} = \langle value \rangle$ .

Constraint:  $\mathbf{nrhs} \geq 0$ .

On entry,  $\mathbf{pda} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} > 0$ .

On entry,  $\mathbf{pdaf} = \langle value \rangle$ .

Constraint:  $\mathbf{pdaf} > 0$ .

On entry,  $\mathbf{pdb} = \langle value \rangle$ .

Constraint:  $\mathbf{pdb} > 0$ .

On entry,  $\mathbf{pdx} = \langle value \rangle$ .

Constraint:  $\mathbf{pdx} > 0$ .

### NE\_INT\_2

On entry,  $\mathbf{pda} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{n})$ .

On entry,  $\mathbf{pdaf} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{pdaf} \geq \max(1, \mathbf{n})$ .

On entry,  $\mathbf{pdb} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{pdb} \geq \max(1, \mathbf{n})$ .

On entry,  $\mathbf{pdb} = \langle value \rangle$  and  $\mathbf{nrhs} = \langle value \rangle$ .

Constraint:  $\mathbf{pdb} \geq \max(1, \mathbf{nrhs})$ .

On entry,  $\mathbf{pdx} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{pdx} \geq \max(1, \mathbf{n})$ .

On entry,  $\mathbf{pdx} = \langle value \rangle$  and  $\mathbf{nrhs} = \langle value \rangle$ .

Constraint:  $\mathbf{pdx} \geq \max(1, \mathbf{nrhs})$ .

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in the Essential Introduction for further information.

### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in the Essential Introduction for further information.

## 7 Accuracy

The bounds returned in **ferr** are not rigorous, because they are estimated, not computed exactly; but in practice they almost always overestimate the actual error.

## 8 Parallelism and Performance

nag\_zgerfs (f07avc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag\_zgerfs (f07avc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

For each right-hand side, computation of the backward error involves a minimum of  $16n^2$  real floating-point operations. Each step of iterative refinement involves an additional  $24n^2$  real operations. At most five steps of iterative refinement are performed, but usually only one or two steps are required.

Estimating the forward error involves solving a number of systems of linear equations of the form  $Ax = b$  or  $A^Hx = b$ ; the number is usually 5 and never more than 11. Each solution involves approximately  $8n^2$  real operations.

The real analogue of this function is nag\_dgerfs (f07ahc).

## 10 Example

This example solves the system of equations  $AX = B$  using iterative refinement and to compute the forward and backward error bounds, where

$$A = \begin{pmatrix} -1.34 + 2.55i & 0.28 + 3.17i & -6.39 - 2.20i & 0.72 - 0.92i \\ -0.17 - 1.41i & 3.31 - 0.15i & -0.15 + 1.34i & 1.29 + 1.38i \\ -3.29 - 2.39i & -1.91 + 4.42i & -0.14 - 1.35i & 1.72 + 1.35i \\ 2.41 + 0.39i & -0.56 + 1.47i & -0.83 - 0.69i & -1.96 + 0.67i \end{pmatrix}$$

and

$$B = \begin{pmatrix} 26.26 + 51.78i & 31.32 - 6.70i \\ 6.43 - 8.68i & 15.86 - 1.42i \\ -5.75 + 25.31i & -2.15 + 30.19i \\ 1.16 + 2.57i & -2.56 + 7.55i \end{pmatrix}.$$

Here  $A$  is nonsymmetric and must first be factorized by nag\_zgetrf (f07arc).

### 10.1 Program Text

```
/* nag_zgerfs (f07avc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagx04.h>
```

```

int main(void)
{
    /* Scalars */
    Integer      berr_len, i, ferr_len, ipiv_len, j, n, nrhs;
    Integer      pda, pdaf, pdb, pdx;
    Integer      exit_status = 0;
    NagError     fail;
    Nag_OrderType order;
    /* Arrays */
    Complex      *a = 0, *af = 0, *b = 0, *x = 0;
    double       *berr = 0, *ferr = 0;
    Integer      *ipiv = 0;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J)  a[(J-1)*pda + I - 1]
#define AF(I, J) af[(J-1)*pdaf + I - 1]
#define B(I, J)  b[(J-1)*pdb + I - 1]
#define X(I, J)  x[(J-1)*pdx + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J)  a[(I-1)*pda + J - 1]
#define AF(I, J) af[(I-1)*pdaf + J - 1]
#define B(I, J)  b[(I-1)*pdb + J - 1]
#define X(I, J)  x[(I-1)*pdx + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_zgerfs (f07avc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
#ifdef _WIN32
    scanf_s("%"NAG_IFMT%"NAG_IFMT"%*[\n] ", &n, &nrhs);
#else
    scanf("%"NAG_IFMT%"NAG_IFMT"%*[\n] ", &n, &nrhs);
#endif
#ifdef NAG_COLUMN_MAJOR
    pda = n;
    pdaf = n;
    pdb = n;
    pdx = n;
#else
    pda = n;
    pdaf = n;
    pdb = nrhs;
    pdx = nrhs;
#endif
    ipiv_len = n;
    ferr_len = n;
    berr_len = nrhs;

    /* Allocate memory */
    if (!(a = NAG_ALLOC(n * n, Complex)) ||
        !(af = NAG_ALLOC(n * n, Complex)) ||
        !(b = NAG_ALLOC(n * nrhs, Complex)) ||
        !(x = NAG_ALLOC(n * n, Complex)) ||
        !(berr = NAG_ALLOC(berr_len, double)) ||
        !(ferr = NAG_ALLOC(ferr_len, double)) ||
        !(ipiv = NAG_ALLOC(ipiv_len, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
}

```

```

/* Read A and B from data file, and copy A to AF and B to X */
for (i = 1; i <= n; ++i)
  {
    for (j = 1; j <= n; ++j)
#ifdef _WIN32
      scanf_s(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#else
      scanf(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#endif
    }
#ifdef _WIN32
  scanf_s("%*[\n] ");
#else
  scanf("%*[\n] ");
#endif
  for (i = 1; i <= n; ++i)
    {
      for (j = 1; j <= nrhs; ++j)
#ifdef _WIN32
        scanf_s(" ( %lf , %lf )", &B(i, j).re, &B(i, j).im);
#else
        scanf(" ( %lf , %lf )", &B(i, j).re, &B(i, j).im);
#endif
      }
#ifdef _WIN32
  scanf_s("%*[\n] ");
#else
  scanf("%*[\n] ");
#endif

  for (i = 1; i <= n; ++i)
    {
      for (j = 1; j <= n; ++j)
        {
          AF(i, j).re = A(i, j).re;
          AF(i, j).im = A(i, j).im;
        }
    }
  for (i = 1; i <= n; ++i)
    {
      for (j = 1; j <= nrhs; ++j)
        {
          X(i, j).re = B(i, j).re;
          X(i, j).im = B(i, j).im;
        }
    }
/* Factorize A in the array AF */
/* nag_zgetrf (f07arc).
 * LU factorization of complex m by n matrix
 */
nag_zgetrf(order, n, n, af, pdaf, ipiv, &fail);
if (fail.code != NE_NOERROR)
  {
    printf("Error from nag_zgetrf (f07arc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
  }
/* Compute solution in the array X */
/* nag_zgetrs (f07asc).
 * Solution of complex system of linear equations, multiple
 * right-hand sides, matrix already factorized by nag_zgetrf
 * (f07arc)
 */
nag_zgetrs(order, Nag_NoTrans, n, nrhs, af, pdaf, ipiv, x, pdx, &fail);
if (fail.code != NE_NOERROR)
  {
    printf("Error from nag_zgetrs (f07asc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
  }
/* Improve solution, and compute backward errors and */

```

```

/* estimated bounds on the forward errors */
/* nag_zgerfs (f07avc).
 * Refined solution with error bounds of complex system of
 * linear equations, multiple right-hand sides
 */
nag_zgerfs(order, Nag_NoTrans, n, nrhs, a, pda, af, pdaf, ipiv, b, pdb, x,
           pdx, ferr, berr, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_zgerfs (f07avc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print solution */
/* nag_gen_complx_mat_print_comp (x04dbc).
 * Print complex general matrix (comprehensive)
 */
fflush(stdout);
nag_gen_complx_mat_print_comp(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n,
                              nrhs, x, pdx, Nag_BracketForm, "%7.4f",
                              "Solution(s)", Nag_IntegerLabels,
                              0, Nag_IntegerLabels, 0, 80, 0, 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_complx_mat_print_comp (x04dbc).\n%s\n",
          fail.message);
    exit_status = 1;
    goto END;
}

printf("\nBackward errors (machine-dependent)\n");

for (j = 1; j <= nrhs; ++j)
    printf("%11.1e%s", berr[j-1], j%4 == 0?"\n":"" );
printf("\nEstimated forward error bounds (machine-dependent)\n");
for (j = 1; j <= nrhs; ++j)
    printf("%11.1e%s", ferr[j-1], j%4 == 0 || j == nrhs?"\n":"" );
END:
NAG_FREE(a);
NAG_FREE(af);
NAG_FREE(b);
NAG_FREE(x);
NAG_FREE(berr);
NAG_FREE(ferr);
NAG_FREE(ipiv);
return exit_status;
}

```

## 10.2 Program Data

```

nag_zgerfs (f07avc) Example Program Data
  4 2                                     :Values of N and NRHS
(-1.34, 2.55) ( 0.28, 3.17) (-6.39,-2.20) ( 0.72,-0.92)
(-0.17,-1.41) ( 3.31,-0.15) (-0.15, 1.34) ( 1.29, 1.38)
(-3.29,-2.39) (-1.91, 4.42) (-0.14,-1.35) ( 1.72, 1.35)
( 2.41, 0.39) (-0.56, 1.47) (-0.83,-0.69) (-1.96, 0.67) :End of matrix A
(26.26, 51.78) (31.32, -6.70)
( 6.43, -8.68) (15.86, -1.42)
(-5.75, 25.31) (-2.15, 30.19)
( 1.16, 2.57) (-2.56, 7.55)                                     :End of matrix B

```

## 10.3 Program Results

nag\_zgerfs (f07avc) Example Program Results

```

Solution(s)
           1           2
1 ( 1.0000, 1.0000) (-1.0000,-2.0000)
2 ( 2.0000,-3.0000) ( 5.0000, 1.0000)

```



3 (-4.0000,-5.0000) (-3.0000, 4.0000)  
4 ( 0.0000, 6.0000) ( 2.0000,-3.0000)

Backward errors (machine-dependent)

4.1e-17 8.7e-17

Estimated forward error bounds (machine-dependent)

5.8e-14 7.8e-14

---