

NAG Library Function Document

nag_zgbcon (f07buc)

1 Purpose

nag_zgbcon (f07buc) estimates the condition number of a complex band matrix A , where A has been factorized by nag_zgbtrf (f07brc).

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_zgbcon (Nag_OrderType order, Nag_NormType norm, Integer n,
                Integer kl, Integer ku, const Complex ab[], Integer pdab,
                const Integer ipiv[], double anorm, double *rcond, NagError *fail)
```

3 Description

nag_zgbcon (f07buc) estimates the condition number of a complex band matrix A , in either the 1-norm or the ∞ -norm:

$$\kappa_1(A) = \|A\|_1 \|A^{-1}\|_1 \quad \text{or} \quad \kappa_\infty(A) = \|A\|_\infty \|A^{-1}\|_\infty.$$

Note that $\kappa_\infty(A) = \kappa_1(A^H)$.

Because the condition number is infinite if A is singular, the function actually returns an estimate of the **reciprocal** of the condition number.

The function should be preceded by a call to nag_zgb_norm (f16ubc) to compute $\|A\|_1$ or $\|A\|_\infty$, and a call to nag_zgbtrf (f07brc) to compute the LU factorization of A . The function then uses Higham's implementation of Hager's method (see Higham (1988)) to estimate $\|A^{-1}\|_1$ or $\|A^{-1}\|_\infty$.

4 References

Higham N J (1988) FORTRAN codes for estimating the one-norm of a real or complex matrix, with applications to condition estimation *ACM Trans. Math. Software* **14** 381–396

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **norm** – Nag_NormType *Input*
On entry: indicates whether $\kappa_1(A)$ or $\kappa_\infty(A)$ is estimated.
norm = Nag_OneNorm
 $\kappa_1(A)$ is estimated.

- norm** = Nag_InfNorm
 $\kappa_{\infty}(A)$ is estimated.
 Constraint: **norm** = Nag_OneNorm or Nag_InfNorm.
- 3: **n** – Integer *Input*
 On entry: n , the order of the matrix A .
 Constraint: **n** \geq 0.
- 4: **kl** – Integer *Input*
 On entry: k_l , the number of subdiagonals within the band of the matrix A .
 Constraint: **kl** \geq 0.
- 5: **ku** – Integer *Input*
 On entry: k_u , the number of superdiagonals within the band of the matrix A .
 Constraint: **ku** \geq 0.
- 6: **ab**[*dim*] – const Complex *Input*
Note: the dimension, *dim*, of the array **ab** must be at least $\max(1, \mathbf{pdab} \times \mathbf{n})$.
 On entry: the LU factorization of A , as returned by nag_zgbtrf (f07brc).
- 7: **pdab** – Integer *Input*
 On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix in the array **ab**.
 Constraint: **pdab** \geq $2 \times \mathbf{kl} + \mathbf{ku} + 1$.
- 8: **ipiv**[*dim*] – const Integer *Input*
Note: the dimension, *dim*, of the array **ipiv** must be at least $\max(1, \mathbf{n})$.
 On entry: the pivot indices, as returned by nag_zgbtrf (f07brc).
- 9: **anorm** – double *Input*
 On entry: if **norm** = Nag_OneNorm, the 1-norm of the **original** matrix A .
 If **norm** = Nag_InfNorm, the ∞ -norm of the **original** matrix A .
anorm may be computed by calling nag_zgb_norm (f16ubc) with the same value for the argument **norm**.
anorm must be computed either **before** calling nag_zgbtrf (f07brc) or else from a **copy** of the original matrix A (see Section 10).
 Constraint: **anorm** \geq 0.0.
- 10: **rcond** – double * *Output*
 On exit: an estimate of the reciprocal of the condition number of A . **rcond** is set to zero if exact singularity is detected or the estimate underflows. If **rcond** is less than *machine precision*, A is singular to working precision.
- 11: **fail** – NagError * *Input/Output*
 The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.
See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{kl} = \langle value \rangle$.
Constraint: $\mathbf{kl} \geq 0$.

On entry, $\mathbf{ku} = \langle value \rangle$.
Constraint: $\mathbf{ku} \geq 0$.

On entry, $\mathbf{n} = \langle value \rangle$.
Constraint: $\mathbf{n} \geq 0$.

On entry, $\mathbf{pdab} = \langle value \rangle$.
Constraint: $\mathbf{pdab} > 0$.

NE_INT_3

On entry, $\mathbf{pdab} = \langle value \rangle$, $\mathbf{kl} = \langle value \rangle$ and $\mathbf{ku} = \langle value \rangle$.
Constraint: $\mathbf{pdab} \geq 2 \times \mathbf{kl} + \mathbf{ku} + 1$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.
See Section 3.6.6 in the Essential Introduction for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.
See Section 3.6.5 in the Essential Introduction for further information.

NE_REAL

On entry, $\mathbf{anorm} = \langle value \rangle$.
Constraint: $\mathbf{anorm} \geq 0.0$.

7 Accuracy

The computed estimate \mathbf{rcond} is never less than the true value ρ , and in practice is nearly always less than 10ρ , although examples can be constructed where \mathbf{rcond} is much larger.

8 Parallelism and Performance

nag_zgbcon (f07buc) is not threaded by NAG in any implementation.

nag_zgbcon (f07buc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

A call to nag_zgbcon (f07buc) involves solving a number of systems of linear equations of the form $Ax = b$ or $A^Hx = b$; the number is usually 5 and never more than 11. Each solution involves approximately $8n(2k_l + k_u)$ real floating-point operations (assuming $n \gg k_l$ and $n \gg k_u$) but takes considerably longer than a call to nag_zgbtrs (f07bsc) with one right-hand side, because extra care is taken to avoid overflow when A is approximately singular.

The real analogue of this function is nag_dgbcon (f07bgc).

10 Example

This example estimates the condition number in the 1-norm of the matrix A , where

$$A = \begin{pmatrix} -1.65 + 2.26i & -2.05 - 0.85i & 0.97 - 2.84i & 0.00 + 0.00i \\ 0.00 + 6.30i & -1.48 - 1.75i & -3.99 + 4.01i & 0.59 - 0.48i \\ 0.00 + 0.00i & -0.77 + 2.83i & -1.06 + 1.94i & 3.33 - 1.04i \\ 0.00 + 0.00i & 0.00 + 0.00i & 4.48 - 1.09i & -0.46 - 1.72i \end{pmatrix}.$$

10.1 Program Text

```

/* nag_zgbcon (f07buc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <naga02.h>
#include <nagf07.h>
#include <nagx02.h>

int main(void)
{
    /* Scalars */
    Integer      i, ipiv_len, j, kl, ku, n, pdab;
    Integer      exit_status = 0;
    double       anorm, rcond, sum;
    NagError     fail;
    Nag_OrderType order;

    /* Arrays */
    Complex      *ab = 0;
    Integer      *ipiv = 0;

#ifdef NAG_COLUMN_MAJOR
#define AB(I, J) ab[(J-1)*pdab + kl + ku + I - J]
    order = Nag_ColMajor;
#else
#define AB(I, J) ab[(I-1)*pdab + kl + J - I]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_zgbcon (f07buc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
#ifdef _WIN32
    scanf_s("%"NAG_IFMT%"%"NAG_IFMT%"%"NAG_IFMT%"%*[\n] ", &n, &kl, &ku);

```

```

#else
    scanf("%"NAG_IFMT%"NAG_IFMT%"NAG_IFMT"%*[\n] ", &n, &kl, &ku);
#endif
    ipiv_len = n;
    pdab = 2*kl + ku + 1;

    /* Allocate memory */
    if (!(ab = NAG_ALLOC((2*kl+ku+1) * n, Complex)) ||
        !(ipiv = NAG_ALLOC(ipiv_len, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read A from data file */
    for (i = 1; i <= n; ++i)
    {
        for (j = MAX(i-kl, 1); j <= MIN(i+ku, n); ++j)
#ifdef _WIN32
            scanf_s(" ( %lf , %lf )", &AB(i, j).re, &AB(i, j).im);
#else
            scanf(" ( %lf , %lf )", &AB(i, j).re, &AB(i, j).im);
#endif
    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
    /* Compute norm of A */
    anorm = 0.0;
    for (j = 1; j <= n; ++j)
    {
        sum = 0.0;
        for (i = MAX(j-ku, 1); i <= MIN(j+kl, n); ++i)
            /* nag_complex_abs (a02dbc).
             * Modulus of a complex number
             */
            sum = sum + nag_complex_abs(AB(i, j));
        anorm = MAX(anorm, sum);
    }
    /* Factorize A */
    /* nag_zgbtrf (f07brc).
     * LU factorization of complex m by n band matrix
     */
    nag_zgbtrf(order, n, n, kl, ku, ab, pdab, ipiv, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_zgbtrf (f07brc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Estimate condition number */
    /* nag_zgbcon (f07buc).
     * Estimate condition number of complex band matrix, matrix
     * already factorized by nag_zgbtrf (f07brc)
     */
    nag_zgbcon(order, Nag_OneNorm, n, kl, ku, ab, pdab, ipiv,
               anorm, &rcond, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_zgbcon (f07buc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Print condition number */
    /* nag_machine_precision (x02ajc).
     * The machine precision
     */
    if (rcond > nag_machine_precision)

```

```

    printf("Estimate of condition number = %11.2e\n", 1.0/rcond);
else
    printf("A is singular to working precision\n");
END:
NAG_FREE(ab);
NAG_FREE(ipiv);
return exit_status;
}

```

10.2 Program Data

```

nag_zgbcon (f07buc) Example Program Data
  4 1 2                                     :Values of N, KL and KU
(-1.65, 2.26) (-2.05,-0.85) ( 0.97,-2.84)
( 0.00, 6.30) (-1.48,-1.75) (-3.99, 4.01) ( 0.59,-0.48)
              (-0.77, 2.83) (-1.06, 1.94) ( 3.33,-1.04)
              ( 4.48,-1.09) (-0.46,-1.72) :End of matrix A

```

10.3 Program Results

```

nag_zgbcon (f07buc) Example Program Results

```

```

Estimate of condition number =    1.04e+02

```
