

NAG Library Function Document

nag_zhetrf (f07mrc)

1 Purpose

nag_zhetrf (f07mrc) computes the Bunch–Kaufman factorization of a complex Hermitian indefinite matrix.

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_zhetrf (Nag_OrderType order, Nag_UploType uplo, Integer n,
                Complex a[], Integer pda, Integer ipiv[], NagError *fail)
```

3 Description

nag_zhetrf (f07mrc) factorizes a complex Hermitian matrix A , using the Bunch–Kaufman diagonal pivoting method. A is factorized either as $A = PUDU^H P^T$ if **uplo** = Nag_Upper or $A = PLDL^H P^T$ if **uplo** = Nag_Lower, where P is a permutation matrix, U (or L) is a unit upper (or lower) triangular matrix and D is an Hermitian block diagonal matrix with 1 by 1 and 2 by 2 diagonal blocks; U (or L) has 2 by 2 unit diagonal blocks corresponding to the 2 by 2 blocks of D . Row and column interchanges are performed to ensure numerical stability while keeping the matrix Hermitian.

This method is suitable for Hermitian matrices which are not known to be positive definite. If A is in fact positive definite, no interchanges are performed and no 2 by 2 blocks occur in D .

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **uplo** – Nag_UploType *Input*

On entry: specifies whether the upper or lower triangular part of A is stored and how A is to be factorized.

uplo = Nag_Upper

The upper triangular part of A is stored and A is factorized as $PUDU^H P^T$, where U is upper triangular.

uplo = Nag_Lower

The lower triangular part of A is stored and A is factorized as $PLDL^H P^T$, where L is lower triangular.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.
- 4: **a**[*dim*] – Complex *Input/Output*
Note: the dimension, *dim*, of the array **a** must be at least $\max(1, \mathbf{pda} \times \mathbf{n})$.
On entry: the n by n Hermitian indefinite matrix A .
If **order** = Nag_ColMajor, A_{ij} is stored in **a**[($j - 1$) \times **pda** + $i - 1$].
If **order** = Nag_RowMajor, A_{ij} is stored in **a**[($i - 1$) \times **pda** + $j - 1$].
If **uplo** = Nag_Upper, the upper triangular part of A must be stored and the elements of the array below the diagonal are not referenced.
If **uplo** = Nag_Lower, the lower triangular part of A must be stored and the elements of the array above the diagonal are not referenced.
On exit: the upper or lower triangle of A is overwritten by details of the block diagonal matrix D and the multipliers used to obtain the factor U or L as specified by **uplo**.
- 5: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix A in the array **a**.
Constraint: $\mathbf{pda} \geq \max(1, \mathbf{n})$.
- 6: **ipiv**[*dim*] – Integer *Output*
Note: the dimension, *dim*, of the array **ipiv** must be at least $\max(1, \mathbf{n})$.
On exit: details of the interchanges and the block structure of D . More precisely,
if **ipiv**[$i - 1$] = $k > 0$, d_{ii} is a 1 by 1 pivot block and the i th row and column of A were interchanged with the k th row and column;
if **uplo** = Nag_Upper and **ipiv**[$i - 2$] = **ipiv**[$i - 1$] = $-l < 0$, $\begin{pmatrix} d_{i-1,i-1} & \bar{d}_{i,i-1} \\ \bar{d}_{i,i-1} & d_{ii} \end{pmatrix}$ is a 2 by 2 pivot block and the ($i - 1$)th row and column of A were interchanged with the l th row and column;
if **uplo** = Nag_Lower and **ipiv**[$i - 1$] = **ipiv**[i] = $-m < 0$, $\begin{pmatrix} d_{ii} & d_{i+1,i} \\ d_{i+1,i} & d_{i+1,i+1} \end{pmatrix}$ is a 2 by 2 pivot block and the ($i + 1$)th row and column of A were interchanged with the m th row and column.
- 7: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 0 .

On entry, **pda** = $\langle value \rangle$.

Constraint: **pda** > 0 .

NE_INT_2

On entry, **pda** = $\langle value \rangle$ and **n** = $\langle value \rangle$.

Constraint: **pda** $\geq \max(1, \mathbf{n})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in the Essential Introduction for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in the Essential Introduction for further information.

NE_SINGULAR

Element $\langle value \rangle$ of the diagonal is exactly zero. The factorization has been completed, but the block diagonal matrix D is exactly singular, and division by zero will occur if it is used to solve a system of equations.

7 Accuracy

If **uplo** = Nag_Upper, the computed factors U and D are the exact factors of a perturbed matrix $A + E$, where

$$|E| \leq c(n)\epsilon P|U||D||U^H|P^T,$$

$c(n)$ is a modest linear function of n , and ϵ is the *machine precision*.

If **uplo** = Nag_Lower, a similar statement holds for the computed factors L and D .

8 Parallelism and Performance

nag_zhtrf (f07mrc) is not threaded by NAG in any implementation.

nag_zhtrf (f07mrc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The elements of D overwrite the corresponding elements of A ; if D has 2 by 2 blocks, only the upper or lower triangle is stored, as specified by **uplo**.

The unit diagonal elements of U or L and the 2 by 2 unit diagonal blocks are not stored. The remaining elements of U or L are stored in the corresponding columns of the array **a**, but additional row interchanges must be applied to recover U or L explicitly (this is seldom necessary). If **ipiv**[$i - 1$] = i ,

for $i = 1, 2, \dots, n$ (as is the case when A is positive definite), then U or L is stored explicitly (except for its unit diagonal elements which are equal to 1).

The total number of real floating-point operations is approximately $\frac{4}{3}n^3$.

A call to `nag_zhetrf` (f07mrc) may be followed by calls to the functions:

- `nag_zhetrs` (f07msc) to solve $AX = B$;
- `nag_zhecon` (f07muc) to estimate the condition number of A ;
- `nag_zhetri` (f07mwc) to compute the inverse of A .

The real analogue of this function is `nag_dsytrf` (f07mdc).

10 Example

This example computes the Bunch–Kaufman factorization of the matrix A , where

$$A = \begin{pmatrix} -1.36 + 0.00i & 1.58 + 0.90i & 2.21 - 0.21i & 3.91 + 1.50i \\ 1.58 - 0.90i & -8.87 + 0.00i & -1.84 - 0.03i & -1.78 + 1.18i \\ 2.21 + 0.21i & -1.84 + 0.03i & -4.63 + 0.00i & 0.11 + 0.11i \\ 3.91 - 1.50i & -1.78 - 1.18i & 0.11 - 0.11i & -1.84 + 0.00i \end{pmatrix}.$$

10.1 Program Text

```

/* nag_zhetrf (f07mrc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer      i, j, n, nrhs, pda, pdb;
    Integer      exit_status = 0;
    Nag_UploType uplo;
    Nag_ErrorType fail;
    Nag_OrderType order;
    /* Arrays */
    Integer      *ipiv = 0;
    char         nag_enum_arg[40];
    Complex      *a = 0, *b = 0;

#ifdef NAG_LOAD_FP
    /* The following line is needed to force the Microsoft linker
       to load floating point support */
    float        force_loading_of_ms_float_support = 0;
#endif /* NAG_LOAD_FP */

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
#define B(I, J) b[(J-1)*pdb + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
#define B(I, J) b[(I-1)*pdb + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

```

```

printf("nag_zhetrf (f07mrc) Example Program Results\n\n");

/* Skip heading in data file */
#ifdef _WIN32
scanf_s("%*[\n] ");
#else
scanf("%*[\n] ");
#endif
#ifdef _WIN32
scanf_s("%"NAG_IFMT%"NAG_IFMT"%*[\n] ", &n, &nrhs);
#else
scanf("%"NAG_IFMT%"NAG_IFMT"%*[\n] ", &n, &nrhs);
#endif
#ifdef NAG_COLUMN_MAJOR
pda = n;
pdb = n;
#else
pda = n;
pdb = nrhs;
#endif

/* Allocate memory */
if (!(ipiv = NAG_ALLOC(n, Integer)) ||
    !(a = NAG_ALLOC(n * n, Complex)) ||
    !(b = NAG_ALLOC(n * nrhs, Complex)))
{
printf("Allocation failure\n");
exit_status = -1;
goto END;
}

/* Read A and B from data file */
#ifdef _WIN32
scanf_s(" %39s%*[\n] ", nag_enum_arg, _countof(nag_enum_arg));
#else
scanf(" %39s%*[\n] ", nag_enum_arg);
#endif
/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);

if (uplo == Nag_Upper)
{
for (i = 1; i <= n; ++i)
{
for (j = i; j <= n; ++j)
#ifdef _WIN32
scanf_s(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#else
scanf(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#endif
}
}
#ifdef _WIN32
scanf_s("%*[\n] ");
#else
scanf("%*[\n] ");
#endif
}
else
{
for (i = 1; i <= n; ++i)
{
for (j = 1; j <= i; ++j)
#ifdef _WIN32
scanf_s(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#else
scanf(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#endif
}
}
}
#endif

```

```

    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
    }

    for (i = 1; i <= n; ++i)
    {
        for (j = 1; j <= nrhs; ++j)
#ifdef _WIN32
            scanf_s(" ( %lf , %lf )", &B(i, j).re, &B(i, j).im);
#else
            scanf(" ( %lf , %lf )", &B(i, j).re, &B(i, j).im);
#endif
    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif

    /* Factorize A */
    /* nag_zhetrf (f07mrc).
     * Bunch-Kaufman factorization of complex Hermitian
     * indefinite matrix
     */
    nag_zhetrf(order, uplo, n, a, pda, ipiv, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_zhetrf (f07mrc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Compute solution */
    /* nag_zhetrs (f07msc).
     * Solution of complex Hermitian indefinite system of linear
     * equations, multiple right-hand sides, matrix already
     * factorized by nag_zhetrf (f07mrc)
     */
    nag_zhetrs(order, uplo, n, nrhs, a, pda, ipiv, b, pdb,
               &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_zhetrs (f07msc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

    /* Print solution */
    /* nag_gen_complx_mat_print_comp (x04dbc).
     * Print complex general matrix (comprehensive)
     */
    fflush(stdout);
    nag_gen_complx_mat_print_comp(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n,
                                  nrhs, b, pdb, Nag_BracketForm, "%7.4f",
                                  "Solution(s)", Nag_IntegerLabels, 0,
                                  Nag_IntegerLabels, 0, 80, 0, 0, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_gen_complx_mat_print_comp (x04dbc).\n%s\n",
              fail.message);
        exit_status = 1;
        goto END;
    }
}
END:

```

```

NAG_FREE(ipiv);
NAG_FREE(a);
NAG_FREE(b);
return exit_status;
}

```

10.2 Program Data

```

nag_zhetrf (f07mrc) Example Program Data
  4  2                                     :Values of n and nrhs
  Nag_Lower                               :Value of uplo
(-1.36, 0.00)
( 1.58,-0.90) (-8.87, 0.00)
( 2.21, 0.21) (-1.84, 0.03) (-4.63, 0.00)
( 3.91,-1.50) (-1.78,-1.18) ( 0.11,-0.11) (-1.84, 0.00) :End of matrix A
( 7.79,  5.48) (-35.39, 18.01)
(-0.77,-16.05) (  4.23,-70.02)
(-9.58,  3.88) (-24.79, -8.40)
( 2.98,-10.18) ( 28.68,-39.89)           :End of matrix B

```

10.3 Program Results

```

nag_zhetrf (f07mrc) Example Program Results

Solution(s)
          1          2
1 ( 1.0000,-1.0000) ( 3.0000,-4.0000)
2 (-1.0000, 2.0000) (-1.0000, 5.0000)
3 ( 3.0000,-2.0000) ( 7.0000,-2.0000)
4 ( 2.0000, 1.0000) (-8.0000, 6.0000)

```
