

## NAG Library Function Document

### nag\_real\_sparse\_eigensystem\_monit (f12aec)

**Note:** this function uses **optional arguments** to define choices in the problem specification. If you wish to use default settings for all of the optional arguments, then the option setting function `nag_real_sparse_eigensystem_option (f12adc)` need not be called. If, however, you wish to reset some or all of the settings please refer to Section 11 in `nag_real_sparse_eigensystem_option (f12adc)` for a detailed description of the specification of the optional arguments.

#### 1 Purpose

`nag_real_sparse_eigensystem_monit (f12aec)` can be used to return additional monitoring information during computation. It is in a suite of functions consisting of `nag_real_sparse_eigensystem_init (f12aac)`, `nag_real_sparse_eigensystem_iter (f12abc)`, `nag_real_sparse_eigensystem_sol (f12acc)`, `nag_real_sparse_eigensystem_option (f12adc)` and `nag_real_sparse_eigensystem_monit (f12aec)`.

#### 2 Specification

```
#include <nag.h>
#include <nagf12.h>

void nag_real_sparse_eigensystem_monit (Integer *niter, Integer *nconv,
    double ritzr[], double ritzl[], double rzest[], const Integer icomm[],
    const double comm[])
```

#### 3 Description

The suite of functions is designed to calculate some of the eigenvalues,  $\lambda$ , (and optionally the corresponding eigenvectors,  $x$ ) of a standard eigenvalue problem  $Ax = \lambda x$ , or of a generalized eigenvalue problem  $Ax = \lambda Bx$  of order  $n$ , where  $n$  is large and the coefficient matrices  $A$  and  $B$  are sparse, real and nonsymmetric. The suite can also be used to find selected eigenvalues/eigenvectors of smaller scale dense, real and nonsymmetric problems.

On an intermediate exit from `nag_real_sparse_eigensystem_iter (f12abc)` with `irevcn = 4`, `nag_real_sparse_eigensystem_monit (f12aec)` may be called to return monitoring information on the progress of the Arnoldi iterative process. The information returned by `nag_real_sparse_eigensystem_monit (f12aec)` is:

- the number of the current Arnoldi iteration;
- the number of converged eigenvalues at this point;
- the real and imaginary parts of the converged eigenvalues;
- the error bounds on the converged eigenvalues.

`nag_real_sparse_eigensystem_monit (f12aec)` does not have an equivalent function from the ARPACK package which prints various levels of detail of monitoring information through an output channel controlled via an argument value (see Lehoucq *et al.* (1998) for details of ARPACK routines). `nag_real_sparse_eigensystem_monit (f12aec)` should not be called at any time other than immediately following an `irevcn = 4` return from `nag_real_sparse_eigensystem_iter (f12abc)`.

#### 4 References

Lehoucq R B (2001) Implicitly restarted Arnoldi methods and subspace iteration *SIAM Journal on Matrix Analysis and Applications* **23** 551–562

Lehoucq R B and Scott J A (1996) An evaluation of software for computing eigenvalues of sparse nonsymmetric matrices *Preprint MCS-P547-1195* Argonne National Laboratory

Lehoucq R B and Sorensen D C (1996) Deflation techniques for an implicitly restarted Arnoldi iteration *SIAM Journal on Matrix Analysis and Applications* **17** 789–821

Lehoucq R B, Sorensen D C and Yang C (1998) *ARPACK Users' Guide: Solution of Large-scale Eigenvalue Problems with Implicitly Restarted Arnoldi Methods* SIAM, Philadelphia

## 5 Arguments

- 1: **niter** – Integer \* *Output*  
*On exit:* the number of the current Arnoldi iteration.
  
- 2: **nconv** – Integer \* *Output*  
*On exit:* the number of converged eigenvalues so far.
  
- 3: **ritzr**[*dim*] – double *Output*  
**Note:** the dimension, *dim*, of the array **ritzr** must be at least **nconv** (see `nag_real_sparse_eigensystem_init (f12aac)`).  
*On exit:* the first **nconv** locations of the array **ritzr** contain the real parts of the converged approximate eigenvalues.
  
- 4: **ritz**[*dim*] – double *Output*  
**Note:** the dimension, *dim*, of the array **ritz** must be at least **nconv** (see `nag_real_sparse_eigensystem_init (f12aac)`).  
*On exit:* the first **nconv** locations of the array **ritz** contain the imaginary parts of the converged approximate eigenvalues.
  
- 5: **rzest**[*dim*] – double *Output*  
**Note:** the dimension, *dim*, of the array **rzest** must be at least **nconv** (see `nag_real_sparse_eigensystem_init (f12aac)`).  
*On exit:* the first **nconv** locations of the array **rzest** contain the Ritz estimates (error bounds) on the converged approximate eigenvalues.
  
- 6: **icomm**[*dim*] – const Integer *Communication Array*  
**Note:** the dimension, *dim*, of the array **icomm** must be at least  $\max(1, \mathbf{licomm})$ , where **licomm** is passed to the setup function (see `nag_real_sparse_eigensystem_init (f12aac)`).  
*On entry:* the array **icomm** output by the preceding call to `nag_real_sparse_eigensystem_iter (f12abc)`.
  
- 7: **comm**[*dim*] – const double *Communication Array*  
**Note:** the dimension, *dim*, of the array **comm** must be at least  $\max(1, \mathbf{licomm})$ , where **licomm** is passed to the setup function (see `nag_real_sparse_eigensystem_init (f12aac)`).  
*On entry:* the array **comm** output by the preceding call to `nag_real_sparse_eigensystem_iter (f12abc)`.

## 6 Error Indicators and Warnings

None.

## 7 Accuracy

A Ritz value,  $\lambda$ , is deemed to have converged if its Ritz estimate  $\leq \mathbf{Tolerance} \times |\lambda|$ . The default **Tolerance** used is the *machine precision* given by `nag_machine_precision (X02AJC)`.

## 8 Parallelism and Performance

Not applicable.

## 9 Further Comments

None.

## 10 Example

This example solves  $Ax = \lambda Bx$  in shifted-real mode, where  $A$  is the tridiagonal matrix with 2 on the diagonal,  $-2$  on the subdiagonal and 3 on the superdiagonal. The matrix  $B$  is the tridiagonal matrix with 4 on the diagonal and 1 on the off-diagonals. The shift sigma,  $\sigma$ , is a complex number, and the operator used in the shifted-real iterative process is  $OP = \text{real}((A - \sigma B)_{-1}B)$ .

### 10.1 Program Text

```

/* nag_real_sparse_eigensystem_monit (f12aec) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 8, 2005.
 */

#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <stdio.h>
#include <naga02.h>
#include <nagf12.h>
#include <nagf16.h>

static void mv(Integer, double *, double *);
static void av(Integer, double *, double *);
static int ytax(Integer, double *, double *, double *);
static int ytmx(Integer, double *, double *, double *);
static void my_zgttrf(Integer, Complex *, Complex *, Complex *,
                    Complex *, Integer *, Integer *);
static void my_zgttrs(Integer, Complex *, Complex *, Complex *,
                    Complex *, Integer *, Complex *);

int main(void)
{
  /* Constants */
  Integer    licomm = 140, imon = 1;
  /* Scalars */
  Complex    c1, c2, c3, eigv, num, den;
  double     estnrm, deni, denr, i2, numi, numr, r2;
  double     sigmai, sigmar;
  Integer    exit_status, info, irevcm, j, k, lcomm, n;
  Integer    nconv, ncv, nev, niter, nshift;
  /* Nag types */
  Nag_Boolean first;
  NagError   fail;

  /* Arrays */
  Complex    *cdd = 0, *cdl = 0, *cdu = 0, *cdu2 = 0, *ctemp = 0;
  double     *comm = 0, *eigvr = 0, *eigvi = 0, *eigest = 0;
  double     *resid = 0, *v = 0;
  Integer    *icomm = 0, *ipiv = 0;
  /* Pointers */
  double     *mx = 0, *x = 0, *y = 0;

  exit_status = 0;
  INIT_FAIL(fail);

  printf("nag_real_sparse_eigensystem_monit (f12aec) Example Program "

```

```

        "Results\n");
    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif

    /* Read problem parameter values from data file. */
#ifdef _WIN32
    scanf_s("%"NAG_IFMT%"NAG_IFMT%"NAG_IFMT"%lf%lf%*[\n] ", &n, &nev, &ncv,
            &sigmar, &sigmai);
#else
    scanf("%"NAG_IFMT%"NAG_IFMT%"NAG_IFMT"%lf%lf%*[\n] ", &n, &nev, &ncv,
            &sigmar, &sigmai);
#endif

    /* Allocate memory */
    lcomm = 3*n + 3*ncv*ncv + 6*ncv + 60;
    if (!(cdd = NAG_ALLOC(n, Complex)) ||
        !(cdl = NAG_ALLOC(n, Complex)) ||
        !(cdu = NAG_ALLOC(n, Complex)) ||
        !(cdu2 = NAG_ALLOC(n, Complex)) ||
        !(ctemp = NAG_ALLOC(n, Complex)) ||
        !(comm = NAG_ALLOC(lcomm, double)) ||
        !(eigvr = NAG_ALLOC(ncv, double)) ||
        !(eigvi = NAG_ALLOC(ncv, double)) ||
        !(eigest = NAG_ALLOC(ncv, double)) ||
        !(resid = NAG_ALLOC(n, double)) ||
        !(v = NAG_ALLOC(n * ncv, double)) ||
        !(icomm = NAG_ALLOC(lcomm, Integer)) ||
        !(ipiv = NAG_ALLOC(n, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Initialise communication arrays for problem using
       nag_real_sparse_eigensystem_init (f12aac). */
    nag_real_sparse_eigensystem_init(n, nev, ncv, icomm, licomm, comm,
                                     lcomm, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf(
            "Error from nag_real_sparse_eigensystem_init (f12aac).\n%s\n",
            fail.message);
        exit_status = 1;
        goto END;
    }

    /* Select the required spectrum using
       nag_real_sparse_eigensystem_option (f12adc). */
    nag_real_sparse_eigensystem_option("SHIFTED REAL", icomm, comm,
                                       &fail);

    /* Select the problem type using
       nag_real_sparse_eigensystem_option (f12adc). */
    nag_real_sparse_eigensystem_option("GENERALIZED", icomm, comm,
                                       &fail);

    /* Solve A*x = lambda*B*x in shift-invert mode. */
    /* The shift, sigma, is a complex number (sigmar, sigmai). */
    /* OP = Real_Part{inv[A-(sigmar,sigmai)*M]*M and B = M. */
    c1 = nag_complex(-2. - sigmar, -sigmai);
    c2 = nag_complex(2. - sigmar * 4., sigmai * -4.);
    c3 = nag_complex(3. - sigmar, -sigmai);

    for (j = 0; j <= n - 2; ++j)
    {
        cdl[j] = c1;
        cdd[j] = c2;
        cdu[j] = c3;
    }
    cdd[n-1] = c2;

```

```

my_zgttrf(n, cdl, cdd, cdu, cdu2, ipiv, &info);

irevcm = 0;
REVCOMLOOP:
/* repeated calls to reverse communication routine
   nag_real_sparse_eigensystem_iter (f12abc). */
nag_real_sparse_eigensystem_iter(&irevcm, resid, v, &x, &y, &mx,
                                &nshift, comm, icomm, &fail);
if (irevcm != 5)
{
  if (irevcm == -1)
  {
    /* Perform  $x \leftarrow OP*x = inv[A-SIGMA*M]*M*x$  */
    mv(n, x, y);
    for (j = 0; j <= n-1; ++j)
    {
      ctemp[j].re = y[j], ctemp[j].im = 0.;
    }
    my_zgttrs(n, cdl, cdd, cdu, cdu2, ipiv, ctemp);
    for (j = 0; j <= n-1; ++j)
    {
      y[j] = ctemp[j].re;
    }
  }
  else if (irevcm == 1)
  {
    /* Perform  $x \leftarrow OP*x = inv[A-SIGMA*M]*M*x$ , */
    /*  $M*X$  stored in  $MX$ . */
    for (j = 0; j <= n-1; ++j)
    {
      ctemp[j].re = mx[j], ctemp[j].im = 0.;
    }
    my_zgttrs(n, cdl, cdd, cdu, cdu2, ipiv, ctemp);
    for (j = 0; j <= n-1; ++j)
    {
      y[j] = ctemp[j].re;
    }
  }
  else if (irevcm == 2)
  {
    /* Perform  $y \leftarrow M*x$  */
    mv(n, x, y);
  }
  else if (irevcm == 4 && imon == 1)
  {
    /* If imon=1, get monitoring information using
       nag_real_sparse_eigensystem_monit (f12aec). */
    nag_real_sparse_eigensystem_monit(&niter, &nconv, eigvr,
                                       eigvi, eigest, icomm, comm);
    /* Compute 2-norm of Ritz estimates using
       nag_dge_norm (f16rac).*/
    nag_dge_norm(Nag_ColMajor, Nag_FrobeniusNorm, nev, 1, eigest,
                 nev, &estnrm, &fail);
    printf("Iteration %3"NAG_IFMT", ", niter);
    printf(" No. converged = %3"NAG_IFMT",", nconv);
    printf(" norm of estimates = %17.8e\n", estnrm);
  }
  goto REVCOMLOOP;
}
if (fail.code == NE_NOERROR)
{
  /* Post-Process using nag_real_sparse_eigensystem_sol
     (f12acc) to compute eigenvalues/vectors. */
  nag_real_sparse_eigensystem_sol(&nconv, eigvr, eigvi, v, sigmar,
                                  sigmai, resid, v, comm, icomm,
                                  &fail);

  first = Nag_TRUE;
  k = 0;
  for (j = 0; j <= nconv-1; ++j)
  {

```

```

/* Use Rayleigh Quotient to recover eigenvalues of the */
/* original problem. */
if (eigvi[j] == 0.)
{
  /* Ritz value is real. */
  /* Numerator = Vj . AVj where Vj is jth Ritz vector */
  if (ytax(n, &v[k], &v[k], &numr))
  {
    goto END;
  }
  /* Denominator = Vj . MVj */
  if (ytmx(n, &v[k], &v[k], &denr))
  {
    goto END;
  }
  eigvr[j] = numr / denr;
}
else if (first)
{
  /* Ritz value is complex: (x,y). */
  /* Compute x'(Ax) and y'(Ax). */
  if (ytax(n, &v[k], &v[k], &numr))
  {
    goto END;
  }
  if (ytax(n, &v[k], &v[k+n], &numi))
  {
    goto END;
  }
  /* Compute y'(Ay) and x'(Ay). */
  if (ytax(n, &v[k+n], &v[k+n], &r2))
  {
    goto END;
  }
  if (ytax(n, &v[k+n], &v[k], &i2))
  {
    goto END;
  }
  numr += r2;
  numi = i2 - numi;
  /* Assign to Complex type using nag_complex (a02bac). */
  num = nag_complex(numr, numi);
  /* Compute x'(Mx) and y'(Mx). */
  if (ytmx(n, &v[k], &v[k], &denr))
  {
    goto END;
  }
  if (ytmx(n, &v[k], &v[k+n], &deni))
  {
    goto END;
  }
  /* Compute y'(Ay) and x'(Ay). */
  if (ytmx(n, &v[k+n], &v[k+n], &r2))
  {
    goto END;
  }
  if (ytmx(n, &v[k+n], &v[k], &i2))
  {
    goto END;
  }
  denr += r2;
  deni = i2 - deni;
  /* Assign to Complex type using nag_complex (a02bac). */
  den = nag_complex(denr, deni);
  /* eigv = x'(Ax)/x'(Mx) */
  /* Compute Complex division using nag_complex_divide
  (a02cdc). */
  eigv = nag_complex_divide(num, den);
  eigvr[j] = eigv.re;
  eigvi[j] = eigv.im;
  first = Nag_FALSE;
}

```

```

    }
    else
    {
        /* Second of complex conjugate pair. */
        eigvr[j] = eigvr[j-1];
        eigvi[j] = -eigvi[j-1];
        first = Nag_TRUE;
    }
    k = k + n;
}
/* Print computed eigenvalues. */
printf("\n The %4"NAG_IFMT" generalized Ritz values closest", nconv);
printf(" to ( %8.4f , %8.4f ) are:\n\n", sigmar, sigmai);
for (j = 0; j <= nconv-1; ++j)
{
    printf("%8"NAG_IFMT"%5s( %7.4f, %7.4f )\n", j+1, "",
           eigvr[j], eigvi[j]);
}
}
else
{
    printf(
        " Error from nag_real_sparse_eigensystem_iter (f12abc).\n%s\n",
        fail.message);
    exit_status = 1;
    goto END;
}
END:
NAG_FREE(cdd);
NAG_FREE(cdl);
NAG_FREE(cdu);
NAG_FREE(cdu2);
NAG_FREE(ctemp);
NAG_FREE(comm);
NAG_FREE(eigvr);
NAG_FREE(eigvi);
NAG_FREE(eigest);
NAG_FREE(resid);
NAG_FREE(v);
NAG_FREE(icom);
NAG_FREE(ipiv);

return exit_status;
}

static void mv(Integer n, double *v, double *y)
{
    /* Compute the matrix vector multiplication y<---M*x, */
    /* where M is mass matrix formed by using piecewise linear elements */
    /* on [0,1]. */

    /* Scalars */
    Integer j;

    /* Function Body */
    y[0] = v[0] * 4. + v[1];
    for (j = 1; j <= n - 2; ++j)
    {
        y[j] = v[j-1] + v[j] * 4. + v[j+1];
    }
    y[n-1] = v[n-2] + v[n-1] * 4.;
    return;
} /* mv */

static void av(Integer n, double *v, double *w)
{
    /* Scalars */
    Integer j;

    /* Function Body */

```

```

w[0] = v[0] * 2. + v[1] * 3.;
for (j = 1; j <= n - 2; ++j)
    {
        w[j] = v[j-1] * -2. + v[j] * 2. + v[j+1] * 3.;
    }
w[n-1] = v[n-2] * -2. + v[n-1] * 2.;
return;
} /* av */

static int ytax(Integer n, double x[], double y[], double *r)
{
    /* Given the vectors x and y, Performs the operation */
    /* y'Ax and returns the scalar value. */

    /* Scalars */
    Integer exit_status, j;
    /* Arrays */
    double *ax = 0;

    /* Function Body */
    exit_status = 0;
    /* Allocate memory */
    if (!(ax = NAG_ALLOC(n, double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto YTAXEND;
    }
    av(n, x, ax);
    *r = 0.0;
    for (j = 0; j <= n - 1; ++j)
    {
        *r = *r + y[j] * ax[j];
    }
YTAXEND:
    NAG_FREE(ax);
    return exit_status;
} /* ytax */

static int ytmx(Integer n, double x[], double y[], double *r)
{
    /* Given the vectors x and y, Performs the operation */
    /* y'Mx and returns the scalar value. */

    /* Scalars */
    Integer exit_status, j;
    /* Arrays */
    double *mx = 0;

    /* Function Body */
    exit_status = 0;
    /* Allocate memory */
    if (!(mx = NAG_ALLOC(n, double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto YTMXEND;
    }
    mv(n, x, mx);
    *r = 0.0;
    for (j = 0; j <= n - 1; ++j)
    {
        *r = *r + y[j] * mx[j];
    }
YTMXEND:
    NAG_FREE(mx);
    return exit_status;
} /* ytmx */

static void my_zgtrrf(Integer n, Complex dl[], Complex d[],
                    Complex du[], Complex du2[], Integer ipiv[],

```



```

        Integer *info)
{
    /* A simple C version of the Lapack routine zgtrf with argument
       checking removed */
    /* Scalars */
    Complex temp, fact, z1;
    Integer i;
    /* Function Body */
    *info = 0;
    for (i = 0; i < n; ++i)
    {
        ipiv[i] = i;
    }
    for (i = 0; i < n - 2; ++i)
    {
        du2[i] = nag_complex(0.0, 0.0);
    }
    for (i = 0; i < n - 2; ++i)
    {
        if (fabs(d[i].re)+fabs(d[i].im) >= fabs(dl[i].re)+fabs(dl[i].im))
        {
            /* No row interchange required, eliminate dl[i]. */
            if (fabs(d[i].re)+fabs(d[i].im) != 0.0)
            {
                /* Compute Complex division using nag_complex_divide
                   (a02cdc). */
                fact = nag_complex_divide(dl[i], d[i]);
                dl[i] = fact;
                /* Compute Complex multiply using nag_complex_multiply
                   (a02ccc). */
                fact = nag_complex_multiply(fact, du[i]);
                /* Compute Complex subtraction using
                   nag_complex_subtract (a02cbc). */
                d[i+1] = nag_complex_subtract(d[i+1], fact);
            }
        }
        else
        {
            /* Interchange rows I and I+1, eliminate dl[I] */
            /* Compute Complex division using nag_complex_divide
               (a02cdc). */
            fact = nag_complex_divide(d[i], dl[i]);
            d[i] = dl[i];
            dl[i] = fact;
            temp = du[i];
            du[i] = d[i+1];
            /* Compute Complex multiply using nag_complex_multiply
               (a02ccc). */
            z1 = nag_complex_multiply(fact, d[i+1]);
            /* Compute Complex subtraction using nag_complex_subtract
               (a02cbc). */
            d[i+1] = nag_complex_subtract(temp, z1);
            du2[i] = du[i+1];
            /* Compute Complex multiply using nag_complex_multiply
               (a02ccc). */
            du[i+1] = nag_complex_multiply(fact, du[i+1]);
            /* Perform Complex negation using nag_complex_negate
               (a02cec). */
            du[i+1] = nag_complex_negate(du[i+1]);
            ipiv[i] = i + 1;
        }
    }
}
if (n > 1)
{
    i = n - 2;
    if (fabs(d[i].re)+fabs(d[i].im) >= fabs(dl[i].re)+fabs(dl[i].im))
    {
        if (fabs(d[i].re)+fabs(d[i].im) != 0.0)
        {
            /* Compute Complex division using nag_complex_divide
               (a02cdc). */

```

```

        fact = nag_complex_divide(dl[i], d[i]);
        dl[i] = fact;
        /* Compute Complex multiply using nag_complex_multiply
           (a02ccc). */
        fact = nag_complex_multiply(fact, du[i]);
        /* Compute Complex subtraction using
           nag_complex_subtract (a02cbc). */
        d[i+1] = nag_complex_subtract(d[i+1], fact);
    }
}
else
{
    /* Compute Complex division using nag_complex_divide
       (a02cdc). */
    fact = nag_complex_divide(d[i], dl[i]);
    d[i] = dl[i];
    dl[i] = fact;
    temp = du[i];
    du[i] = d[i+1];
    /* Compute Complex multiply using nag_complex_multiply
       (a02ccc). */
    z1 = nag_complex_multiply(fact, d[i+1]);
    /* Compute Complex subtraction using nag_complex_subtract
       (a02cbc). */
    d[i+1] = nag_complex_subtract(temp, z1);
    ipiv[i] = i + 1;
}
}
/* Check for a zero on the diagonal of U. */
for (i = 0; i < n; ++i)
{
    if (fabs(d[i].re)+fabs(d[i].im) == 0.0)
    {
        *info = i;
        goto END;
    }
}
END:
return;
}

static void my_zgttrs(Integer n, Complex dl[], Complex d[],
                    Complex du[], Complex du2[], Integer ipiv[],
                    Complex b[])
{
    /* A simple C version of the Lapack routine zgttrs with argument
       checking removed, the number of right-hand-sides=1, Trans='N' */
    /* Scalars */
    Complex temp, z1;
    Integer i;
    /* Solve L*x = b. */
    for (i = 0; i < n - 1; ++i)
    {
        if (ipiv[i] == i)
        {
            /* b[i+1] = b[i+1] - dl[i]*b[i] */
            /* Compute Complex multiply using nag_complex_multiply
               (a02ccc). */
            temp = nag_complex_multiply(dl[i], b[i]);
            /* Compute Complex subtraction using nag_complex_subtract
               (a02cbc). */
            b[i+1] = nag_complex_subtract(b[i+1], temp);
        }
        else
        {
            temp = b[i];
            b[i] = b[i+1];
            /* Compute Complex multiply using nag_complex_multiply
               (a02ccc). */
            z1 = nag_complex_multiply(dl[i], b[i]);
            /* Compute Complex subtraction using nag_complex_subtract

```

```

        (a02cbc). */
        b[i+1] = nag_complex_subtract(temp, z1);
    }
}
/* Solve U*x = b. */
/* Compute Complex division using nag_complex_divide (a02cdc). */
b[n-1] = nag_complex_divide(b[n-1], d[n-1]);
if (n > 1)
{
    /* Compute Complex multiply using nag_complex_multiply
    (a02ccc). */
    temp = nag_complex_multiply(du[n-2], b[n-1]);
    /* Compute Complex subtraction using nag_complex_subtract
    (a02cbc). */
    z1 = nag_complex_subtract(b[n-2], temp);
    /* Compute Complex division using nag_complex_divide (a02cdc). */
    b[n-2] = nag_complex_divide(z1, d[n-2]);
}
for (i = n - 3; i >= 0; --i)
{
    /* b[i] = (b[i]-du[i]*b[i+1]-du2[i]*b[i+2])/d[i]; */
    /* Compute Complex multiply using nag_complex_multiply
    (a02ccc). */
    temp = nag_complex_multiply(du[i], b[i+1]);
    z1 = nag_complex_multiply(du2[i], b[i+2]);
    /* Compute Complex addition using nag_complex_add
    (a02cac). */
    temp = nag_complex_add(temp, z1);
    /* Compute Complex subtraction using nag_complex_subtract
    (a02cbc). */
    z1 = nag_complex_subtract(b[i], temp);
    /* Compute Complex division using nag_complex_divide
    (a02cdc). */
    b[i] = nag_complex_divide(z1, d[i]);
}
return;
}

```

## 10.2 Program Data

nag\_real\_sparse\_eigensystem\_monit (f12aec) Example Program Data  
 100 4 20 4.0e-1 6.0e-1 : Values for nx, nev, ncv, sigmar, sigmai

## 10.3 Program Results

nag\_real\_sparse\_eigensystem\_monit (f12aec) Example Program Results

Iteration	1,	No. converged =	0,	norm of estimates =	1.05198320e-01
Iteration	2,	No. converged =	0,	norm of estimates =	1.18821782e-03
Iteration	3,	No. converged =	0,	norm of estimates =	1.38923424e-06
Iteration	4,	No. converged =	0,	norm of estimates =	3.93878037e-09
Iteration	5,	No. converged =	0,	norm of estimates =	1.15839744e-11
Iteration	6,	No. converged =	0,	norm of estimates =	5.22183096e-14

The 4 generalized Ritz values closest to ( 0.4000 , 0.6000 ) are:

1	( 0.5000, -0.5958 )
2	( 0.5000, 0.5958 )
3	( 0.5000, -0.6331 )
4	( 0.5000, 0.6331 )

---