

# NAG Library Function Document

## nag\_rand\_logistic (g05slc)

### 1 Purpose

nag\_rand\_logistic (g05slc) generates a vector of pseudorandom numbers from a logistic distribution with mean  $a$  and spread  $b$ .

### 2 Specification

```
#include <nag.h>
#include <nagg05.h>
void nag_rand_logistic (Integer n, double a, double b, Integer state[],
    double x[], NagError *fail)
```

### 3 Description

The distribution has PDF (probability density function)

$$f(x) = \frac{e^{(x-a)/b}}{b(1 + e^{(x-a)/b})^2}.$$

nag\_rand\_logistic (g05slc) returns the value

$$a + b \ln\left(\frac{y}{1-y}\right),$$

where  $y$  is a pseudorandom number uniformly distributed over  $(0, 1)$ .

One of the initialization functions nag\_rand\_init\_repeatable (g05kfc) (for a repeatable sequence if computed sequentially) or nag\_rand\_init\_nonrepeatable (g05kgc) (for a non-repeatable sequence) must be called prior to the first call to nag\_rand\_logistic (g05slc).

### 4 References

Kendall M G and Stuart A (1969) *The Advanced Theory of Statistics (Volume 1)* (3rd Edition) Griffin  
 Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison–Wesley

### 5 Arguments

- |    |  |              |
|----|--|--------------|
| 1: | <b>n</b> – Integer   | <i>Input</i> |
|    | <i>On entry:</i> $n$ , the number of pseudorandom numbers to be generated.   |              |
|    | <i>Constraint:</i> $n \geq 0$ .  |              |
| 2: | <b>a</b> – double  | <i>Input</i> |
|    | <i>On entry:</i> $a$ , the mean of the distribution.   |              |
| 3: | <b>b</b> – double  | <i>Input</i> |
|    | <i>On entry:</i> $b$ , the spread of the distribution, where ‘spread’ is $\frac{\sqrt{3}}{\pi} \times$ standard deviation. |              |
|    | <i>Constraint:</i> $b \geq 0.0$ .  |              |

- 4: **state**[*dim*] – Integer *Communication Array*  
**Note:** the dimension, *dim*, of this array is dictated by the requirements of associated functions that must have been previously called. This array **MUST** be the same array passed as argument **state** in the previous call to `nag_rand_init_repeatable` (g05kfc) or `nag_rand_init_nonrepeatable` (g05kgc).  
*On entry:* contains information on the selected base generator and its current state.  
*On exit:* contains updated information on the state of the generator.
- 5: **x**[**n**] – double *Output*  
*On exit:* the *n* pseudorandom numbers from the specified logistic distribution.
- 6: **fail** – NagError \* *Input/Output*  
The NAG error argument (see Section 3.6 in the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.  
See Section 3.2.1.2 in the Essential Introduction for further information.

### NE\_BAD\_PARAM

On entry, argument *<value>* had an illegal value.

### NE\_INT

On entry, **n** = *<value>*.  
Constraint: **n** ≥ 0.

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.  
See Section 3.6.6 in the Essential Introduction for further information.

### NE\_INVALID\_STATE

On entry, **state** vector has been corrupted or not initialized.

### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.  
See Section 3.6.5 in the Essential Introduction for further information.

### NE\_REAL

On entry, **b** = *<value>*.  
Constraint: **b** ≥ 0.0.

## 7 Accuracy

Not applicable.

## 8 Parallelism and Performance

`nag_rand_logistic` (g05slc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

None.

## 10 Example

This example prints the first five pseudorandom real numbers from a logistic distribution with mean 1.0 and spread 2.0, generated by a single call to `nag_rand_logistic (g05slc)`, after initialization by `nag_rand_init_repeatable (g05kfc)`.

### 10.1 Program Text

```

/* nag_rand_logistic (g05slc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 9, 2009.
 */
/* Pre-processor includes */
#include <stdio.h>
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg05.h>

int main(void)
{
    /* Integer scalar and array declarations */
    Integer    exit_status = 0;
    Integer    i, lstate;
    Integer    *state = 0;

    /* NAG structures */
    NagError    fail;

    /* Double scalar and array declarations */
    double     *x = 0;

    /* Set the distribution parameters */
    double     a = 1.0e0;
    double     b = 2.0e0;

    /* Set the sample size */
    Integer    n = 5;

    /* Choose the base generator */
    Nag_BaseRNG genid = Nag_Basic;
    Integer    subid = 0;

    /* Set the seed */
    Integer    seed[] = { 1762543 };
    Integer    lseed = 1;

    /* Initialise the error structure */
    INIT_FAIL(fail);

    printf("nag_rand_logistic (g05slc) Example Program Results\n\n");

    /* Get the length of the state array */
    lstate = -1;
    nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
    if (fail.code != NE_NOERROR)
    {

```

```

    printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Allocate arrays */
if (!(x = NAG_ALLOC(n, double)) ||
    !(state = NAG_ALLOC(1state, Integer)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Initialise the generator to a repeatable sequence */
nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Generate the variates*/
nag_rand_logistic(n, a, b, state, x, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_logistic (g05slc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Display the variates*/
for (i = 0; i < n; i++)
    printf("%10.4f\n", x[i]);

END:
NAG_FREE(x);
NAG_FREE(state);

return exit_status;
}

```

## 10.2 Program Data

None.

## 10.3 Program Results

nag\_rand\_logistic (g05slc) Example Program Results

```

2.1193
-3.2544
3.1552
3.7510
-3.2944

```

---