

NAG Library Function Document

nag_rand_uniform (g05sqc)

1 Purpose

nag_rand_uniform (g05sqc) generates a vector of pseudorandom numbers uniformly distributed over the interval $[a, b]$.

2 Specification

```
#include <nag.h>
#include <nagg05.h>

void nag_rand_uniform (Integer n, double a, double b, Integer state[],
                      double x[], NagError *fail)
```

3 Description

If $a = 0$ and $b = 1$, nag_rand_uniform (g05sqc) returns the next n values y_i from a uniform $(0, 1]$ generator (see nag_rand_basic (g05sac) for details).

For other values of a and b , nag_rand_uniform (g05sqc) applies the transformation

$$x_i = a + (b - a)y_i.$$

The function ensures that the values x_i lie in the closed interval $[a, b]$.

One of the initialization functions nag_rand_init_repeatable (g05kfc) (for a repeatable sequence if computed sequentially) or nag_rand_init_nonrepeatable (g05kge) (for a non-repeatable sequence) must be called prior to the first call to nag_rand_uniform (g05sqc).

4 References

Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison–Wesley

5 Arguments

1: **n** – Integer *Input*

On entry: n , the number of pseudorandom numbers to be generated.

Constraint: $n \geq 0$.

2: **a** – double *Input*

3: **b** – double *Input*

On entry: the end points a and b of the uniform distribution.

Constraint: $a \leq b$.

4: **state** $[dim]$ – Integer *Communication Array*

Note: the dimension, dim , of this array is dictated by the requirements of associated functions that must have been previously called. This array **MUST** be the same array passed as argument **state** in the previous call to nag_rand_init_repeatable (g05kfc) or nag_rand_init_nonrepeatable (g05kge).

On entry: contains information on the selected base generator and its current state.

On exit: contains updated information on the state of the generator.

- 5: **x[n]** – double *Output*
On exit: the n pseudorandom numbers from the specified uniform distribution.
- 6: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.
See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{n} = \langle value \rangle$.
Constraint: $\mathbf{n} \geq 0$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.
See Section 3.6.6 in the Essential Introduction for further information.

NE_INVALID_STATE

On entry, **state** vector has been corrupted or not initialized.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.
See Section 3.6.5 in the Essential Introduction for further information.

NE_REAL_2

On entry, $\mathbf{a} = \langle value \rangle$ and $\mathbf{b} = \langle value \rangle$.
Constraint: $\mathbf{b} \geq \mathbf{a}$.

7 Accuracy

Not applicable.

8 Parallelism and Performance

nag_rand_uniform (g05sqc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

Although y_i takes a value from the half closed interval $(0, 1]$ and $x_i = a + (b - a)y_i$, x_i is documented as taking values from the closed interval $[a, b]$. This is because for some values of a and b , `nag_rand_uniform` (g05sqc) may return a value of a due to numerical rounding.

10 Example

This example prints five pseudorandom numbers from a uniform distribution between -1.0 and 1.0 , generated by a single call to `nag_rand_uniform` (g05sqc), after initialization by `nag_rand_init_repeatabl` (g05kfc).

10.1 Program Text

```

/* nag_rand_uniform (g05sqc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 9, 2009.
 */
/* Pre-processor includes */
#include <stdio.h>
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg05.h>

int main(void)
{
    /* Integer scalar and array declarations */
    Integer    exit_status = 0;
    Integer    i, lstate;
    Integer    *state = 0;

    /* NAG structures */
    NagError   fail;

    /* Double scalar and array declarations */
    double     *x = 0;

    /* Set the distribution parameters */
    double     a = -1.0e0;
    double     b = 1.0e0;

    /* Set the sample size */
    Integer    n = 5;

    /* Choose the base generator */
    Nag_BaseRNG genid = Nag_Basic;
    Integer    subid = 0;

    /* Set the seed */
    Integer    seed[] = { 1762543 };
    Integer    lseed = 1;

    /* Initialise the error structure */
    INIT_FAIL(fail);

    printf("nag_rand_uniform (g05sqc) Example Program Results\n\n");

    /* Get the length of the state array */
    lstate = -1;
    nag_rand_init_repeatabl(genid, subid, seed, lseed, state, &lstate, &fail);
    if (fail.code != NE_NOERROR)
    {
        printf("Error from nag_rand_init_repeatabl (g05kfc).\n%s\n",
            fail.message);
        exit_status = 1;
    }
}

```

```

    goto END;
}

/* Allocate arrays */
if (!(x = NAG_ALLOC(n, double)) ||
    !(state = NAG_ALLOC(1state, Integer)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Initialise the generator to a repeatable sequence */
nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
        fail.message);
    exit_status = 1;
    goto END;
}

/* Generate the variates */
nag_rand_uniform(n, a, b, state, x, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_uniform (g05sqc).\n%s\n",
        fail.message);
    exit_status = 1;
    goto END;
}

/* Display the variates*/
for (i = 0; i < n; i++)
    printf("%10.4f\n", x[i]);

END:
NAG_FREE(x);
NAG_FREE(state);

return exit_status;
}

```

10.2 Program Data

None.

10.3 Program Results

nag_rand_uniform (g05sqc) Example Program Results

```

0.2727
-0.7870
0.4921
0.5965
-0.7908

```
