

NAG Library Function Document

nag_rand_gen_discrete (g05tdc)

1 Purpose

nag_rand_gen_discrete (g05tdc) generates a vector of pseudorandom integers from a discrete distribution with a given PDF (probability density function) or CDF (cumulative distribution function) p .

2 Specification

```
#include <nag.h>
#include <nagg05.h>

void nag_rand_gen_discrete (Nag_ModeRNG mode, Integer n, const double p[],
    Integer np, Integer ip1, Nag_DiscreteDistrib itype, double r[],
    Integer lr, Integer state[], Integer x[], NagError *fail)
```

3 Description

nag_rand_gen_discrete (g05tdc) generates a sequence of n integers x_i , from a discrete distribution defined by information supplied in \mathbf{p} . This may either be the PDF or CDF of the distribution. A reference vector is first set up to contain the CDF of the distribution in its higher elements, followed by an index.

Setting up the reference vector and subsequent generation of variates can each be performed by separate calls to nag_rand_gen_discrete (g05tdc) or may be combined in a single call.

One of the initialization functions nag_rand_init_repeatable (g05kfc) (for a repeatable sequence if computed sequentially) or nag_rand_init_nonrepeatable (g05kge) (for a non-repeatable sequence) must be called prior to the first call to nag_rand_gen_discrete (g05tdc).

4 References

Kendall M G and Stuart A (1969) *The Advanced Theory of Statistics (Volume 1)* (3rd Edition) Griffin
 Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison–Wesley

5 Arguments

1: **mode** – Nag_ModeRNG *Input*

On entry: a code for selecting the operation to be performed by the function.

mode = Nag_InitializeReference
 Set up reference vector only.

mode = Nag_GenerateFromReference
 Generate variates using reference vector set up in a prior call to nag_rand_gen_discrete (g05tdc).

mode = Nag_InitializeAndGenerate
 Set up reference vector and generate variates.

mode = Nag_GenerateWithoutReference
 Generate variates without using the reference vector.

Constraint: **mode** = Nag_InitializeReference, Nag_GenerateFromReference, Nag_InitializeAndGenerate or Nag_GenerateWithoutReference.

- 2: **n** – Integer *Input*
On entry: n , the number of pseudorandom numbers to be generated.
Constraint: $n \geq 0$.
- 3: **p[np]** – const double *Input*
On entry: the PDF or CDF of the distribution.
Constraints:
 $0.0 \leq \mathbf{p}[i-1] \leq 1.0$, for $i = 1, 2, \dots, \mathbf{np}$;
if **itype** = Nag_PDF, $\sum_{i=1}^{\mathbf{np}} \mathbf{p}[i-1] = 1.0$;
if **itype** = Nag_CDF, $\mathbf{p}[i-1] < \mathbf{p}[j-1]$, $i < j$ and $\mathbf{p}[\mathbf{np}-1] = 1.0$.
- 4: **np** – Integer *Input*
On entry: the number of values supplied in **p** defining the PDF or CDF of the discrete distribution.
Constraint: $\mathbf{np} > 0$.
- 5: **ip1** – Integer *Input*
On entry: the value of the variate, a whole number, to which the probability in **p**[0] corresponds.
- 6: **itype** – Nag_DiscreteDistrib *Input*
On entry: indicates the type of information contained in **p**.
itype = Nag_PDF
p contains a probability distribution function (PDF).
itype = Nag_CDF
p contains a cumulative distribution function (CDF).
Constraint: **itype** = Nag_PDF or Nag_CDF.
- 7: **r[lr]** – double *Communication Array*
On entry: if **mode** = Nag_GenerateFromReference, the reference vector from the previous call to nag_rand_gen_discrete (g05tdc).
On exit: the reference vector.
- 8: **lr** – Integer *Input*
On entry: the dimension of the array **r**.
Suggested value:
if **mode** \neq Nag_GenerateWithoutReference, $\mathbf{lr} = 10 + 1.4 \times \mathbf{np}$ approximately (for optimum efficiency in generating variates);
otherwise $\mathbf{lr} = 1$.
Constraints:
if **mode** = Nag_InitializeReference or Nag_InitializeAndGenerate, $\mathbf{lr} \geq \mathbf{np} + 8$;
if **mode** = Nag_GenerateFromReference, **lr** should remain unchanged from the previous call to nag_rand_gen_discrete (g05tdc).
- 9: **state[dim]** – Integer *Communication Array*
Note: the dimension, *dim*, of this array is dictated by the requirements of associated functions that must have been previously called. This array MUST be the same array passed as argument **state** in the previous call to nag_rand_init_repeatable (g05kfc) or nag_rand_init_nonrepeatable (g05kgc).

On entry: contains information on the selected base generator and its current state.

On exit: contains updated information on the state of the generator.

10: **x[n]** – Integer

Output

On exit: contains n pseudorandom numbers from the specified discrete distribution.

11: **fail** – NagError *

Input/Output

The NAG error argument (see Section 3.6 in the Essential Introduction).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **lr** is too small when **mode** = Nag_InitializeReference or Nag_InitializeAndGenerate:
lr = $\langle value \rangle$, minimum length required = $\langle value \rangle$.

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 0 .

On entry, **np** = $\langle value \rangle$.

Constraint: **np** > 0 .

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in the Essential Introduction for further information.

NE_INVALID_STATE

On entry, **state** vector has been corrupted or not initialized.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in the Essential Introduction for further information.

NE_PREV_CALL

The value of **np** or **ip1** is not the same as when **r** was set up in a previous call.

Previous value of **np** = $\langle value \rangle$ and **np** = $\langle value \rangle$.

Previous value of **ip1** = $\langle value \rangle$ and **ip1** = $\langle value \rangle$.

NE_REAL_ARRAY

On entry, at least one element of the vector **p** is less than 0.0 or greater than 1.0.

On entry, **itype** = Nag_CDF and the values of **p** are not all in strictly ascending order.

On entry, **itype** = Nag_PDF and the sum of the elements of **p** do not equal one.

On entry, $\mathbf{p}[\mathbf{np} - 1] = \langle \text{value} \rangle$.
 Constraint: if $\mathbf{itype} = \text{Nag_CDF}$, $\mathbf{p}[\mathbf{np} - 1] = 1.0$.

NE_REF_VEC

On entry, some of the elements of the array \mathbf{r} have been corrupted or have not been initialized.

7 Accuracy

Not applicable.

8 Parallelism and Performance

nag_rand_gen_discrete (g05tdc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

This example prints 20 pseudorandom variates from a discrete distribution whose PDF, p , is defined as follows:

n	p
-5	0.01
-4	0.02
-3	0.04
-2	0.08
-1	0.20
0	0.30
1	0.20
2	0.08
3	0.04
4	0.02
5	0.01

The reference vector is set up and the variates are generated by a single call to nag_rand_gen_discrete (g05tdc), after initialization by nag_rand_init_repeatable (g05kfc).

10.1 Program Text

```

/* nag_rand_gen_discrete (g05tdc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * Mark 9, 2009.
 */
/* Pre-processor includes */
#include <stdio.h>
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg05.h>

int main(void)
{
  /* Integer scalar and array declarations */

```

```

Integer          exit_status = 0;
Integer          i, lr, lstate;
Integer          *state = 0, *x = 0;

/* NAG structures */
NagError         fail;
Nag_ModeRNG     mode;

/* Double scalar and array declarations */
double          *r = 0;

/* Set the distribution parameters */
Integer         np = 11;
Nag_DiscreteDistrib itype = Nag_PDF;
double         p[] = { 0.010e0, 0.020e0, 0.040e0, 0.080e0, 0.20e0,
                      0.30e0, 0.20e0, 0.080e0, 0.040e0, 0.020e0,
                      0.010e0 };
Integer         ipl = -5;

/* Set the sample size */
Integer         n = 20;

/* Choose the base generator */
Nag_BaseRNG     genid = Nag_Basic;
Integer         subid = 0;

/* Set the seed */
Integer         seed[] = { 1762543 };
Integer         lseed = 1;

/* Initialise the error structure */
INIT_FAIL(fail);

printf("nag_rand_gen_discrete (g05tdc) Example Program Results\n\n");

/* Get the length of the state array */
lstate = -1;
nag_rand_init_repeatabe(genid, subid, seed, lseed, state, &lstate, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_init_repeatabe (g05kfc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Calculate the size of the reference vector */
lr = 10+1.4*np;

/* Allocate arrays */
if (!(r = NAG_ALLOC(lr, double)) ||
    !(state = NAG_ALLOC(lstate, Integer)) ||
    !(x = NAG_ALLOC(n, Integer)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Initialise the generator to a repeatable sequence */
nag_rand_init_repeatabe(genid, subid, seed, lseed, state, &lstate, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_init_repeatabe (g05kfc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Generate the variates, initialising the reference
vector at the same time */

```

```
mode = Nag_InitializeAndGenerate;
nag_rand_gen_discrete(mode, n, p, np, ip1, itype, r, lr, state, x, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_rand_gen_discrete (g05tdc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Display the variates*/
for (i = 0; i < n; i++)
    printf("%12"NAG_IFMT"\n", x[i]);

END:
NAG_FREE(r);
NAG_FREE(state);
NAG_FREE(x);

return exit_status;
}
```

10.2 Program Data

None.

10.3 Program Results

nag_rand_gen_discrete (g05tdc) Example Program Results

```
0
-2
1
1
-2
0
0
1
0
1
-3
-1
0
-3
0
-1
-1
5
2
0
```
