

NAG Library Function Document

nag_dsptri (f07pjc)

1 Purpose

nag_dsptri (f07pjc) computes the inverse of a real symmetric indefinite matrix A , where A has been factorized by nag_dsptrf (f07pdc), using packed storage.

2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_dsptri (Nag_OrderType order, Nag_UploType uplo, Integer n,
                double ap[], const Integer ipiv[], NagError *fail)
```

3 Description

nag_dsptri (f07pjc) is used to compute the inverse of a real symmetric indefinite matrix A , the function must be preceded by a call to nag_dsptrf (f07pdc), which computes the Bunch–Kaufman factorization of A , using packed storage.

If **uplo** = Nag_Upper, $A = PUDU^T P^T$ and A^{-1} is computed by solving $U^T P^T X P U = D^{-1}$.

If **uplo** = Nag_Lower, $A = PLDL^T P^T$ and A^{-1} is computed by solving $L^T P^T X P L = D^{-1}$.

4 References

Du Croz J J and Higham N J (1992) Stability of methods for matrix inversion *IMA J. Numer. Anal.* **12** 1–19

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **uplo** – Nag_UploType *Input*
On entry: specifies how A has been factorized.
uplo = Nag_Upper
 $A = PUDU^T P^T$, where U is upper triangular.
uplo = Nag_Lower
 $A = PLDL^T P^T$, where L is lower triangular.
Constraint: **uplo** = Nag_Upper or Nag_Lower.
- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: **n** \geq 0.

4: **ap**[*dim*] – double *Input/Output*

Note: the dimension, *dim*, of the array **ap** must be at least $\max(1, \mathbf{n} \times (\mathbf{n} + 1)/2)$.

On entry: the factorization of *A* stored in packed form, as returned by nag_dsptf (f07pdc).

On exit: the factorization is overwritten by the *n* by *n* matrix A^{-1} .

The storage of elements A_{ij} depends on the **order** and **uplo** arguments as follows:

if **order** = Nag_ColMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ap**[(*j* – 1) × *j*/2 + *i* – 1], for $i \leq j$;
 if **order** = Nag_ColMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ap**[(2*n* – *j*) × (*j* – 1)/2 + *i* – 1], for $i \geq j$;
 if **order** = Nag_RowMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ap**[(2*n* – *i*) × (*i* – 1)/2 + *j* – 1], for $i \leq j$;
 if **order** = Nag_RowMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ap**[(*i* – 1) × *i*/2 + *j* – 1], for $i \geq j$.

5: **ipiv**[*dim*] – const Integer *Input*

Note: the dimension, *dim*, of the array **ipiv** must be at least $\max(1, \mathbf{n})$.

On entry: details of the interchanges and the block structure of *D*, as returned by nag_dsptf (f07pdc).

6: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument *<value>* had an illegal value.

NE_INT

On entry, **n** = *<value>*.

Constraint: **n** ≥ 0.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in How to Use the NAG Library and its Documentation for further information.

NE_SINGULAR

Element *<value>* of the diagonal is exactly zero. *D* is singular and the inverse of *A* cannot be computed.

7 Accuracy

The computed inverse X satisfies a bound of the form

$$\text{if } \mathbf{uplo} = \text{Nag_Upper}, |DU^T P^T X P U - I| \leq c(n)\epsilon(|D||U^T|P^T|X|P|U| + |D||D^{-1}|);$$

$$\text{if } \mathbf{uplo} = \text{Nag_Lower}, |DL^T P^T X P L - I| \leq c(n)\epsilon(|D||L^T|P^T|X|P|L| + |D||D^{-1}|),$$

$c(n)$ is a modest linear function of n , and ϵ is the *machine precision*.

8 Parallelism and Performance

nag_dsptri (f07pjc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is approximately $\frac{2}{3}n^3$.

The complex analogues of this function are nag_zhptri (f07pwc) for Hermitian matrices and nag_zsptri (f07qwc) for symmetric matrices.

10 Example

This example computes the inverse of the matrix A , where

$$A = \begin{pmatrix} 2.07 & 3.87 & 4.20 & -1.15 \\ 3.87 & -0.21 & 1.87 & 0.63 \\ 4.20 & 1.87 & 1.15 & 2.06 \\ -1.15 & 0.63 & 2.06 & -1.81 \end{pmatrix}.$$

Here A is symmetric indefinite, stored in packed form, and must first be factorized by nag_dsptrf (f07pdc).

10.1 Program Text

```

/* nag_dsptri (f07pjc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer i, j, n;
    Integer exit_status = 0;
    NagError fail;
    Nag_UploType uplo;
    Nag_OrderType order;
    /* Arrays */

```

```

Integer *ipiv = 0;
char nag_enum_arg[40];
double *ap = 0;

#ifdef NAG_LOAD_FP
/* The following line is needed to force the Microsoft linker
to load floating point support */
float force_loading_of_ms_float_support = 0;
#endif /* NAG_LOAD_FP */

#ifdef NAG_COLUMN_MAJOR
#define A_UPPER(I, J) ap[J*(J-1)/2 + I - 1]
#define A_LOWER(I, J) ap[(2*n-J)*(J-1)/2 + I - 1]
order = Nag_ColMajor;
#else
#define A_LOWER(I, J) ap[I*(I-1)/2 + J - 1]
#define A_UPPER(I, J) ap[(2*n-I)*(I-1)/2 + J - 1]
order = Nag_RowMajor;
#endif

INIT_FAIL(fail);

printf("nag_dsptri (f07pjc) Example Program Results\n\n");

/* Skip heading in data file */
#ifdef _WIN32
scanf_s("%*[\n] ");
#else
scanf("%*[\n] ");
#endif
#ifdef _WIN32
scanf_s("%" NAG_IFMT "%*[\n] ", &n);
#else
scanf("%" NAG_IFMT "%*[\n] ", &n);
#endif

/* Allocate memory */
if (!(ipiv = NAG_ALLOC(n, Integer)) ||
    !(ap = NAG_ALLOC(n * (n + 1) / 2, double)))
{
printf("Allocation failure\n");
exit_status = -1;
goto END;
}

/* Read A from data file */
#ifdef _WIN32
scanf_s(" %39s%*[\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
scanf(" %39s%*[\n] ", nag_enum_arg);
#endif
/* nag_enum_name_to_value (x04nac).
* Converts NAG enum member name to value
*/
uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);

if (uplo == Nag_Upper) {
for (i = 1; i <= n; ++i) {
for (j = i; j <= n; ++j)
#ifdef _WIN32
scanf_s("%lf", &A_UPPER(i, j));
#else
scanf("%lf", &A_UPPER(i, j));
#endif
}
#ifdef _WIN32
scanf_s("%*[\n] ");
#else
scanf("%*[\n] ");
#endif
}
}

```

```

    else {
        for (i = 1; i <= n; ++i) {
            for (j = 1; j <= i; ++j)
#ifdef _WIN32
                scanf_s("%lf", &A_LOWER(i, j));
#else
                scanf("%lf", &A_LOWER(i, j));
#endif
        }
#ifdef _WIN32
        scanf_s("%*[\n] ");
#else
        scanf("%*[\n] ");
#endif
    }

    /* Factorize A */
    /* nag_dsptrf (f07pdc).
     * Bunch-Kaufman factorization of real symmetric indefinite
     * matrix, packed storage
     */
    nag_dsptrf(order, uplo, n, ap, ipiv, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_dsptrf (f07pdc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Compute inverse of A */
    /* nag_dsptri (f07pjc).
     * Inverse of real symmetric indefinite matrix, matrix
     * already factorized by nag_dsptrf (f07pdc), packed storage
     */
    nag_dsptri(order, uplo, n, ap, ipiv, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_dsptri (f07pjc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Print inverse */
    /* nag_pack_real_mat_print (x04ccc).
     * Print real packed triangular matrix (easy-to-use)
     */
    fflush(stdout);
    nag_pack_real_mat_print(order, uplo, Nag_NonUnitDiag, n, ap,
                            "Inverse", 0, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_pack_real_mat_print (x04ccc).\n%s\n",
              fail.message);
        exit_status = 1;
        goto END;
    }
}
END:
    NAG_FREE(ipiv);
    NAG_FREE(ap);
    return exit_status;
}

```

10.2 Program Data

```

nag_dsptri (f07pjc) Example Program Data
4                               :Value of n
Nag_Lower                       :Value of uplo
2.07
3.87  -0.21
4.20  1.87  1.15
-1.15  0.63  2.06  -1.81  :End of matrix A

```

10.3 Program Results

nag_dsptri (f07pjc) Example Program Results

```
Inverse
      1          2          3          4
1      0.7485
2      0.5221    -0.1605
3     -1.0058    -0.3131    1.3501
4     -1.4386    -0.7440    2.0667    2.4547
```
