

# NAG Library Function Document

## nag\_dormrz (f08bkc)

### 1 Purpose

nag\_dormrz (f08bkc) multiplies a general real  $m$  by  $n$  matrix  $C$  by the real orthogonal matrix  $Z$  from an  $RZ$  factorization computed by nag\_dtzrf (f08bhc).

### 2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_dormrz (Nag_OrderType order, Nag_SideType side,
                Nag_TransType trans, Integer m, Integer n, Integer k, Integer l,
                const double a[], Integer pda, const double tau[], double c[],
                Integer pdc, NagError *fail)
```

### 3 Description

nag\_dormrz (f08bkc) is intended to be used following a call to nag\_dtzrf (f08bhc), which performs an  $RZ$  factorization of a real upper trapezoidal matrix  $A$  and represents the orthogonal matrix  $Z$  as a product of elementary reflectors.

This function may be used to form one of the matrix products

$$ZC, \quad Z^T C, \quad CZ, \quad CZ^T,$$

overwriting the result on  $C$ , which may be any real rectangular  $m$  by  $n$  matrix.

### 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

### 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **side** – Nag\_SideType *Input*

*On entry:* indicates how  $Z$  or  $Z^T$  is to be applied to  $C$ .

**side** = Nag\_LeftSide

$Z$  or  $Z^T$  is applied to  $C$  from the left.

**side** = Nag\_RightSide

$Z$  or  $Z^T$  is applied to  $C$  from the right.

*Constraint:* **side** = Nag\_LeftSide or Nag\_RightSide.

- 3: **trans** – Nag\_TransType *Input*  
*On entry:* indicates whether  $Z$  or  $Z^T$  is to be applied to  $C$ .  
**trans** = Nag\_NoTrans  
 $Z$  is applied to  $C$ .  
**trans** = Nag\_Trans  
 $Z^T$  is applied to  $C$ .  
*Constraint:* **trans** = Nag\_NoTrans or Nag\_Trans.
- 4: **m** – Integer *Input*  
*On entry:*  $m$ , the number of rows of the matrix  $C$ .  
*Constraint:* **m**  $\geq$  0.
- 5: **n** – Integer *Input*  
*On entry:*  $n$ , the number of columns of the matrix  $C$ .  
*Constraint:* **n**  $\geq$  0.
- 6: **k** – Integer *Input*  
*On entry:*  $k$ , the number of elementary reflectors whose product defines the matrix  $Z$ .  
*Constraints:*  
if **side** = Nag\_LeftSide, **m**  $\geq$  **k**  $\geq$  0;  
if **side** = Nag\_RightSide, **n**  $\geq$  **k**  $\geq$  0.
- 7: **l** – Integer *Input*  
*On entry:*  $l$ , the number of columns of the matrix  $A$  containing the meaningful part of the Householder reflectors.  
*Constraints:*  
if **side** = Nag\_LeftSide, **m**  $\geq$  **l**  $\geq$  0;  
if **side** = Nag\_RightSide, **n**  $\geq$  **l**  $\geq$  0.
- 8: **a**[*dim*] – const double *Input*  
**Note:** the dimension, *dim*, of the array **a** must be at least  
 $\max(1, \mathbf{pda} \times \mathbf{m})$  when **side** = Nag\_LeftSide and **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{k} \times \mathbf{pda})$  when **side** = Nag\_LeftSide and **order** = Nag\_RowMajor;  
 $\max(1, \mathbf{pda} \times \mathbf{n})$  when **side** = Nag\_RightSide and **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{k} \times \mathbf{pda})$  when **side** = Nag\_RightSide and **order** = Nag\_RowMajor.  
The ( $i, j$ )th element of the matrix  $A$  is stored in  
**a**[( $j - 1$ )  $\times$  **pda** +  $i - 1$ ] when **order** = Nag\_ColMajor;  
**a**[( $i - 1$ )  $\times$  **pda** +  $j - 1$ ] when **order** = Nag\_RowMajor.  
*On entry:* the  $i$ th row of **a** must contain the vector which defines the elementary reflector  $H_i$ , for  $i = 1, 2, \dots, k$ , as returned by nag\_dtzrzf (f08bkc).
- 9: **pda** – Integer *Input*  
*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **a**.

*Constraints:*

if **order** = Nag\_ColMajor, **pda**  $\geq$  max(1, **k**);  
 if **order** = Nag\_RowMajor,  
     if **side** = Nag\_LeftSide, **pda**  $\geq$  max(1, **m**);  
     if **side** = Nag\_RightSide, **pda**  $\geq$  max(1, **n**)..

10: **tau**[*dim*] – const double *Input*

**Note:** the dimension, *dim*, of the array **tau** must be at least max(1, **k**).

*On entry:* **tau**[*i* – 1] must contain the scalar factor of the elementary reflector  $H_i$ , as returned by nag\_dtzrzf (f08bhc).

11: **c**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **c** must be at least

max(1, **pd**c  $\times$  **n**) when **order** = Nag\_ColMajor;  
 max(1, **m**  $\times$  **pd**c) when **order** = Nag\_RowMajor.

The (*i*, *j*)th element of the matrix *C* is stored in

**c**[(*j* – 1)  $\times$  **pd**c + *i* – 1] when **order** = Nag\_ColMajor;  
**c**[(*i* – 1)  $\times$  **pd**c + *j* – 1] when **order** = Nag\_RowMajor.

*On entry:* the *m* by *n* matrix *C*.

*On exit:* **c** is overwritten by *ZC* or  $Z^T C$  or *CZ* or  $Z^T C$  as specified by **side** and **trans**.

12: **pd**c – Integer *Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **c**.

*Constraints:*

if **order** = Nag\_ColMajor, **pd**c  $\geq$  max(1, **m**);  
 if **order** = Nag\_RowMajor, **pd**c  $\geq$  max(1, **n**).

13: **fail** – NagError \* *Input/Output*

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in How to Use the NAG Library and its Documentation for further information.

### NE\_BAD\_PARAM

On entry, argument *value* had an illegal value.

### NE\_ENUM\_INT\_3

On entry, **side** = *value*, **m** = *value*, **n** = *value* and **k** = *value*.

Constraint: if **side** = Nag\_LeftSide, **m**  $\geq$  **k**  $\geq$  0;

if **side** = Nag\_RightSide, **n**  $\geq$  **k**  $\geq$  0.

On entry, **side** =  $\langle value \rangle$ , **m** =  $\langle value \rangle$ , **n** =  $\langle value \rangle$  and **l** =  $\langle value \rangle$ .

Constraint: if **side** = Nag\_LeftSide,  $\mathbf{m} \geq \mathbf{l} \geq 0$ ;

if **side** = Nag\_RightSide,  $\mathbf{n} \geq \mathbf{l} \geq 0$ .

On entry, **side** =  $\langle value \rangle$ , **pda** =  $\langle value \rangle$ , **m** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .

Constraint: if **side** = Nag\_LeftSide,  $\mathbf{pda} \geq \max(1, \mathbf{m})$ ;

if **side** = Nag\_RightSide,  $\mathbf{pda} \geq \max(1, \mathbf{n})$ .

## NE\_INT

On entry, **m** =  $\langle value \rangle$ .

Constraint:  $\mathbf{m} \geq 0$ .

On entry, **n** =  $\langle value \rangle$ .

Constraint:  $\mathbf{n} \geq 0$ .

On entry, **pda** =  $\langle value \rangle$ .

Constraint:  $\mathbf{pda} > 0$ .

On entry, **pdv** =  $\langle value \rangle$ .

Constraint:  $\mathbf{pdv} > 0$ .

## NE\_INT\_2

On entry, **pda** =  $\langle value \rangle$  and **k** =  $\langle value \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{k})$ .

On entry, **pdv** =  $\langle value \rangle$  and **m** =  $\langle value \rangle$ .

Constraint:  $\mathbf{pdv} \geq \max(1, \mathbf{m})$ .

On entry, **pdv** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .

Constraint:  $\mathbf{pdv} \geq \max(1, \mathbf{n})$ .

## NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in How to Use the NAG Library and its Documentation for further information.

## NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in How to Use the NAG Library and its Documentation for further information.

## 7 Accuracy

The computed result differs from the exact result by a matrix  $E$  such that

$$\|E\|_2 = O\epsilon\|C\|_2$$

where  $\epsilon$  is the *machine precision*.

## 8 Parallelism and Performance

nag\_dormrz (f08bkc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## **9 Further Comments**

The total number of floating-point operations is approximately  $4nlk$  if **side** = Nag\_LeftSide and  $4mlk$  if **side** = Nag\_RightSide.

The complex analogue of this function is nag\_zunmrz (f08bxc).

## **10 Example**

See Section 10 in nag\_dtzrzf (f08bhc).

---