

# NAG Library Function Document

## nag\_dgebal (f08nhc)

### 1 Purpose

nag\_dgebal (f08nhc) balances a real general matrix in order to improve the accuracy of computed eigenvalues and/or eigenvectors.

### 2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_dgebal (Nag_OrderType order, Nag_JobType job, Integer n, double a[],
                Integer pda, Integer *ilo, Integer *ihi, double scale[], NagError *fail)
```

### 3 Description

nag\_dgebal (f08nhc) balances a real general matrix  $A$ . The term ‘balancing’ covers two steps, each of which involves a similarity transformation of  $A$ . The function can perform either or both of these steps.

1. The function first attempts to permute  $A$  to block upper triangular form by a similarity transformation:

$$PAP^T = A' = \begin{pmatrix} A'_{11} & A'_{12} & A'_{13} \\ 0 & A'_{22} & A'_{23} \\ 0 & 0 & A'_{33} \end{pmatrix}$$

where  $P$  is a permutation matrix, and  $A'_{11}$  and  $A'_{33}$  are upper triangular. Then the diagonal elements of  $A'_{11}$  and  $A'_{33}$  are eigenvalues of  $A$ . The rest of the eigenvalues of  $A$  are the eigenvalues of the central diagonal block  $A'_{22}$ , in rows and columns  $i_{lo}$  to  $i_{hi}$ . Subsequent operations to compute the eigenvalues of  $A$  (or its Schur factorization) need only be applied to these rows and columns; this can save a significant amount of work if  $i_{lo} > 1$  and  $i_{hi} < n$ . If no suitable permutation exists (as is often the case), the function sets  $i_{lo} = 1$  and  $i_{hi} = n$ , and  $A'_{22}$  is the whole of  $A$ .

2. The function applies a diagonal similarity transformation to  $A'$ , to make the rows and columns of  $A'_{22}$  as close in norm as possible:

$$A'' = DA'D^{-1} = \begin{pmatrix} I & 0 & 0 \\ 0 & D_{22} & 0 \\ 0 & 0 & I \end{pmatrix} \begin{pmatrix} A'_{11} & A'_{12} & A'_{13} \\ 0 & A'_{22} & A'_{23} \\ 0 & 0 & A'_{33} \end{pmatrix} \begin{pmatrix} I & 0 & 0 \\ 0 & D_{22}^{-1} & 0 \\ 0 & 0 & I \end{pmatrix}.$$

This scaling can reduce the norm of the matrix (i.e.,  $\|A''_{22}\| < \|A'_{22}\|$ ) and hence reduce the effect of rounding errors on the accuracy of computed eigenvalues and eigenvectors.

### 4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

### 5 Arguments

- 1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by

**order** = Nag\_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **job** – Nag\_JobType *Input*

*On entry:* indicates whether  $A$  is to be permuted and/or scaled (or neither).

**job** = Nag\_DoNothing

$A$  is neither permuted nor scaled (but values are assigned to **ilo**, **ihi** and **scale**).

**job** = Nag\_Permute

$A$  is permuted but not scaled.

**job** = Nag\_Scale

$A$  is scaled but not permuted.

**job** = Nag\_DoBoth

$A$  is both permuted and scaled.

*Constraint:* **job** = Nag\_DoNothing, Nag\_Permute, Nag\_Scale or Nag\_DoBoth.

3: **n** – Integer *Input*

*On entry:*  $n$ , the order of the matrix  $A$ .

*Constraint:*  $n \geq 0$ .

4: **a**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **a** must be at least  $\max(1, \mathbf{pda} \times \mathbf{n})$ .

Where  $\mathbf{A}(i, j)$  appears in this document, it refers to the array element

$\mathbf{a}[(j-1) \times \mathbf{pda} + i - 1]$  when **order** = Nag\_ColMajor;

$\mathbf{a}[(i-1) \times \mathbf{pda} + j - 1]$  when **order** = Nag\_RowMajor.

*On entry:* the  $n$  by  $n$  matrix  $A$ .

*On exit:* **a** is overwritten by the balanced matrix. If **job** = Nag\_DoNothing, **a** is not referenced.

5: **pda** – Integer *Input*

*On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **a**.

*Constraint:*  $\mathbf{pda} \geq \max(1, \mathbf{n})$ .

6: **ilo** – Integer \* *Output*

7: **ihi** – Integer \* *Output*

*On exit:* the values  $i_{lo}$  and  $i_{hi}$  such that on exit  $\mathbf{A}(i, j)$  is zero if  $i > j$  and  $1 \leq j < i_{lo}$  or  $i_{hi} < i \leq n$ .

If **job** = Nag\_DoNothing or Nag\_Scale,  $i_{lo} = 1$  and  $i_{hi} = n$ .

8: **scale**[**n**] – double *Output*

*On exit:* details of the permutations and scaling factors applied to  $A$ . More precisely, if  $p_j$  is the index of the row and column interchanged with row and column  $j$  and  $d_j$  is the scaling factor used to balance row and column  $j$  then

$$\mathbf{scale}[j-1] = \begin{cases} p_j, & j = 1, 2, \dots, i_{lo} - 1 \\ d_j, & j = i_{lo}, i_{lo} + 1, \dots, i_{hi} \\ p_j, & j = i_{hi} + 1, i_{hi} + 2, \dots, n. \end{cases} \quad \text{and}$$

The order in which the interchanges are made is  $n$  to  $i_{hi} + 1$  then 1 to  $i_{lo} - 1$ .

9: **fail** – NagError \*

*Input/Output*

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in How to Use the NAG Library and its Documentation for further information.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_INT

On entry,  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{n} \geq 0$ .

On entry,  $\mathbf{pda} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} > 0$ .

### NE\_INT\_2

On entry,  $\mathbf{pda} = \langle value \rangle$  and  $\mathbf{n} = \langle value \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{n})$ .

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 3.6.6 in How to Use the NAG Library and its Documentation for further information.

### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 3.6.5 in How to Use the NAG Library and its Documentation for further information.

## 7 Accuracy

The errors are negligible.

## 8 Parallelism and Performance

nag\_dgebal (f08nhc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

If the matrix  $A$  is balanced by nag\_dgebal (f08nhc), then any eigenvectors computed subsequently are eigenvectors of the matrix  $A''$  (see Section 3) and hence nag\_dgebak (f08njc) **must** then be called to transform them back to eigenvectors of  $A$ .

If the Schur vectors of  $A$  are required, then this function must **not** be called with `job = Nag_Scale` or `Nag_DoBoth`, because then the balancing transformation is not orthogonal. If this function is called with `job = Nag_Permute`, then any Schur vectors computed subsequently are Schur vectors of the matrix  $A''$ , and `nag_dgebak` (f08njc) **must** be called (with `side = Nag_RightSide`) to transform them back to Schur vectors of  $A$ .

The total number of floating-point operations is approximately proportional to  $n^2$ .

The complex analogue of this function is `nag_zgebal` (f08nvc).

## 10 Example

This example computes all the eigenvalues and right eigenvectors of the matrix  $A$ , where

$$A = \begin{pmatrix} 5.14 & 0.91 & 0.00 & -32.80 \\ 0.91 & 0.20 & 0.00 & 34.50 \\ 1.90 & 0.80 & -0.40 & -3.00 \\ -0.33 & 0.35 & 0.00 & 0.66 \end{pmatrix}.$$

The program first calls `nag_dgebal` (f08nhc) to balance the matrix; it then computes the Schur factorization of the balanced matrix, by reduction to Hessenberg form and the  $QR$  algorithm. Then it calls `nag_dtrevc` (f08qkc) to compute the right eigenvectors of the balanced matrix, and finally calls `nag_dgebak` (f08njc) to transform the eigenvectors back to eigenvectors of the original matrix  $A$ .

### 10.1 Program Text

```

/* nag_dgebal (f08nhc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer firstnz, i, ihi, ilo, j, m, n, pda, pdh, pdvr;
    Integer scale_len, tau_len, wi_len, wr_len;
    Integer exit_status = 0;
    NagError fail;
    Nag_OrderType order;
    /* Arrays */
    double *a = 0, *h = 0, *scale = 0, *tau = 0, *v1 = 0, *vr = 0;
    double *wi = 0, *wr = 0;
    Nag_Boolean *select = 0;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J)  a[(J-1)*pda + I - 1]
#define H(I, J)  h[(J-1)*pdh + I - 1]
#define VR(I, J) vr[(J-1)*pdvr + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J)  a[(I-1)*pda + J - 1]
#define H(I, J)  h[(I-1)*pdh + J - 1]
#define VR(I, J) vr[(I-1)*pdvr + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

```

```

printf("nag_dgebal (f08nhc) Example Program Results\n\n");

/* Skip heading in data file */
#ifdef _WIN32
scanf_s("%*[\n] ");
#else
scanf("%*[\n] ");
#endif
#ifdef _WIN32
scanf_s("%" NAG_IFMT "%*[\n] ", &n);
#else
scanf("%" NAG_IFMT "%*[\n] ", &n);
#endif

pda = n;
pdh = n;
pdvr = n;
scale_len = n;
tau_len = n;
wi_len = n;
wr_len = n;

/* Allocate memory */
if (!(a = NAG_ALLOC(n * n, double)) ||
    !(h = NAG_ALLOC(n * n, double)) ||
    !(scale = NAG_ALLOC(scale_len, double)) ||
    !(tau = NAG_ALLOC(tau_len, double)) ||
    !(vl = NAG_ALLOC(1 * 1, double)) ||
    !(vr = NAG_ALLOC(n * n, double)) ||
    !(wi = NAG_ALLOC(wi_len, double)) ||
    !(wr = NAG_ALLOC(wr_len, double)) ||
    !(select = NAG_ALLOC(1, Nag_Boolean)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read A from data file */
for (i = 1; i <= n; ++i) {
    for (j = 1; j <= n; ++j)
#ifdef _WIN32
        scanf_s("%lf", &A(i, j));
#else
        scanf("%lf", &A(i, j));
#endif
}
#ifdef _WIN32
scanf_s("%*[\n] ");
#else
scanf("%*[\n] ");
#endif

/* Balance A */
/* nag_dgebal (f08nhc).
 * Balance real general matrix
 */
nag_dgebal(order, Nag_DoBoth, n, a, pda, &ilo, &ihi, scale, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_dgebal (f08nhc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Reduce A to upper Hessenberg form H = (Q^T)*A*Q */
/* nag_dgehrd (f08nec).
 * Orthogonal reduction of real general matrix to upper
 * Hessenberg form
 */
nag_dgehrd(order, n, ilo, ihi, a, pda, tau, &fail);

```

```

if (fail.code != NE_NOERROR) {
    printf("Error from nag_dgehrd (f08nec).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Copy A to H and VR */
for (i = 1; i <= n; ++i) {
    for (j = 1; j <= n; ++j) {
        H(i, j) = A(i, j);
        VR(i, j) = A(i, j);
    }
}

/* Form Q explicitly, storing the result in VR */
/* nag_dorghr (f08nfc).
 * Generate orthogonal transformation matrix from reduction
 * to Hessenberg form determined by nag_dgehrd (f08nec)
 */
nag_dorghr(order, n, 1, n, vr, pdvr, tau, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_dorghr (f08nfc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Calculate the eigenvalues and Schur factorization of A */
/* nag_dhseqr (f08pec).
 * Eigenvalues and Schur factorization of real upper
 * Hessenberg matrix reduced from real general matrix
 */
nag_dhseqr(order, Nag_Schur, Nag_UpdateZ, n, ilo, ihi, h, pdh,
           wr, wi, vr, pdvr, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_dhseqr (f08pec).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
printf(" Eigenvalues\n");
for (i = 1; i <= n; ++i)
    printf("(%.4f,%.4f)\n", wr[i - 1], wi[i - 1]);
/* Calculate the eigenvectors of A, storing the result in VR */
/* nag_dtrevc (f08qkc).
 * Left and right eigenvectors of real upper
 * quasi-triangular matrix
 */
nag_dtrevc(order, Nag_RightSide, Nag_BackTransform, select, n,
           h, pdh, vl, 1, vr, pdvr, n, &m, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_dtrevc (f08qkc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
/* nag_dgebak (f08njc).
 * Transform eigenvectors of real balanced matrix to those
 * of original matrix supplied to nag_dgebal (f08nhc)
 */
nag_dgebak(order, Nag_DoBoth, Nag_RightSide, n, ilo, ihi, scale,
           m, vr, pdvr, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_dgebak (f08njc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Normalize the left eigenvectors */
for (j = 1; j <= n; j++) {
    firstnz = n;
    for (i = n; i >= 1; i--) {
        if (VR(i, j) != 0) {
            firstnz = i;
        }
    }
}

```

```

    }
  }
  for (i = n; i >= 1; i--) {
    VR(i, j) = VR(i, j) / VR(firstnz, j);
  }
}

/* Print eigenvectors */
printf("\n");
/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
fflush(stdout);
nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n, m, vr,
                       pdvr, "Contents of array VR", 0, &fail);
if (fail.code != NE_NOERROR) {
  printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n", fail.message);
  exit_status = 1;
  goto END;
}
}
END:
  NAG_FREE(a);
  NAG_FREE(h);
  NAG_FREE(scale);
  NAG_FREE(tau);
  NAG_FREE(v1);
  NAG_FREE(vr);
  NAG_FREE(wi);
  NAG_FREE(wr);
  NAG_FREE(select);

  return exit_status;
}

```

## 10.2 Program Data

```

nag_dgebal (f08nhc) Example Program Data
  4                               :Value of N
  5.14  0.91  0.00 -32.80
  0.91  0.20  0.00  34.50
  1.90  0.80 -0.40 -3.00
-0.33  0.35  0.00  0.66   :End of matrix A

```

## 10.3 Program Results

```

nag_dgebal (f08nhc) Example Program Results

```

```

Eigenvalues
( -0.4000,  0.0000)
( -4.0208,  0.0000)
(  3.0136,  0.0000)
(  7.0072,  0.0000)

```

```

Contents of array VR

```

	1	2	3	4
1	0.0000	1.0000	1.0000	1.0000
2	0.0000	-2.0366	1.6950	-0.1802
3	1.0000	0.1098	0.8555	0.2621
4	0.0000	0.2228	0.1119	-0.0619

---