

## NAG Library Function Document

### nag\_mills\_ratio (g01mbc)

## 1 Purpose

nag\_mills\_ratio (g01mbc) returns the reciprocal of Mills' Ratio.

## 2 Specification

```
#include <nag.h>
#include <nagg01.h>
double nag_mills_ratio (double x)
```

## 3 Description

nag\_mills\_ratio (g01mbc) calculates the reciprocal of Mills' Ratio, the hazard rate,  $\lambda(x)$ , for the standard Normal distribution. It is defined as the ratio of the ordinate to the upper tail area of the standard Normal distribution, that is,

$$\lambda(x) = \frac{Z(x)}{Q(x)} = \frac{\frac{1}{\sqrt{2\pi}}e^{-(x^2/2)}}{\frac{1}{\sqrt{2\pi}} \int_x^\infty e^{-(t^2/2)} dt}.$$

The calculation is based on a Chebyshev expansion as described in nag\_erfcx (s15agc).

## 4 References

Gross A J and Clark V A (1975) *Survival Distributions: Reliability Applications in the Biomedical Sciences* Wiley

## 5 Arguments

1: <b>x</b> – double	<i>Input</i>
----------------------	--------------

*On entry:*  $x$ , the argument of the reciprocal of Mills' Ratio.

## 6 Error Indicators and Warnings

None.

## 7 Accuracy

In the left-hand tail,  $x < 0.0$ , if  $\frac{1}{2}e^{-(1/2)x^2} \leq$  the safe range argument (nag\_real\_safe\_small\_number (X02AMC)), then 0.0 is returned, which is close to the true value.

The relative accuracy is bounded by the effective **machine precision**. See nag\_erfcx (s15agc) for further discussion.

## 8 Parallelism and Performance

nag\_mills\_ratio (g01mbc) is not threaded in any implementation.

## 9 Further Comments

If, before entry,  $x$  is not a standard Normal variable, it has to be standardized, and on exit, nag\_mills\_ratio (g01mbc) has to be divided by the standard deviation. That is, if the Normal distribution has mean  $\mu$  and variance  $\sigma^2$ , then its hazard rate,  $\lambda(x; \mu, \sigma^2)$ , is given by

$$\lambda(x; \mu, \sigma^2) = \lambda((x - \mu)/\sigma)/\sigma.$$

## 10 Example

The hazard rate is evaluated at different values of  $x$  for Normal distributions with different means and variances. The results are then printed.

### 10.1 Program Text

```
/* nag_mills_ratio (g01mbc) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdl�.h>
#include <nagg01.h>

int main(void)
{
    /* Scalars */
    Integer exit_status = 0;
    double rm, x, xm, xsig, z;
    Integer i;

    printf("nag_mills_ratio (g01mbc) Example Program Results\n");

    /* Skip heading in data file */
#ifndef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif

    printf("\n%2sMean%5sSigma%4sX%8sReciprocal", "", "", "", "");
    printf("                                Mills Ratio\n\n");
    for (i = 1; i <= 3; ++i) {
#ifndef _WIN32
        scanf_s("%lf%lf%lf%*[^\n] ", &x, &xm, &xsig);
#else
        scanf("%lf%lf%lf%*[^\n] ", &x, &xm, &xsig);
#endif
        z = (x - xm) / xsig;
        /* nag_mills_ratio (g01mbc).
         * Computes reciprocal of Mills' Ratio
         */
        rm = nag_mills_ratio(z) / xsig;
        printf("%7.4f%2s%7.4f%2s%7.4f%2s%7.4f", xm, "", xsig, "", x, "", rm);
        printf("\n");
    }

    return exit_status;
}
```

## 10.2 Program Data

```
nag_mills_ratio (g01mbc) Example Program Data
0.0 0.0 1.0
-2.0 1.0 2.5
10.3 9.0 1.6
```

## 10.3 Program Results

```
nag_mills_ratio (g01mbc) Example Program Results
```

Mean	Sigma	X	Reciprocal Mills Ratio
0.0000	1.0000	0.0000	0.7979
1.0000	2.5000	-2.0000	0.0878
9.0000	1.6000	10.3000	0.8607

---