

NAG Library Function Document

nag_implementation_separated_details (a00adc)

1 Purpose

nag_implementation_separated_details (a00adc) provides information about the version of the NAG C Library in use.

2 Specification

```
#include <nag.h>
#include <naga00.h>

void nag_implementation_separated_details (char *impl, char *prec,
    char *pcode, char *mkmaj, char *mkmin, char *hardware, char *opsys,
    char *ccomp, char *fcomp, char *vend, Nag_Boolean *licval)
```

3 Description

The NAG C Library is available for use on a number of different computer systems. For each distinct system an implementation of the library is prepared and this implementation is given a unique code. The specifics that define the implementation are: the working precision, the major and minor marks of the NAG C Library, the target hardware and operating system, the compiler used, and the vendor library (if any) that is also required to be linked. nag_implementation_separated_details (a00adc) may be called to return, in separate arguments, these specific details of the NAG C Library implementation that is being used; it also returns whether a valid licence has been found for this implementation. This differs from nag_implementation_details (a00aac) which simply outputs the collected information in a readable form directly to the stdout (standard output) stream.

4 References

None.

5 Arguments

- | | | |
|----|--|---------------|
| 1: | impl – char * | <i>Output</i> |
| | <i>On exit:</i> the implementation title which usually lists the target platform, operating system and compiler. | |
| 2: | prec – char * | <i>Output</i> |
| | <i>On exit:</i> the working or basic precision of the implementation. Some functions may perform operations in reduced precision or additional precision, but the great majority will perform all operations in basic precision. | |
| 3: | pcode – char * | <i>Output</i> |
| | <i>On exit:</i> the product code for the NAG C Library implementation that is being used. The code has a discernible structure, but it is not necessary to know the details of this structure. The product code can be used to differentiate between individual product licence codes. | |
| 4: | mkmaj – char * | <i>Output</i> |
| | <i>On exit:</i> the major mark of the NAG C Library implementation that is being used. | |

- 5: **mkmin** – char * *Output*
On exit: the minor mark of the NAG C Library implementation that is being used.
- 6: **hdware** – char * *Output*
On exit: the target hardware for the NAG C Library implementation that is being used.
- 7: **opsys** – char * *Output*
On exit: the target operating system for the NAG C Library implementation that is being used.
- 8: **ccomp** – char * *Output*
On exit: the C compiler used to build the NAG C Library implementation that is being used.
- 9: **fcomp** – char * *Output*
On exit: the Fortran compiler used to build the NAG C Library implementation that is being used.
- 10: **vend** – char * *Output*
On exit: the subsidiary library, if any, that must be linked with the NAG C Library implementation that is being used. If the implementation does not require a subsidiary library then the string
 '(self-contained)'
 will be returned in **vend**.
- 11: **licval** – Nag_Boolean * *Output*
On exit: specifies whether or not a valid licence has been found for the NAG C Library implementation that is being used.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Parallelism and Performance

Not applicable.

9 Further Comments

None.

10 Example

This example makes a call of `nag_implementation_separated_details` (a00adc), collects information on the NAG C Library implementation that is being used and prints it out in a form that is similar to the output obtained by a call to `nag_implementation_details` (a00aac).

10.1 Program Text

```

/* nag_implementation_separated_details (a00adc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <nag.h>
#include <stdio.h>
#include <string.h>
#include <time.h>
#include <nag_stdlib.h>
#include <naga00.h>

int main(void)
{
    int exit_status = 0;
    int max_char_len = 180;
    char *impl = 0, *prec = 0, *pcode = 0, *mkmaj = 0, *mkmin = 0,
          *hardware = 0, *opsys = 0, *ccomp = 0, *fcomp = 0, *vend = 0;
    Nag_Boolean licval;
    time_t t;

    printf("nag_implementation_separated_details (a00adc)"
           " Example Program Results\n\n");

    if (!(impl = NAG_ALLOC(max_char_len, char)) ||
        !(prec = NAG_ALLOC(max_char_len, char)) ||
        !(pcode = NAG_ALLOC(max_char_len, char)) ||
        !(mkmaj = NAG_ALLOC(max_char_len, char)) ||
        !(mkmin = NAG_ALLOC(max_char_len, char)) ||
        !(hardware = NAG_ALLOC(max_char_len, char)) ||
        !(opsys = NAG_ALLOC(max_char_len, char)) ||
        !(ccomp = NAG_ALLOC(max_char_len, char)) ||
        !(fcomp = NAG_ALLOC(max_char_len, char)) ||
        !(vend = NAG_ALLOC(max_char_len, char)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    nag_implementation_separated_details(impl, prec, pcode, mkmaj, mkmin,
                                         hardware, opsys, ccomp, fcomp, vend,
                                         &licval);

    /* Print implementation details. */
    printf("*** Start of NAG C library implementation details ***\n\n");
    printf(" Implementation title: %s\n", impl);
    printf("           Precision: %s\n", prec);
    printf("           Product Code: %s\n", pcode);
    printf("           Mark: %s.%s\n", mkmaj, mkmin);
    if (!strcmp(vend, "(self-contained)")) {
        printf("           Vendor library: None\n");
    }
    else {
        printf("           Vendor library: %s\n", vend);
    }
    printf(" Applicable to:\n");
    printf("           hardware: %s\n", hardware);
    printf("           operating system: %s\n", opsys);
    printf("           C compiler: %s\n", ccomp);
    printf("           Fortran compiler: %s\n", fcomp);
    printf(" and compatible systems.\n");
    if (!licval) {
        printf("           Licence query: %s\n\n", "Unsuccessful");
    }
}

```

```

else {
    printf("        Licence query: %s\n\n", "Successful");
}
printf(" *** End of NAG C Library implementation details ***\n");

printf("\n This program was run on the following date:\n");
t = time(NULL);
printf("    %s", ctime(&t));

END:

NAG_FREE(impl);
NAG_FREE(prec);
NAG_FREE(pcode);
NAG_FREE(mkmaj);
NAG_FREE(mkmin);
NAG_FREE(hardware);
NAG_FREE(opsys);
NAG_FREE(ccomp);
NAG_FREE(fcomp);
NAG_FREE(vend);

return exit_status;
}

```

10.2 Program Data

None.

10.3 Program Results

nag_implementation_separated_details (a00adc) Example Program Results

```

*** Start of NAG C library implementation details ***

Implementation title: ?OS?, ?x?-bit, ?C compiler? (?y?-bit integers)
    Precision: double
    Product Code: ?CL?
    Mark: ?z?
    Vendor library: ?vendlib?
Applicable to:
    hardware: ?hardware?
    operating system: ?OS long?
    C compiler: ?C compiler long?
    Fortran compiler: ?Fortran compiler long?
and compatible systems.
    Licence query: Successful

*** End of NAG C Library implementation details ***

This program was run on the following date:
    Day MMM DD HH:MM:SS YYYY

```
