

NAG Library Function Document

nag_matop_real_gen_matrix_sqrt (f01enc)

1 Purpose

nag_matop_real_gen_matrix_sqrt (f01enc) computes the principal matrix square root, $A^{1/2}$, of a real n by n matrix A .

2 Specification

```
#include <nag.h>
#include <nagf01.h>
void nag_matop_real_gen_matrix_sqrt (Integer n, double a[], Integer pda,
NagError *fail)
```

3 Description

A square root of a matrix A is a solution X to the equation $X^2 = A$. A nonsingular matrix has multiple square roots. For a matrix with no eigenvalues on the closed negative real line, the principal square root, denoted by $A^{1/2}$, is the unique square root whose eigenvalues lie in the open right half-plane.

$A^{1/2}$ is computed using the algorithm described in Higham (1987). This is a real arithmetic version of the algorithm of Björck and Hammarling (1983). In addition a blocking scheme described in Deadman *et al.* (2013) is used.

4 References

Björck D and Hammarling S (1983) A Schur method for the square root of a matrix *Linear Algebra Appl.* **52/53** 127–140

Deadman E, Higham N J and Ralha R (2013) Blocked Schur Algorithms for Computing the Matrix Square Root *Applied Parallel and Scientific Computing: 11th International Conference, (PARA 2012, Helsinki, Finland)* P. Manninen and P. Úster, Eds *Lecture Notes in Computer Science* **7782** 171–181 Springer–Verlag

Higham N J (1987) Computing real square roots of a real matrix *Linear Algebra Appl.* **88/89** 405–430

Higham N J (2008) *Functions of Matrices: Theory and Computation* SIAM, Philadelphia, PA, USA

5 Arguments

1: **n** – Integer *Input*

On entry: n , the order of the matrix A .

Constraint: $\mathbf{n} \geq 0$.

2: **a[dim]** – double *Input/Output*

Note: the dimension, dim , of the array **a** must be at least **pda** × **n**.

The (i, j) th element of the matrix A is stored in **a**[($j - 1$) × **pda** + $i - 1$].

On entry: the n by n matrix A .

On exit: contains, if **fail.code** = NE_NOERROR, the n by n principal matrix square root, $A^{1/2}$. Alternatively, if **fail.code** = NE_EIGENVALUES, contains an n by n non-principal square root of A .

3: pda – Integer	<i>Input</i>
On entry: the stride separating matrix row elements in the array a .	
Constraint: pda $\geq n$.	
4: fail – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).	

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_EIGENVALUES

A has a semisimple vanishing eigenvalue. A non-principal square root is returned.

NE_INT

On entry, $n = \langle value \rangle$.

Constraint: $n \geq 0$.

NE_INT_2

On entry, $\mathbf{pda} = \langle value \rangle$ and $n = \langle value \rangle$.

Constraint: $\mathbf{pda} \geq n$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NEGATIVE_EIGVAL

A has a negative real eigenvalue. The principal square root is not defined. nag_matop_complex_gen_matrix_sqrt (f01fnc) can be used to return a complex, non-principal square root.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

NE_SINGULAR

A has a defective vanishing eigenvalue. The square root cannot be found in this case.

7 Accuracy

The computed square root \hat{X} satisfies $\hat{X}^2 = A + \Delta A$, where $\|\Delta A\|_F \approx O(\epsilon)n^3\|\hat{X}\|_F^2$, where ϵ is machine precision.

For further discussion of the condition of the matrix square root see Section 6.1 of Higham (2008).

8 Parallelism and Performance

`nag_matop_real_gen_matrix_sqrt` (f01enc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

`nag_matop_real_gen_matrix_sqrt` (f01enc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The cost of the algorithm is $85n^3/3$ floating-point operations; see Algorithm 6.7 of Higham (2008). $O(2 \times n^2)$ of real allocatable memory is required by the function.

If condition number and residual bound estimates are required, then `nag_matop_real_gen_matrix_cond_sqrt` (f01jdc) should be used.

10 Example

This example finds the principal matrix square root of the matrix

$$A = \begin{pmatrix} 507 & 622 & 300 & -202 \\ 237 & 352 & 126 & -60 \\ 751 & 950 & 440 & -286 \\ -286 & -326 & -192 & 150 \end{pmatrix}.$$

10.1 Program Text

```
/* nag_matop_real_gen_matrix_sqrt (f01enc) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf01.h>
#include <nagx04.h>

#define A(I,J) a[J*pda + I]

int main(void)
{
    /* Scalars */
    Integer exit_status = 0;
    Integer i, j, n, pda;
    /* Arrays */
    double *a = 0;
    /* Nag Types */
    Nag_OrderType order = Nag_ColMajor;
    NagError fail;

    INIT_FAIL(fail);

    /* Output preamble */
    printf("nag_matop_real_gen_matrix_sqrt (f01enc) ");
}
```

```

printf("Example Program Results\n\n");
fflush(stdout);

/* Skip heading in data file */
#ifndef _WIN32
scanf_s("%*[^\n] ");
#else
scanf("%*[^\n] ");
#endif

/* Read in the problem size */
#ifndef _WIN32
scanf_s("%" NAG_IFMT "%*[^\n]", &n);
#else
scanf("%" NAG_IFMT "%*[^\n]", &n);
#endif

pda = n;
if (!(a = NAG_ALLOC(pda * n, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read in the matrix A from data file */
for (i = 0; i < n; i++) {
    for (j = 0; j < n; j++) {
#ifndef _WIN32
        scanf_s("%lf", &A(i, j));
#else
        scanf("%lf", &A(i, j));
#endif
    }
}
#ifndef _WIN32
scanf_s("%*[^\n] ");
#else
scanf("%*[^\n] ");
#endif

/* Find matrix square root using
 * nag_matop_real_gen_matrix_sqrt (f01enc)
 * Real matrix square root
 */
nag_matop_real_gen_matrix_sqrt(n, a, pda, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_matop_real_gen_matrix_sqrt (f01enc)\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

/* Print matrix sqrt(A) using
 * nag_gen_real_mat_print (x04cac)
 * Print real general matrix (easy-to-use)
 */
nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag,
                       n, n, a, pda, "sqrt(A)", NULL, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_gen_real_mat_print (x04cac)\n%s\n",
           fail.message);
    exit_status = 2;
    goto END;
}

END:
NAG_FREE(a);
return exit_status;
}

```

10.2 Program Data

```
nag_matop_real_gen_matrix_sqrt (f01enc) Example Program Data
4                               :Value of n
507.0      622.0      300.0      -202.0
237.0      352.0      126.0      -60.0
751.0      950.0      440.0      -286.0
-286.0     -326.0     -192.0     150.0  :End of matrix a
```

10.3 Program Results

```
nag_matop_real_gen_matrix_sqrt (f01enc) Example Program Results
sqrt(A)
      1           2           3           4
1  1.5000e+01  1.4000e+01  8.0000e+00 -6.0000e+00
2  6.0000e+00  1.4000e+01  3.0000e+00  9.6589e-15
3  2.1000e+01  2.4000e+01  1.2000e+01 -8.0000e+00
4 -5.0000e+00 -4.0000e+00 -7.0000e+00  8.0000e+00
```
