

NAG Library Function Document

nag_zungql (f08ctc)

1 Purpose

nag_zungql (f08ctc) generates all or part of the complex m by m unitary matrix Q from a QL factorization computed by nag_zgeqlf (f08csc).

2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_zungql (Nag_OrderType order, Integer m, Integer n, Integer k,
                 Complex a[], Integer pda, const Complex tau[], NagError *fail)
```

3 Description

nag_zungql (f08ctc) is intended to be used after a call to nag_zgeqlf (f08csc), which performs a QL factorization of a complex matrix A . The unitary matrix Q is represented as a product of elementary reflectors.

This function may be used to generate Q explicitly as a square matrix, or to form only its trailing columns.

Usually Q is determined from the QL factorization of an m by p matrix A with $m \geq p$. The whole of Q may be computed by:

```
nag_zungql(order, m, m, p, a, pda, tau, &fail)
```

(note that the array **a** must have at least m columns) or its trailing p columns by:

```
nag_zungql(order, m, p, p, a, pda, tau, &fail)
```

The columns of Q returned by the last call form an orthonormal basis for the space spanned by the columns of A ; thus nag_zgeqlf (f08csc) followed by nag_zungql (f08ctc) can be used to orthogonalize the columns of A .

The information returned by nag_zgeqlf (f08csc) also yields the QL factorization of the trailing k columns of A , where $k < p$. The unitary matrix arising from this factorization can be computed by:

```
nag_zungql(order, m, m, k, a, pda, tau, &fail)
```

or its trailing k columns by:

```
nag_zungql(order, m, k, k, a, pda, tau, &fail)
```

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by

order = Nag_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

- 2: **m** – Integer *Input*
On entry: m , the number of rows of the matrix Q .
Constraint: $m \geq 0$.
- 3: **n** – Integer *Input*
On entry: n , the number of columns of the matrix Q .
Constraint: $m \geq n \geq 0$.
- 4: **k** – Integer *Input*
On entry: k , the number of elementary reflectors whose product defines the matrix Q .
Constraint: $n \geq k \geq 0$.
- 5: **a**[*dim*] – Complex *Input/Output*
Note: the dimension, *dim*, of the array **a** must be at least
 $\max(1, \mathbf{pda} \times \mathbf{n})$ when **order** = Nag_ColMajor;
 $\max(1, \mathbf{m} \times \mathbf{pda})$ when **order** = Nag_RowMajor.
On entry: details of the vectors which define the elementary reflectors, as returned by nag_zgeqlf (f08csc).
On exit: the m by n matrix Q .
If **order** = Nag_ColMajor, the (i, j) th element of the matrix is stored in $\mathbf{a}[(j - 1) \times \mathbf{pda} + i - 1]$.
If **order** = Nag_RowMajor, the (i, j) th element of the matrix is stored in $\mathbf{a}[(i - 1) \times \mathbf{pda} + j - 1]$.
- 6: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) in the array **a**.
Constraints:
if **order** = Nag_ColMajor, $\mathbf{pda} \geq \max(1, \mathbf{m})$;
if **order** = Nag_RowMajor, $\mathbf{pda} \geq \max(1, \mathbf{n})$.
- 7: **tau**[*dim*] – const Complex *Input*
Note: the dimension, *dim*, of the array **tau** must be at least $\max(1, \mathbf{k})$.
On entry: further details of the elementary reflectors, as returned by nag_zgeqlf (f08csc).
- 8: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{m} = \langle value \rangle$.

Constraint: $\mathbf{m} \geq 0$.

On entry, $\mathbf{pda} = \langle value \rangle$.

Constraint: $\mathbf{pda} > 0$.

NE_INT_2

On entry, $\mathbf{m} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{m} \geq \mathbf{n} \geq 0$.

On entry, $\mathbf{n} = \langle value \rangle$ and $\mathbf{k} = \langle value \rangle$.

Constraint: $\mathbf{n} \geq \mathbf{k} \geq 0$.

On entry, $\mathbf{pda} = \langle value \rangle$ and $\mathbf{m} = \langle value \rangle$.

Constraint: $\mathbf{pda} \geq \max(1, \mathbf{m})$.

On entry, $\mathbf{pda} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{pda} \geq \max(1, \mathbf{n})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

The computed matrix Q differs from an exactly unitary matrix by a matrix E such that

$$\|E\|_2 = O(\epsilon),$$

where ϵ is the *machine precision*.

8 Parallelism and Performance

nag_zungql (f08ctc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of real floating-point operations is approximately $16mnk - 8(m+n)k^2 + \frac{16}{3}k^3$; when $n = k$, the number is approximately $\frac{8}{3}n^2(3m - n)$.

The real analogue of this function is nag_dorgql (f08cfc).

10 Example

This example generates the first four columns of the matrix Q of the QL factorization of A as returned by nag_zgeqlf (f08csc), where

$$A = \begin{pmatrix} 0.96 - 0.81i & -0.03 + 0.96i & -0.91 + 2.06i & -0.05 + 0.41i \\ -0.98 + 1.98i & -1.20 + 0.19i & -0.66 + 0.42i & -0.81 + 0.56i \\ 0.62 - 0.46i & 1.01 + 0.02i & 0.63 - 0.17i & -1.11 + 0.60i \\ -0.37 + 0.38i & 0.19 - 0.54i & -0.98 - 0.36i & 0.22 - 0.20i \\ 0.83 + 0.51i & 0.20 + 0.01i & -0.17 - 0.46i & 1.47 + 1.59i \\ 1.08 - 0.28i & 0.20 - 0.12i & -0.07 + 1.23i & 0.26 + 0.26i \end{pmatrix}.$$

10.1 Program Text

```

/* nag_zungql (f08ctc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer i, j, m, n, pda;
    Integer exit_status = 0;
    /* Arrays */
    char *title = 0;
    Complex *a = 0, *tau = 0;
    /* Nag Types */
    Nag_OrderType order;
    NagError fail;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J - 1) * pda + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I - 1) * pda + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_zungql (f08ctc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n]");
#else
    scanf("%*[\n]");
#endif
}

```

```

    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%*[\n]", &m, &n);
#else
    scanf("%" NAG_IFMT "%" NAG_IFMT "%*[\n]", &m, &n);
#endif

#ifdef NAG_COLUMN_MAJOR
    pda = m;
#else
    pda = n;
#endif

/* Allocate memory */
if (!(title = NAG_ALLOC(31, char)) ||
    !(a = NAG_ALLOC(m * n, Complex)) || !(tau = NAG_ALLOC(n, Complex)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read A from data file */
for (i = 1; i <= m; ++i)
    for (j = 1; j <= n; ++j)
#ifdef _WIN32
        scanf_s(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#else
        scanf(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#endif
#ifdef _WIN32
    scanf_s("%*[\n]");
#else
    scanf("%*[\n]");
#endif

/* nag_zgeqlf (f08csc).
 * Compute the QL factorization of A.
 */
nag_zgeqlf(order, m, n, a, pda, tau, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_zgeqlf (f08csc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* nag_zungql (f08ctc).
 * Form the leading n columns of Q explicitly.
 */
nag_zungql(order, m, n, n, a, pda, tau, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_zungql (f08ctc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

#ifdef _WIN32
    sprintf_s(title, 31, "The leading %4" NAG_IFMT " columns of Q", n);
#else
    sprintf(title, "The leading %4" NAG_IFMT " columns of Q", n);
#endif

/* nag_gen_complx_mat_print_comp (x04dbc).
 * Print the leading n columns of Q.
 */
fflush(stdout);
nag_gen_complx_mat_print_comp(order, Nag_GeneralMatrix, Nag_NonUnitDiag, m,
                              n, a, pda, Nag_BracketForm, "%7.4f", title,
                              Nag_IntegerLabels, 0, Nag_IntegerLabels, 0,
                              80, 0, 0, &fail);

if (fail.code != NE_NOERROR) {
    printf("Error from nag_gen_complx_mat_print_comp (x04dbc).\n%s\n",
          fail.message);
}

```

```

    exit_status = 1;
}

END:
  NAG_FREE(title);
  NAG_FREE(a);
  NAG_FREE(tau);

  return exit_status;
}

#undef A

```

10.2 Program Data

nag_zungql (f08ctc) Example Program Data

```

    6              4              :Values of M and N

( 0.96,-0.81) (-0.03, 0.96) (-0.91, 2.06) (-0.05, 0.41)
(-0.98, 1.98) (-1.20, 0.19) (-0.66, 0.42) (-0.81, 0.56)
( 0.62,-0.46) ( 1.01, 0.02) ( 0.63,-0.17) (-1.11, 0.60)
(-0.37, 0.38) ( 0.19,-0.54) (-0.98,-0.36) ( 0.22,-0.20)
( 0.83, 0.51) ( 0.20, 0.01) (-0.17,-0.46) ( 1.47, 1.59)
( 1.08,-0.28) ( 0.20,-0.12) (-0.07, 1.23) ( 0.26, 0.26) :End of matrix A

```

10.3 Program Results

nag_zungql (f08ctc) Example Program Results

```

The leading      4 columns of Q
                1          2          3          4
1 ( 0.2810, 0.5020) (-0.2051,-0.1092) ( 0.3083,-0.6874) ( 0.0181,-0.1483)
2 ( 0.2707,-0.3296) ( 0.5711, 0.0432) ( 0.2251,-0.1313) ( 0.2930,-0.2025)
3 (-0.2864,-0.0094) (-0.5416, 0.0454) (-0.2062, 0.0691) ( 0.4015,-0.2170)
4 ( 0.2262,-0.3854) (-0.3387, 0.2228) ( 0.3259, 0.1178) (-0.0796, 0.0723)
5 ( 0.0341,-0.0760) ( 0.0098,-0.0712) ( 0.0753, 0.1412) (-0.5317,-0.5751)
6 (-0.3936,-0.2083) (-0.1296, 0.3691) ( 0.0264,-0.4134) (-0.0940,-0.0940)

```
