

NAG Library Function Document

nag_sparse_sym_precon_ssor_solve (f11jdc)

1 Purpose

`nag_sparse_sym_precon_ssor_solve (f11jdc)` solves a system of linear equations involving the preconditioning matrix corresponding to SSOR applied to a real sparse symmetric matrix, represented in symmetric coordinate storage format.

2 Specification

```
#include <nag.h>
#include <nagf11.h>
void nag_sparse_sym_precon_ssor_solve (Integer n, Integer nnz,
    const double a[], const Integer irow[], const Integer icol[],
    const double rdiag[], double omega, Nag_SparseSym_CheckData check,
    const double y[], double x[], NagError *fail)
```

3 Description

`nag_sparse_sym_precon_ssor_solve (f11jdc)` solves a system of equations

$$Mx = y$$

involving the preconditioning matrix

$$M = \frac{1}{\omega(2-\omega)}(D + \omega L)D^{-1}(D + \omega L)^T$$

corresponding to symmetric successive-over-relaxation (SSOR) (see Young (1971)) on a linear system $Ax = b$, where A is a sparse symmetric matrix stored in symmetric coordinate storage (SCS) format (see Section 2.1.2 in the f11 Chapter Introduction).

In the definition of M given above D is the diagonal part of A , L is the strictly lower triangular part of A , and ω is a user-defined relaxation parameter.

It is envisaged that a common use of `nag_sparse_sym_precon_ssor_solve (f11jdc)` will be to carry out the preconditioning step required in the application of `nag_sparse_sym_basic_solver (f11gec)` to sparse linear systems. For an illustration of this use of `nag_sparse_sym_precon_ssor_solve (f11jdc)` see the example program given in Section 10.1. `nag_sparse_sym_precon_ssor_solve (f11jdc)` is also used for this purpose by the Black Box function `nag_sparse_sym_sol (f11jec)`.

4 References

Young D (1971) *Iterative Solution of Large Linear Systems* Academic Press, New York

5 Arguments

- | | | |
|----|---|--------------|
| 1: | n – Integer | <i>Input</i> |
| | <i>On entry:</i> n , the order of the matrix A . | |
| | <i>Constraint:</i> $n \geq 1$. | |
| 2: | nnz – Integer | <i>Input</i> |
| | <i>On entry:</i> the number of nonzero elements in the lower triangular part of A . | |
| | <i>Constraint:</i> $1 \leq \text{nnz} \leq n \times (n + 1)/2$. | |

3:	a[nnz] – const double	<i>Input</i>
<i>On entry:</i> the nonzero elements in the lower triangular part of the matrix A , ordered by increasing row index, and by increasing column index within each row. Multiple entries for the same row and column indices are not permitted. The function nag_sparse_sym_sort (f11zbc) may be used to order the elements in this way.		
4:	irow[nnz] – const Integer	<i>Input</i>
5:	icol[nnz] – const Integer	<i>Input</i>
<i>On entry:</i> the row and column indices of the nonzero elements supplied in array a .		
<i>Constraints:</i>		
irow and icol must satisfy these constraints (which may be imposed by a call to nag_sparse_sym_sort (f11zbc)):		
$1 \leq \text{irow}[i] \leq n$ and $1 \leq \text{icol}[i] \leq \text{irow}[i]$, for $i = 0, 1, \dots, nnz - 1$; $\text{irow}[i - 1] < \text{irow}[i]$ or $\text{irow}[i - 1] = \text{irow}[i]$ and $\text{icol}[i - 1] < \text{icol}[i]$, for $i = 1, 2, \dots, nnz - 1$.		
6:	rdiag[n] – const double	<i>Input</i>
<i>On entry:</i> the elements of the diagonal matrix D^{-1} , where D is the diagonal part of A .		
7:	omega – double	<i>Input</i>
<i>On entry:</i> the relaxation parameter ω .		
<i>Constraint:</i> $0.0 < \text{omega} < 2.0$.		
8:	check – Nag_SparseSym_CheckData	<i>Input</i>
<i>On entry:</i> specifies whether or not the input data should be checked.		
check = Nag_SparseSym_Check		
Checks are carried out on the values of n , nnz , irow , icol and omega .		
check = Nag_SparseSym_NoCheck		
None of these checks are carried out.		
See also Section 9.2.		
<i>Constraint:</i> check = Nag_SparseSym_Check or Nag_SparseSym_NoCheck.		
9:	y[n] – const double	<i>Input</i>
<i>On entry:</i> the right-hand side vector y .		
10:	x[n] – double	<i>Output</i>
<i>On exit:</i> the solution vector x .		
11:	fail – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).		

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{n} \geq 1$.

On entry, $\mathbf{nnz} = \langle value \rangle$.

Constraint: $\mathbf{nnz} \geq 1$.

NE_INT_2

On entry, $\mathbf{nnz} = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{nnz} \leq \mathbf{n} \times (\mathbf{n} + 1)/2$

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_INVALID_SCS

On entry, $I = \langle value \rangle$, $\mathbf{icol}[I - 1] = \langle value \rangle$ and $\mathbf{irow}[I - 1] = \langle value \rangle$.

Constraint: $\mathbf{icol}[I - 1] \geq 1$ and $\mathbf{icol}[I - 1] \leq \mathbf{irow}[I - 1]$.

On entry, $i = \langle value \rangle$, $\mathbf{irow}[i - 1] = \langle value \rangle$ and $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{irow}[i - 1] \geq 1$ and $\mathbf{irow}[i - 1] \leq \mathbf{n}$.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

NE_NOT_STRICTLY_INCREASING

On entry, $\mathbf{a}[i - 1]$ is out of order: $i = \langle value \rangle$.

On entry, the location $(\mathbf{irow}[I - 1], \mathbf{icol}[I - 1])$ is a duplicate: $I = \langle value \rangle$. Consider calling nag_sparse_sym_sort (f11zbc) to reorder and sum or remove duplicates.

NE_REAL

On entry, $\mathbf{omega} = \langle value \rangle$.

Constraint: $0.0 < \mathbf{omega} < 2.0$

NE_ZERO_DIAG_ELEM

The matrix A has no diagonal entry in row $\langle value \rangle$.

7 Accuracy

The computed solution x is the exact solution of a perturbed system of equations $(M + \delta M)x = y$, where

$$|\delta M| \leq c(n)\epsilon|D + \omega L||D^{-1}||(D + \omega L)^T|,$$

$c(n)$ is a modest linear function of n , and ϵ is the **machine precision**.

8 Parallelism and Performance

`nag_sparse_sym_precon_ssor_solve` (f11jdc) is not threaded in any implementation.

9 Further Comments

9.1 Timing

The time taken for a call to `nag_sparse_sym_precon_ssor_solve` (f11jdc) is proportional to **nnz**.

9.2 Use of check

It is expected that a common use of `nag_sparse_sym_precon_ssor_solve` (f11jdc) will be to carry out the preconditioning step required in the application of `nag_sparse_sym_basic_solver` (f11gec) to sparse symmetric linear systems. In this situation `nag_sparse_sym_precon_ssor_solve` (f11jdc) is likely to be called many times with the same matrix M . In the interests of both reliability and efficiency, you are recommended to set `check = Nag_SparseSym_Check` for the first of such calls, and to set `check = Nag_SparseSym_NoCheck` for all subsequent calls.

10 Example

This example solves a sparse symmetric linear system of equations

$$Ax = b,$$

using the conjugate-gradient (CG) method with SSOR preconditioning.

The CG algorithm itself is implemented by the reverse communication function `nag_sparse_sym_basic_solver` (f11gec), which returns repeatedly to the calling program with various values of the argument **irevcm**. This argument indicates the action to be taken by the calling program.

If **irevcm** = 1, a matrix-vector product $v = Au$ is required. This is implemented by a call to `nag_sparse_sym_matvec` (f11xec).

If **irevcm** = 2, a solution of the preconditioning equation $Mv = u$ is required. This is achieved by a call to `nag_sparse_sym_precon_ssor_solve` (f11jdc).

If **irevcm** = 4, `nag_sparse_sym_basic_solver` (f11gec) has completed its tasks. Either the iteration has terminated, or an error condition has arisen.

For further details see the function document for `nag_sparse_sym_basic_solver` (f11gec).

10.1 Program Text

```
/* nag_sparse_sym_precon_ssor_solve (f11jdc) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <nag.h>
#include <nag_stdlb.h>
#include <nagf11.h>
int main(void)
{
    /* Scalars */
    Integer exit_status = 0;
    double anorm, omega, sigerr, sigmax, sigtol, stplhs, stprhs, tol;
    Integer i, irevcm, itemr, itn, its, j, listr, lcneed, lcomm,
           maxitn, maxits, monit, n, nnz, nnzl;
    /* Arrays */
    char nag_enum_arg[100];
    double *a = 0, *b = 0, *rdiag = 0, *wgt = 0, *commarray = 0, *x = 0;
    Integer *icol = 0, *irow = 0, *istr = 0;
```

```

/* NAG types */
Nag_NormType norm;
Nag_SparseSym_Method method;
Nag_SparseSym_PrecType precon;
Nag_SparseSym_Bisection sigcmp;
Nag_SparseSym_CheckData ckjd, ckxe;
Nag_SparseSym_Dups dup;
Nag_SparseSym_Weight weight;
Nag_SparseSym_Zeros zero;
NagError fail, fail1;

INIT_FAIL(fail);

printf("nag_sparse_sym_precon_ssor_solve (f11jdc) Example Program Results");
printf("\n\n");
/* Skip heading in data file */
#ifdef _WIN32
scanf_s("%*[^\n]");
#else
scanf("%*[^\n]");
#endif
/* Read algorithmic parameters */
#ifdef _WIN32
scanf_s("%" NAG_IFMT "%*[^\n]", &n);
#else
scanf("%" NAG_IFMT "%*[^\n]", &n);
#endif
#ifdef _WIN32
scanf_s("%" NAG_IFMT "%*[^\n]", &nnz);
#else
scanf("%" NAG_IFMT "%*[^\n]", &nnz);
#endif

/* Allocate memory */
listr = n + 1;
lcomm = 6 * n + 120;
if (!(a = NAG_ALLOC(nnz, double)) ||
    !(b = NAG_ALLOC(n, double)) ||
    !(rdiag = NAG_ALLOC(n, double)) ||
    !(wgt = NAG_ALLOC(n, double)) ||
    !(comarray = NAG_ALLOC(lcomm, double)) ||
    !(x = NAG_ALLOC(n, double)) ||
    !(icol = NAG_ALLOC(nnz, Integer)) ||
    !(irow = NAG_ALLOC(nnz, Integer)) || !(istr = NAG_ALLOC(listr, Integer)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

#ifdef _WIN32
scanf_s("%99s%*[^\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
scanf("%99s%*[^\n] ", nag_enum_arg);
#endif
/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
method = (Nag_SparseSym_Method) nag_enum_name_to_value(nag_enum_arg);
#ifdef _WIN32
scanf_s("%99s%*[^\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
scanf("%99s%*[^\n] ", nag_enum_arg);
#endif
precon = (Nag_SparseSym_PrecType) nag_enum_name_to_value(nag_enum_arg);
#ifdef _WIN32
scanf_s("%99s%*[^\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
scanf("%99s%*[^\n] ", nag_enum_arg);
#endif

```

```

sigcmp = (Nag_SparseSym_Bisection) nag_enum_name_to_value(nag_enum_arg);
#ifndef _WIN32
    scanf_s("%99s*[^\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
    scanf("%99s*[^\n] ", nag_enum_arg);
#endif
norm = (Nag_NormType) nag_enum_name_to_value(nag_enum_arg);
#ifndef _WIN32
    scanf_s("%" NAG_IFMT "%*[^\n] ", &iterm);
#else
    scanf("%" NAG_IFMT "%*[^\n] ", &iterm);
#endif
#ifndef _WIN32
    scanf_s("%lf%" NAG_IFMT "%*[^\n]", &tol, &maxitn);
#else
    scanf("%lf%" NAG_IFMT "%*[^\n]", &tol, &maxitn);
#endif
#ifndef _WIN32
    scanf_s("%lf%lf%*[^\n]", &anorm, &sigmax);
#else
    scanf("%lf%lf%*[^\n]", &anorm, &sigmax);
#endif
#ifndef _WIN32
    scanf_s("%lf%" NAG_IFMT "%*[^\n]", &sigtol, &maxits);
#else
    scanf("%lf%" NAG_IFMT "%*[^\n]", &sigtol, &maxits);
#endif
#ifndef _WIN32
    scanf_s("%lf%*[^\n]", &omega);
#else
    scanf("%lf%*[^\n]", &omega);
#endif

/* Read the matrix a */
for (i = 0; i <= nnz - 1; i++)
#ifndef _WIN32
    scanf_s("%lf%" NAG_IFMT "%" NAG_IFMT "%*[^\n] ", &a[i], &irow[i],
            &icoll[i]);
#else
    scanf("%lf%" NAG_IFMT "%" NAG_IFMT "%*[^\n] ", &a[i], &irow[i], &icoll[i]);
#endif

/* Sort matrix a removing zero or duplicate elements using
 * nag_sparse_sym_sort (f11zbc).
 */
nnz1 = nnz;
dup = Nag_SparseSym_RemoveDups;
zero = Nag_SparseSym_RemoveZeros;
nag_sparse_sym_sort(n, &nnz1, a, irow, icol, dup, zero, istr, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_sparse_sym_sort (f11zbc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
if (nnz != nnz1) {
    printf("Warning, input Matrix has zero or duplicate elements\n");
    printf("      nnz has been reduced from %" NAG_IFMT " to %" NAG_IFMT
          "\n", nnz, nnz1);
    nnz = nnz1;
}

/* Check for zero diagonal matrix elements and calculate reciprocals. */
for (i = 0; i < n; i++) {
    /* j points to last element in row i */
    j = istr[i + 1] - 2;
    if (irow[j] == icoll[j])
        rdiag[irow[j] - 1] = 1.0 / a[j];
    else {
        printf("Matrix has a missing element for diagonal %" NAG_IFMT "\n", i);
        goto END;
    }
}

```

```

}

/* Read right-hand side vector b and initial approximate solution x */
for (i = 0; i <= n - 1; i++)
#ifdef _WIN32
    scanf_s("%lf", &b[i]);
#else
    scanf("%lf", &b[i]);
#endif
#ifdef _WIN32
    scanf_s("%*[^\n]");
#else
    scanf("%*[^\n]");
#endif
    for (i = 0; i <= n - 1; i++)
#ifdef _WIN32
    scanf_s("%lf", &x[i]);
#else
    scanf("%lf", &x[i]);
#endif

/* Initialize the basic symmetric solver (f11gec) using
 * nag_sparse_sym_basic_setup (f11gdc)
 */
weight = Nag_SparseSym_UnWeighted;
monit = 0;
nag_sparse_sym_basic_setup(method, precon, sigcmp, norm, weight, iterm, n,
                            tol, maxitn, anorm, sigmax, sigtol, maxits,
                            monit, &lcneed, commarray, lcomm, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_sparse_sym_setup (f11gdc).\n%s\n", fail.message);
    exit_status = 2;
    goto END;
}

/* call solver repeatedly to solve the equations */
irevcm = 0;
ckxe = Nag_SparseSym_Check;
ckjd = Nag_SparseSym_Check;
while (1) {
    /* nag_sparse_sym_basic_solver (f11gec).
     * Real sparse symmetric linear systems, preconditioned conjugate gradient
     * or Lanczos method.
     */
    nag_sparse_sym_basic_solver(&irevcm, x, b, wgt, commarray, lcomm, &fail);
    if (irevcm != 4) {
        INIT_FAIL(fail1);
        switch (irevcm) {
        case 1:
            /* Compute sparse symmetric matrix vector product using
             * nag_sparse_sym_matvec (f11xec).
             */
            nag_sparse_sym_matvec(n, nnz, a, irow, icol, ckxe, x, b, &fail1);
            ckxe = Nag_SparseSym_NoCheck;
            break;
        case 2:
            /* SSOR preconditioning
             * nag_sparse_sym_precon_ssor_solve (f11jdc).
             * Solution of linear system involving preconditioning matrix
             * generated by applying SSOR to real sparse symmetric matrix
             */
            nag_sparse_sym_precon_ssor_solve(n, nnz, a, irow, icol, rdiag,
                                             omega, ckjd, x, b, &fail1);
            ckjd = Nag_SparseSym_NoCheck;
        }
        if (fail1.code != NE_NOERROR)
            irevcm = 6;
    }
    else if (fail.code != NE_NOERROR) {
        printf("Error from nag_sparse_sym_basic_solver (f11gec).\n%s\n",
               fail.message);
    }
}

```

```

        exit_status = 3;
        goto END;
    }
    else
        goto END_LOOP;
}
END_LOOP:
/* Obtain and print diagnostic statistics using
 * nag_sparse_sym_basic_diagnostic (f11gfc).
 */
nag_sparse_sym_basic_diagnostic(&itn, &stplhs, &stprhs, &anorm, &sigmax,
                                &its, &sigerr, commarray, lcomm, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_sparse_sym_basic_diagnostic (f11gfc).\n%s\n",
           fail.message);
    exit_status = 4;
    goto END;
}
printf("Converged in %10" NAG_IFMT " iterations \n", itn);
printf("Final residual norm = %11.3e\n\n", stplhs);
/* Output solution */
printf("%16s\n", "Solution");
for (i = 0; i <= n - 1; i++)
    printf("%16.4e\n", x[i]);

END:
NAG_FREE(a);
NAG_FREE(b);
NAG_FREE(rdiag);
NAG_FREE(wgt);
NAG_FREE(commarray);
NAG_FREE(x);
NAG_FREE(icol);
NAG_FREE(irow);
NAG_FREE(istr);
return exit_status;
}

```

10.2 Program Data

```

nag_sparse_sym_precon_ssor_solve (f11jdc) Example Program Data
7                      : n
16                     : nnz
Nag_SparseSym_CG       : method
Nag_SparseSym_Prec     : precon
Nag_SparseSym_NoBisect : sigcmp
Nag_InfNorm            : norm
1                      : iterm
1.0e-6 100             : tol, maxitn
0.0   0.0               : anorm, sigmax
0.0   10                : sigtol, maxits
1.0                  : omega
4.   1     1
1.   2     1
5.   2     2
2.   3     3
2.   4     2
3.   4     4
-1.  5     1
1.   5     4
4.   5     5
1.   6     2
-2.  6     5
3.   6     6
2.   7     1
-1.  7     2
-2.  7     3

```

```
5.    7      7      : a[i], irow[i], icol[i], i=0,...,nnz-1  
15.   18.   -8.    21.    :  
11.   10     29.    : b[i], i=0,...,n-1  
 0.    0.     0.    :  
 0.    0.     0.    : x[i], i=0,...,n-1
```

10.3 Program Results

nag_sparse_sym_precon_ssor_solve (f11jdc) Example Program Results

```
Converged in          6 iterations  
Final residual norm = 7.105e-15
```

```
Solution  
1.0000e+00  
2.0000e+00  
3.0000e+00  
4.0000e+00  
5.0000e+00  
6.0000e+00  
7.0000e+00
```
