

NAG Library Function Document

nag_anderson_darling_uniform_prob (g08cjc)

1 Purpose

`nag_anderson_darling_uniform_prob (g08cjc)` calculates the Anderson–Darling goodness-of-fit test statistic and its probability for the case of standard uniformly distributed data.

2 Specification

```
#include <nag.h>
#include <nagg08.h>
void nag_anderson_darling_uniform_prob (Integer n, Nag_Boolean issort,
                                         double y[], double *a2, double *p, NagError *fail)
```

3 Description

Calculates the Anderson–Darling test statistic A^2 (see `nag_anderson_darling_stat (g08chc)`) and its upper tail probability by using the approximation method of Marsaglia and Marsaglia (2004) for the case of uniformly distributed data.

4 References

Anderson T W and Darling D A (1952) Asymptotic theory of certain ‘goodness-of-fit’ criteria based on stochastic processes *Annals of Mathematical Statistics* **23** 193–212

Marsaglia G and Marsaglia J (2004) Evaluating the Anderson–Darling distribution *J. Statist. Software* **9** (2)

5 Arguments

- | | | |
|----|-----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| 1: | n – Integer | <i>Input</i> |
| | <i>On entry:</i> n , the number of observations. | |
| | <i>Constraint:</i> $n > 1$. | |
| 2: | issort – Nag_Boolean | <i>Input</i> |
| | <i>On entry:</i> set issort = Nag_TRUE if the observations are sorted in ascending order; otherwise the function will sort the observations. | |
| 3: | y[n] – double | <i>Input/Output</i> |
| | <i>On entry:</i> y_i , for $i = 1, 2, \dots, n$, the n observations. | |
| | <i>On exit:</i> if issort = Nag_FALSE, the data sorted in ascending order; otherwise the array is unchanged. | |
| | <i>Constraint:</i> if issort = Nag_TRUE, the values must be sorted in ascending order. Each y_i must lie in the interval $(0, 1)$. | |
| 4: | a2 – double * | <i>Output</i> |
| | <i>On exit:</i> A^2 , the Anderson–Darling test statistic. | |

5: p – double *	<i>Output</i>
On exit: p , the upper tail probability for A^2 .	
6: fail – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).	

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_BOUND

The data in y must lie in the interval $(0, 1)$.

NE_INT

On entry, $n = \langle value \rangle$.

Constraint: $n > 1$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

NE_NOT_INCREASING

issort = Nag_TRUE and the data in y is not sorted in ascending order.

7 Accuracy

Probabilities greater than approximately 0.09 are accurate to five decimal places; lower value probabilities are accurate to six decimal places.

8 Parallelism and Performance

`nag_anderson_darling_uniform_prob` (g08ejc) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example calculates the A^2 statistic and its p -value for uniform data obtained by transforming exponential variates.

10.1 Program Text

```
/* nag_anderson_darling_uniform_prob (g08cjc) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <stdio.h>
#include <string.h>
#include <math.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg08.h>

int main(void)
{
    /* Scalars */
    Integer exit_status = 0, i, n;
    double a2, mu, p;
    /* Arrays */
    double *x = 0, *y = 0;
    /* Nag types */
    Nag_Boolean issort;
    NagError fail;

    printf("%s\n\n",
           "nag_anderson_darling_uniform_prob (g08cjc) Example Program Results");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif

    /* Read number of observations and parameter value */
#ifdef _WIN32
    scanf_s("%" NAG_IFMT "", &n);
#else
    scanf("%" NAG_IFMT "", &n);
#endif
#ifdef _WIN32
    scanf_s("%lf", &mu);
#else
    scanf("%lf", &mu);
#endif
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif

    /* Memory allocation */
    if (!(x = NAG_ALLOC((n), double)) || !(y = NAG_ALLOC((n), double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read observations */

```

```

    for (i = 0; i < n; i++) {
#define _WIN32
    scanf_s("%lf", x + i);
#else
    scanf("%lf", x + i);
#endif
}
#define _WIN32
scanf_s("%*[^\n]");
#else
scanf("%*[^\n]");
#endif

/* PIT */
for (i = 0; i < n; i++) {
    y[i] = 1.0 - exp(-x[i] / mu);
}

/* Let nag_anderson_darling_uniform_prob (g08cjc) sort the uniform variates */
issort = Nag_FALSE;

/* Calculate the Anderson-Darling goodness-of-fit test statistic and its
   probability for the case of uniformly distributed data */
INIT_FAIL(fail);
/* nag_anderson_darling_uniform_prob (g08cjc) */
nag_anderson_darling_uniform_prob(n, issort, y, &a2, &p, &fail);

/* Results */
printf("%s ", " H0: data from exponential distribution with mean");
printf("%f\n", mu);
printf("%s ", " Test statistic, A-squared: ");
printf("%f\n", a2);
printf("%s ", " Upper tail probability:      ");
printf("%f\n", p);

END:
NAG_FREE(x);
NAG_FREE(y);

return exit_status;
}

```

10.2 Program Data

```

nag_anderson_darling_uniform_prob (g08cjc) Example Program Data
26 1.65 :: n, mu
0.4782745 1.2858962 1.1163891 2.0410619 2.2648109 0.0833660 1.2527554
0.4031288 0.7808981 0.1977674 3.2539440 1.8113504 1.2279834 3.9178773
1.4494309 0.1358438 1.8061778 6.0441929 0.9671624 3.2035042 0.8067364
0.4179364 3.5351774 0.3975414 0.6120960 0.1332589 :: end of observations

```

10.3 Program Results

```

nag_anderson_darling_uniform_prob (g08cjc) Example Program Results

H0: data from exponential distribution with mean 1.650000
Test statistic, A-squared:  0.182982
Upper tail probability:  0.994487

```
