

NAG Library Function Document

nag_cumul_normal (s15abc)

1 Purpose

`nag_cumul_normal (s15abc)` returns the value of the cumulative Normal distribution function, $P(x)$.

2 Specification

```
#include <nag.h>
#include <nags.h>
double nag_cumul_normal (double x)
```

3 Description

`nag_cumul_normal (s15abc)` evaluates an approximate value for the cumulative Normal distribution function

$$P(x) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^x e^{-u^2/2} du.$$

The function is based on the fact that

$$P(x) = \frac{1}{2} \operatorname{erfc}\left(\frac{-x}{\sqrt{2}}\right)$$

and it calls `nag_erfc (s15adc)` to obtain a value of erfc for the appropriate argument.

4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

5 Arguments

1: `x` – double *Input*

On entry: the argument x of the function.

6 Error Indicators and Warnings

None.

7 Accuracy

Because of its close relationship with erfc , the accuracy of this function is very similar to that in `nag_erfc (s15adc)`. If ϵ and δ are the relative errors in result and argument, respectively, they are in principle related by

$$|\epsilon| \simeq \left| \frac{x e^{-\frac{1}{2}x^2}}{\sqrt{2\pi} P(x)} \delta \right|$$

so that the relative error in the argument, x , is amplified by a factor, $\frac{x e^{-\frac{1}{2}x^2}}{\sqrt{2\pi} P(x)}$, in the result.

For x small and for x positive this factor is always less than one and accuracy is mainly limited by *machine precision*.

For large negative x the factor behaves like $\sim x^2$ and hence to a certain extent relative accuracy is unavoidably lost.

However the absolute error in the result, E , is given by

$$|E| \simeq \left| \frac{xe^{-\frac{1}{2}x^2}}{\sqrt{2\pi}} \delta \right|$$

so absolute accuracy can be guaranteed for all x .

8 Parallelism and Performance

`nag_cumul_normal` (`s15abc`) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example reads values of the argument x from a file, evaluates the function at each value of x and prints the results.

10.1 Program Text

```
/* nag_cumul_normal (s15abc) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <nag.h>
#include <stdio.h>
#include <nag_stlib.h>
#include <nags.h>

int main(void)
{
    Integer exit_status = 0;
    double x, y;

    /* Skip heading in data file */
#ifndef _WIN32
    scanf_s("%*[^\n]");
#else
    scanf("%*[^\n]");
#endif
    printf("nag_cumul_normal (s15abc) Example Program Results\n");
    printf("      x          y\n");
#ifndef _WIN32
    while (scanf_s("%lf", &x) != EOF)
#else
    while (scanf("%lf", &x) != EOF)
#endif
    {
        /* nag_cumul_normal (s15abc).
         * Cumulative Normal distribution function P(x)
         */
        y = nag_cumul_normal(x);
    }
}
```

```
    printf("%12.3e%12.3e\n", x, y);  
}  
  
return exit_status;  
}
```

10.2 Program Data

```
nag_cumul_normal (s15abc) Example Program Data  
-20.0  
-1.0  
0.0  
1.0  
2.0  
20.0
```

10.3 Program Results

```
nag_cumul_normal (s15abc) Example Program Results  
      x        y  
-2.000e+01  2.754e-89  
-1.000e+00  1.587e-01  
0.000e+00   5.000e-01  
1.000e+00   8.413e-01  
2.000e+00   9.772e-01  
2.000e+01   1.000e+00
```
