

NAG Library Function Document

nag_rand_sample_unequal (g05nec)

1 Purpose

nag_rand_sample_unequal (g05nec) selects a pseudorandom sample, without replacement and allowing for unequal probabilities.

2 Specification

```
#include <nag.h>
#include <nagg05.h>
void nag_rand_sample_unequal (Nag_SortOrder sortorder, const double wt[],
    const Integer ipop[], Integer n, Integer isamp[], Integer m,
    Integer state[], NagError *fail)
```

3 Description

nag_rand_sample_unequal (g05nec) selects m elements from either the set of values $(1, 2, \dots, n)$ or a supplied population vector of length n . The probability of selecting the i th element is proportional to a user-supplied weight, w_i . Each element will appear at most once in the sample, i.e., the sampling is done without replacement.

One of the initialization functions nag_rand_init_repeatable (g05kfc) (for a repeatable sequence if computed sequentially) or nag_rand_init_nonrepeatable (g05kgc) (for a non-repeatable sequence) must be called prior to the first call to nag_rand_sample_unequal (g05nec).

4 References

None.

5 Arguments

- | | | |
|----|----------------------------------|--------------|
| 1: | sortorder – Nag_SortOrder | <i>Input</i> |
|----|----------------------------------|--------------|
- On entry:* a flag indicating the sorted status of the **wt** vector.
- sortorder** = Nag_Ascending
wt is sorted in ascending order,
- sortorder** = Nag_Descending
wt is sorted in descending order,
- sortorder** = Nag_Unsorted
wt is unsorted and nag_rand_sample_unequal (g05nec) will sort the weights prior to using them.

Irrespective of the value of **sortorder**, no checks are made on the sorted status of **wt**, e.g., it is possible to supply **sortorder** = Nag_Ascending, even when **wt** is not sorted. In such cases the **wt** array will not be sorted internally, but nag_rand_sample_unequal (g05nec) will still work correctly except, possibly, in cases of extreme weight values.

It is usually more efficient to specify a value of **sortorder** that is consistent with the status of **wt**.

Constraint: **sortorder** = Nag_Ascending, Nag_Descending or Nag_Unsorted.

2:	wt[n] – const double	<i>Input</i>
<i>On entry:</i> w_i , the relative probability weights. These weights need not sum to 1.0.		
<i>Constraints:</i>		
	$\text{wt}[i - 1] \geq 0.0$, for $i = 1, 2, \dots, n$;	
at least m values must be nonzero.		
3:	ipop[dim] – const Integer	<i>Input</i>
Note: the dimension, <i>dim</i> , of the array ipop must be at least n when ipop is not NULL .		
<i>On entry:</i> the population to be sampled. If ipop is NULL then the population is assumed to be the set of values $(1, 2, \dots, n)$ and the array ipop is not referenced. Elements of ipop with the same value are not combined, therefore if $\text{wt}[i - 1] \neq 0, \text{wt}[j - 1] \neq 0$ and $i \neq j$ then there is a nonzero probability that the sample will contain both ipop[i - 1] and ipop[j - 1] . If ipop[i - 1] = ipop[j - 1] then that value can appear in isampl more than once.		
4:	n – Integer	<i>Input</i>
<i>On entry:</i> n , the size of the population.		
<i>Constraint:</i> $n \geq 1$.		
5:	isampl[m] – Integer	<i>Output</i>
<i>On exit:</i> the selected sample.		
6:	m – Integer	<i>Input</i>
<i>On entry:</i> m , the size of the sample required.		
<i>Constraint:</i> $0 \leq m \leq n$.		
7:	state[dim] – Integer	<i>Communication Array</i>
Note: the dimension, <i>dim</i> , of this array is dictated by the requirements of associated functions that must have been previously called. This array MUST be the same array passed as argument state in the previous call to nag_rand_init_repeatable (g05kfc) or nag_rand_init_nonrepeatable (g05kgc).		
<i>On entry:</i> contains information on the selected base generator and its current state.		
<i>On exit:</i> contains updated information on the state of the generator.		
8:	fail – NagError *	<i>Input/Output</i>
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).		

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle\text{value}\rangle$ had an illegal value.

NE_INT

On entry, $\mathbf{n} = \langle \text{value} \rangle$.

Constraint: $\mathbf{n} \geq 1$.

NE_INT_2

On entry, $\mathbf{m} = \langle \text{value} \rangle$ and $\mathbf{n} = \langle \text{value} \rangle$.

Constraint: $0 \leq \mathbf{m} \leq \mathbf{n}$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_INVALID_STATE

On entry, **state** vector has been corrupted or not initialized.

NE_NEG_WEIGHT

On entry, at least one weight was less than zero.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

NE_NON_ZERO_WEIGHTS

On entry, $\mathbf{m} = \langle \text{value} \rangle$, number of nonzero weights = $\langle \text{value} \rangle$.

Constraint: must be at least \mathbf{m} nonzero weights.

7 Accuracy

Not applicable.

8 Parallelism and Performance

`nag_rand_sample Unequal (g05nec)` is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

`nag_rand_sample Unequal (g05nec)` internally allocates $(\mathbf{n} + 1)$ doubles and \mathbf{n} Integers.

Although it is possible to use `nag_rand_sample Unequal (g05nec)` to sample using equal probabilities, by setting all elements of the input array **wt** to the same positive value, it is more efficient to use `nag_rand_sample (g05ndc)`. To sample with replacement, `nag_rand_gen_discrete (g05tdc)` can be used when the probabilities are unequal and `nag_rand_discrete_uniform (g05tlc)` when the probabilities are equal.

10 Example

This example samples from a population of 25.

10.1 Program Text

```

/* nag_rand_sample_unequal (g05nec) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg05.h>

int main(void)
{
    /* Scalars */
    Integer exit_status = 0, lseed = 1;
    Integer i, lstate, m, n, subid;

    /* Arrays */
    Integer *ipop = 0, *isampl = 0, *state = 0;
    Integer seed[1];
    double *wt = 0;
    char cgenid[40], csortorder[40], cpop_supplied[40];

    /* NAG structures */
    NagError fail;
    Nag_BaseRNG genid;
    Nag_SortOrder sortorder;
    Nag_Boolean pop_supplied;

    /* Initialize the error structure to print out any error messages */
    INIT_FAIL(fail);

    printf("nag_rand_sample_unequal (g05nec) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif

    /* Read in the base generator information and seed */
#ifdef _WIN32
    scanf_s("%39s%" NAG_IFMT "%" NAG_IFMT "%*[^\n] ", cgenid,
            (unsigned)_countof(cgenid), &subid, &seed[0]);
#else
    scanf("%39s%" NAG_IFMT "%" NAG_IFMT "%*[^\n] ", cgenid, &subid, &seed[0]);
#endif
    genid = (Nag_BaseRNG) nag_enum_name_to_value(cgenid);

    /* Query to obtain the length of the state array using
     * nag_rand_init_repeatable (g05kfc).
     */
    lstate = 0;
    nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
               fail.message);
        exit_status = 1;
        goto END;
    }

    /* Allocate memory to state */
    if (!(state = NAG_ALLOC(lstate, Integer))) {
        printf("Allocation failure\n");
        exit_status = -1;
}

```

```

        goto END;
    }

/* Initialize the RNG using
 * nag_rand_init_repeatable (g05kfc)
 */
nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
           fail.message);
    exit_status = 2;
    goto END;
}

/* Read in the problem size, pop_supplied is a True / False flag indicating
 * whether population flags are supplied (Nag_TRUE) or taken as the integers
 * 1 to n (Nag_FALSE)
 */
#ifndef _WIN32
scanf_s("%" NAG_IFMT "%" NAG_IFMT "%39s%39s%*[^\n] ", &n, &m, csortorder,
       (unsigned)_countof(csortorder), cpop_supplied,
       (unsigned)_countof(cpop_supplied));
#else
scanf("%" NAG_IFMT "%" NAG_IFMT "%39s%39s%*[^\n] ", &n, &m, csortorder,
      cpop_supplied);
#endif
sortorder = (Nag_SortOrder) nag_enum_name_to_value(csortorder);
pop_supplied = (Nag_Boolean) nag_enum_name_to_value(cpop_supplied);

/* Allocate memory for input arrays */
if (!(wt = NAG_ALLOC(n, double)) || !(isampl = NAG_ALLOC(m, Integer)))
{
    printf("Allocation failure\n");
    exit_status = -2;
    goto END;
}

if (pop_supplied) {
    /* Read in the population and weights */
    if (!(ipop = NAG_ALLOC(n, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -3;
        goto END;
    }
#ifndef _WIN32
    for (i = 0; i < n; i++)
        scanf_s("%" NAG_IFMT "%lf%*[^\n] ", &ipop[i], &wt[i]);
#else
    for (i = 0; i < n; i++)
        scanf("%" NAG_IFMT "%lf%*[^\n] ", &ipop[i], &wt[i]);
#endif
    else {
        /* Read in just the weights */
#ifndef _WIN32
        for (i = 0; i < n; i++)
            scanf_s("%lf%*[^\n] ", &wt[i]);
#else
        for (i = 0; i < n; i++)
            scanf("%lf%*[^\n] ", &wt[i]);
#endif
    }
}

/* Generate the sample without replacement, unequal weights using
 * nag_rand_sample_unequal (g05nec)
 */
nag_rand_sample_unequal(sortorder, wt, ipop, n, isampl, m, state, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_rand_sample_unequal (g05nec).\n%s\n",

```

```

        fail.message);
exit_status = 3;
goto END;
}

/* Display the results */
for (i = 0; i < m; i++)
    printf("%5" NAG_IFMT "", isampl[i]);
printf("\n");

END:
NAG_FREE(wt);
NAG_FREE(ipop);
NAG_FREE(isampl);
NAG_FREE(state);

return exit_status;
}

```

10.2 Program Data

```

nag_rand_sample_unequal (g05nec) Example Program Data
Nag_MersenneTwister          0   1762543 :: genid, subid, seed[0]
25      10      Nag_Unsorted  Nag_TRUE :: n, m, sortorder, pop_supplied
171     85.54
52      71.78
172     118.13
139     13.68
196     153.60
125     165.35
36      122.35
70      35.87
25      151.78
86      128.33
76      178.27
37      183.37
185     165.81
40      101.41
90      145.16
27      42.01
79      59.08
118     17.53
142     87.14
127     69.20
101     31.13
22      60.26
41      21.00
199     85.06
59      119.73           :: End of ipop,wt

```

10.3 Program Results

```
nag_rand_sample_unequal (g05nec) Example Program Results
```

125	41	185	40	37	196	22	25	76	172
-----	----	-----	----	----	-----	----	----	----	-----
