

NAG Library Function Document

nag_tsa_spectrum_bivar_cov (g13ccc)

1 Purpose

nag_tsa_spectrum_bivar_cov (g13ccc) calculates the smoothed sample cross spectrum of a bivariate time series using one of four lag windows: rectangular, Bartlett, Tukey or Parzen.

2 Specification

```
#include <nag.h>
#include <naggl3.h>

void nag_tsa_spectrum_bivar_cov (Integer nxy,
    NagMeanOrTrend mtxy_correction, double pxy, Integer iw, Integer mw,
    Integer ish, Integer ic, Integer nc, double cxy[], double cyx[],
    Integer kc, Integer l, double xg[], double yg[], Complex g[],
    Integer *ng, NagError *fail)
```

3 Description

The smoothed sample cross spectrum is a complex valued function of frequency ω , $f_{xy}(\omega) = cf(\omega) + iqf(\omega)$, defined by its real part or co-spectrum

$$cf(\omega) = \frac{1}{2\pi} \sum_{k=-M+1}^{M-1} w_k C_{xy}(k+S) \cos(\omega k)$$

and imaginary part or quadrature spectrum

$$qf(\omega) = \frac{1}{2\pi} \sum_{k=-M+1}^{M-1} w_k C_{xy}(k+S) \sin(\omega k)$$

where $w_k = w_{-k}$, for $k = 0, 1, \dots, M-1$, is the smoothing lag window as defined in the description of nag_tsa_spectrum_univar_cov (g13cac). The alignment shift S is recommended to be chosen as the lag k at which the cross-covariances $c_{xy}(k)$ peak, so as to minimize bias.

The results are calculated for frequency values

$$\omega_j = \frac{2\pi j}{L}, \quad j = 0, 1, \dots, [L/2],$$

where $[]$ denotes the integer part.

The cross-covariances $c_{xy}(k)$ may be supplied by you, or constructed from supplied series x_1, x_2, \dots, x_n ; y_1, y_2, \dots, y_n as

$$c_{xy}(k) = \frac{\sum_{t=1}^{n-k} x_t y_{t+k}}{n}, \quad k \geq 0$$

$$c_{xy}(k) = \frac{\sum_{t=1-k}^n x_t y_{t+k}}{n} = c_{yx}(-k), \quad k < 0$$

this convolution being carried out using the finite Fourier transform.

The supplied series may be mean and trend corrected and tapered before calculation of the cross-covariances, in exactly the manner described in nag_tsa_spectrum_univar_cov (g13cac) for univariate spectrum estimation. The results are corrected for any bias due to tapering.

The bandwidth associated with the estimates is not returned. It will normally already have been calculated in previous calls of `nag_tsa_spectrum_univar_cov` (`g13cac`) for estimating the univariate spectra of y_t and x_t .

4 References

Bloomfield P (1976) *Fourier Analysis of Time Series: An Introduction* Wiley

Jenkins G M and Watts D G (1968) *Spectral Analysis and its Applications* Holden-Day

5 Arguments

- 1: **nxy** – Integer *Input*
On entry: n , the length of the time series x and y .
Constraint: $nxy \geq 1$.
- 2: **mtxy_correction** – NagMeanOrTrend *Input*
On entry: if cross-covariances are to be calculated by the function ($ic = 0$), **mtxy_correction** must specify whether the data is to be initially mean or trend corrected.
mtxy_correction = Nag_NoCorrection
 For no correction.
mtxy_correction = Nag_Mean
 For mean correction.
mtxy_correction = Nag_Trend
 For trend correction.
 If cross-covariances are supplied ($ic \neq 0$), **mtxy_correction** should be set to **mtxy_correction** = Nag_NoCorrection
Constraint: if $ic = 0$, **mtxy_correction** = Nag_NoCorrection, Nag_Mean or Nag_Trend.
- 3: **pxy** – double *Input*
On entry: if cross-covariances are to be calculated by the function ($ic = 0$), **pxy** must specify the proportion of the data (totalled over both ends) to be initially tapered by the split cosine bell taper. A value of 0.0 implies no tapering.
 If cross-covariances are supplied ($ic \neq 0$), **pxy** is not used.
Constraint: if $ic = 0$, $0.0 \leq pxy \leq 1.0$.
- 4: **iw** – Integer *Input*
On entry: the choice of lag window.
iw = 1
 Rectangular.
iw = 2
 Bartlett.
iw = 3
 Tukey.
iw = 4
 Parzen.
Constraint: $1 \leq iw \leq 4$.

- 5: **mw** – Integer *Input*
On entry: M , the ‘cut-off’ point of the lag window, relative to any alignment shift that has been applied. Windowed cross-covariances at lags $(-mw + ish)$ or less, and at lags $(mw + ish)$ or greater are zero.
Constraints:

$$mw \geq 1;$$

$$mw + |ish| \leq nxy.$$
- 6: **ish** – Integer *Input*
On entry: S , the alignment shift between the x and y series. If x leads y , the shift is positive.
Constraint: $-mw < ish < mw$.
- 7: **ic** – Integer *Input*
On entry: indicates whether cross-covariances are to be calculated in the function or supplied in the call to the function.
ic = 0
 Cross-covariances are to be calculated.
ic \neq 0
 Cross-covariances are to be supplied.
- 8: **nc** – Integer *Input*
On entry: the number of cross-covariances to be calculated in the function or supplied in the call to the function.
Constraint: $mw + |ish| \leq nc \leq nxy$.
- 9: **cx**[**nc**] – double *Input/Output*
On entry: if **ic** \neq 0, **cx** must contain the **nc** cross-covariances between values in the y series and earlier values in time in the x series, for lags from 0 to $(nc - 1)$.
 If **ic** = 0, **cx** need not be set.
On exit: if **ic** = 0, **cx** will contain the **nc** calculated cross-covariances.
 If **ic** \neq 0, the contents of **cx** will be unchanged.
- 10: **cy**[**nc**] – double *Input/Output*
On entry: if **ic** \neq 0, **cy** must contain the **nc** cross-covariances between values in the y series and later values in time in the x series, for lags from 0 to $(nc - 1)$.
 If **ic** = 0, **cy** need not be set.
On exit: if **ic** = 0, **cy** will contain the **nc** calculated cross-covariances.
 If **ic** \neq 0, the contents of **cy** will be unchanged.
- 11: **kc** – Integer *Input*
On entry: if **ic** = 0, **kc** must specify the order of the fast Fourier transform (FFT) used to calculate the cross-covariances.
 If **ic** \neq 0, that is if covariances are supplied, **kc** is not used.
Constraint: $kc \geq nxy + nc$.

- 12: **l** – Integer *Input*
- On entry:* L , the frequency division of the spectral estimates as $\frac{2\pi}{L}$. Therefore it is also the order of the FFT used to construct the sample spectrum from the cross-covariances.
- Constraint:* $l \geq 2 \times \mathbf{mw} - 1$.
- 13: **xg**[*dim*] – double *Input/Output*
- Note:** the dimension, *dim*, of the array **xg** must be at least $\max(\mathbf{kc}, l)$, when **ic** = 0;
- On entry:* if the cross-covariances are to be calculated (**ic** = 0) **xg** must contain the **nx**y data points of the *x* series. If covariances are supplied (**ic** ≠ 0) **xg** may contain any values.
- On exit:* contains the real parts of the **ng** complex spectral estimates in elements **xg**[0] to **xg**[**ng** – 1], and **xg**[**ng**] to **xg**[*dim* – 1] contain 0.0. The *y* series leads the *x* series.
- 14: **yg**[*dim*] – double *Input/Output*
- Note:** the dimension, *dim*, of the array **yg** must be at least $\max(\mathbf{kc}, l)$, when **ic** = 0;
- On entry:* if the cross-covariances are to be calculated (**ic** = 0) **yg** must contain the **ny**x data points of the *y* series. If covariances are supplied (**ic** ≠ 0) **yg** may contain any values.
- On exit:* contains the imaginary parts of the **ng** complex spectral estimates in elements **yg**[0] to **yg**[**ng** – 1], and **yg**[**ng**] to **yg**[*dim* – 1] contain 0.0. The *y* series leads the *x* series.
- 15: **g**[$l/2 + 1$] – Complex *Output*
- On exit:* the complex vector that contains the **ng** cross spectral estimates in elements **g**[0] to **g**[**ng** – 1]. The *y* series leads the *x* series.
- 16: **ng** – Integer * *Output*
- On exit:* the number, $[l/2] + 1$, of complex spectral estimates.
- 17: **fail** – NagError * *Input/Output*
- The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument *<value>* had an illegal value.

NE_INT

On entry, **iw** = *<value>*.

Constraint: **iw** = 1, 2, 3 or 4.

On entry, **mtxy_correction** = $\langle value \rangle$.

Constraint: if **ic** = 0 then **mtxy_correction** \neq Nag_NoCorrection, Nag_Mean or Nag_Trend.

On entry, **mw** = $\langle value \rangle$.

Constraint: **mw** \geq 1.

On entry, **nxy** = $\langle value \rangle$.

Constraint: **nxy** \geq 1.

NE_INT_2

On entry, **ish** = $\langle value \rangle$ and **mw** = $\langle value \rangle$.

Constraint: $|\mathbf{ish}| \leq \mathbf{mw}$.

On entry, **l** = $\langle value \rangle$ and **mw** = $\langle value \rangle$.

Constraint: **l** \geq $2 \times \mathbf{mw} - 1$.

On entry, **nc** = $\langle value \rangle$ and **nxy** = $\langle value \rangle$.

Constraint: **nc** \leq **nxy**.

NE_INT_3

On entry, **kc** = $\langle value \rangle$, **nxy** = $\langle value \rangle$ and **nc** = $\langle value \rangle$.

Constraint: if **ic** = 0, **kc** \geq **nxy** + **nc**.

On entry, **mw** = $\langle value \rangle$, **ish** = $\langle value \rangle$ and **nxy** = $\langle value \rangle$.

Constraint: **mw** + $|\mathbf{ish}| \leq \mathbf{nxy}$.

On entry, **nc** = $\langle value \rangle$, **mw** = $\langle value \rangle$ and **ish** = $\langle value \rangle$.

Constraint: **nc** \geq **mw** + $|\mathbf{ish}|$.

NE_INT_REAL

On entry, **pxy** = $\langle value \rangle$.

Constraint: if **ic** = 0, **pxy** \leq 1.0.

On entry, **pxy** = $\langle value \rangle$.

Constraint: if **ic** = 0, **pxy** \geq 0.0.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

The FFT is a numerically stable process, and any errors introduced during the computation will normally be insignificant compared with uncertainty in the data.

8 Parallelism and Performance

nag_tsa_spectrum_bivar_cov (g13ccc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag_tsa_spectrum_bivar_cov (g13ccc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

`nag_tsa_spectrum_bivar_cov` (g13ccc) carries out two FFTs of length `kc` to calculate the sample cross-covariances and one FFT of length `L` to calculate the sample spectrum. The timing of `nag_tsa_spectrum_bivar_cov` (g13ccc) is therefore dependent on the choice of these values. The time taken for an FFT of length `n` is approximately proportional to $n \log(n)$ (but see Section 9 in `nag_sum_fft_realherm_1d` (c06pac) for further details).

10 Example

This example reads two time series of length 296. It then selects mean correction, a 10% tapering proportion, the Parzen smoothing window and a cut-off point of 35 for the lag window. The alignment shift is set to 3 and 50 cross-covariances are chosen to be calculated. The program then calls `nag_tsa_spectrum_bivar_cov` (g13ccc) to calculate the cross spectrum and then prints the cross-covariances and cross spectrum.

10.1 Program Text

```

/* nag_tsa_spectrum_bivar_cov (g13ccc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg13.h>

int main(void)
{
    /* Scalars */
    double pxy;
    Integer exit_status, i, ic, ii, ish, iw, kc, lf, mw, nc, ng, nxy, nxyg;

    /* Arrays */
    double *cxy = 0, *cyx = 0, *xg = 0, *yg = 0;
    Complex *g = 0;

    NagMeanOrTrend mtxy;

    NagError fail;

    INIT_FAIL(fail);

    exit_status = 0;

    printf("nag_tsa_spectrum_bivar_cov (g13ccc) Example Program Results\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif

#ifdef _WIN32
    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &nxy, &nc, &ic);
#else

```

```

scanf("%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &nxy, &nc, &ic);
#endif

if (nxy > 0 && nc > 0) {
    /* Set parameters for call to nag_tsa_spectrum_bivar_cov (g13ccc) */
    /* Mean correction and 10 percent taper */
    mtxy = Nag_Mean;
    pxy = 0.1;

    /* Parzen window and zero covariance at lag 35 */
    iw = 4;
    mw = 35;

    /* Alignment shift of 3, 50 covariances to be calculated */
    ish = 3;
    kc = 350;
    lf = 80;

    if (ic == 0)
        nxyg = MAX(kc, lf);
    else
        nxyg = lf;

    /* Allocate arrays xg, yg, cxy and cyx */
    if (!(xg = NAG_ALLOC(nxyg, double)) ||
        !(yg = NAG_ALLOC(nxyg, double)) ||
        !(cxy = NAG_ALLOC(nc, double)) ||
        !(cyx = NAG_ALLOC(nc, double)) ||
        !(g = NAG_ALLOC((lf / 2) + 1, Complex)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    if (ic == 0) {
        for (i = 1; i <= nxy; ++i)
#ifdef _WIN32
            scanf_s("%lf", &xg[i - 1]);
#else
            scanf("%lf", &xg[i - 1]);
#endif
#ifdef _WIN32
            scanf_s("%*[\n] ");
#else
            scanf("%*[\n] ");
#endif
        for (i = 1; i <= nxy; ++i)
#ifdef _WIN32
            scanf_s("%lf", &yg[i - 1]);
#else
            scanf("%lf", &yg[i - 1]);
#endif
#ifdef _WIN32
            scanf_s("%*[\n] ");
#else
            scanf("%*[\n] ");
#endif
    }
    else {
        for (i = 1; i <= nc; ++i)
#ifdef _WIN32
            scanf_s("%lf", &cxy[i - 1]);
#else
            scanf("%lf", &cxy[i - 1]);
#endif
#ifdef _WIN32
            scanf_s("%*[\n] ");
#else
            scanf("%*[\n] ");
#endif
    }
}
#endif

```

```

        for (i = 1; i <= nc; ++i)
#ifdef _WIN32
            scanf_s("%lf", &cyx[i - 1]);
#else
            scanf("%lf", &cyx[i - 1]);
#endif
#ifdef _WIN32
            scanf_s("%*[^\\n] ");
#else
            scanf("%*[^\\n] ");
#endif
    }

    /* nag_tsa_spectrum_bivar_cov (g13ccc).
     * Multivariate time series, smoothed sample cross spectrum
     * using rectangular, Bartlett, Tukey or Parzen lag window
     */
    nag_tsa_spectrum_bivar_cov(nxy, mtxy, pxy, iw, mw, ish, ic, nc, cxy, cyx,
                               kc, lf, xg, yg, g, &ng, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_tsa_spectrum_bivar_cov (g13ccc).\n%s\n",
              fail.message);
        exit_status = 1;
        goto END;
    }

    printf("\n");
    printf("                Returned cross covariances\n");
    printf("\n");
    printf("Lag      XY      YX      Lag      XY      YX      Lag"
          "\n      XY      YX\n");
    for (i = 1; i <= nc; i += 3) {
        for (ii = i; ii <= MIN(i + 2, nc); ++ii)
            printf("%4" NAG_IFMT "%9.4f%9.4f ", ii - 1, cxy[ii - 1], cyx[ii - 1]);
        printf("\n");
    }

    printf("\n");
    printf("                Returned sample spectrum\n");
    printf("\n");
    printf("          Real Imaginary          Real Imaginary "
          "\n          Real Imaginary\n");
    printf("Lag  part  part  Lag  part  part  Lag"
          "\n  part  part\n");
    for (i = 1; i <= ng; i += 3) {
        for (ii = i; ii <= MIN(i + 2, ng); ++ii)
            printf("%4" NAG_IFMT "%9.4f%9.4f ", ii - 1, g[ii - 1].re,
                  g[ii - 1].im);
        printf("\n");
    }
}

END:
    NAG_FREE(cxy);
    NAG_FREE(cyx);
    NAG_FREE(xg);
    NAG_FREE(yg);
    NAG_FREE(g);

    return exit_status;
}

```

10.2 Program Data

```

nag_tsa_spectrum_bivar_cov (g13ccc) Example Program Data
296 50 0
-0.109 0.000 0.178 0.339 0.373 0.441 0.461 0.348
0.127 -0.180 -0.588 -1.055 -1.421 -1.520 -1.302 -0.814
-0.475 -0.193 0.088 0.435 0.771 0.866 0.875 0.891
0.987 1.263 1.775 1.976 1.934 1.866 1.832 1.767

```



```

1.608 1.265 0.790 0.360 0.115 0.088 0.331 0.645
0.960 1.409 2.670 2.834 2.812 2.483 1.929 1.485
1.214 1.239 1.608 1.905 2.023 1.815 0.535 0.122
0.009 0.164 0.671 1.019 1.146 1.155 1.112 1.121
1.223 1.257 1.157 0.913 0.620 0.255 -0.280 -1.080
-1.551 -1.799 -1.825 -1.456 -0.944 -0.570 -0.431 -0.577
-0.960 -1.616 -1.875 -1.891 -1.746 -1.474 -1.201 -0.927
-0.524 0.040 0.788 0.943 0.930 1.006 1.137 1.198
1.054 0.595 -0.080 -0.314 -0.288 -0.153 -0.109 -0.187
-0.255 -0.299 -0.007 0.254 0.330 0.102 -0.423 -1.139
-2.275 -2.594 -2.716 -2.510 -1.790 -1.346 -1.081 -0.910
-0.876 -0.885 -0.800 -0.544 -0.416 -0.271 0.000 0.403
0.841 1.285 1.607 1.746 1.683 1.485 0.993 0.648
0.577 0.577 0.632 0.747 0.999 0.993 0.968 0.790
0.399 -0.161 -0.553 -0.603 -0.424 -0.194 -0.049 0.060
0.161 0.301 0.517 0.566 0.560 0.573 0.592 0.671
0.933 1.337 1.460 1.353 0.772 0.218 -0.237 -0.714
-1.099 -1.269 -1.175 -0.676 0.033 0.556 0.643 0.484
0.109 -0.310 -0.697 -1.047 -1.218 -1.183 -0.873 -0.336
0.063 0.084 0.000 0.001 0.209 0.556 0.782 0.858
0.918 0.862 0.416 -0.336 -0.959 -1.813 -2.378 -2.499
-2.473 -2.330 -2.053 -1.739 -1.261 -0.569 -0.137 -0.024
-0.050 -0.135 -0.276 -0.534 -0.871 -1.243 -1.439 -1.422
-1.175 -0.813 -0.634 -0.582 -0.625 -0.713 -0.848 -1.039
-1.346 -1.628 -1.619 -1.149 -0.488 -0.160 -0.007 -0.092
-0.620 -1.086 -1.525 -1.858 -2.029 -2.024 -1.961 -1.952
-1.794 -1.302 -1.030 -0.918 -0.798 -0.867 -1.047 -1.123
-0.876 -0.395 0.185 0.662 0.709 0.605 0.501 0.603
0.943 1.223 1.249 0.824 0.102 0.025 0.382 0.922
1.032 0.866 0.527 0.093 -0.458 -0.748 -0.947 -1.029
-0.928 -0.645 -0.424 -0.276 -0.158 -0.033 0.102 0.251
0.280 0.000 -0.493 -0.759 -0.824 -0.740 -0.528 -0.204
0.034 0.204 0.253 0.195 0.131 0.017 -0.182 -0.262
53.8 53.6 53.5 53.5 53.4 53.1 52.7 52.4 52.2 52.0 52.0 52.4 53.0 54.0 54.9 56.0
56.8 56.8 56.4 55.7 55.0 54.3 53.2 52.3 51.6 51.2 50.8 50.5 50.0 49.2 48.4 47.9
47.6 47.5 47.5 47.6 48.1 49.0 50.0 51.1 51.8 51.9 51.7 51.2 50.0 48.3 47.0 45.8
45.6 46.0 46.9 47.8 48.2 48.3 47.9 47.2 47.2 48.1 49.4 50.6 51.5 51.6 51.2 50.5
50.1 49.8 49.6 49.4 49.3 49.2 49.3 49.7 50.3 51.3 52.8 54.4 56.0 56.9 57.5 57.3
56.6 56.0 55.4 55.4 56.4 57.2 58.0 58.4 58.4 58.1 57.7 57.0 56.0 54.7 53.2 52.1
51.6 51.0 50.5 50.4 51.0 51.8 52.4 53.0 53.4 53.6 53.7 53.8 53.8 53.8 53.3 53.0
52.9 53.4 54.6 56.4 58.0 59.4 60.2 60.0 59.4 58.4 57.6 56.9 56.4 56.0 55.7 55.3
55.0 54.4 53.7 52.8 51.6 50.6 49.4 48.8 48.5 48.7 49.2 49.8 50.4 50.7 50.9 50.7
50.5 50.4 50.2 50.4 51.2 52.3 53.2 53.9 54.1 54.0 53.6 53.2 53.0 52.8 52.3 51.9
51.6 51.6 51.4 51.2 50.7 50.0 49.4 49.3 49.7 50.6 51.8 53.0 54.0 55.3 55.9 55.9
54.6 53.5 52.4 52.1 52.3 53.0 53.8 54.6 55.4 55.9 55.9 55.2 54.4 53.7 53.6 53.6
53.2 52.5 52.0 51.4 51.0 50.9 52.4 53.5 55.6 58.0 59.5 60.0 60.4 60.5 60.2 59.7
59.0 57.6 56.4 55.2 54.5 54.1 54.1 54.4 55.5 56.2 57.0 57.3 57.4 57.0 56.4 55.9
55.5 55.3 55.2 55.4 56.0 56.5 57.1 57.3 56.8 55.6 55.0 54.1 54.3 55.3 56.4 57.2
57.8 58.3 58.6 58.8 58.8 58.6 58.0 57.4 57.0 56.4 56.3 56.4 56.4 56.0 55.2 54.0
53.0 52.0 51.6 51.6 51.1 50.4 50.0 50.0 52.0 54.0 55.1 54.5 52.8 51.4 50.8 51.2
52.0 52.8 53.8 54.5 54.9 54.9 54.8 54.4 53.7 53.3 52.8 52.6 52.6 53.0 54.3 56.0
57.0 58.0 58.6 58.5 58.3 57.8 57.3 57.0

```

10.3 Program Results

nag_tsa_spectrum_bivar_cov (g13ccc) Example Program Results

Returned cross covariances

Lag	XY	YX	Lag	XY	YX	Lag	XY	YX
0	-1.6700	-1.6700	1	-2.0581	-1.3606	2	-2.4859	-1.1383
3	-2.8793	-0.9926	4	-3.1473	-0.9009	5	-3.2239	-0.8382
6	-3.0929	-0.7804	7	-2.7974	-0.7074	8	-2.4145	-0.6147
9	-2.0237	-0.5080	10	-1.6802	-0.4032	11	-1.4065	-0.3159
12	-1.2049	-0.2554	13	-1.0655	-0.2250	14	-0.9726	-0.2238
15	-0.9117	-0.2454	16	-0.8658	-0.2784	17	-0.8180	-0.3081
18	-0.7563	-0.3257	19	-0.6750	-0.3315	20	-0.5754	-0.3321
21	-0.4701	-0.3308	22	-0.3738	-0.3312	23	-0.3023	-0.3332
24	-0.2665	-0.3384	25	-0.2645	-0.3506	26	-0.2847	-0.3727
27	-0.3103	-0.3992	28	-0.3263	-0.4152	29	-0.3271	-0.4044

30	-0.3119	-0.3621	31	-0.2837	-0.2919	32	-0.2568	-0.2054
33	-0.2427	-0.1185	34	-0.2490	-0.0414	35	-0.2774	0.0227
36	-0.3218	0.0697	37	-0.3705	0.1039	38	-0.4083	0.1356
39	-0.4197	0.1805	40	-0.3920	0.2460	41	-0.3241	0.3319
42	-0.2273	0.4325	43	-0.1216	0.5331	44	-0.0245	0.6199
45	0.0528	0.6875	46	0.1074	0.7329	47	0.1448	0.7550
48	0.1713	0.7544	49	0.1943	0.7349			

Returned sample spectrum

Lag	Real part	Imaginary part	Lag	Real part	Imaginary part	Lag	Real part	Imaginary part
0	-6.5500	0.0000	1	-5.4267	-1.9842	2	-3.1323	-2.7307
3	-1.2649	-2.3998	4	-0.2102	-1.7520	5	0.3411	-1.1903
6	0.6063	-0.7420	7	0.6178	-0.3586	8	0.4391	-0.1008
9	0.2422	0.0061	10	0.1233	0.0409	11	0.0574	0.0529
12	0.0174	0.0452	13	-0.0008	0.0289	14	-0.0058	0.0161
15	-0.0051	0.0084	16	-0.0027	0.0040	17	-0.0010	0.0015
18	-0.0006	0.0006	19	-0.0005	0.0003	20	-0.0003	0.0003
21	-0.0003	0.0004	22	-0.0003	0.0003	23	-0.0003	0.0002
24	-0.0004	0.0001	25	-0.0004	-0.0000	26	-0.0003	-0.0001
27	-0.0002	-0.0001	28	-0.0001	0.0001	29	-0.0002	0.0003
30	-0.0003	0.0002	31	-0.0002	0.0001	32	-0.0001	0.0000
33	-0.0000	-0.0000	34	0.0001	-0.0001	35	0.0001	-0.0002
36	0.0001	-0.0001	37	0.0001	-0.0001	38	0.0001	-0.0001
39	0.0001	-0.0001	40	0.0001	0.0000			
