

NAG Library Function Document

nag_bessel_k_nu (s18efc)

1 Purpose

nag_bessel_k_nu (s18efc) returns the value of the modified Bessel function $K_{\nu/4}(x)$ for real $x > 0$.

2 Specification

```
#include <nag.h>
#include <nags.h>
double nag_bessel_k_nu (double x, Integer nu, NagError *fail)
```

3 Description

nag_bessel_k_nu (s18efc) evaluates an approximation to the modified Bessel function of the second kind $K_{\nu/4}(x)$, where the order $\nu = -3, -2, -1, 1, 2$ or 3 and x is real and positive. For negative orders the formula

$$K_{-\nu/4}(x) = K_{\nu/4}(x)$$

is used.

4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

5 Arguments

- | | | |
|----|--|---------------------|
| 1: | x – double | <i>Input</i> |
| | <i>On entry:</i> the argument x of the function.
<i>Constraint:</i> $x > 0.0$. | |
| 2: | nu – Integer | <i>Input</i> |
| | <i>On entry:</i> the argument ν of the function.
<i>Constraint:</i> $1 \leq \text{abs}(\mathbf{nu}) \leq 3$. | |
| 3: | fail – NagError * | <i>Input/Output</i> |
| | The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation). | |

6 Error Indicators and Warnings

NE_INT

On entry, **nu** = $\langle \text{value} \rangle$.
Constraint: $1 \leq \text{abs}(\mathbf{nu}) \leq 3$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_OVERFLOW_LIKELY

The evaluation has been abandoned due to the likelihood of overflow. The result is returned as zero.

NE_REAL

On entry, $x = \langle value \rangle$.
Constraint: $x > 0.0$.

NE_TERMINATION_FAILURE

The evaluation has been abandoned due to failure to satisfy the termination condition. The result is returned as zero.

NE_TOTAL_PRECISION_LOSS

The evaluation has been abandoned due to total loss of precision. The result is returned as zero.

NW_SOME_PRECISION_LOSS

The evaluation has been completed but some precision has been lost.

7 Accuracy

All constants in the underlying function are specified to approximately 18 digits of precision. If t denotes the number of digits of precision in the floating-point arithmetic being used, then clearly the maximum number of correct digits in the results obtained is limited by $p = \min(t, 18)$. Because of errors in argument reduction when computing elementary functions inside the underlying function, the actual number of correct digits is limited, in general, by $p - s$, where $s \approx \max(1, |\log_{10} x|)$ represents the number of digits lost due to the argument reduction. Thus the larger the value of x , the less the precision in the result.

8 Parallelism and Performance

nag_bessel_k_nu (s18efc) is not threaded in any implementation.

9 Further Comments

None.

10 Example

The example program reads values of the arguments x and ν from a file, evaluates the function and prints the results.

10.1 Program Text

```
/* nag_bessel_k_nu (s18efc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * NAG C Library
 *
 * Mark 26, 2016.
```

```

*/

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nags.h>

int main(void)
{
    Integer exit_status = 0, nu;
    NagError fail;
    double x, y;

    INIT_FAIL(fail);

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n]");
#else
    scanf("%*[\n]");
#endif
    printf("nag_bessel_k_nu (s18efc) Example Program Results\n");
    printf("  x          nu          y\n");
#ifdef _WIN32
    while (scanf_s("%lf %" NAG_IFMT "%*[\n]", &x, &nu) != EOF)
#else
    while (scanf("%lf %" NAG_IFMT "%*[\n]", &x, &nu) != EOF)
#endif
    #endif
    {
        /* nag_bessel_k_nu (s18efc).
        * Modified Bessel function K_(nu/4)(x)
        */
        y = nag_bessel_k_nu(x, nu, &fail);
        if (fail.code != NE_NOERROR) {
            printf("Error from nag_bessel_k_nu (s18efc).\n%s\n", fail.message);
            exit_status = 1;
            goto END;
        }
        printf("%4.1f %6" NAG_IFMT " %13.4e\n", x, nu, y);
    }
END:
    return exit_status;
}

```

10.2 Program Data

```

nag_bessel_k_nu (s18efc) Example Program Data
3.9  -3
1.4  -2
8.2  -1
6.7   1
0.5   2
2.3   3 : Values of x and nu

```

10.3 Program Results

```

nag_bessel_k_nu (s18efc) Example Program Results
  x          nu          y
3.9         -3    1.3315e-02
1.4         -2    2.6121e-01
8.2         -1    1.1892e-04
6.7          1    5.8826e-04
0.5          2    1.0750e+00
2.3          3    8.7724e-02

```
