

# NAG Library Routine Document

## F01VMF (ZTFTTP)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F01VMF (ZTFTTP) copies a complex triangular matrix stored in a Rectangular Full Packed (RFP) format to packed format. The RFP storage format is described in Section 3.3.3 in the F07 Chapter Introduction and the packed storage format is described in Section 3.3.2 in the F07 Chapter Introduction.

### 2 Specification

```
SUBROUTINE F01VMF (TRANSR, UPLO, N, ARF, AP, INFO)
```

```
INTEGER                N, INFO
COMPLEX (KIND=nag_wp) ARF(N*(N+1)/2), AP(N*(N+1)/2)
CHARACTER(1)          TRANSR, UPLO
```

The routine may be called by its LAPACK name *zfttp*.

### 3 Description

F01VMF (ZTFTTP) packs a complex  $n$  by  $n$  triangular matrix  $A$  stored in RFP format to packed format. This routine is intended for possible use in conjunction with routines from Chapters F06 and F07 where some routines that use triangular matrices store them in RFP format.

### 4 References

None.

### 5 Parameters

- 1: TRANSR – CHARACTER(1) *Input*  
*On entry:* specifies whether the normal RFP representation of  $A$  or its conjugate transpose is stored.  
 TRANSR = 'N'  
     The matrix  $A$  is stored in normal RFP format.  
 TRANSR = 'C'  
     The conjugate transpose of the RFP representation of the matrix  $A$  is stored.  
*Constraint:* TRANSR = 'N' or 'C'.
- 2: UPLO – CHARACTER(1) *Input*  
*On entry:* specifies whether  $A$  is upper or lower triangular.  
 UPLO = 'U'  
      $A$  is upper triangular.  
 UPLO = 'L'  
      $A$  is lower triangular.  
*Constraint:* UPLO = 'U' or 'L'.

- 3: N – INTEGER *Input*  
*On entry:*  $n$ , the order of the matrix  $A$ .  
*Constraint:*  $N \geq 0$ .
- 4: ARF( $N \times (N + 1)/2$ ) – COMPLEX (KIND=nag\_wp) array *Input*  
*On entry:* the triangular matrix  $A$  in RFP format, as described in Section 3.3.3 in the F07 Chapter Introduction.
- 5: AP( $N \times (N + 1)/2$ ) – COMPLEX (KIND=nag\_wp) array *Output*  
*On exit:* the  $n$  by  $n$  triangular matrix  $A$ , packed by columns.  
 More precisely,  
   if UPLO = 'U', the upper triangle of  $A$  is stored with element  $A_{ij}$  in AP( $i + j(j - 1)/2$ ) for  $i \leq j$ ;  
   if UPLO = 'L', the lower triangle of  $A$  is stored with element  $A_{ij}$  in AP( $i + (2n - j)(j - 1)/2$ ) for  $i \geq j$ .
- 6: INFO – INTEGER *Output*  
*On exit:* INFO = 0 unless the routine detects an error (see Section 6).

## 6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO =  $-i$ , argument  $i$  had an illegal value. An explanatory message is output, and execution of the program is terminated.

## 7 Accuracy

Not applicable.

## 8 Further Comments

None.

## 9 Example

This example reads in a triangular matrix in RFP format and copies it to packed format.

### 9.1 Program Text

```

Program f01vmfe

!   F01VMF Example Program Text
!   Mark 24 Release. NAG Copyright 2012.

!   .. Use Statements ..
!   Use nag_library, Only: nag_wp, x04dbf, ztfttp
!   .. Implicit None Statement ..
!   Implicit None
!   .. Parameters ..
Integer, Parameter          :: incl = 1, indent = 0, ncols = 80,    &
                             nin = 5, nout = 6
Character (1), Parameter   :: brac = 'B', diag = 'N', intlabel =    &
                             'I', matrix = 'G', nolabel = 'N'

```

```

Character (4), Parameter      :: form = 'F5.2'
! .. Local Scalars ..
Integer                      :: ifail, info, lenap, lenarf, n
Character (21)                :: title
Character (1)                 :: transr, uplo
! .. Local Arrays ..
Complex (Kind=nag_wp), Allocatable :: ap(:), arf(:)
Character (1)                  :: clabs(1), rlabs(1)
! .. Executable Statements ..
Write (nout,*) 'F01VMF Example Program Results'
! Skip heading in data file
Read (nin,*)
Write (nout,*)
Flush (nout)
Read (nin,*) n, uplo, transr
lenap = (n*(n+1))/2
lenarf = lenap

Allocate (ap(lenap),arf(lenarf))

! Read an RFP matrix into array ARF
Read (nin,*) arf

! Print the Rectangular Full Packed array
title = 'RFP Packed Array ARF:'
ifail = 0
Call x04dbf(matrix,diag,lenarf,incl,arf,lenarf,brac,form,title,intlabel, &
  rlabs,nolabel,clabs,ncols,indent,ifail)

Write (nout,*)
Flush (nout)

! Convert to packed vector form
info = 0
! The NAG name equivalent of ztfttp is f01vmf
Call ztfttp(transr,uplo,n,arf,ap,info)

! Print the packed vector
title = 'Packed Array AP:      '
ifail = 0
Call x04dbf(matrix,diag,lenap,incl,ap,lenap,brac,form,title,intlabel, &
  rlabs,nolabel,clabs,ncols,indent,ifail)

End Program f01vmfe

```

## 9.2 Program Data

```

F01VMF Example Program Data
4 'U' 'N'                : n, uplo, 'N'
( 1.10, 1.10)
( 1.20, 1.20)
( 2.20, 2.20)
( 1.30, 1.30)
( 2.30, 2.30)
( 3.30, 3.30)
( 1.40, 1.40)
( 2.40, 2.40)
( 3.40, 3.40)
( 4.40, 4.40)          : RFP Array ARF

```

## 9.3 Program Results

F01VMF Example Program Results

```

RFP Packed Array ARF:
1 ( 1.10, 1.10)
2 ( 1.20, 1.20)
3 ( 2.20, 2.20)
4 ( 1.30, 1.30)
5 ( 2.30, 2.30)

```

```
6 ( 3.30, 3.30)
7 ( 1.40, 1.40)
8 ( 2.40, 2.40)
9 ( 3.40, 3.40)
10 ( 4.40, 4.40)
```

Packed Array AP:

```
1 ( 1.30,-1.30)
2 ( 2.30,-2.30)
3 ( 4.40,-4.40)
4 ( 1.10, 1.10)
5 ( 1.20, 1.20)
6 ( 2.20, 2.20)
7 ( 3.30, 3.30)
8 ( 1.40, 1.40)
9 ( 2.40, 2.40)
10 ( 3.40, 3.40)
```

---