

NAG Library Routine Document

F06EWF (DSCTR)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06EWF (DSCTR) scatters the elements of a sparse real vector x stored in compressed form, into a real vector y in full storage form.

2 Specification

```
SUBROUTINE F06EWF (NZ, X, INDX, Y)
```

```
INTEGER          NZ, INDX(*)
```

```
REAL (KIND=nag_wp) X(*), Y(*)
```

The routine may be called by its BLAS name *dsctr*.

3 Description

F06EWF (DSCTR) scatters the elements of a vector x , stored in compressed form, into a vector, y , in full storage form.

4 References

Dodson D S, Grimes R G and Lewis J G (1991) Sparse extensions to the Fortran basic linear algebra subprograms *ACM Trans. Math. Software* **17** 253–263

5 Parameters

- | | | |
|----|---|---------------|
| 1: | NZ – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the number of nonzeros in the sparse vector x . | |
| 2: | X(*) – REAL (KIND=nag_wp) array | <i>Input</i> |
| | Note: the dimension of the array X must be at least $\max(1, \text{NZ})$. | |
| | <i>On entry:</i> the nonzero elements of the sparse vector x . | |
| 3: | INDX(*) – INTEGER array | <i>Input</i> |
| | Note: the dimension of the array INDX must be at least $\max(1, \text{NZ})$. | |
| | <i>On entry:</i> INDX(i) must contain the index of X(i) in the sparse vector x , for $i = 1, 2, \dots, \text{NZ}$. | |
| | <i>Constraint:</i> the indices must be distinct. | |
| 4: | Y(*) – REAL (KIND=nag_wp) array | <i>Output</i> |
| | Note: the dimension of the array Y must be at least $\max_k \{\text{INDX}(k)\}$. | |
| | <i>On exit:</i> the vector y . Only elements corresponding to indices in INDX are altered. | |

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

None.
