

# NAG Library Routine Document

## F08HAF (DSBEV)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F08HAF (DSBEV) computes all the eigenvalues and, optionally, all the eigenvectors of a real  $n$  by  $n$  symmetric band matrix  $A$  of bandwidth  $(2k_d + 1)$ .

### 2 Specification

```
SUBROUTINE F08HAF (JOBZ, UPLO, N, KD, AB, LDAB, W, Z, LDZ, WORK, INFO)
```

```
INTEGER          N, KD, LDAB, LDZ, INFO
REAL (KIND=nag_wp) AB(LDAB,*), W(N), Z(LDZ,*), WORK(3*N-2)
CHARACTER(1)     JOBZ, UPLO
```

The routine may be called by its LAPACK name *dsbev*.

### 3 Description

The symmetric band matrix  $A$  is first reduced to tridiagonal form, using orthogonal similarity transformations, and then the  $QR$  algorithm is applied to the tridiagonal matrix to compute the eigenvalues and (optionally) the eigenvectors.

### 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

### 5 Parameters

1: JOBZ – CHARACTER(1) *Input*

*On entry:* indicates whether eigenvectors are computed.

JOBZ = 'N'

Only eigenvalues are computed.

JOBZ = 'V'

Eigenvalues and eigenvectors are computed.

*Constraint:* JOBZ = 'N' or 'V'.

2: UPLO – CHARACTER(1) *Input*

*On entry:* if UPLO = 'U', the upper triangular part of  $A$  is stored.

If UPLO = 'L', the lower triangular part of  $A$  is stored.

*Constraint:* UPLO = 'U' or 'L'.

- 3: N – INTEGER *Input*  
*On entry:*  $n$ , the order of the matrix  $A$ .  
*Constraint:*  $N \geq 0$ .
- 4: KD – INTEGER *Input*  
*On entry:* if UPLO = 'U', the number of superdiagonals,  $k_d$ , of the matrix  $A$ .  
 If UPLO = 'L', the number of subdiagonals,  $k_d$ , of the matrix  $A$ .  
*Constraint:*  $KD \geq 0$ .
- 5: AB(LDAB,\*) – REAL (KIND=nag\_wp) array *Input/Output*  
**Note:** the second dimension of the array AB must be at least  $\max(1, N)$ .  
*On entry:* the upper or lower triangle of the  $n$  by  $n$  symmetric band matrix  $A$ .  
 The matrix is stored in rows 1 to  $k_d + 1$ , more precisely,  
     if UPLO = 'U', the elements of the upper triangle of  $A$  within the band must be stored with  
     element  $A_{ij}$  in  $AB(k_d + 1 + i - j, j)$  for  $\max(1, j - k_d) \leq i \leq j$ ;  
     if UPLO = 'L', the elements of the lower triangle of  $A$  within the band must be stored with  
     element  $A_{ij}$  in  $AB(1 + i - j, j)$  for  $j \leq i \leq \min(n, j + k_d)$ .  
*On exit:* AB is overwritten by values generated during the reduction to tridiagonal form.  
 The first superdiagonal or subdiagonal and the diagonal of the tridiagonal matrix  $T$  are returned in  
 AB using the same storage format as described above.
- 6: LDAB – INTEGER *Input*  
*On entry:* the first dimension of the array AB as declared in the (sub)program from which F08HAF  
 (DSBEV) is called.  
*Constraint:*  $LDAB \geq KD + 1$ .
- 7: W(N) – REAL (KIND=nag\_wp) array *Output*  
*On exit:* the eigenvalues in ascending order.
- 8: Z(LDZ,\*) – REAL (KIND=nag\_wp) array *Output*  
**Note:** the second dimension of the array Z must be at least  $\max(1, N)$  if JOBZ = 'V', and at least 1  
 otherwise.  
*On exit:* if JOBZ = 'V', Z contains the orthonormal eigenvectors of the matrix  $A$ , with the  $i$ th  
 column of Z holding the eigenvector associated with  $W(i)$ .  
 If JOBZ = 'N', Z is not referenced.
- 9: LDZ – INTEGER *Input*  
*On entry:* the first dimension of the array Z as declared in the (sub)program from which F08HAF  
 (DSBEV) is called.  
*Constraints:*  
     if JOBZ = 'V',  $LDZ \geq \max(1, N)$ ;  
     otherwise  $LDZ \geq 1$ .
- 10: WORK( $3 \times N - 2$ ) – REAL (KIND=nag\_wp) array *Workspace*
- 11: INFO – INTEGER *Output*  
*On exit:* INFO = 0 unless the routine detects an error (see Section 6).

## 6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO =  $-i$ , argument  $i$  had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

If INFO =  $i$ , the algorithm failed to converge;  $i$  off-diagonal elements of an intermediate tridiagonal form did not converge to zero.

## 7 Accuracy

The computed eigenvalues and eigenvectors are exact for a nearby matrix  $(A + E)$ , where

$$\|E\|_2 = O(\epsilon)\|A\|_2,$$

and  $\epsilon$  is the *machine precision*. See Section 4.7 of Anderson *et al.* (1999) for further details.

## 8 Further Comments

The total number of floating point operations is proportional to  $n^3$  if JOBZ = 'V' and is proportional to  $k_d n^2$  otherwise.

The complex analogue of this routine is F08HNF (ZHBEV).

## 9 Example

This example finds all the eigenvalues and eigenvectors of the symmetric band matrix

$$A = \begin{pmatrix} 1 & 2 & 3 & 0 & 0 \\ 2 & 2 & 3 & 4 & 0 \\ 3 & 3 & 3 & 4 & 5 \\ 0 & 4 & 4 & 4 & 5 \\ 0 & 0 & 5 & 5 & 5 \end{pmatrix},$$

together with approximate error bounds for the computed eigenvalues and eigenvectors.

### 9.1 Program Text

```

Program f08hafa
!
!   F08HAF Example Program Text
!
!   Mark 24 Release. NAG Copyright 2012.
!
!   .. Use Statements ..
!   Use nag_library, Only: ddisna, dsbev, nag_wp, x02ajf, x04caf
!   .. Implicit None Statement ..
!   Implicit None
!   .. Parameters ..
!   Integer, Parameter          :: nin = 5, nout = 6
!   Character (1), Parameter    :: uplo = 'U'
!   .. Local Scalars ..
!   Real (Kind=nag_wp)          :: eerrbd, eps
!   Integer                      :: i, ifail, info, j, kd, ldab, ldz, n
!   .. Local Arrays ..
!   Real (Kind=nag_wp), Allocatable :: ab(:,,:), rcondz(:), w(:), work(:), &
!                                     z(:,,:), zerrbd(:)
!
!   .. Intrinsic Procedures ..
!   Intrinsic                    :: abs, max, min
!   .. Executable Statements ..

```

```

Write (nout,*) 'F08HAF Example Program Results'
Write (nout,*)
! Skip heading in data file
Read (nin,*)
Read (nin,*) n, kd
ldab = kd + 1
ldz = n
Allocate (ab(ldab,n),rcondz(n),w(n),work(3*n-2),z(ldz,n),zerrbd(n))

! Read the upper or lower triangular part of the symmetric band
! matrix A from data file

If (uplo=='U') Then
  Read (nin,*)((ab(kd+1+i-j,j),j=i,min(n,i+kd)),i=1,n)
Else If (uplo=='L') Then
  Read (nin,*)((ab(1+i-j,j),j=max(1,i-kd),i),i=1,n)
End If

! Solve the band symmetric eigenvalue problem

! The NAG name equivalent of dsbev is f08haf
Call dsbev('Vectors',uplo,n,kd,ab,ldab,w,z,ldz,work,info)

If (info==0) Then

!   Print solution

  Write (nout,*) 'Eigenvalues'
  Write (nout,99999) w(1:n)
  Flush (nout)

!   Standardize the eigenvectors so that first elements are non-negative.
  Do i = 1, n
    If (z(1,i)<0.0_nag_wp) z(1:n,i) = -z(1:n,i)
  End Do

!   ifail: behaviour on error exit
!           =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
  ifail = 0
  Call x04caf('General',' ',n,n,z,ldz,'Eigenvectors',ifail)

!   Get the machine precision, EPS and compute the approximate
!   error bound for the computed eigenvalues. Note that for
!   the 2-norm, max( abs(W(i)) ) = norm(A), and since the
!   eigenvalues are returned in ascending order
!   max( abs(W(i)) ) = max( abs(W(1)), abs(W(n)) )

  eps = x02ajf()
  eerrbd = eps*max(abs(w(1)),abs(w(n)))

!   Call DDISNA (F08FLF) to estimate reciprocal condition
!   numbers for the eigenvectors
  Call ddisna('Eigenvectors',n,n,w,rcondz,info)

!   Compute the error estimates for the eigenvectors

  Do i = 1, n
    zerrbd(i) = eerrbd/rcondz(i)
  End Do

!   Print the approximate error bounds for the eigenvalues
!   and vectors

  Write (nout,*)
  Write (nout,*) 'Error estimate for the eigenvalues'
  Write (nout,99998) eerrbd
  Write (nout,*)
  Write (nout,*) 'Error estimates for the eigenvectors'
  Write (nout,99998) zerrbd(1:n)
Else
  Write (nout,99997) 'Failure in DSBEV. INFO =', info

```

```

      End If

99999 Format (3X,(8F8.4))
99998 Format (4X,1P,6E11.1)
99997 Format (1X,A,I4)
      End Program f08hafa

```

## 9.2 Program Data

F08HAF Example Program Data

```

5      2      :Values of N and KD

1.0  2.0  3.0
      2.0  3.0  4.0
           3.0  4.0  5.0
                4.0  5.0
                     5.0 :End of matrix A

```

## 9.3 Program Results

F08HAF Example Program Results

Eigenvalues

```
-3.2474 -2.6633  1.7511  4.1599 14.9997
```

Eigenvectors

```

      1      2      3      4      5
1  0.0394  0.6238  0.5635  0.5165  0.1582
2  0.5721 -0.2575 -0.3896  0.5955  0.3161
3 -0.4372 -0.5900  0.4008  0.1470  0.5277
4 -0.4424  0.4308 -0.5581 -0.0470  0.5523
5  0.5332  0.1039  0.2421 -0.5956  0.5400

```

Error estimate for the eigenvalues

```
1.7E-15
```

Error estimates for the eigenvectors

```
2.9E-15  2.9E-15  6.9E-16  6.9E-16  1.5E-16
```

---