

NAG Library Routine Document

F16DNF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F16DNF computes the largest component of an integer vector, along with the index of that component.

2 Specification

```
SUBROUTINE F16DNF (N, X, INCX, K, I)
```

```
INTEGER N, X(1+(N-1)*ABS(INCX)), INCX, K, I
```

3 Description

F16DNF computes the largest component, i , of an n -element integer vector x , and determines the smallest index, k , such that

$$i = x_k = \max_j x_j.$$

4 References

Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001) *Basic Linear Algebra Subprograms Technical (BLAST) Forum Standard* University of Tennessee, Knoxville, Tennessee <http://www.netlib.org/blas/blast-forum/blas-report.pdf>

5 Parameters

- | | | |
|----|---|---------------|
| 1: | N – INTEGER | <i>Input</i> |
| | <i>On entry:</i> n , the number of elements in x . | |
| 2: | X(1 + (N – 1) × INCX) – INTEGER array | <i>Input</i> |
| | <i>On entry:</i> the vector x . Element x_i is stored in X(($i - 1$) × INCX + 1), for $i = 1, 2, \dots, n$. | |
| 3: | INCX – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the increment in the subscripts of X between successive elements of x . | |
| | <i>Constraint:</i> INCX ≠ 0. | |
| 4: | K – INTEGER | <i>Output</i> |
| | <i>On exit:</i> k , the index, from the set $\{1, 1 + INCX , \dots, 1 + (N - 1) \times INCX \}$, of the largest component of x . If $N \leq 0$ on input then K is returned as 0. | |
| 5: | I – INTEGER | <i>Output</i> |
| | <i>On exit:</i> i , the largest component of x . If $N \leq 0$ on input then I is returned as 0. | |

6 Error Indicators and Warnings

If INCX = 0, an error message is printed and program execution is terminated.

7 Accuracy

The BLAS standard requires accurate implementations which avoid unnecessary over/underflow (see Section 2.7 of Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001)).

8 Further Comments

None.

9 Example

This example computes the largest component and index of that component for the vector

$$x = (1, 10, 11, -2, 9)^T.$$

9.1 Program Text

```

Program f16dnfe

!      F16DNF Example Program Text

!      Mark 24 Release. NAG Copyright 2012.

!      .. Use Statements ..
      Use nag_library, Only: f16dnf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Integer                    :: i, incx, j, k, n
!      .. Local Arrays ..
      Integer, Allocatable       :: x(:)
!      .. Intrinsic Procedures ..
      Intrinsic                  :: abs
!      .. Executable Statements ..
      Write (nout,*) 'F16DNF Example Program Results'

!      Skip heading in data file
      Read (nin,*)

      Read (nin,*) n, incx
      Allocate (x(1+(n-1)*abs(incx)))

      Read (nin,*)(x(j),j=1,1+(n-1)*abs(incx),incx)

!      Find K = ARGMAX(X) and I = MAX(X).

      Call f16dnf(n,x,incx,k,i)

      Write (nout,*)
      Write (nout,99999) k
      Write (nout,99998) i

99999 Format (1X,'Index of largest component of X is',I3)
99998 Format (1X,'Largest component of X is',I12)
      End Program f16dnfe

```

9.2 Program Data

```

F16DNF Example Program Data
  5  1                                : N and INCX
  1 10 11 -2 9                        : Array X

```

9.3 Program Results

F16DNF Example Program Results

```
Index of largest component of X is 3
Largest component of X is      11
```
