

NAG Library Routine Document

G02BRF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

G02BRF computes Kendall and/or Spearman nonparametric rank correlation coefficients for a set of data, omitting completely any cases with a missing observation for any variable; the data array is preserved, and the ranks of the observations are not available on exit from the routine.

2 Specification

```

SUBROUTINE G02BRF (N, M, X, LDX, MISS, XMISS, ITYPE, RR, LDRR, NCASES,      &
                  INCASE, KWORKA, KWORKB, KWORKC, WORK1, WORK2, IFAIL)
INTEGER           N, M, LDX, MISS(M), ITYPE, LDRR, NCASES, INCASE(N),    &
                  KWORKA(N), KWORKB(N), KWORKC(N), IFAIL
REAL (KIND=nag_wp) X(LDX,M), XMISS(M), RR(LDRR,M), WORK1(N), WORK2(N)

```

3 Description

The input data consists of n observations for each of m variables, given as an array

$$[x_{ij}], \quad i = 1, 2, \dots, n (n \geq 2), \quad j = 1, 2, \dots, m (m \geq 2),$$

where x_{ij} is the i th observation on the j th variable. In addition, each of the m variables may optionally have associated with it a value which is to be considered as representing a missing observation for that variable; the missing value for the j th variable is denoted by xm_j . Missing values need not be specified for all variables.

Let $w_i = 0$ if observation i contains a missing value for any of those variables for which missing values have been declared, i.e., if $x_{ij} = xm_j$ for any j for which an xm_j has been assigned (see also Section 7); and $w_i = 1$ otherwise, for $i = 1, 2, \dots, n$.

The observations are first ranked as follows.

For a given variable, j say, each of the observations x_{ij} for which $w_i = 1$, ($i = 1, 2, \dots, n$) has associated with it an additional number, the 'rank' of the observation, which indicates the magnitude of that observation relative to the magnitudes of the other observations on that same variable for which $w_i = 1$.

The smallest of these valid observations for variable j is assigned the rank 1, the second smallest observation for variable j the rank 2, the third smallest the rank 3, and so on until the largest such observation is given the rank n_c , where $n_c = \sum_{i=1}^n w_i$.

If a number of cases all have the same value for the given variable, j , then they are each given an 'average' rank, e.g., if in attempting to assign the rank $h + 1$, k observations for which $w_i = 1$ were found to have the same value, then instead of giving them the ranks

$$h + 1, h + 2, \dots, h + k,$$

all k observations would be assigned the rank

$$\frac{2h + k + 1}{2}$$

and the next value in ascending order would be assigned the rank

$$h + k + 1.$$

The process is repeated for each of the m variables.

Let y_{ij} be the rank assigned to the observation x_{ij} when the j th variable is being ranked. For those observations, i , for which $w_i = 0$, $y_{ij} = 0$, for $j = 1, 2, \dots, m$.

The quantities calculated are:

(a) Kendall's tau rank correlation coefficients:

$$R_{jk} = \frac{\sum_{h=1}^n \sum_{i=1}^n w_h w_i \operatorname{sign}(y_{hj} - y_{ij}) \operatorname{sign}(y_{hk} - y_{ik})}{\sqrt{[n_c(n_c - 1) - T_j][n_c(n_c - 1) - T_k]}}, \quad j, k = 1, 2, \dots, m,$$

$$\text{where } n_c = \sum_{i=1}^n w_i$$

and $\operatorname{sign} u = 1$ if $u > 0$

$\operatorname{sign} u = 0$ if $u = 0$

$\operatorname{sign} u = -1$ if $u < 0$

and $T_j = \sum t_j(t_j - 1)$ where t_j is the number of ties of a particular value of variable j , and the summation is over all tied values of variable j .

(b) Spearman's rank correlation coefficients:

$$R_{jk}^* = \frac{n_c(n_c^2 - 1) - 6 \sum_{i=1}^n w_i (y_{ij} - y_{ik})^2 - \frac{1}{2}(T_j^* + T_k^*)}{\sqrt{[n_c(n_c^2 - 1) - T_j^*][n_c(n_c^2 - 1) - T_k^*]}}, \quad j, k = 1, 2, \dots, m,$$

where $n_c = \sum_{i=1}^n w_i$ and $T_j^* = \sum t_j(t_j^2 - 1)$ where t_j is the number of ties of a particular value of variable j , and the summation is over all tied values of variable j .

4 References

Siegel S (1956) *Non-parametric Statistics for the Behavioral Sciences* McGraw-Hill

5 Parameters

- 1: N – INTEGER *Input*
On entry: n , the number of observations or cases.
Constraint: $N \geq 2$.
- 2: M – INTEGER *Input*
On entry: m , the number of variables.
Constraint: $M \geq 2$.
- 3: X(LDX,M) – REAL (KIND=nag_wp) array *Input*
On entry: $X(i, j)$ must be set to x_{ij} , the value of the i th observation on the j th variable, where $i = 1, 2, \dots, n$ and $j = 1, 2, \dots, m$.

- 4: LDX – INTEGER *Input*
On entry: the first dimension of the array X as declared in the (sub)program from which G02BRF is called.
Constraint: $LDX \geq N$.
- 5: MISS(M) – INTEGER array *Input/Output*
On entry: MISS(*j*) must be set equal to 1 if a missing value, x_{m_j} , is to be specified for the *j*th variable in the array X, or set equal to 0 otherwise. Values of MISS must be given for all *m* variables in the array X.
On exit: the array MISS is overwritten by the routine, and the information it contained on entry is lost.
- 6: XMISS(M) – REAL (KIND=nag_wp) array *Input/Output*
On entry: XMISS(*j*) must be set to the missing value, x_{m_j} , to be associated with the *j*th variable in the array X, for those variables for which missing values are specified by means of the array MISS (see Section 7).
On exit: the array XMISS is overwritten by the routine, and the information it contained on entry is lost.
- 7: ITYPE – INTEGER *Input*
On entry: the type of correlation coefficients which are to be calculated.
 ITYPE = -1
 Only Kendall's tau coefficients are calculated.
 ITYPE = 0
 Both Kendall's tau and Spearman's coefficients are calculated.
 ITYPE = 1
 Only Spearman's coefficients are calculated.
Constraint: ITYPE = -1, 0 or 1.
- 8: RR(LDRR,M) – REAL (KIND=nag_wp) array *Output*
On exit: the requested correlation coefficients.
 If only Kendall's tau coefficients are requested (ITYPE = -1), RR(*j*, *k*) contains Kendall's tau for the *j*th and *k*th variables.
 If only Spearman's coefficients are requested (ITYPE = 1), RR(*j*, *k*) contains Spearman's rank correlation coefficient for the *j*th and *k*th variables.
 If both Kendall's tau and Spearman's coefficients are requested (ITYPE = 0), the upper triangle of RR contains the Spearman coefficients and the lower triangle the Kendall coefficients. That is, for the *j*th and *k*th variables, where *j* is less than *k*, RR(*j*, *k*) contains the Spearman rank correlation coefficient, and RR(*k*, *j*) contains Kendall's tau, for $j = 1, 2, \dots, m$ and $k = 1, 2, \dots, m$.
 (Diagonal terms, RR(*j*, *j*), are unity for all three values of ITYPE.)
- 9: LDRR – INTEGER *Input*
On entry: the first dimension of the array RR as declared in the (sub)program from which G02BRF is called.
Constraint: $LDRR \geq M$.
- 10: NCASES – INTEGER *Output*
On exit: the number of cases, n_c , actually used in the calculations (when cases involving missing values have been eliminated).

- 11: INCASE(N) – INTEGER array *Output*
On exit: INCASE(i) holds the value 1 if the i th case was included in the calculations, and the value 0 if the i th case contained a missing value for at least one variable. That is, $\text{INCASE}(i) = w_i$ (see Section 3), for $i = 1, 2, \dots, n$.
- 12: KWORKA(N) – INTEGER array *Workspace*
 13: KWORKB(N) – INTEGER array *Workspace*
 14: KWORKC(N) – INTEGER array *Workspace*
 15: WORK1(N) – REAL (KIND=nag_wp) array *Workspace*
 16: WORK2(N) – REAL (KIND=nag_wp) array *Workspace*
- 17: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.
- For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**
- On exit:* IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, $N < 2$.

IFAIL = 2

On entry, $M < 2$.

IFAIL = 3

On entry, $LDX < N$,
 or $LDRR < M$.

IFAIL = 4

On entry, $ITYPE < -1$,
 or $ITYPE > 1$.

IFAIL = 5

After observations with missing values were omitted, fewer than 2 cases remained.

7 Accuracy

You are warned of the need to exercise extreme care in your selection of missing values. G02BRF treats all values in the inclusive range $\left(1 \pm 0.1^{(X02BEF-2)}\right) \times xm_j$, where xm_j is the missing value for variable j specified in XMISS.

You must therefore ensure that the missing value chosen for each variable is sufficiently different from all valid values for that variable so that none of the valid values fall within the range indicated above.

8 Further Comments

The time taken by G02BRF depends on n and m , and the occurrence of missing values.

9 Example

This example reads in a set of data consisting of nine observations on each of three variables. Missing values of 0.99 and 0.0 are declared for the first and third variables respectively; no missing value is specified for the second variable. The program then calculates and prints both Kendall's tau and Spearman's rank correlation coefficients for all three variables, omitting completely all cases containing missing values; cases 5, 8 and 9 are therefore eliminated, leaving only six cases in the calculations.

9.1 Program Text

```

Program g02brfe

!      G02BRF Example Program Text

!      Mark 24 Release. NAG Copyright 2012.

!      .. Use Statements ..
Use nag_library, Only: g02brf, nag_wp
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Integer                     :: i, ifail, itype, ldr, ldx, m, n,      &
                             ncases
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: rr(:, :), work1(:), work2(:), x(:, :), &
                             xmiss(:)
Integer, Allocatable         :: incase(:), kworka(:), kworkb(:),      &
                             kworkc(:), miss(:)
!      .. Executable Statements ..
Write (nout,*) 'G02BRF Example Program Results'
Write (nout,*)

!      Skip heading in data file
Read (nin,*)

!      Read in the problem size
Read (nin,*) n, m, itype

      ldr = m
      ldx = n
      Allocate (rr(ldr,m),work1(n),work2(n),x(ldx,m),xmiss(m),incase(n), &
               kworka(n),kworkb(n),kworkc(n),miss(m))

!      Read in data
Read (nin,*)(x(i,1:m),i=1,n)

!      Read in missing value flags
Read (nin,*) miss(1:m)
Read (nin,*) xmiss(1:m)

!      Display data
Write (nout,99999) 'Number of variables (columns) =', m
Write (nout,99999) 'Number of cases      (rows)      =', n
Write (nout,*)
Write (nout,*) 'Data matrix is:-'
Write (nout,*)
Write (nout,99998)(i,i=1,m)
Write (nout,99997)(i,x(i,1:m),i=1,n)
Write (nout,*)

!      Calculate correlation coefficients
ifail = 0

```

```

Call g02brf(n,m,x,ldx,miss,xmiss,itype,rr,ldrr,ncases,incase,kworka, &
  kworkb,kworkc,work1,work2,ifail)

!   Display results
Write (nout,*) 'Matrix of rank correlation coefficients:'
Write (nout,*) 'Upper triangle -- Spearman''s'
Write (nout,*) 'Lower triangle -- Kendall''s tau'
Write (nout,*)
Write (nout,99998)(i,i=1,m)
Write (nout,99997)(i,rr(i,1:m),i=1,m)
Write (nout,*)
Write (nout,99999) 'Number of cases actually used:', ncases

99999 Format (1X,A,I5)
99998 Format (1X,3I12)
99997 Format (1X,I3,3F12.4)
End Program g02brfe

```

9.2 Program Data

```

G02BRF Example Program Data
9 3 0 :: N, M, ITYPE
1.70 1.00 0.50
2.80 4.00 3.00
0.60 6.00 2.50
1.80 9.00 6.00
0.99 4.00 2.50
1.40 2.00 5.50
1.80 9.00 7.50
2.50 7.00 0.00
0.99 5.00 3.00 :: End of X
1 0 1 :: MISS
0.99 0.00 0.00 :: XMISS

```

9.3 Program Results

G02BRF Example Program Results

```

Number of variables (columns) = 3
Number of cases (rows) = 9

```

Data matrix is:-

	1	2	3
1	1.7000	1.0000	0.5000
2	2.8000	4.0000	3.0000
3	0.6000	6.0000	2.5000
4	1.8000	9.0000	6.0000
5	0.9900	4.0000	2.5000
6	1.4000	2.0000	5.5000
7	1.8000	9.0000	7.5000
8	2.5000	7.0000	0.0000
9	0.9900	5.0000	3.0000

```

Matrix of rank correlation coefficients:
Upper triangle -- Spearman's
Lower triangle -- Kendall's tau

```

	1	2	3
1	1.0000	0.2941	0.4058
2	0.1429	1.0000	0.7537
3	0.2760	0.5521	1.0000

```

Number of cases actually used: 6

```
