

# NAG Library Routine Document

## G05TEF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

G05TEF generates a vector of pseudorandom integers from the discrete hypergeometric distribution of the number of specified items in a sample of size  $l$ , taken from a population of size  $k$  with  $m$  specified items in it.

### 2 Specification

SUBROUTINE G05TEF (MODE, N, NS, NP, M, R, LR, STATE, X, IFAIL)

INTEGER MODE, N, NS, NP, M, LR, STATE(\*), X(N), IFAIL

REAL (KIND=nag\_wp) R(LR)

### 3 Description

G05TEF generates  $n$  integers  $x_i$  from a discrete hypergeometric distribution, where the probability of  $x_i = I$  is

$$P(i = I) = \frac{l!m!(k-l)!(k-m)!}{I!(l-I)!(m-I)!(k-m-l+I)!k!} \quad \text{if } I = \max(0, m+l-k), \dots, \min(l, m),$$

$$P(i = I) = 0 \quad \text{otherwise.}$$

The variates can be generated with or without using a search table and index. If a search table is used then it is stored with the index in a reference vector and subsequent calls to G05TEF with the same parameter values can then use this reference vector to generate further variates. The reference array is generated by a recurrence relation if  $lm(k-l)(k-m) < 50k^3$ , otherwise Stirling's approximation is used.

One of the initialization routines G05KFF (for a repeatable sequence if computed sequentially) or G05KGF (for a non-repeatable sequence) must be called prior to the first call to G05TEF.

### 4 References

Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison-Wesley

### 5 Parameters

1: MODE – INTEGER

*Input*

*On entry:* a code for selecting the operation to be performed by the routine.

MODE = 0

Set up reference vector only.

MODE = 1

Generate variates using reference vector set up in a prior call to G05TEF.

MODE = 2

Set up reference vector and generate variates.

MODE = 3

Generate variates without using the reference vector.

*Constraint:* MODE = 0, 1, 2 or 3.

- 2: N – INTEGER *Input*  
*On entry:*  $n$ , the number of pseudorandom numbers to be generated.  
*Constraint:*  $N \geq 0$ .
- 3: NS – INTEGER *Input*  
*On entry:*  $l$ , the sample size of the hypergeometric distribution.  
*Constraint:*  $0 \leq NS \leq NP$ .
- 4: NP – INTEGER *Input*  
*On entry:*  $k$ , the population size of the hypergeometric distribution.  
*Constraint:*  $NP \geq 0$ .
- 5: M – INTEGER *Input*  
*On entry:*  $m$ , the number of specified items of the hypergeometric distribution.  
*Constraint:*  $0 \leq M \leq NP$ .
- 6: R(LR) – REAL (KIND=nag\_wp) array *Communication Array*  
*On entry:* if MODE = 1, the reference vector from the previous call to G05TEF.  
 If MODE = 3, R is not referenced by G05TEF.  
*On exit:* the reference vector.
- 7: LR – INTEGER *Input*  
*On entry:* the dimension of the array R as declared in the (sub)program from which G05TEF is called.  
*Suggested value:*  
     if MODE  $\neq$  3,  $LR = 28 + 20 \times \sqrt{(NS \times M \times (NP - M) \times (NP - NS)) / NP^3}$  approximately;  
     otherwise LR = 1.  
*Constraints:*  
     if MODE = 0 or 2, LR must not be too small, but the limit is too complicated to specify;  
     if MODE = 1, LR must remain unchanged from the previous call to G05TEF.
- 8: STATE(\*) – INTEGER array *Communication Array*  
**Note:** the actual argument supplied must be the array STATE supplied to the initialization routines G05KFF or G05KGF.  
*On entry:* contains information on the selected base generator and its current state.  
*On exit:* contains updated information on the state of the generator.
- 9: X(N) – INTEGER array *Output*  
*On exit:* the pseudorandom numbers from the specified hypergeometric distribution.
- 10: IFAIL – INTEGER *Input/Output*  
*On entry:* IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value  $-1$  or  $1$  is recommended. If the output of error messages is undesirable, then the value  $1$  is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is  $0$ . **When the value  $-1$  or  $1$  is used it is essential to test the value of IFAIL on exit.**

*On exit:* IFAIL =  $0$  unless the routine detects an error or a warning has been flagged (see Section 6).

## 6 Error Indicators and Warnings

If on entry IFAIL =  $0$  or  $-1$ , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL =  $1$

On entry, MODE  $\neq 0, 1, 2$  or  $3$ .

IFAIL =  $2$

On entry,  $N < 0$ .

IFAIL =  $3$

On entry, NS  $>$  NP,  
or NS  $< 0$ .

IFAIL =  $4$

On entry, NP  $< 0$ .

IFAIL =  $5$

On entry, M  $>$  NP,  
or M  $< 0$ .

IFAIL =  $6$

On entry, at least one of NS, NP or M is not the same as when R was set up in a previous call to G05TEF with MODE =  $0$  or  $2$ .

On entry, the R vector was not initialized correctly or has been corrupted.

IFAIL =  $7$

On entry, LR is too small when MODE =  $0$  or  $2$ .

IFAIL =  $8$

On entry, STATE vector was not initialized or has been corrupted.

## 7 Accuracy

Not applicable.

## 8 Further Comments

None.

## 9 Example

The example program prints 20 pseudorandom integers from a hypergeometric distribution with  $l = 500$ ,  $m = 900$  and  $n = 1000$ , generated by a single call to G05TEF, after initialization by G05KFF.

### 9.1 Program Text

Program g05tefe

```

!      G05TEF Example Program Text
!
!      Mark 24 Release. NAG Copyright 2012.
!
!      .. Use Statements ..
!      Use nag_library, Only: g05kff, g05tef, nag_wp
!      .. Implicit None Statement ..
!      Implicit None
!      .. Parameters ..
!      Integer, Parameter          :: lseed = 1, maxlr = 5000, nin = 5,      &
!                                   nout = 6
!
!      .. Local Scalars ..
!      Real (Kind=nag_wp)          :: anp, tmp
!      Integer                     :: genid, ifail, lr, lstate, m, mode,      &
!                                   n, np, ns, subid
!
!      .. Local Arrays ..
!      Real (Kind=nag_wp), Allocatable :: r(:)
!      Integer                         :: seed(lseed)
!      Integer, Allocatable            :: state(:), x(:)
!
!      .. Intrinsic Procedures ..
!      Intrinsic                     :: int, real, sqrt
!
!      .. Executable Statements ..
!      Write (nout,*) 'G05TEF Example Program Results'
!      Write (nout,*)
!
!      Skip heading in data file
!      Read (nin,*)
!
!      Read in the base generator information and seed
!      Read (nin,*) genid, subid, seed(1)
!
!      Initial call to initialiser to get size of STATE array
!      lstate = 0
!      Allocate (state(lstate))
!      ifail = 0
!      Call g05kff(genid,subid,seed,lseed,state,lstate,ifail)
!
!      Reallocate STATE
!      Deallocate (state)
!      Allocate (state(lstate))
!
!      Initialize the generator to a repeatable sequence
!      ifail = 0
!      Call g05kff(genid,subid,seed,lseed,state,lstate,ifail)
!
!      Read in sample size
!      Read (nin,*) n
!
!      Read in the distribution parameters
!      Read (nin,*) ns, m, np
!
!      Use suggested value for LR
!      anp = real(np,kind=nag_wp)
!      tmp = (real(np-m,kind=nag_wp)/anp)*(real(np-ns,kind=nag_wp)/anp)* &
!            (real(m*ns,kind=nag_wp)/real(np,kind=nag_wp))
!      lr = 28 + 20*int(sqrt(tmp))
!
!      If R is a reasonable size use MODE = 2
!      else do not reference R and use MODE = 3
!      If (lr<maxlr) Then

```

```

        mode = 2
    Else
        mode = 3
        lr = 0
    End If

    Allocate (x(n),r(lr))

!   Generate the variates
    ifail = -1
    Call g05tef(mode,n,ns,np,m,r,lr,state,x,ifail)

!   Display the variates
    Write (nout,99999) x(1:n)

99999 Format (1X,I12)
    End Program g05tefe

```

## 9.2 Program Data

```

G05TEF Example Program Data
1 1 1762543      :: GENID,SUBID,SEED(1)
20              :: N
500 900 1000    :: NS,M,NP
10 5 100
100 2500 10000
9780 50 10000

```

## 9.3 Program Results

G05TEF Example Program Results

```

452
444
453
454
444
450
449
454
450
452
442
447
451
442
451
447
447
462
456
450

```

---