

NAG Library Routine Document

S15AGF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

S15AGF returns the value of the scaled complementary error function $\operatorname{erfcx}(x)$, via the function name.

2 Specification

```
FUNCTION S15AGF (X, IFAIL)
REAL (KIND=nag_wp) S15AGF
INTEGER IFAIL
REAL (KIND=nag_wp) X
```

3 Description

S15AGF calculates an approximate value for the scaled complementary error function

$$\operatorname{erfcx}(x) = e^{x^2} \operatorname{erfc}(x) = \frac{2}{\sqrt{\pi}} e^{x^2} \int_x^\infty e^{-t^2} dt = e^{x^2} (1 - \operatorname{erf}(x)).$$

Let \hat{x} be the root of the equation $\operatorname{erfc}(x) - \operatorname{erf}(x) = 0$ (then $\hat{x} \approx 0.46875$). For $|x| \leq \hat{x}$ the value of $\operatorname{erfcx}(x)$ is based on the following rational Chebyshev expansion for $\operatorname{erf}(x)$:

$$\operatorname{erf}(x) \approx x R_{\ell,m}(x^2),$$

where $R_{\ell,m}$ denotes a rational function of degree ℓ in the numerator and m in the denominator.

For $|x| > \hat{x}$ the value of $\operatorname{erfcx}(x)$ is based on a rational Chebyshev expansion for $\operatorname{erfc}(x)$: for $\hat{x} < |x| \leq 4$ the value is based on the expansion

$$\operatorname{erfc}(x) \approx e^{x^2} R_{\ell,m}(x);$$

and for $|x| > 4$ it is based on the expansion

$$\operatorname{erfc}(x) \approx \frac{e^{x^2}}{x} \left(\frac{1}{\sqrt{\pi}} + \frac{1}{x^2} R_{\ell,m}(1/x^2) \right).$$

For each expansion, the specific values of ℓ and m are selected to be minimal such that the maximum relative error in the expansion is of the order 10^{-d} , where d is the maximum number of decimal digits that can be accurately represented for the particular implementation (see X02BEF).

Asymptotically, $\operatorname{erfcx}(x) \sim 1/(\sqrt{\pi}|x|)$. There is a danger of setting underflow in $\operatorname{erfcx}(x)$ whenever $x \geq x_{\text{hi}} = \min(x_{\text{huge}}, 1/(\sqrt{\pi}x_{\text{tiny}}))$, where x_{huge} is the largest positive model number (see X02ALF) and x_{tiny} is the smallest positive model number (see X02AKF). In this case S15AGF exits with IFAIL = 1 and returns $\operatorname{erfcx}(x) = 0$. For x in the range $1/(2\sqrt{\epsilon}) \leq x < x_{\text{hi}}$, where ϵ is the *machine precision*, the asymptotic value $1/(\sqrt{\pi}|x|)$ is returned for $\operatorname{erfcx}(x)$ and S15AGF exits with IFAIL = 2.

There is a danger of setting overflow in e^{x^2} whenever $x < x_{\text{neg}} = -\sqrt{\log(x_{\text{huge}}/2)}$. In this case S15AGF exits with IFAIL = 3 and returns $\operatorname{erfcx}(x) = x_{\text{huge}}$.

The values of x_{hi} , $1/(2\sqrt{\epsilon})$ and x_{neg} are given in the Users' Note for your implementation.

4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

Cody W J (1969) Rational Chebyshev approximations for the error function *Math.Comp.* **23** 631–637

5 Parameters

1: X – REAL (KIND=nag_wp) *Input*

On entry: the argument x of the function.

2: IFAIL – INTEGER *Input/Output*

On entry: IFAIL must be set to 0, –1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value –1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, because for this routine the values of the output parameters may be useful even if IFAIL \neq 0 on exit, the recommended value is –1. **When the value –1 or 1 is used it is essential to test the value of IFAIL on exit.**

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or –1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Note: S15AGF may return useful information for one or more of the following detected errors or warnings.

Errors or warnings detected by the routine:

IFAIL = 1

On entry, $X \geq x_{hi}$ (see Section 3). On soft failure the function value returned is 0.

IFAIL = 2

On entry, $1/(2\sqrt{\epsilon}) \leq X < x_{hi}$ (see Section 3). On soft failure the function value returned is $1/(\sqrt{\pi} \text{abs}(X))$.

IFAIL = 3

On entry, $X < x_{neg}$ (see Section 3). On soft failure the function value returned is the largest positive model number.

7 Accuracy

The relative error in computing $\text{erfcx}(x)$ may be estimated by evaluating

$$E = \frac{\text{erfcx}(x) - e^{x^2} \sum_{n=1}^{\infty} I^n \text{erfc}(x)}{\text{erfcx}(x)},$$

where I^n denotes repeated integration. Empirical results suggest that on the interval $(\hat{x}, 2)$ the loss in base b significant digits for maximum relative error is around 3.3, while for root-mean-square relative error on that interval it is 1.2 (see X02BHF for the definition of the model parameter b). On the interval $(2, 20)$ the

values are around 3.5 for maximum and 0.45 for root-mean-square relative errors; note that on these two intervals $\operatorname{erfc}(x)$ is the primary computation. See also Section 7 in S15ADF.

8 Further Comments

None.

9 Example

This example reads values of the argument x from a file, evaluates the function at each value of x and prints the results.

9.1 Program Text

```

Program s15agfe

!      S15AGF Example Program Text

!      Mark 24 Release. NAG Copyright 2012.

!      .. Use Statements ..
Use nag_library, Only: nag_wp, s15agf
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Real (Kind=nag_wp)         :: x, y
Integer                    :: ifail, ioerr
!      .. Executable Statements ..
Write (nout,*) 'S15AGF Example Program Results'

!      Skip heading in data file
Read (nin,*)

Write (nout,*)
Write (nout,*) '      X          erfcx(X)'
Write (nout,*)

data: Do
  Read (nin,*,Iostat=ioerr) x

  If (ioerr<0) Then
    Exit data
  End If

  ifail = -1
  y = s15agf(x,ifail)

  If (ifail<0) Then
    Exit data
  End If

  Write (nout,99999) x, y
End Do data

99999 Format (1X,1P,2(1X,E13.5))
End Program s15agfe

```

9.2 Program Data

```
S15AGF Example Program Data
      -6.0
      -4.5
      -1.0
       1.0
       4.5
       6.0
```

9.3 Program Results

```
S15AGF Example Program Results
```

| X | erfcx(X) |
|--------------|-------------|
| -6.00000E+00 | 8.62246E+15 |
| -4.50000E+00 | 1.24593E+09 |
| -1.00000E+00 | 5.00898E+00 |
| 1.00000E+00 | 4.27584E-01 |
| 4.50000E+00 | 1.22485E-01 |
| 6.00000E+00 | 9.27766E-02 |
