

# NAG Library Routine Document

## C06FJF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

C06FJF computes the multidimensional discrete Fourier transform of a multivariate sequence of complex data values.

### 2 Specification

SUBROUTINE C06FJF (NDIM, ND, N, X, Y, WORK, LWORK, IFAIL)

INTEGER NDIM, ND(NDIM), N, LWORK, IFAIL

REAL (KIND=nag\_wp) X(N), Y(N), WORK(LWORK)

### 3 Description

C06FJF computes the multidimensional discrete Fourier transform of a multidimensional sequence of complex data values  $z_{j_1 j_2 \dots j_m}$ , where  $j_1 = 0, 1, \dots, n_1 - 1$ ,  $j_2 = 0, 1, \dots, n_2 - 1$ , and so on. Thus the individual dimensions are  $n_1, n_2, \dots, n_m$ , and the total number of data values is  $n = n_1 \times n_2 \times \dots \times n_m$ .

The discrete Fourier transform is here defined (e.g., for  $m = 2$ ) by:

$$\hat{z}_{k_1, k_2} = \frac{1}{\sqrt{n}} \sum_{j_1=0}^{n_1-1} \sum_{j_2=0}^{n_2-1} z_{j_1 j_2} \times \exp\left(-2\pi i \left(\frac{j_1 k_1}{n_1} + \frac{j_2 k_2}{n_2}\right)\right),$$

where  $k_1 = 0, 1, \dots, n_1 - 1$ ,  $k_2 = 0, 1, \dots, n_2 - 1$ .

The extension to higher dimensions is obvious. (Note the scale factor of  $\frac{1}{\sqrt{n}}$  in this definition.)

To compute the inverse discrete Fourier transform, defined with  $\exp(+2\pi i(\dots))$  in the above formula instead of  $\exp(-2\pi i(\dots))$ , this routine should be preceded and followed by the complex conjugation of the data values and the transform (by negating the imaginary parts stored in  $y$ ).

The data values must be supplied in a pair of one-dimensional arrays (real and imaginary parts separately), in accordance with the Fortran convention for storing multidimensional data (i.e., with the first subscript  $j_1$  varying most rapidly).

This routine calls C06FCF to perform one-dimensional discrete Fourier transforms by the fast Fourier transform (FFT) algorithm in Brigham (1974), and hence there are some restrictions on the values of the  $n_i$  (see Section 5).

### 4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice-Hall

### 5 Parameters

1: NDIM – INTEGER

*Input*

*On entry:*  $m$ , the number of dimensions (or variables) in the multivariate data.

*Constraint:* NDIM  $\geq$  1.

- 2: ND(NDIM) – INTEGER array *Input*  
*On entry:* ND( $i$ ) must contain  $n_i$  (the dimension of the  $i$ th variable), for  $i = 1, 2, \dots, m$ . The largest prime factor of each ND( $i$ ) must not exceed 19, and the total number of prime factors of ND( $i$ ), counting repetitions, must not exceed 20.  
*Constraint:* ND( $i$ )  $\geq 1$ , for  $i = 1, 2, \dots, \text{NDIM}$ .
- 3: N – INTEGER *Input*  
*On entry:*  $n$ , the total number of data values.  
*Constraint:*  $N = \text{ND}(1) \times \text{ND}(2) \times \dots \times \text{ND}(\text{NDIM})$ .
- 4: X(N) – REAL (KIND=nag\_wp) array *Input/Output*  
*On entry:* X( $1 + j_1 + n_1 j_2 + n_1 n_2 j_3 + \dots$ ) must contain the real part of the complex data value  $z_{j_1 j_2 \dots j_m}$ , for  $0 \leq j_1 \leq n_1 - 1, 0 \leq j_2 \leq n_2 - 1, \dots$ ; i.e., the values are stored in consecutive elements of the array according to the Fortran convention for storing multidimensional arrays.  
*On exit:* the real parts of the corresponding elements of the computed transform.
- 5: Y(N) – REAL (KIND=nag\_wp) array *Input/Output*  
*On entry:* the imaginary parts of the complex data values, stored in the same way as the real parts in the array X.  
*On exit:* the imaginary parts of the corresponding elements of the computed transform.
- 6: WORK(LWORK) – REAL (KIND=nag\_wp) array *Workspace*  
 7: LWORK – INTEGER *Input*  
*On entry:* the dimension of the array WORK as declared in the (sub)program from which C06FJF is called.  
*Constraint:* LWORK  $\geq 3 \times \max\{\text{ND}(i)\}$ .
- 8: IFAIL – INTEGER *Input/Output*  
*On entry:* IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.  
 For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**  
*On exit:* IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

## 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, NDIM < 1.

IFAIL = 2

On entry,  $N \neq \text{ND}(1) \times \text{ND}(2) \times \dots \times \text{ND}(\text{NDIM})$ .

IFAIL =  $10 \times l + 1$

At least one of the prime factors of  $ND(l)$  is greater than 19.

IFAIL =  $10 \times l + 2$

$ND(l)$  has more than 20 prime factors.

IFAIL =  $10 \times l + 3$

On entry,  $ND(l) < 1$ .

IFAIL =  $10 \times l + 4$

On entry,  $LWORK < 3 \times ND(l)$ .

## 7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

## 8 Further Comments

The time taken is approximately proportional to  $n \times \log n$ , but also depends on the factorization of the individual dimensions  $ND(i)$ . C06FJF is faster if the only prime factors are 2, 3 or 5; and fastest of all if they are powers of 2.

## 9 Example

This example reads in a bivariate sequence of complex data values and prints the two-dimensional Fourier transform. It then performs an inverse transform and prints the sequence so obtained, which may be compared to the original data values.

### 9.1 Program Text

```
! C06FJF Example Program Text
! Mark 24 Release. NAG Copyright 2012.

Module c06fjfe_mod

! C06FJF Example Program Module:
! Parameters and User-defined Routines

! .. Use Statements ..
Use nag_library, Only: nag_wp
! .. Implicit None Statement ..
Implicit None
! .. Parameters ..
Integer, Parameter :: nin = 5, nout = 6
Contains
Subroutine readxy(nin,x,y,n1,n2)
! Read 2-dimensional complex data

! .. Scalar Arguments ..
Integer, Intent (In) :: n1, n2, nin
! .. Array Arguments ..
Real (Kind=nag_wp), Intent (Out) :: x(n1,n2), y(n1,n2)
! .. Local Scalars ..
Integer :: i, j
! .. Executable Statements ..
Do i = 1, n1
Read (nin,*)(x(i,j),j=1,n2)
Read (nin,*)(y(i,j),j=1,n2)
End Do
Return
```

```

End Subroutine readxy

Subroutine writxy(nout,x,y,n1,n2)
!   Print 2-dimensional complex data

!   .. Scalar Arguments ..
Integer, Intent (In)           :: n1, n2, nout
!   .. Array Arguments ..
Real (Kind=nag_wp), Intent (In) :: x(n1,n2), y(n1,n2)
!   .. Local Scalars ..
Integer                         :: i, j
!   .. Executable Statements ..
Do i = 1, n1
  Write (nout,*)
  Write (nout,99999) 'Real ', (x(i,j),j=1,n2)
  Write (nout,99999) 'Imag ', (y(i,j),j=1,n2)
End Do
Return

99999  Format (1X,A,7F10.3/(6X,7F10.3))
End Subroutine writxy
End Module c06fjfe_mod

Program c06fjfe

!   C06FJF Example Main Program

!   .. Use Statements ..
Use nag_library, Only: c06fjf, c06gcf, nag_wp
Use c06fjfe_mod, Only: nin, nout, readxy, writxy
!   .. Implicit None Statement ..
Implicit None
!   .. Local Scalars ..
Integer                         :: ieof, ifail, lwork, n, ndim
!   .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: work(:), x(:), y(:)
Integer, Allocatable            :: nd(:)
!   .. Intrinsic Procedures ..
Intrinsic                       :: maxval, product
!   .. Executable Statements ..
Write (nout,*) 'C06FJF Example Program Results'
!   Skip heading in data file
Read (nin,*)
loop: Do
  Read (nin,*,Iostat=ieof) ndim
  If (ieof<0) Exit loop

  Allocate (nd(ndim))
  Read (nin,*) nd(1:ndim)
  n = product(nd(1:ndim))
  lwork = 3*maxval(nd(1:ndim))
  Allocate (x(n),y(n),work(lwork))

  Call readxy(nin,x,y,nd(1),nd(2))
  Write (nout,*)
  Write (nout,*) 'Original data values'
  Call writxy(nout,x,y,nd(1),nd(2))

!   ifail: behaviour on error exit
!           =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
  ifail = 0
!   Compute transform
  Call c06fjf(ndim,nd,n,x,y,work,lwork,ifail)

  Write (nout,*)
  Write (nout,*) 'Components of discrete Fourier transform'
  Call writxy(nout,x,y,nd(1),nd(2))

!   Compute inverse transform
  Call c06gcf(y,n,ifail)
  Call c06fjf(ndim,nd,n,x,y,work,lwork,ifail)

```

```

      Call c06gcf(y,n,ifail)

      Write (nout,*)
      Write (nout,*) 'Original sequence as restored by inverse transform'
      Call writxy(nout,x,y,nd(1),nd(2))
      Deallocate (x,y,work,nd)

      End Do loop

      End Program c06fjfe

```

## 9.2 Program Data

C06FJF Example Program Data

```

2                                     : ndim
3   5                                 : nd(1), nd(2)
1.000    0.999    0.987    0.936    0.802
0.000   -0.040   -0.159   -0.352   -0.597
0.994    0.989    0.963    0.891    0.731
-0.111   -0.151   -0.268   -0.454   -0.682
0.903    0.885    0.823    0.694    0.467
-0.430   -0.466   -0.568   -0.720   -0.884   : x, y

```

## 9.3 Program Results

C06FJF Example Program Results

Original data values

Real	1.000	0.999	0.987	0.936	0.802
Imag	0.000	-0.040	-0.159	-0.352	-0.597
Real	0.994	0.989	0.963	0.891	0.731
Imag	-0.111	-0.151	-0.268	-0.454	-0.682
Real	0.903	0.885	0.823	0.694	0.467
Imag	-0.430	-0.466	-0.568	-0.720	-0.884

Components of discrete Fourier transform

Real	3.373	0.481	0.251	0.054	-0.419
Imag	-1.519	-0.091	0.178	0.319	0.415
Real	0.457	0.055	0.009	-0.022	-0.076
Imag	0.137	0.032	0.039	0.036	0.004
Real	-0.170	-0.037	-0.042	-0.038	-0.002
Imag	0.493	0.058	0.008	-0.025	-0.083

Original sequence as restored by inverse transform

Real	1.000	0.999	0.987	0.936	0.802
Imag	-0.000	-0.040	-0.159	-0.352	-0.597
Real	0.994	0.989	0.963	0.891	0.731
Imag	-0.111	-0.151	-0.268	-0.454	-0.682
Real	0.903	0.885	0.823	0.694	0.467
Imag	-0.430	-0.466	-0.568	-0.720	-0.884