NAG Library Routine Document

F04BJF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

F04BJF computes the solution to a real system of linear equations AX = B, where A is an n by n symmetric matrix, stored in packed format and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

2 Specification

```
SUBROUTINE F04BJF (UPLO, N, NRHS, AP, IPIV, B, LDB, RCOND, ERRBND, IFAIL)

INTEGER

N, NRHS, IPIV(N), LDB, IFAIL

REAL (KIND=nag_wp) AP(*), B(LDB,*), RCOND, ERRBND

CHARACTER(1) UPLO
```

3 Description

The diagonal pivoting method is used to factor A as $A = UDU^{\mathsf{T}}$, if $\mathsf{UPLO} = \mathsf{'U'}$, or $A = LDL^{\mathsf{T}}$, if $\mathsf{UPLO} = \mathsf{'L'}$, where U (or L) is a product of permutation and unit upper (lower) triangular matrices, and D is symmetric and block diagonal with 1 by 1 and 2 by 2 diagonal blocks. The factored form of A is then used to solve the system of equations AX = B.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia http://www.netlib.org/lapack/lug

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

5 Parameters

1: UPLO – CHARACTER(1)

Input

On entry: if UPLO = 'U', the upper triangle of the matrix A is stored.

If UPLO = 'L', the lower triangle of the matrix A is stored.

Constraint: UPLO = 'U' or 'L'.

2: N – INTEGER

Input

On entry: the number of linear equations n, i.e., the order of the matrix A.

Constraint: $N \ge 0$.

3: NRHS – INTEGER

Input

On entry: the number of right-hand sides r, i.e., the number of columns of the matrix B.

Constraint: NRHS ≥ 0 .

Mark 24 F04BJF.1

F04BJF NAG Library Manual

4: AP(*) - REAL (KIND=nag_wp) array

Input/Output

Note: the dimension of the array AP must be at least $max(1, N \times (N+1)/2)$.

On entry: the n by n symmetric matrix A, packed column-wise in a linear array. The jth column of the matrix A is stored in the array AP as follows:

if UPLO = 'U', AP
$$(i + (j-1)j/2) = a_{ij}$$
, for $1 \le i \le j$;
if UPLO = 'L', AP $(i + (j-1)(2n-j)/2) = a_{ij}$, for $j \le i \le n$.

See Section 8 below for further details.

On exit: if IFAIL ≥ 0 , the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization $A = UDU^{\mathsf{T}}$ or $A = LDL^{\mathsf{T}}$ as computed by F07PDF (DSPTRF), stored as a packed triangular matrix in the same storage format as A.

5: IPIV(N) – INTEGER array

Output

On exit: if IFAIL ≥ 0 , details of the interchanges and the block structure of D, as determined by F07PDF (DSPTRF).

If IPIV(k) > 0, then rows and columns k and IPIV(k) were interchanged, and d_{kk} is a 1 by 1 diagonal block;

if UPLO = 'U' and IPIV(k) = IPIV(k-1) < 0, then rows and columns k-1 and -IPIV(k) were interchanged and $d_{k-1:k,k-1:k}$ is a 2 by 2 diagonal block;

if UPLO = 'L' and IPIV(k) = IPIV(k+1) < 0, then rows and columns k+1 and -IPIV(k) were interchanged and $d_{k:k+1,k:k+1}$ is a 2 by 2 diagonal block.

6: B(LDB,*) - REAL (KIND=nag_wp) array

Input/Output

Note: the second dimension of the array B must be at least max(1, NRHS).

On entry: the n by r matrix of right-hand sides B.

On exit: if IFAIL = 0 or N + 1, the n by r solution matrix X.

7: LDB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F04BJF is called.

Constraint: LDB $\geq \max(1, N)$.

8: RCOND – REAL (KIND=nag wp)

Output

On exit: if no constraints are violated, an estimate of the reciprocal of the condition number of the matrix A, computed as $RCOND = 1/(\|A\|_1 \|A^{-1}\|_1)$.

9: ERRBND – REAL (KIND=nag wp)

Output

On exit: if IFAIL = 0 or N + 1, an estimate of the forward error bound for a computed solution \hat{x} , such that $\|\hat{x} - x\|_1 / \|x\|_1 \le \text{ERRBND}$, where \hat{x} is a column of the computed solution returned in the array B and x is the corresponding column of the exact solution X. If RCOND is less than **machine precision**, then ERRBND is returned as unity.

10: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the

F04BJF.2 Mark 24

recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL < 0 and IFAIL $\neq -999$

If IFAIL = -i, the *i*th argument had an illegal value.

IFAIL = -999

Allocation of memory failed. The integer allocatable memory required is N, and the real allocatable memory required is $2 \times N$. Allocation failed before the solution could be computed.

IFAIL > 0 and IFAIL < N

If IFAIL = i, d_{ii} is exactly zero. The factorization has been completed, but the block diagonal matrix D is exactly singular, so the solution could not be computed.

IFAIL = N + 1

RCOND is less than *machine precision*, so that the matrix A is numerically singular. A solution to the equations AX = B has nevertheless been computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A+E)\hat{x}=b$$
,

where

$$||E||_1 = O(\epsilon)||A||_1$$

and ϵ is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \le \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$, the condition number of A with respect to the solution of the linear equations. F04BJF uses the approximation $\|E\|_1 = \epsilon \|A\|_1$ to estimate ERRBND. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Further Comments

The packed storage scheme is illustrated by the following example when n=4 and UPLO = 'U'. Two-dimensional storage of the symmetric matrix A:

Packed storage of the upper triangle of A:

$$AP = \begin{bmatrix} a_{11}, & a_{12}, & a_{22}, & a_{13}, & a_{23}, & a_{33}, & a_{14}, & a_{24}, & a_{34}, & a_{44} \end{bmatrix}$$

Mark 24 *F04BJF.3*

F04BJF NAG Library Manual

The total number of floating point operations required to solve the equations AX = B is proportional to $\left(\frac{1}{3}n^3 + 2n^2r\right)$. The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

The complex analogues of F04BJF are F04CJF for complex Hermitian matrices, and F04DJF for complex symmetric matrices.

9 Example

This example solves the equations

$$AX = B$$
,

where A is the symmetric indefinite matrix

$$A = \begin{pmatrix} -1.81 & 2.06 & 0.63 & -1.15 \\ 2.06 & 1.15 & 1.87 & 4.20 \\ 0.63 & 1.87 & -0.21 & 3.87 \\ -1.15 & 4.20 & 3.87 & 2.07 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 0.96 & 3.93 \\ 6.07 & 19.25 \\ 8.38 & 9.90 \\ 9.50 & 27.85 \end{pmatrix}.$$

An estimate of the condition number of A and an approximate error bound for the computed solutions are also printed.

9.1 Program Text

```
Program f04bjfe
!
      FO4BJF Example Program Text
!
     Mark 24 Release. NAG Copyright 2012.
      .. Use Statements ..
     Use nag_library, Only: f04bjf, nag_wp, x04caf, x04ccf
      .. Implicit None Statement ..
     Implicit None
!
      .. Parameters ..
     Integer, Parameter :: nin = 5, nout = 6
Character (1), Parameter :: uplo = 'U'
!
      .. Local Scalars ..
     Real (Kind=nag_wp)
                                       :: errbnd, rcond
                                       :: i, ierr, ifail, j, ldb, n, nrhs
      Integer
      .. Local Arrays ..
!
     Real (Kind=nag_wp), Allocatable :: ap(:), b(:,:)
     Integer, Allocatable
                                       :: ipiv(:)
!
      .. Executable Statements ..
      Write (nout,*) 'FO4BJF Example Program Results'
     Write (nout,*)
      Flush (nout)
      Skip heading in data file
!
      Read (nin,*)
     Read (nin,*) n, nrhs
      ldb = n
     Allocate (ap((n*(n+1))/2),b(ldb,nrhs),ipiv(n))
!
     Read the upper or lower triangular part of the matrix A from
!
      data file
     If (uplo=='U') Then
        Read (nin,*)((ap(i+(j*(j-1))/2),j=i,n),i=1,n)
     Else If (uplo=='L') Then
        Read (nin,*)((ap(i+((2*n-j)*(j-1))/2),j=1,i),i=1,n)
     End If
!
     Read B from data file
      Read (nin,*)(b(i,1:nrhs),i=1,n)
```

F04BJF.4 Mark 24

```
Solve the equations AX = B for X
!
      ifail: behaviour on error exit
             =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 1
      Call f04bjf(uplo,n,nrhs,ap,ipiv,b,ldb,rcond,errbnd,ifail)
      If (ifail==0) Then
        Print solution, estimate of condition number and approximate
        error bound
        ierr = 0
        Call x04caf('General',' ',n,nrhs,b,ldb,'Solution',ierr)
        Write (nout,*)
        Write (nout,*) 'Estimate of condition number'
        Write (nout,99999) 1.0E0_nag_wp/rcond
        Write (nout,*)
        Write (nout,*) 'Estimate of error bound for computed solutions'
        Write (nout,99999) errbnd
      Else If (ifail==n+1) Then
        Matrix A is numerically singular. Print estimate of
        reciprocal of condition number and solution
!
        Write (nout,*)
        Write (nout,*) 'Estimate of reciprocal of condition number'
        Write (nout, 99999) rcond
        Write (nout,*)
        Flush (nout)
        ierr = 0
        Call x04caf('General',' ',n,nrhs,b,ldb,'Solution',ierr)
      Else If (ifail>0 .And. ifail<=n) Then</pre>
        The upper triangular matrix U is exactly singular. Print
1
        details of factorization
        Write (nout,*)
        Flush (nout)
        ierr = 0
        Call x04ccf(uplo,'Non-unit diagonal',n,ap,'Details of factorization', &
          ierr)
        Print pivot indices
!
        Write (nout, *)
        Write (nout,*) 'Pivot indices'
        Write (nout,99998) ipiv(1:n)
      Else
        Write (nout, 99997) ifail
      End If
99999 Format (6X,1P,E9.1)
99998 Format ((3X,7I11))
99997 Format (1X,'**F04BJF returned with IFAIL = ',I5)
    End Program f04bjfe
9.2
    Program Data
FO4BJF Example Program Data
```

```
4 2 :Values of N and NRHS

-1.81 2.06 0.63 -1.15
1.15 1.87 4.20
-0.21 3.87
2.07 :End of matrix A

0.96 3.93
6.07 19.25
8.38 9.90
```

9.50 27.85

Mark 24 *F04BJF.*5

:End of matrix B

F04BJF NAG Library Manual

9.3 Program Results

FO4BJF Example Program Results

Solution

	1	2
1	-5.0000	2.0000
2	-2.0000	3.0000
3	1.0000	4.0000
4	4.0000	1.0000

Estimate of condition number 7.6E+01

Estimate of error bound for computed solutions 8.4 E-15

F04BJF.6 (last)

Mark 24