

NAG Library Routine Document

G13BDF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

G13BDF calculates preliminary estimates of the parameters of a transfer function model.

2 Specification

```
SUBROUTINE G13BDF (R0, R, NL, NNA, S, NWDS, WA, IWA, WDS, ISF, IFAIL)
```

```
INTEGER NL, NNA(3), NWDS, IWA, ISF(2), IFAIL
```

```
REAL (KIND=nag_wp) R0, R(NL), S, WA(IWA), WDS(NWDS)
```

3 Description

G13BDF calculates estimates of parameters $\delta_1, \delta_2, \dots, \delta_p, \omega_0, \omega_1, \dots, \omega_q$ in the transfer function model

$$y_t = \delta_1 y_{t-1} + \delta_2 y_{t-2} + \dots + \delta_p y_{t-p} + \omega_0 x_{t-b} - \omega_1 x_{t-b-1} - \dots - \omega_q x_{t-b-q}$$

given cross-correlations between the series x_t and lagged values of y_t :

$$r_{xy}(l), \quad l = 0, 1, \dots, L$$

and the ratio of standard deviations s_y/s_x , as supplied by G13BCF.

It is assumed that the series x_t used to calculate the cross-correlations is a sample from a time series with true autocorrelations of zero. Otherwise the cross-correlations between the series b_t and a_t , as defined in the description of G13BAF, should be used in place of those between y_t and x_t .

The estimates are obtained by solving for $\delta_1, \delta_2, \dots, \delta_p$ the equations

$$r_{xy}(b+q+j) = \delta_1 r_{xy}(b+q+j-1) + \dots + \delta_p r_{xy}(b+q+j-p), \quad j = 1, 2, \dots, p$$

then calculating

$$\omega_i = \pm (s_y/s_x) [r_{xy}(b+i) - \delta_1 r_{xy}(b+i-1) - \dots - \delta_p r_{xy}(b+i-p)], \quad i = 0, 1, \dots, q$$

where the '+' is used for ω_0 and '-' for $\omega_i, i > 0$.

Any value of $r_{xy}(l)$ arising in these equations for $l < b$ is taken as zero. The parameters $\delta_1, \delta_2, \dots, \delta_p$ are checked as to whether they satisfy the stability criterion.

4 References

Box G E P and Jenkins G M (1976) *Time Series Analysis: Forecasting and Control* (Revised Edition) Holden-Day

5 Parameters

1: R0 – REAL (KIND=nag_wp) *Input*

On entry: the cross-correlation between the two series at lag 0, $r_{xy}(0)$.

Constraint: $-1.0 \leq R0 \leq 1.0$.

- 2: R(NL) – REAL (KIND=nag_wp) array Input
On entry: the cross-correlations between the two series at lags 1 to L , $r_{xy}(l)$, for $l = 1, 2, \dots, L$.
Constraint: $-1.0 \leq R(i) \leq 1.0$, for $i = 1, 2, \dots, NL$.
- 3: NL – INTEGER Input
On entry: L , the number of lagged cross-correlations in the array R.
Constraint: $NL \geq \max(NNA(1) + NNA(2) + NNA(3), 1)$.
- 4: NNA(3) – INTEGER array Input
On entry: the transfer function model orders in the standard form b, q, p (i.e., delay time, number of moving-average MA-like followed by number of autoregressive AR-like parameters).
Constraint: $NNA(i) \geq 0$, for $i = 1, 2, 3$.
- 5: S – REAL (KIND=nag_wp) Input
On entry: the ratio of the standard deviation of the y series to that of the x series, s_y/s_x .
Constraint: $S > 0.0$.
- 6: NWDS – INTEGER Input
On entry: the exact number of parameters in the transfer function model.
Constraint: $NWDS = NNA(2) + NNA(3) + 1$.
- 7: WA(IWA) – REAL (KIND=nag_wp) array Workspace
 8: IWA – INTEGER Input
On entry: the dimension of the array WA as declared in the (sub)program from which G13BDF is called.
Constraint: $IWA \geq NNA(3) \times (NNA(3) + 1)$.
- 9: WDS(NWDS) – REAL (KIND=nag_wp) array Output
On exit: the preliminary estimates of the parameters of the transfer function model in the order of $q + 1$ MA-like parameters followed by the p AR-like parameters. If the estimation of either type of parameter fails then these parameters are set to 0.0.
- 10: ISF(2) – INTEGER array Output
On exit: indicators of the success of the estimation of MA-like and AR-like parameters respectively. A value 0 indicates that there are no parameters of that type to be estimated. A value of 1 or -1 indicates that there are parameters of that type in the model and the estimation of that type has been successful or unsuccessful respectively. Note that there is always at least one MA-like parameter in the model.
- 11: IFAIL – INTEGER Input/Output
On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.
 For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**
On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry $IFAIL = 0$ or -1 , explanatory error messages are output on the current error message unit (as defined by $X04AAF$).

Errors or warnings detected by the routine:

$IFAIL = 1$

On entry, $NNA(i) < 0$, for $i = 1, 2, 3$,
 or $NL < \max(NNA(1) + NNA(2) + NNA(3), 1)$,
 or $R0 < -1.0$ or $R0 > 1.0$,
 or $R(i) < -1.0$ or $R(i) > 1.0$, for some $i = 1, 2, \dots, NL$,
 or $S \leq 0.0$,
 or $NWDS \neq NNA(2) + NNA(3) + 1$,
 or $IWA < NNA(3) \times (NNA(3) + 1)$.

$IFAIL = -999$

Internal memory allocation failed.

7 Accuracy

Equations used in the computations may become unstable, in which case results are reset to zero with array ISF values set accordingly.

8 Further Comments

If $NNA(3) > 0$, a local workspace array of fixed length is allocated internally by G13BDF. The total size of this array amounts to $NNA(3)$ integer elements and $NNA(3) \times (NNA(3) + 1)$ real elements.

The time taken by G13BDF is roughly proportional to $NWDS^3$.

9 Example

This example reads the cross-correlations between two series at lags 0 to 6. It then reads a (3,2,1) transfer function model and calculates and prints the preliminary estimates of the parameters of the model.

9.1 Program Text

```

Program g13bdfe

!      G13BDF Example Program Text

!      Mark 24 Release. NAG Copyright 2012.

!      .. Use Statements ..
      Use nag_library, Only: g13bdf, nag_wp
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Real (Kind=nag_wp)          :: r0, s
      Integer                     :: ifail, iwa, nl, nwds
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: r(:), wa(:), wds(:)
      Integer                     :: isf(2), nna(3)
!      .. Executable Statements ..
      Write (nout,*) 'G13BDF Example Program Results'
      Write (nout,*)

!      Skip heading in data file
      Read (nin,*)

```

```

!      Read in problem size and cross-correlation at lag 0
      Read (nin,*) nl, r0

      Allocate (r(nl))

!      Read in rest of cross-correlations
      Read (nin,*) r(1:nl)

!      Read in transfer function model orders
      Read (nin,*) nna(1:3)

!      Read in standard deviation ratio
      Read (nin,*) s

      nwds = nna(2) + nna(3) + 1
      iwa = nna(3)*(nna(3)+1)
      Allocate (wa(iwa),wds(nwds))

!      Calculate parameter estimates
      ifail = 0
      Call g13bdf(r0,r,nl,nna,s,nwds,wa,iwa,wds,isf,ifail)

!      Display results
      Write (nout,99999) 'Success/failure indicator', isf(1), isf(2)
      Write (nout,*)
      Write (nout,99999) 'Transfer function model B, Q, P =', nna(1:3)
      Write (nout,*)
      Write (nout,*) 'Parameter initial estimates'
      Write (nout,99998) wds(1:nwds)

99999 Format (1X,A,3I4)
99998 Format (1X,4F10.4)
      End Program g13bdf

```

9.2 Program Data

```

G13BDF Example Program Data
   6   -0.0155           :: NL,R0
  0.0339 -0.0374 -0.2895 -0.3430 -0.4518 -0.2787 :: R
   3     2     1       :: NNA
  1.9256                :: S

```

9.3 Program Results

G13BDF Example Program Results

```

Success/failure indicator   1   1

Transfer function model B, Q, P =   3   2   1

Parameter initial estimates
   -0.5575    0.3166    0.4626    0.6169

```
