

# NAG Library Routine Document

## D02TXF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

D02TXF allows a solution to a nonlinear two-point boundary value problem computed by D02TKF to be used as an initial approximation in the solution of a related nonlinear two-point boundary value problem in a continuation call to D02TKF.

### 2 Specification

SUBROUTINE D02TXF (MXMESH, NMESH, MESH, IPMESH, RWORK, IWORK, IFAIL)

INTEGER MXMESH, NMESH, IPMESH(MXMESH), IWORK(\*), IFAIL

REAL (KIND=nag\_wp) MESH(MXMESH), RWORK(\*)

### 3 Description

D02TXF and its associated routines (D02TKF, D02TVF, D02TYF and D02TZF) solve the two-point boundary value problem for a nonlinear system of ordinary differential equations

$$\begin{aligned} y_1^{(m_1)}(x) &= f_1(x, y_1, y_1^{(1)}, \dots, y_1^{(m_1-1)}, y_2, \dots, y_n^{(m_n-1)}) \\ y_2^{(m_2)}(x) &= f_2(x, y_1, y_1^{(1)}, \dots, y_1^{(m_1-1)}, y_2, \dots, y_n^{(m_n-1)}) \\ &\vdots \\ y_n^{(m_n)}(x) &= f_n(x, y_1, y_1^{(1)}, \dots, y_1^{(m_1-1)}, y_2, \dots, y_n^{(m_n-1)}) \end{aligned}$$

over an interval  $[a, b]$  subject to  $p (> 0)$  nonlinear boundary conditions at  $a$  and  $q (> 0)$  nonlinear boundary conditions at  $b$ , where  $p + q = \sum_{i=1}^n m_i$ . Note that  $y_i^{(m)}(x)$  is the  $m$ th derivative of the  $i$ th solution component. Hence  $y_i^{(0)}(x) = y_i(x)$ . The left boundary conditions at  $a$  are defined as

$$g_i(z(y(a))) = 0, \quad i = 1, 2, \dots, p,$$

and the right boundary conditions at  $b$  as

$$\bar{g}_j(z(y(b))) = 0, \quad j = 1, 2, \dots, q,$$

where  $y = (y_1, y_2, \dots, y_n)$  and

$$z(y(x)) = (y_1(x), y_1^{(1)}(x), \dots, y_1^{(m_1-1)}(x), y_2(x), \dots, y_n^{(m_n-1)}(x)).$$

First, D02TVF must be called to specify the initial mesh, error requirements and other details. Then, D02TKF can be used to solve the boundary value problem. After successful computation, D02TZF can be used to ascertain details about the final mesh. D02TYF can be used to compute the approximate solution anywhere on the interval  $[a, b]$  using interpolation.

If the boundary value problem being solved is one of a sequence of related problems, for example as part of some continuation process, then D02TXF should be used between calls to D02TKF. This avoids the overhead of a complete initialization when the setup routine D02TVF is used. D02TXF allows the solution values computed in the previous call to D02TKF to be used as an initial approximation for the solution in the next call to D02TKF.

You must specify the new initial mesh. The previous mesh can be obtained by a call to D02TZF. It may be used unchanged as the new mesh, in which case any fixed points in the previous mesh remain as fixed

points in the new mesh. Fixed and other points may be added or subtracted from the mesh by manipulation of the contents of the array parameter IPMESH. Initial values for the solution components on the new mesh are computed by interpolation on the values for the solution components on the previous mesh.

The routines are based on modified versions of the codes COLSYS and COLNEW (see Ascher *et al.* (1979) and Ascher and Bader (1987)). A comprehensive treatment of the numerical solution of boundary value problems can be found in Ascher *et al.* (1988) and Keller (1992).

## 4 References

Ascher U M and Bader G (1987) A new basis implementation for a mixed order boundary value ODE solver *SIAM J. Sci. Stat. Comput.* **8** 483–500

Ascher U M, Christiansen J and Russell R D (1979) A collocation solver for mixed order systems of boundary value problems *Math. Comput.* **33** 659–679

Ascher U M, Mattheij R M M and Russell R D (1988) *Numerical Solution of Boundary Value Problems for Ordinary Differential Equations* Prentice–Hall

Keller H B (1992) *Numerical Methods for Two-point Boundary-value Problems* Dover, New York

## 5 Parameters

- 1: MXMESH – INTEGER *Input*  
*On entry:* the maximum number of points allowed in the mesh.  
*Constraint:* this must be identical to the value supplied for the parameter MXMESH in the prior call to D02TVF.
- 2: NMESH – INTEGER *Input*  
*On entry:* the number of points to be used in the new initial mesh.  
*Suggested value:*  $(n^* + 1)/2$ , where  $n^*$  is the number of mesh points used in the previous mesh as returned in the parameter NMESH of D02TZF.  
*Constraint:*  $6 \leq \text{NMESH} \leq (\text{MXMESH} + 1)/2$ .
- 3: MESH(MXMESH) – REAL (KIND=nag\_wp) array *Input*  
*On entry:* the NMESH points to be used in the new initial mesh as specified by IPMESH.  
*Suggested value:* the parameter MESH returned from a call to D02TZF.  
*Constraint:*  $\text{MESH}(i_j) < \text{MESH}(i_{j+1})$ , for  $j = 1, 2, \dots, \text{NMESH} - 1$ , the values of  $i_1, i_2, \dots, i_{\text{NMESH}}$  are defined in IPMESH.  
MESH( $i_1$ ) must contain the left boundary point,  $a$ , and MESH( $i_{\text{NMESH}}$ ) must contain the right boundary point,  $b$ , as specified in the previous call to D02TVF.
- 4: IPMESH(MXMESH) – INTEGER array *Input*  
*On entry:* specifies the points in MESH to be used as the new initial mesh. Let  $\{i_j : j = 1, 2, \dots, \text{NMESH}\}$  be the set of array indices of IPMESH such that IPMESH( $i_j$ ) = 1 or 2 and  $1 = i_1 < i_2 < \dots < i_{\text{NMESH}}$ . Then MESH( $i_j$ ) will be included in the new initial mesh.  
If IPMESH( $i_j$ ) = 1, MESH( $i_j$ ) will be a fixed point in the new initial mesh.  
If IPMESH( $k$ ) = 3 for any  $k$ , then MESH( $k$ ) will not be included in the new mesh.  
*Suggested value:* the parameter IPMESH returned in a call to D02TZF.

*Constraints:*

$$\begin{aligned} \text{IPMESH}(k) &= 1, 2 \text{ or } 3, \text{ for } k = 1, 2, \dots, i_{\text{NMESH}}; \\ \text{IPMESH}(1) &= \text{IPMESH}(i_{\text{NMESH}}) = 1. \end{aligned}$$

5: RWORK(\*) – REAL (KIND=nag\_wp) array *Input/Output*

**Note:** the dimension of the array RWORK must be at least LRWORK (see D02TVF).

*On entry:* this must be the same array as supplied to D02TKF and **must** remain unchanged between calls.

*On exit:* contains information about the solution for use on subsequent calls to associated routines.

6: IWORK(\*) – INTEGER array *Input/Output*

**Note:** the dimension of the array IWORK must be at least LIWORK (see D02TVF).

*On entry:* this must be the same array as supplied to D02TKF and **must** remain unchanged between calls.

*On exit:* contains information about the solution for use on subsequent calls to associated routines.

7: IFAIL – INTEGER *Input/Output*

*On entry:* IFAIL must be set to 0, –1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value –1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value –1 or 1 is used it is essential to test the value of IFAIL on exit.**

*On exit:* IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

## 6 Error Indicators and Warnings

If on entry IFAIL = 0 or –1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

An invalid call to D02TXF was made, for example without a previous successful call to the solver routine D02TKF, or, on entry, an invalid value for NMESH, MESH or IPMESH was detected.

## 7 Accuracy

Not applicable.

## 8 Further Comments

For problems where sharp changes of behaviour are expected over short intervals it may be advisable to:

- cluster the mesh points where sharp changes in behaviour are expected;
- maintain fixed points in the mesh using the parameter IPMESH to ensure that the remeshing process does not inadvertently remove mesh points from areas of known interest.

In the absence of any other information about the expected behaviour of the solution, using the values suggested in Section 5 for NMESH, IPMESH and MESH is strongly recommended.

## 9 Example

This example illustrates the use of continuation, solution on an infinite range, and solution of a system of two differential equations of orders 3 and 2. See also D02TKF, D02TVF, D02TYF and D02TZF, for the illustration of other facilities.

Consider the problem of swirling flow over an infinite stationary disk with a magnetic field along the axis of rotation. See Ascher *et al.* (1988) and the references therein. After transforming from a cylindrical coordinate system  $(r, \theta, z)$ , in which the  $\theta$  component of the corresponding velocity field behaves like  $r^{-n}$ , the governing equations are

$$\begin{aligned} f''' + \frac{1}{2}(3-n)ff'' + n(f')^2 + g^2 - sf' &= \gamma^2 \\ g'' + \frac{1}{2}(3-n)fg' + (n-1)gf' - s(g-1) &= 0 \end{aligned}$$

with boundary conditions

$$f(0) = f'(0) = g(0) = 0, \quad f'(\infty) = 0, \quad g(\infty) = \gamma,$$

where  $s$  is the magnetic field strength, and  $\gamma$  is the Rossby number.

Some solutions of interest are for  $\gamma = 1$ , small  $n$  and  $s \rightarrow 0$ . An added complication is the infinite range, which we approximate by  $[0, L]$ . We choose  $n = 0.2$  and first solve for  $L = 60.0, s = 0.24$  using the initial approximations  $f(x) = -x^2e^{-x}$  and  $g(x) = 1.0 - e^{-x}$ , which satisfy the boundary conditions, on a uniform mesh of 21 points. Simple continuation on the parameters  $L$  and  $s$  using the values  $L = 120.0, s = 0.144$  and then  $L = 240.0, s = 0.0864$  is used to compute further solutions. We use the suggested values for N\_MESH, IP\_MESH and MESH in the call to D02TXF prior to a continuation call, that is only every second point of the preceding mesh is used.

The equations are first mapped onto  $[0, 1]$  to yield

$$\begin{aligned} f''' &= L^3(\gamma^2 - g^2) + L^2sg' - L\left(\frac{1}{2}(3-n)ff'' + n(g')^2\right) \\ g'' &= L^2s(g-1) - L\left(\frac{1}{2}(3-n)fg' + (n-1)f'g\right). \end{aligned}$$

### 9.1 Program Text

```
! D02TXF Example Program Text
! Mark 24 Release. NAG Copyright 2012.

Module d02txfe_mod

! D02TXF Example Program Module:
! Parameters and User-defined Routines

! .. Use Statements ..
Use nag_library, Only: nag_wp
! .. Implicit None Statement ..
Implicit None
! .. Parameters ..
Real (Kind=nag_wp), Parameter :: half = 0.5_nag_wp
Real (Kind=nag_wp), Parameter :: one = 1.0_nag_wp
Real (Kind=nag_wp), Parameter :: three = 3.0_nag_wp
Real (Kind=nag_wp), Parameter :: two = 2.0_nag_wp
Real (Kind=nag_wp), Parameter :: xsplit = 30.0_nag_wp
Integer, Parameter :: m1 = 3, m2 = 2, mmax = 3, &
neq = 2, nin = 5, nlbc = 3, &
nleft = 15, nout = 6, nrbc = 2, &
nright = 10

! .. Local Scalars ..
Real (Kind=nag_wp) :: el, en, s
Contains
Subroutine ffun(x,y,neq,m,f)

! .. Scalar Arguments ..
Real (Kind=nag_wp), Intent (In) :: x
```

```

        Integer, Intent (In)                :: neq
!      .. Array Arguments ..
        Real (Kind=nag_wp), Intent (Out)    :: f(neq)
        Real (Kind=nag_wp), Intent (In)     :: y(neq,0:*)
        Integer, Intent (In)                :: m(neq)
!      .. Local Scalars ..
        Real (Kind=nag_wp)                  :: t1, y11, y20
!      .. Executable Statements ..
        t1 = half*(three-en)*y(1,0)
        y11 = y(1,1)
        y20 = y(2,0)
        f(1) = (el**3)*(one-y20**2) + (el**2)*s*y11 - el*(t1*y(1,2)+en*y11**2)
        f(2) = (el**2)*s*(y20-one) - el*(t1*y(2,1)+(en-one)*y11*y20)
        Return
End Subroutine ffun
Subroutine fjac(x,y,neq,m,dfdy)

!      .. Scalar Arguments ..
        Real (Kind=nag_wp), Intent (In)     :: x
        Integer, Intent (In)                :: neq
!      .. Array Arguments ..
        Real (Kind=nag_wp), Intent (Inout)  :: dfdy(neq,neq,0:*)
        Real (Kind=nag_wp), Intent (In)     :: y(neq,0:*)
        Integer, Intent (In)                :: m(neq)
!      .. Executable Statements ..
        dfdy(1,2,0) = -two*el**3*y(2,0)
        dfdy(1,1,0) = -el*half*(three-en)*y(1,2)
        dfdy(1,1,1) = el**2*s - el*two*en*y(1,1)
        dfdy(1,1,2) = -el*half*(three-en)*y(1,0)
        dfdy(2,2,0) = el**2*s - el*(en-one)*y(1,1)
        dfdy(2,2,1) = -el*half*(three-en)*y(1,0)
        dfdy(2,1,0) = -el*half*(three-en)*y(2,1)
        dfdy(2,1,1) = -el*(en-one)*y(2,0)
        Return
End Subroutine fjac
Subroutine gafun(ya,neq,m,nlbc,ga)

!      .. Scalar Arguments ..
        Integer, Intent (In)                :: neq, nlbc
!      .. Array Arguments ..
        Real (Kind=nag_wp), Intent (Out)    :: ga(nlbc)
        Real (Kind=nag_wp), Intent (In)     :: ya(neq,0:*)
        Integer, Intent (In)                :: m(neq)
!      .. Executable Statements ..
        ga(1) = ya(1,0)
        ga(2) = ya(1,1)
        ga(3) = ya(2,0)
        Return
End Subroutine gafun
Subroutine gbfun(yb,neq,m,nrbc,gb)

!      .. Scalar Arguments ..
        Integer, Intent (In)                :: neq, nrbc
!      .. Array Arguments ..
        Real (Kind=nag_wp), Intent (Out)    :: gb(nrbc)
        Real (Kind=nag_wp), Intent (In)     :: yb(neq,0:*)
        Integer, Intent (In)                :: m(neq)
!      .. Executable Statements ..
        gb(1) = yb(1,1)
        gb(2) = yb(2,0) - one
        Return
End Subroutine gbfun
Subroutine gajac(ya,neq,m,nlbc,dgady)

!      .. Scalar Arguments ..
        Integer, Intent (In)                :: neq, nlbc
!      .. Array Arguments ..
        Real (Kind=nag_wp), Intent (Inout)  :: dgady(nlbc,neq,0:*)
        Real (Kind=nag_wp), Intent (In)     :: ya(neq,0:*)
        Integer, Intent (In)                :: m(neq)
!      .. Executable Statements ..

```

```

    dgady(1,1,0) = one
    dgady(2,1,1) = one
    dgady(3,2,0) = one
    Return
End Subroutine gajac
Subroutine gbjac(yb,neq,m,nrbc,dgbdy)

!     .. Scalar Arguments ..
!     Integer, Intent (In)           :: neq, nrbc
!     .. Array Arguments ..
!     Real (Kind=nag_wp), Intent (Inout) :: dgbdy(nrbc,neq,0:*)
!     Real (Kind=nag_wp), Intent (In)   :: yb(neq,0:*)
!     Integer, Intent (In)              :: m(neq)
!     .. Executable Statements ..
    dgbdy(1,1,1) = one
    dgbdy(2,2,0) = one
    Return
End Subroutine gbjac
Subroutine guess(x,neq,m,y,dym)

!     .. Scalar Arguments ..
!     Real (Kind=nag_wp), Intent (In)   :: x
!     Integer, Intent (In)              :: neq
!     .. Array Arguments ..
!     Real (Kind=nag_wp), Intent (Out)  :: dym(neq)
!     Real (Kind=nag_wp), Intent (Inout) :: y(neq,0:*)
!     Integer, Intent (In)              :: m(neq)
!     .. Local Scalars ..
!     Real (Kind=nag_wp)                :: ex, expmx
!     .. Intrinsic Procedures ..
!     Intrinsic                          :: exp
!     .. Executable Statements ..
    ex = x*el
    expmx = exp(-ex)
    y(1,0) = -ex**2*expmx
    y(1,1) = (-two*ex+ex**2)*expmx
    y(1,2) = (-two+4.0E0_nag_wp*ex-ex**2)*expmx
    y(2,0) = one - expmx
    y(2,1) = expmx
    dym(1) = (6.0E0_nag_wp-6.0E0_nag_wp*ex+ex**2)*expmx
    dym(2) = -expmx
    Return
End Subroutine guess
End Module d02txfe_mod
Program d02txfe

!     D02TXF Example Main Program

!     .. Use Statements ..
Use nag_library, Only: d02tkf, d02tvf, d02txf, d02tyf, d02tzf, nag_wp
Use d02txfe_mod, Only: el, en, ffun, fjac, gafun, gajac, gbfun, gbjac, &
    guess, m1, m2, mmax, neq, nin, nlbc, nleft, nout, &
    nrbc, nright, one, s, two, xsplit

!     .. Implicit None Statement ..
Implicit None

!     .. Local Scalars ..
!     Real (Kind=nag_wp)                :: dx, el_init, ermx, s_init, xx
!     Integer                           :: i, iermx, ifail, ijermx, j, &
    liwork, lrwork, mxmesh, ncol, &
    ncont, nmesh

!     .. Local Arrays ..
!     Real (Kind=nag_wp), Allocatable   :: mesh(:), rwork(:)
!     Real (Kind=nag_wp)                :: tol(neq), y(neq,0:mmax-1)
!     Integer, Allocatable               :: ipmesh(:), iwork(:)
!     Integer                            :: m(neq)
!     .. Intrinsic Procedures ..
!     Intrinsic                          :: min, real
!     .. Executable Statements ..
Write (nout,*) 'D02TXF Example Program Results'
Write (nout,*)
!     Skip heading in data file

```

```

      Read (nin,*)
!      Read method parameters
      Read (nin,*) ncol, nmesh, mxmesh
      Read (nin,*) tol(1:neq)

      liwork = mxmesh*(11*neq+6)
      lrwork = mxmesh*(109*neq**2+78*neq+7)
      Allocate (mesh(mxmesh),rwork(lrwork),ipmesh(mxmesh),iwork(liwork))
!      Read problem (initial) parameters
      Read (nin,*) en, el_init, s_init
!      Initialise data
      el = el_init
      s = s_init
      m(1) = m1
      m(2) = m2

      dx = one/real(nmesh-1,kind=nag_wp)
      mesh(1) = 0.0_nag_wp
      Do i = 2, nmesh - 1
         mesh(i) = mesh(i-1) + dx
      End Do
      mesh(nmesh) = 1.0_nag_wp

      ipmesh(1) = 1
      ipmesh(2:nmesh-1) = 2
      ipmesh(nmesh) = 1

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call d02tvf(neq,m,nlbc,nrbc,ncol,tol,mxmesh,nmesh,mesh,ipmesh,rwork, &
         lrwork,iwork,liwork,ifail)

!      Initialize number of continuation steps in el and s
      Read (nin,*) ncont
cont: Do j = 1, ncont
      Write (nout,99997) tol(1), el, s

!      Solve
      ifail = -1
      Call d02tkf(ffun,fjac,gafun,gbfun,gajac,gbjac,guess,rwork,iwork,ifail)
      If (ifail/=0) Exit cont

!      Extract mesh
      ifail = 0
      Call d02tzf(mxmesh,nmesh,mesh,ipmesh,ermx,iermx,ijermx,rwork,iwork, &
         ifail)

      Write (nout,99996) nmesh, ermx, iermx, ijermx
!      Print solution components on mesh
      Write (nout,99999)

!      Left side domain [0,xsplit], evaluate at nleft+1 uniform grid points.
      dx = xsplit/real(nleft,kind=nag_wp)/el
      xx = 0.0_nag_wp
      Do i = 0, nleft
         ifail = 0
         Call d02tyf(xx,y,neq,mmax,rwork,iwork,ifail)
         Write (nout,99998) xx*el, y(1,0), y(2,0)
         xx = xx + dx
      End Do

!      Right side domain (xsplit,L], evaluate at nright uniform grid points.
      dx = (el-xsplit)/real(nright,kind=nag_wp)/el
      xx = xsplit/el
      Do i = 1, nright
         xx = min(1.0_nag_wp,xx+dx)
         ifail = 0
         Call d02tyf(xx,y,neq,mmax,rwork,iwork,ifail)
         Write (nout,99998) xx*el, y(1,0), y(2,0)
      End Do

```

```

!      Select mesh for continuation and update continuation parameters.
      If (j<ncont) Then
        el = two*el
        s = 0.6_nag_wp*s
        nmesh = (nmesh+1)/2
        ifail = 0
        Call d02txf(mxmesh,nmesh,mesh,ipmesh,rwork,iwork,ifail)
      End If
    End Do cont

99999 Format ('/ Solution on original interval: '/6X,'x',8X,'f',10X,'g')
99998 Format (1X,F8.2,2(1X,F10.4))
99997 Format ('/' Tolerance = ',E8.1,' L = ',F8.3,' S =',F7.4)
99996 Format ('/' Used a mesh of ',I4,' points'/' Maximum error = ',E10.2, &
' in interval ',I4,' for component ',I4)
      End Program d02txfe

```

## 9.2 Program Data

D02TXF Example Program Data

```

6 21 250 : (method parameters) ncol, nmesh, mxmesh
1.0E-5 1.0E-5 : tolerances
0.2 60.0 0.24 : (problem parameters) en, el_init, s_init
3 : ncont

```

## 9.3 Program Results

D02TXF Example Program Results

Tolerance = 0.1E-04 L = 60.000 S = 0.2400

Used a mesh of 21 points  
Maximum error = 0.27E-07 in interval 7 for component 1

Solution on original interval:

x	f	g
0.00	0.0000	0.0000
2.00	-0.9769	0.8011
4.00	-2.0900	1.1459
6.00	-2.6093	1.2389
8.00	-2.5498	1.1794
10.00	-2.1397	1.0478
12.00	-1.7176	0.9395
14.00	-1.5465	0.9206
16.00	-1.6127	0.9630
18.00	-1.7466	1.0068
20.00	-1.8286	1.0244
22.00	-1.8338	1.0185
24.00	-1.7956	1.0041
26.00	-1.7582	0.9940
28.00	-1.7445	0.9926
30.00	-1.7515	0.9965
33.00	-1.7695	1.0019
36.00	-1.7730	1.0018
39.00	-1.7673	0.9998
42.00	-1.7645	0.9993
45.00	-1.7659	0.9999
48.00	-1.7672	1.0002
51.00	-1.7671	1.0001
54.00	-1.7666	0.9999
57.00	-1.7665	0.9999
60.00	-1.7666	1.0000

Tolerance = 0.1E-04 L = 120.000 S = 0.1440

Used a mesh of 21 points



Maximum error = 0.69E-05 in interval 7 for component 2

Solution on original interval:

x	f	g
0.00	0.0000	0.0000
2.00	-1.1406	0.7317
4.00	-2.6531	1.1315
6.00	-3.6721	1.3250
8.00	-4.0539	1.3707
10.00	-3.8285	1.3003
12.00	-3.1339	1.1407
14.00	-2.2469	0.9424
16.00	-1.6146	0.8201
18.00	-1.5472	0.8549
20.00	-1.8483	0.9623
22.00	-2.1761	1.0471
24.00	-2.3451	1.0778
26.00	-2.3236	1.0600
28.00	-2.1784	1.0165
30.00	-2.0214	0.9775
39.00	-2.1109	1.0155
48.00	-2.0362	0.9931
57.00	-2.0709	1.0023
66.00	-2.0588	0.9995
75.00	-2.0616	1.0000
84.00	-2.0615	1.0001
93.00	-2.0611	0.9999
102.00	-2.0614	1.0000
111.00	-2.0613	1.0000
120.00	-2.0613	1.0000

Tolerance = 0.1E-04 L = 240.000 S = 0.0864


Used a mesh of 81 points

Maximum error = 0.33E-06 in interval 19 for component 2

Solution on original interval:

x	f	g
0.00	0.0000	0.0000
2.00	-1.2756	0.6404
4.00	-3.1604	1.0463
6.00	-4.7459	1.3011
8.00	-5.8265	1.4467
10.00	-6.3412	1.5036
12.00	-6.2862	1.4824
14.00	-5.6976	1.3886
16.00	-4.6568	1.2263
18.00	-3.3226	1.0042
20.00	-2.0328	0.7718
22.00	-1.4035	0.6943
24.00	-1.6603	0.8218
26.00	-2.2975	0.9928
28.00	-2.8661	1.1139
30.00	-3.1641	1.1641
51.00	-2.5307	1.0279
72.00	-2.3520	0.9919
93.00	-2.3674	0.9975
114.00	-2.3799	1.0003
135.00	-2.3800	1.0002
156.00	-2.3792	1.0000
177.00	-2.3791	1.0000
198.00	-2.3792	1.0000
219.00	-2.3792	1.0000
240.00	-2.3792	1.0000

**Example Program**  
Swirling Flow over Disc under Axial Magnetic Field  
using  $L=60$  and Magnetic Field Strength,  $s=0.24$



Swirling Flow over Disc under Axial Magnetic Field  
Continued to  $L=120$  and Magnetic Field Strength,  $s=0.144$

