

# NAG Library Routine Document

## C06FCF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

C06FCF calculates the discrete Fourier transform of a sequence of  $n$  complex data values (using a work array for extra speed).

### 2 Specification

```
SUBROUTINE C06FCF (X, Y, N, WORK, IFAIL)
  INTEGER          N, IFAIL
  REAL (KIND=nag_wp) X(N), Y(N), WORK(N)
```

### 3 Description

Given a sequence of  $n$  complex data values  $z_j$ , for  $j = 0, 1, \dots, n - 1$ , C06FCF calculates their discrete Fourier transform defined by

$$\hat{z}_k = a_k + ib_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} z_j \times \exp\left(-i \frac{2\pi jk}{n}\right), \quad k = 0, 1, \dots, n - 1.$$

(Note the scale factor of  $\frac{1}{\sqrt{n}}$  in this definition.)

To compute the inverse discrete Fourier transform defined by

$$\hat{w}_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} z_j \times \exp\left(+i \frac{2\pi jk}{n}\right),$$

this routine should be preceded and followed by the complex conjugation of the data values and the transform (by negating the imaginary parts stored in  $y$ ).

C06FCF uses the fast Fourier transform (FFT) algorithm (see Brigham (1974)). There are some restrictions on the value of  $n$  (see Section 5).

### 4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice–Hall

### 5 Parameters

1: X(N) – REAL (KIND=nag\_wp) array *Input/Output*

*On entry:* if X is declared with bounds (0 : N – 1) in the subroutine from which C06FCF is called, then X( $j$ ) must contain  $x_j$ , the real part of  $z_j$ , for  $j = 0, 1, \dots, n - 1$ .

*On exit:* the real parts  $a_k$  of the components of the discrete Fourier transform. If X is declared with bounds (0 : N – 1) in the subroutine from which C06FCF is called, then for  $0 \leq k \leq n - 1$ ,  $a_k$  is contained in X( $k$ ).

2: Y(N) – REAL (KIND=nag\_wp) array *Input/Output*

*On entry:* if Y is declared with bounds (0 : N – 1) in the subroutine from which C06FCF is called, then Y( $j$ ) must contain  $y_j$ , the imaginary part of  $z_j$ , for  $j = 0, 1, \dots, n - 1$ .

*On exit:* the imaginary parts  $b_k$  of the components of the discrete Fourier transform. If Y is declared with bounds  $(0 : N - 1)$  in the subroutine from which C06FCF is called, then for  $0 \leq k \leq n - 1$ ,  $b_k$  is contained in  $Y(k)$ .

3: N – INTEGER *Input*

*On entry:*  $n$ , the number of data values. The largest prime factor of N must not exceed 19, and the total number of prime factors of N, counting repetitions, must not exceed 20.

*Constraint:*  $N > 1$ .

4: WORK(N) – REAL (KIND=nag\_wp) array *Workspace*

5: IFAIL – INTEGER *Input/Output*

*On entry:* IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

*On exit:* IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

## 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

At least one of the prime factors of N is greater than 19.

IFAIL = 2

N has more than 20 prime factors.

IFAIL = 3

On entry,  $N \leq 1$ .

IFAIL = 4

An unexpected error has occurred in an internal call. Check all subroutine calls and array dimensions. Seek expert help.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.8 in the Essential Introduction for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.7 in the Essential Introduction for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.6 in the Essential Introduction for further information.

## 7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

## 8 Parallelism and Performance

Not applicable.

## 9 Further Comments

The time taken is approximately proportional to  $n \times \log(n)$ , but also depends on the factorization of  $n$ . C06FCF is faster if the only prime factors of  $n$  are 2, 3 or 5; and fastest of all if  $n$  is a power of 2.

## 10 Example

This example reads in a sequence of complex data values and prints their discrete Fourier transform (as computed by C06FCF). It then performs an inverse transform using C06FCF, and prints the sequence so obtained alongside the original data values.

### 10.1 Program Text

```

Program c06fcfe

!      C06FCF Example Program Text

!      Mark 25 Release. NAG Copyright 2014.

!      .. Use Statements ..
Use nag_library, Only: c06fcf, c06gcf, nag_wp
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Integer                     :: ieof, ifail, j, n
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: work(:), x(:), xx(:), y(:), yy(:)
!      .. Executable Statements ..
Write (nout,*) 'C06FCF Example Program Results'
!      Skip heading in data file
Read (nin,*)
loop: Do
  Read (nin,*,Iostat=ieof) n
  If (ieof<0) Exit loop

  Allocate (x(0:n-1),xx(0:n-1),y(0:n-1),yy(0:n-1),work(n))
  Read (nin,*)(x(j),y(j),j=0,n-1)
  xx(0:n-1) = x(0:n-1)
  yy(0:n-1) = y(0:n-1)

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
  ifail = 0
  Call c06fcf(x,y,n,work,ifail)

  Write (nout,*)
  Write (nout,*) 'Components of discrete Fourier transform'
  Write (nout,*)

```

```

Write (nout,*) '          Real      Imag'
Write (nout,*)
Write (nout,99999)(j,x(j),y(j),j=0,n-1)

Call c06gcf(y,n,ifail)
Call c06fcf(x,y,n,work,ifail)
Call c06gcf(y,n,ifail)

Write (nout,*)
Write (nout,*) 'Original sequence as restored by inverse transform'
Write (nout,*)
Write (nout,*) '          Original          Restored'
Write (nout,*) '          Real      Imag          Real      Imag'
Write (nout,*)
Write (nout,99998)(j,xx(j),yy(j),x(j),y(j),j=0,n-1)
Deallocate (x,xx,y,yy,work)
End Do loop

99999 Format (1X,I5,2F10.5)
99998 Format (1X,I5,2F10.5,5X,2F10.5)
End Program c06fcfe

```

## 10.2 Program Data

```

C06FCF Example Program Data
7          : n
0.34907  -0.37168
0.54890  -0.35669
0.74776  -0.31175
0.94459  -0.23702
1.13850  -0.13274
1.32850  0.00074
1.51370  0.16298      : x, y

```

## 10.3 Program Results

C06FCF Example Program Results

Components of discrete Fourier transform

	Real	Imag
0	2.48361	-0.47100
1	-0.55180	0.49684
2	-0.36711	0.09756
3	-0.28767	-0.05865
4	-0.22506	-0.17477
5	-0.14825	-0.30840
6	0.01983	-0.56496

Original sequence as restored by inverse transform

	Original		Restored	
	Real	Imag	Real	Imag
0	0.34907	-0.37168	0.34907	-0.37168
1	0.54890	-0.35669	0.54890	-0.35669
2	0.74776	-0.31175	0.74776	-0.31175
3	0.94459	-0.23702	0.94459	-0.23702
4	1.13850	-0.13274	1.13850	-0.13274
5	1.32850	0.00074	1.32850	0.00074
6	1.51370	0.16298	1.51370	0.16298

---