# **NAG Library Routine Document**

# F07THF (DTRRFS)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F07THF (DTRRFS) returns error bounds for the solution of a real triangular system of linear equations with multiple right-hand sides, AX = B or  $A^{T}X = B$ .

## 2 Specification

The routine may be called by its LAPACK name dtrrfs.

### **3** Description

F07THF (DTRRFS) returns the backward errors and estimated bounds on the forward errors for the solution of a real triangular system of linear equations with multiple right-hand sides AX = B or  $A^{T}X = B$ . The routine handles each right-hand side vector (stored as a column of the matrix B) independently, so we describe the function of F07THF (DTRRFS) in terms of a single right-hand side b and solution x.

Given a computed solution x, the routine computes the *component-wise backward error*  $\beta$ . This is the size of the smallest relative perturbation in each element of A and b such that x is the exact solution of a perturbed system

$$(A + \delta A)x = b + \delta b$$
  
$$|\delta a_{ij}| \le \beta |a_{ij}| \quad \text{and} \quad |\delta b_i| \le \beta |b_i|.$$

Then the routine estimates a bound for the *component-wise forward error* in the computed solution, defined by:

 $\max_i |x_i - \hat{x}_i| / \max_i |x_i|$ 

where  $\hat{x}$  is the true solution.

For details of the method, see the F07 Chapter Introduction.

### 4 References

Golub G H and Van Loan C F (1996) Matrix Computations (3rd Edition) Johns Hopkins University Press, Baltimore

### 5 Parameters

1: UPLO – CHARACTER(1)

On entry: specifies whether A is upper or lower triangular.

UPLO = 'U'

A is upper triangular.

F07THF.1

Input

	UPLO = 'L' <i>A</i> is lower triangular.	
	Constraint: UPLO = 'U' or 'L'.	
2:	TRANS – CHARACTER(1) In	put
	On entry: indicates the form of the equations.	
	TRANS = 'N' The equations are of the form $AX = B$ .	
	TRANS = 'T' or 'C' The equations are of the form $A^{T}X = B$ .	
	Constraint: $TRANS = 'N'$ , 'T' or 'C'.	
3:	DIAG – CHARACTER(1) In	put
	On entry: indicates whether A is a nonunit or unit triangular matrix.	
	DIAG = 'N' A is a nonunit triangular matrix.	
	DIAG = 'U' A is a unit triangular matrix; the diagonal elements are not referenced and are assumed be 1.	l to
	Constraint: $DIAG = 'N'$ or 'U'.	
4:	N – INTEGER	put
	On entry: n, the order of the matrix A.	
	Constraint: $N \ge 0$ .	
5:	NRHS – INTEGER	put
	On entry: r, the number of right-hand sides.	
	Constraint: NRHS $\geq 0$ .	
6:	A(LDA, *) – REAL (KIND=nag_wp) array	put
	Note: the second dimension of the array A must be at least $max(1, N)$ .	
	On entry: the $n$ by $n$ triangular matrix $A$ .	
	If UPLO = 'U', $A$ is upper triangular and the elements of the array below the diagonal not referenced.	are
	If UPLO = 'L', $A$ is lower triangular and the elements of the array above the diagonal not referenced.	are
	If $DIAG = U'$ , the diagonal elements of A are assumed to be 1, and are not reference	ed.
7:	LDA – INTEGER In	put
	On entry: the first dimension of the array A as declared in the (sub)program from which F071 (DTRRFS) is called.	ΉF
	Constraint: $LDA \ge max(1, N)$ .	
8:	B(LDB,*) – REAL (KIND=nag_wp) array	put
	Note: the second dimension of the array B must be at least $max(1, NRHS)$ .	
	On entry: the $n$ by $r$ right-hand side matrix $B$ .	

9:	LDB – INTEGER	Input
	<i>On entry</i> : the first dimension of the array B as declared in the (sub)program from (DTRRFS) is called.	which F07THF
	Constraint: $LDB \ge max(1, N)$ .	
10:	X(LDX, *) - REAL (KIND=nag_wp) array	Input
	Note: the second dimension of the array X must be at least $max(1, NRHS)$ .	
	On entry: the $n$ by $r$ solution matrix $X$ , as returned by F07TEF (DTRTRS).	
11:	LDX – INTEGER	Input
	<i>On entry</i> : the first dimension of the array X as declared in the (sub)program from (DTRRFS) is called.	which F07THF
	Constraint: $LDX \ge max(1, N)$ .	
12:	FERR(NRHS) – REAL (KIND=nag_wp) array	Output
	On exit: FERR(j) contains an estimated error bound for the jth solution vector, column of X, for $j = 1, 2,, r$ .	that is, the <i>j</i> th
13:	BERR(NRHS) – REAL (KIND=nag_wp) array	Output
	On exit: BERR(j) contains the component-wise backward error bound $\beta$ for the vector, that is, the <i>j</i> th column of X, for $j = 1, 2,, r$ .	the <i>j</i> th solution
14:	WORK $(3 \times N)$ – REAL (KIND=nag_wp) array	Workspace
15:	IWORK(N) – INTEGER array	Workspace
16:	INFO – INTEGER	Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

# 6 Error Indicators and Warnings

If INFO = -i, argument *i* had an illegal value. An explanatory message is output, and execution of the program is terminated.

# 7 Accuracy

The bounds returned in FERR are not rigorous, because they are estimated, not computed exactly; but in practice they almost always overestimate the actual error.

# 8 Parallelism and Performance

F07THF (DTRRFS) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07THF (DTRRFS) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

INFO < 0

### 9 Further Comments

A call to F07THF (DTRRFS), for each right-hand side, involves solving a number of systems of linear equations of the form Ax = b or  $A^{T}x = b$ ; the number is usually 4 or 5 and never more than 11. Each solution involves approximately  $n^2$  floating-point operations.

The complex analogue of this routine is F07TVF (ZTRRFS).

### 10 Example

This example solves the system of equations AX = B and to compute forward and backward error bounds, where

	/ 4.30	0.00	0.00	0.00			(-12.90)	-21.50	
4 —	-3.96	-4.87	0.00	0.00	and	P	16.75	14.93	).
A =	0.40	0.31	-8.02	0.00		$D \equiv$	-17.55	6.33	
	-0.27	0.07	-5.95	0.12/			-11.04	8.09/	

#### 10.1 Program Text

Program f07thfe

```
!
     FO7THF Example Program Text
1
     Mark 25 Release. NAG Copyright 2014.
1
      .. Use Statements ..
     Use nag_library, Only: dtrrfs, dtrtrs, nag_wp, x04caf
!
      .. Implicit None Statement ..
     Implicit None
!
     .. Parameters ..
     Integer, Parameter
                                      :: nin = 5, nout = 6
     Character (1), Parameter
                                      :: diag = 'N', trans = 'N'
1
      .. Local Scalars ..
     Integer
                                       :: i, ifail, info, lda, ldb, ldx, n, nrhs
     Character (1)
                                       :: uplo
      .. Local Arrays ..
1
     Real (Kind=nag_wp), Allocatable :: a(:,:), b(:,:), berr(:), ferr(:),
                                                                                &
                                          work(:), x(:,:)
     Integer, Allocatable
                                       :: iwork(:)
1
      .. Executable Statements ..
     Write (nout,*) 'FO7THF Example Program Results'
1
     Skip heading in data file
     Read (nin,*)
     Read (nin,*) n, nrhs
     lda = n
     ldb = n
     1dx = n
     Allocate (a(lda,n),b(ldb,nrhs),berr(nrhs),ferr(nrhs),work(3*n),x(ldx,n), &
        iwork(n))
     Read A and B from data file, and copy B to X
1
     Read (nin,*) uplo
     If (uplo=='U') Then
       Read (nin,*)(a(i,i:n),i=1,n)
     Else If (uplo=='L') Then
       Read (nin,*)(a(i,1:i),i=1,n)
     End If
     Read (nin,*)(b(i,1:nrhs),i=1,n)
     x(1:n,1:nrhs) = b(1:n,1:nrhs)
!
     Compute solution in the array X
!
     The NAG name equivalent of dtrtrs is f07tef
     Call dtrtrs(uplo,trans,diag,n,nrhs,a,lda,x,ldx,info)
1
     Compute backward errors and estimated bounds on the
```

```
!
     forward errors
     The NAG name equivalent of dtrrfs is f07thf
1
      Call dtrrfs(uplo,trans,diag,n,nrhs,a,lda,b,ldb,x,ldx,ferr,berr,work, &
        iwork,info)
1
     Print solution
     Write (nout,*)
     Flush (nout)
     ifail: behaviour on error exit
!
!
              =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
     Call x04caf('General',' ',n,nrhs,x,ldx,'Solution(s)',ifail)
     Write (nout,*)
     Write (nout,*) 'Backward errors (machine-dependent)'
     Write (nout,99999) berr(1:nrhs)
     Write (nout,*) 'Estimated forward error bounds (machine-dependent)'
     Write (nout, 99999) ferr(1:nrhs)
99999 Format ((3X,1P,7E11.1))
   End Program f07thfe
```

#### 10.2 Program Data

FO7THF Example Program Data 4 2 :Values of N and NRHS 'L' :Value of UPLO 4.30 -3.96 -4.87 0.31 -8.02 0.40 0.07 0.12 :End of matrix A -0.27 -5.95 -12.90 -21.50 16.75 14.93 -17.55 6.33 -11.04 8.09 :End of matrix B

#### 10.3 Program Results

FO7THF Example Program Results

Solution(s) 1 2 1 -3.0000 -5.0000 1.0000 2 -1.0000 3 2.0000 -1.0000 1.0000 6.0000 4 Backward errors (machine-dependent) 6.9E-17 0.0E+00 Estimated forward error bounds (machine-dependent) 8.3E-14 2.6E-14