

# NAG Library Routine Document

## E02DEF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

E02DEF calculates values of a bicubic spline from its B-spline representation.

### 2 Specification

```
SUBROUTINE E02DEF (M, PX, PY, X, Y, LAMDA, MU, C, FF, WRK, IWRK, IFAIL)
INTEGER          M, PX, PY, IWRK(PY-4), IFAIL
REAL (KIND=nag_wp) X(M), Y(M), LAMDA(PX), MU(PY), C((PX-4)*(PY-4)), &
                FF(M), WRK(PY-4)
```

### 3 Description

E02DEF calculates values of the bicubic spline  $s(x, y)$  at prescribed points  $(x_r, y_r)$ , for  $r = 1, 2, \dots, m$ , from its augmented knot sets  $\{\lambda\}$  and  $\{\mu\}$  and from the coefficients  $c_{ij}$ , for  $i = 1, 2, \dots, PX - 4$  and  $j = 1, 2, \dots, PY - 4$ , in its B-spline representation

$$s(x, y) = \sum_{ij} c_{ij} M_i(x) N_j(y).$$

Here  $M_i(x)$  and  $N_j(y)$  denote normalized cubic B-splines, the former defined on the knots  $\lambda_i$  to  $\lambda_{i+4}$  and the latter on the knots  $\mu_j$  to  $\mu_{j+4}$ .

This routine may be used to calculate values of a bicubic spline given in the form produced by E01DAF, E02DAF, E02DCF and E02DDF. It is derived from the routine B2VRE in Anthony *et al.* (1982).

### 4 References

Anthony G T, Cox M G and Hayes J G (1982) *DASL – Data Approximation Subroutine Library* National Physical Laboratory

Cox M G (1978) The numerical evaluation of a spline from its B-spline representation *J. Inst. Math. Appl.* **21** 135–143

### 5 Arguments

1: M – INTEGER *Input*

*On entry:*  $m$ , the number of points at which values of the spline are required.

*Constraint:*  $M \geq 1$ .

2: PX – INTEGER *Input*

3: PY – INTEGER *Input*

*On entry:* PX and PY must specify the total number of knots associated with the variables  $x$  and  $y$  respectively. They are such that  $PX - 8$  and  $PY - 8$  are the corresponding numbers of interior knots.

*Constraint:*  $PX \geq 8$  and  $PY \geq 8$ .

- 4: X(M) – REAL (KIND=nag\_wp) array Input  
 5: Y(M) – REAL (KIND=nag\_wp) array Input

*On entry:* X and Y must contain  $x_r$  and  $y_r$ , for  $r = 1, 2, \dots, m$ , respectively. These are the coordinates of the points at which values of the spline are required. The order of the points is immaterial.

*Constraint:* X and Y must satisfy

$$\text{LAMDA}(4) \leq X(r) \leq \text{LAMDA}(\text{PX} - 3)$$

and

$$\text{MU}(4) \leq Y(r) \leq \text{MU}(\text{PY} - 3), \quad r = 1, 2, \dots, m.$$

The spline representation is not valid outside these intervals

- 6: LAMDA(PX) – REAL (KIND=nag\_wp) array Input  
 7: MU(PY) – REAL (KIND=nag\_wp) array Input

*On entry:* LAMDA and MU must contain the complete sets of knots  $\{\lambda\}$  and  $\{\mu\}$  associated with the  $x$  and  $y$  variables respectively.

*Constraint:* the knots in each set must be in nondecreasing order, with  $\text{LAMDA}(\text{PX} - 3) > \text{LAMDA}(4)$  and  $\text{MU}(\text{PY} - 3) > \text{MU}(4)$ .

- 8: C((PX - 4) × (PY - 4)) – REAL (KIND=nag\_wp) array Input

*On entry:* C((PY - 4) × (i - 1) + j) must contain the coefficient  $c_{ij}$  described in Section 3, for  $i = 1, 2, \dots, \text{PX} - 4$  and  $j = 1, 2, \dots, \text{PY} - 4$ .

- 9: FF(M) – REAL (KIND=nag\_wp) array Output

*On exit:* FF( $r$ ) contains the value of the spline at the point  $(x_r, y_r)$ , for  $r = 1, 2, \dots, m$ .

- 10: WRK(PY - 4) – REAL (KIND=nag\_wp) array Workspace  
 11: IWRK(PY - 4) – INTEGER array Workspace

- 12: IFAIL – INTEGER Input/Output

*On entry:* IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

*On exit:* IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

## 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry,  $M < 1$ ,  
 or  $\text{PY} < 8$ ,

or  $PX < 8$ .

IFAIL = 2

On entry, the knots in array LAMDA, or those in array MU, are not in nondecreasing order, or  $LAMDA(PX - 3) \leq LAMDA(4)$ , or  $MU(PY - 3) \leq MU(4)$ .

IFAIL = 3

On entry, at least one of the prescribed points  $(x_r, y_r)$  lies outside the rectangle defined by  $LAMDA(4)$ ,  $LAMDA(PX - 3)$  and  $MU(4)$ ,  $MU(PY - 3)$ .

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

## 7 Accuracy

The method used to evaluate the B-splines is numerically stable, in the sense that each computed value of  $s(x_r, y_r)$  can be regarded as the value that would have been obtained in exact arithmetic from slightly perturbed B-spline coefficients. See Cox (1978) for details.

## 8 Parallelism and Performance

E02DEF is not threaded in any implementation.

## 9 Further Comments

Computation time is approximately proportional to the number of points,  $m$ , at which the evaluation is required.

## 10 Example

This program reads in knot sets  $LAMDA(1), \dots, LAMDA(PX)$  and  $MU(1), \dots, MU(PY)$ , and a set of bicubic spline coefficients  $c_{ij}$ . Following these are a value for  $m$  and the coordinates  $(x_r, y_r)$ , for  $r = 1, 2, \dots, m$ , at which the spline is to be evaluated.

### 10.1 Program Text

```

Program e02defe

!      E02DEF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
      Use nag_library, Only: e02def, nag_wp
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..

```

```

Integer, Parameter          :: nin = 5, nout = 6
! .. Local Scalars ..
Integer                    :: i, ifail, m, px, py
! .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: c(:), ff(:), lamda(:), mu(:),      &
                                wrk(:), x(:), y(:)
Integer, Allocatable       :: iwrk(:)
! .. Executable Statements ..
Write (nout,*) 'E02DEF Example Program Results'

! Skip heading in data file
Read (nin,*)

! Read PX and PY, the number of knots in the X and Y directions.

Read (nin,*) px, py
Allocate (lamda(px),mu(py),c((px-4)*(py-4)),wrk(py-4),iwrk(py-4))

! Read the knots LAMDA(1) .. LAMDA(PX) and MU(1) .. MU(PY).

Read (nin,*) lamda(1:px)
Read (nin,*) mu(1:py)

! Read C, the bicubic spline coefficients.

Read (nin,*) c(1:(px-4)*(py-4))

! Read M, the number of spline evaluation points.

Read (nin,*) m
Allocate (x(m),y(m),ff(m))

! Read the X and Y co-ordinates of the evaluation points.

Do i = 1, m
  Read (nin,*) x(i), y(i)
End Do

! Evaluate the spline at the M points.

ifail = 0
Call e02def(m,px,py,x,y,lamda,mu,c,ff,wrk,iwrk,ifail)

Write (nout,*)
Write (nout,*) '          I          X(I)          Y(I)          FF(I)'
Write (nout,99999)(i,x(i),y(i),ff(i),i=1,m)

99999 Format (1X,I7,3F11.3)
End Program e02defe

```

## 10.2 Program Data

E02DEF Example Program Data

11	10										PX	PY
1.0	1.0	1.0	1.0	1.3	1.5	1.6	2.0	2.0	2.0	2.0	LAMDA(1)	.. LAMDA(PX)
0.0	0.0	0.0	0.0	0.4	0.7	1.0	1.0	1.0	1.0		MU(1)	.. MU(PY)
1.0000	1.1333	1.3667	1.7000	1.9000	2.0000							
1.2000	1.3333	1.5667	1.9000	2.1000	2.2000							
1.5833	1.7167	1.9500	2.2833	2.4833	2.5833							
2.1433	2.2767	2.5100	2.8433	3.0433	3.1433							
2.8667	3.0000	3.2333	3.5667	3.7667	3.8667							
3.4667	3.6000	3.8333	4.1667	4.3667	4.4667							
4.0000	4.1333	4.3667	4.7000	4.9000	5.0000							
7											Spline coefficients, C	
											M	
1.0	0.0										X(1), Y(1)	
1.1	0.1											

1.5 0.7  
 1.6 0.4  
 1.9 0.3  
 1.9 0.8  
 2.0 1.0

X(M), Y(M)

### 10.3 Program Results

E02DEF Example Program Results

I	X(I)	Y(I)	FF(I)
1	1.000	0.000	1.000
2	1.100	0.100	1.310
3	1.500	0.700	2.950
4	1.600	0.400	2.960
5	1.900	0.300	3.910
6	1.900	0.800	4.410
7	2.000	1.000	5.000

**Example Program**  
 Evaluation of Least-squares Bicubic Spline Fit  
 at Scattered Points

